SAFETY DATA SHEET



Date of issue/Date of revision7 November 2021Version 4

| Section 1. Identification | | |
|----------------------------------|---|--|
| Product name | : SIGMAZINC 158 PIGMENT GREY | |
| Product code | : 00286103 | |
| Other means of identification | : Not available. | |
| Product type | : Powder. | |
| Relevant identified uses of | the substance or mixture and uses advised against | |
| Product use | : Professional applications, Used by spraying. | |
| Use of the substance/ mixture | : Coating. | |
| Uses advised against | : Not applicable. | |
| Manufacturer | : PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272 | |
| Emergency telephone number | : (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México) | |
| Technical Phone Number | : 888-977-4762 | |

Section 2. Hazards identification

| OSHA/HCS status | This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). |
|--|---|
| Classification of the substance or mixture | : COMBUSTIBLE DUSTS |
| | Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 95% (oral), 95% (dermal) |
| GHS label elements | |
| Signal word | : Warning |
| Hazard statements | : May form combustible dust concentrations in air. |
| Precautionary statements | |
| Prevention | : Not applicable. |
| Response | : Not applicable. |
| Storage | : Not applicable. |
| Disposal | : Not applicable. |

Product name SIGMAZINC 158 PIGMENT GREY

Section 2. Hazards identification

| Supplemental label elements | Keep container tightly closed. Keep away from heat, sparks, open flames and hot surfaces No smoking. Sanding and grinding dusts may be harmful if inhaled. Prevent dust accumulation. Emits toxic fumes when heated. |
|-------------------------------------|--|
| Hazards not otherwise classified | : Fine dust clouds may form explosive mixtures with air. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat. |

Section 3. Composition/information on ingredients

| Substance/mixture | |
|-------------------|--|
| Product name | |

: Mixture

: SIGMAZINC 158 PIGMENT GREY

| Ingredient name | % | CAS number |
|-----------------|-------------|------------|
| zinc oxide | ≥1.0 - ≤5.0 | 1314-13-2 |

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

| Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. |
|--|
| : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. |
| : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. |
| If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting. |
| |

Most important symptoms/effects, acute and delayed

Potential acute health effects Eye contact : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes. Inhalation : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs. Skin contact : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards. Over-exposure signs/symptoms

Product name SIGMAZINC 158 PIGMENT GREY

Section 4. First aid measures

| Eye contact | : | Adverse symptoms may include the following: irritation redness |
|---------------------------|---|---|
| Inhalation | : | Adverse symptoms may include the following: respiratory tract irritation coughing |
| Skin contact Ingestion | | No specific data. No specific data. |
| | | |

| Indication of immediate med | lical attention and special treatment needed, if necessary |
|-----------------------------|--|
| Notes to physician | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments | : No specific treatment. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |

See toxicological information (Section 11)

Section 5. Fire-fighting measures

| Extinguishing media | |
|--|--|
| Suitable extinguishing media | : Use dry chemical powder. |
| Unsuitable extinguishing media | : Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture. |
| Specific hazards arising from the chemical | : Fine dust clouds may form explosive mixtures with air. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. |
| Hazardous thermal decomposition products | : Decomposition products may include the following materials: metal oxide/oxides |
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |

Section 6. Accidental release measures

| | ns, protective equipment and emergency procedures | |
|--|---|--|
| For non-emergency personnel No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition source No flares, smoking or flames in hazard area. Avoid breathing dust. Provide ader ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. | Evacuate surrounding areas. Keep unnecessary and unprotecte entering. Do not touch or walk through spilled material. Shut of No flares, smoking or flames in hazard area. Avoid breathing du ventilation. Wear appropriate respirator when ventilation is inad | ed personnel from ff all ignition sources. ust. Provide adequate |

Product name SIGMAZINC 158 PIGMENT GREY

Section 6. Accidental release measures

| For emergency responders | : | If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". | | | |
|------------------------------|---|---|--|--|--|
| Environmental precautions | : | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. | | | |
| Methods and materials for co | Methods and materials for containment and cleaning up | | | | |
| Small spill | : | Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. | | | |
| Large spill | - | Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. | | | |

Section 7. Handling and storage

Precautions for safe handling

| Protective measures | Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid release to the environment. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container. |
|--|--|
| Advice on general occupational hygiene | Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
| Conditions for safe storage, including any incompatibilities | Storage temperature: 5 to 25°C (41 to 77°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. |

United States Page: 4/12

Product name SIGMAZINC 158 PIGMENT GREY

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|--|--|
| zínc oxide | OSHA PEL (United States, 5/2018). TWA: 5 mg/m ³ 8 hours. Form: Fume TWA: 5 mg/m ³ 8 hours. Form: Respirable fraction TWA: 15 mg/m ³ 8 hours. Form: Total dust ACGIH TLV (United States, 1/2021). STEL: 10 mg/m ³ 15 minutes. Form: Respirable fraction TWA: 2 mg/m ³ 8 hours. Form: Respirable fraction |
| | nacion |
| A = Acceptable Maximum Peak CGIH = American Conference of Governmental Indust C = Ceiling Limit F = Fume PEL = Internal Permissible Exposure Limit DSHA = Occupational Safety and Health Administration R = Respirable Z = OSHA 29 CFR 1910.1200 Subpart Z - Toxic a DSHAI Incal authorities for acceptable expo | SS = Skin sensitization STEL = Short term Exposure limit values TD = Total dust TLV = Threshold Limit Value TWA = Time Weighted Average nd Hazardous Substances |
| Recommended monitoring procedures : If this product atmosphere of the ventilation protective equination Reference to | contains ingredients with exposure limits, personal, workplace or biological monitoring may be required to determine the effectiveness of or other control measures and/or the necessity to use respiratory uipment. Reference should be made to appropriate monitoring standard national guidance documents for methods for the determination of bstances will also be required. |

| Appropriate engineering controls | : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. |
|----------------------------------|--|
| Environmental exposure controls | : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. |
| Individual protection measu | <u>ires</u> |

| Hygiene measures | : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |
|---------------------|---|
| Eye/face protection | : Safety glasses with side shields. |
| Skin protection | |

Product name SIGMAZINC 158 PIGMENT GREY

Section 8. Exposure controls/personal protection

| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
|------------------------|--|
| Body protection | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Other skin protection | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. The respiratory protection shall be in accordance to 29 CFR 1910.134. |

Section 9. Physical and chemical properties

Appearance

| Physical state | ÷ | Solid. |
|--|---|---|
| | | Powder. |
| Color | 1 | Not available. |
| Odor | 1 | Aromatic. |
| Odor threshold | 1 | Not available. |
| рН | 1 | Not applicable. |
| Melting point | 1 | Not available. |
| Boiling point | 1 | Not available. |
| Flash point | 1 | Closed cup: Not applicable. |
| Auto-ignition temperature | 1 | 500°C (932°F) |
| Decomposition temperature | 1 | Not available. |
| Flammability (solid, gas) | 1 | Not available. |
| Lower and upper explosive | : | Not applicable. |
| (flammable) limits | | |
| Evaporation rate | ÷ | Not available. |
| Vapor pressure | 4 | Not available. |
| Vapor density | 1 | Not applicable. |
| Relative density | 1 | 7.1 |
| Density(lbs / gal) | 1 | 59.25 |
| Bulk Density (g/cm ³) | 1 | 7.1 |
| Solubility | 1 | Insoluble in the following materials: cold water. |
| Partition coefficient: n- octanol/water | : | Not applicable. |

Date of issue 7 November 2021 Version 4

Product name SIGMAZINC 158 PIGMENT GREY

Section 9. Physical and chemical properties

Volatility : 0% (v/v), 0% (w/w)

% Solid. (w/w)

: 100

Section 10. Stability and reactivity

| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
|------------------------------------|---|
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8. |
| Incompatible materials | : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids. |
| Hazardous decomposition products | : Evolves hydrogen on contact with water. Depending on conditions, decomposition products may include the following materials: metal oxide/oxides |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---------------------------|--|--------------------|-------------------------|----------|
| zinc oxide | LC50 Inhalation Dusts and mists | Rat | >5700 mg/m ³ | 4 hours |
| | LD50 Dermal | Rat | >2000 mg/kg | - |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| Conclusion/Summary | : There are no data available on the | ne mixture itself. | | |
| Irritation/Corrosion | | | | |
| Conclusion/Summary | | | | |
| Skin | : There are no data available on the | ne mixture itself. | | |
| Eyes | : There are no data available on the mixture itself. | | | |
| Respiratory | : There are no data available on the mixture itself. | | | |
| <u>Sensitization</u> | | | | |
| Conclusion/Summary | | | | |
| Skin | : There are no data available on the | ne mixture itself. | | |
| Respiratory | : There are no data available on the mixture itself. | | | |
| <u>Mutagenicity</u> | | | | |
| Conclusion/Summary | : There are no data available on the mixture itself. | | | |
| Carcinogenicity | | | | |
| Conclusion/Summary | : There are no data available on the | ne mixture itself | | |

Product name SIGMAZINC 158 PIGMENT GREY

Section 11. Toxicological information

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Target organs

: Contains material which may cause damage to the following organs: upper respiratory tract.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

| | | | United States | Page: 8/12 |
|--------------------------------|----|---|---|---|
| Potential delayed effects | ł | There are no data available on the mixture itself. | | |
| Potential immediate effects | ł | There are no data available on the mixture itself. | | |
| <u>Long term exposure</u> | | | | |
| Potential delayed effects | ÷ | There are no data available on the mixture itself. | | |
| Potential immediate effects | : | There are no data available on the mixture itself. | | |
| Short term exposure | | | | |
| Conclusion/Summary | - | There are no data available on the mixture itself. I low level of dust can produce eye irritation. Repeat may lead to chronic respiratory irritation. Ingestion vomiting. This takes into account, where known, of also chronic effects of components from short-term inhalation and dermal routes of exposure and eye | ited or prolonged inha i may cause nausea, o lelayed and immediate n and long-term expos | lation of dust diarrhea and e effects and |
| - | | and also chronic effects from short and long ter | | |
| Ingestion | ; | No specific data. | | |
| Skin contact | : | coughing No specific data. | | |
| Inhalation | : | redness Adverse symptoms may include the following: respiratory tract irritation | | |
| Eye contact | 1 | Adverse symptoms may include the following: irritation | | |
| Over-exposure signs/sympto | on | <u>IS</u> | | |
| Ingestion | | No known significant effects or critical hazards. | | |
| Skin contact | : | may cause irritation of the nose, throat and lungs. No known significant effects or critical hazards. | - | |
| Inhalation | : | may cause irritation of the eyes. Exposure to airborne concentrations above statute | ory or recommended e | exposure limits |
| Eye contact | ÷ | Exposure to airborne concentrations above statute | ory or recommended e | xposure limits |

Product name SIGMAZINC 158 PIGMENT GREY

Section 11. Toxicological information

Potential chronic health effects

- : Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.
- : No known significant effects or critical hazards.
- Mutagenicity : No known significant effects or critical hazards.
- **Reproductive toxicity** : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

General

Carcinogenicity

| Product/ingredient name | Oral (mg/ kg) | Inhalation (gases) (ppm) | (vapors) | Inhalation (dusts and mists) (mg/ I) |
|-------------------------|------------------|--------------------------------|------------|---|
| | N/A N/A | N/A N/A | N/A N/A | N/A N/A |

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|---|---|----------------------|
| zinc oxide | Acute EC50 0.17 mg/l Acute EC50 0.481 mg/l Fresh water | Algae Daphnia - Daphnia magna - Neonate | 72 hours 48 hours |
| | Chronic NOEC 0.017 mg/l Fresh water | Algae | 72 hours |

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

<u>Mobility in soil</u>

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a

United States Page: 9/12

Product name SIGMAZINC 158 PIGMENT GREY

Section 13. Disposal considerations

safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

| • | | | |
|--------------------------------|---|--|--|
| | DOT | IMDG | ΙΑΤΑ |
| UN number | Not regulated. | UN3077 | UN3077 |
| UN proper shipping name | - | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. |
| | | (Zinc powder - zinc dust (stabilized), zinc oxide) | (Zinc powder - zinc dust (stabilized), zinc oxide) |
| Transport hazard class (es) | - | 9 | 9 |
| Packing group | - | Ш | Ш |
| Environmental hazards | No. | Yes. | Yes. |
| Marine pollutant substances | Not applicable. | (Zinc powder - zinc dust (stabilized), zinc oxide) | Not applicable. |
| Product RQ (Ibs) | 1052.6 | Not applicable. | Not applicable. |
| RQ substances | (Zinc powder - zinc dust (stabilized)) | Not applicable. | Not applicable. |

Additional information

| DOT | : Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements. | | | |
|--|---|--|--|--|
| IMDG | This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. The segregation group has been manually assigned based upon product analysis. | | | |
| IATA | : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8. | | | |
| Special prec | autions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. | | | |
| Trepenert in hulk according Net applicable | | | | |

Transport in bulk according : Not applicable. to IMO instruments

Product name SIGMAZINC 158 PIGMENT GREY

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are active or exempted.

SARA 302/304

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Classification

: COMBUSTIBLE DUSTS

Composition/information on ingredients

No products were found.

SARA 313

| Supplier notificationChemical nameSupplier notification: Zinc powder - zinc dust (stabilized) zinc oxide | <u>CAS number</u> 7440-66-6 1314-13-2 | <u>Concentration</u> 60 - 100 1 - 5 |
|---|---|---|
|---|---|---|

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 1 Flammability : 0 Physical hazards : 1

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)Health : 1Flammability : 0Instability : 1Date of previous issue: 5/29/2021Organization that prepared: EHSthe SDS

Product name SIGMAZINC 158 PIGMENT GREY

Section 16. Other information

| Key to abbreviations | : ATE = Acute Toxicity Estimate |
|----------------------|---|
| - | BCF = Bioconcentration Factor |
| | GHS = Globally Harmonized System of Classification and Labelling of Chemicals |
| | IATA = International Air Transport Association |
| | IBC = Intermediate Bulk Container |
| | IMDG = International Maritime Dangerous Goods |
| | LogPow = logarithm of the octanol/water partition coefficient |
| | MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) |
| | N/A = Not available |
| | SGG = Segregation Group |
| | UN = United Nations |
| | |

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.