# **SAFETY DATA SHEET**



#### Date of issue 7 November 2021

Version 3

### Section 1. Product and company identification

Product name
Product code
Other means of identification
Product type

- : SIGMASHIELD 1200 LT HARDENER LIGHT GREY
- : 00322070
- : Not available.
- : Liquid.

#### Relevant identified uses of the substance or mixture and uses advised against

#### **Identified uses**

Coating. Paints. Painting-related materials.

Uses advised against	Reason
Not applicable.	

Supplier's details:	
Supplier	<ul> <li>PPG Industries Colombia Ltda Calle 51 # 40-13 Municipio de Itagüí Antioquia, Colombia (57) (4) 3787400 (Porteria)</li> </ul>
Email address:	: HazComLatam@ppg.com
Emergency telephone number	: Colombia: 01 8000 916012 (CISPROQUIM) + 571 288 6012 (CISPROQUIM) Ecuador: 1800-59-3005 (CISPROQUIM) Peru: 080-050-847 (CISPROQUIM)

### Section 2. Hazards identification

Classification of the substance or mixture	: ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 SKIN CORROSION - Category 1A SERIOUS EYE DAMAGE - Category 1
	SKIN SENSITIZATION - Category 1
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
	AQUATIC HAZARD (ACUTE) - Category 2
	AQUATIC HAZARD (LONG-TERM) - Category 2

Code	00322070	Date of issue	7 November 2021	Version	3	
Product nam	le	SIGMASHIELD 1200 LT HARDENER LIGHT GREY				

Section 2. Hazards	identification
Target organs	: Contains material which causes damage to the following organs: blood, liver, heart, brain.
	Contains material which may cause damage to the following organs: kidneys, the nervous system, upper respiratory tract, skin, eyes, adrenal, central nervous system (CNS).
	Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 12.5% Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation
	toxicity: 11.9%
	Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 9.3%
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	<ul> <li>Harmful if swallowed.</li> <li>Toxic in contact with skin or if inhaled.</li> <li>Causes severe skin burns and eye damage.</li> <li>May cause an allergic skin reaction.</li> <li>May cause damage to organs through prolonged or repeated exposure.</li> <li>Toxic to aquatic life with long lasting effects.</li> </ul>
Precautionary statements	
Prevention	: Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.
Response	: Collect spillage. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	: None known.

3

### Section 3. Composition/information on ingredients

#### Substance/mixture Other means of identification

: Mixture

: Not available.

#### **CAS number/other identifiers**

CAS number

: Not applicable.

Ingredient name	%	CAS number
2,2'-dimethyl-4,4'-methylenebis(cyclohexylamine)	60 - 100	6864-37-5
benzyl alcohol	7 - <10	100-51-6
Formaldehyde, polymer with N,N-dimethyl-1,3-propanediamine and phenol	7 - <10	445498-00-0
N-(3-(trimethoxysilyl)propyl)ethylenediamine	3 - <5	1760-24-3
2,4,6-tris(dimethylaminomethyl)phenol	2 - <3	90-72-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

Description of necessary in	<u>Iu medsures</u>	
Eye contact	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.	
Inhalation	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.	
Skin contact	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.	
Ingestion	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.	
Indication of immediate me	<u>l attention and special treatment needed, if necessary</u>	
Notes to physician Specific treatments	In case of inhalation of decomposition products in a fire, symptoms may be dela The exposed person may need to be kept under medical surveillance for 48 hou No specific treatment.	
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	e I
Potential acute health effect		
Eye contact	Causes serious eye damage.	
Inhalation	Toxic if inhaled.	
Skin contact	Causes severe burns. Toxic in contact with skin. May cause an allergic skin reaction.	
Ingestion	Harmful if swallowed.	

Extinguiorning into and	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides Formaldehyde.
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	<ul> <li>Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.</li> </ul>

### Section 6. Accidental release measures

Personal precautions, protect	tive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### Methods and materials for containment and cleaning up

Small spill: Stop leak if without risk. Move containers from spill area. Dilute with water and<br/>mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry<br/>material and place in an appropriate waste disposal container. Dispose of via a<br/>licensed waste disposal contractor.

Code Product nam	00322070 1e	Date of issue SIGMASHIELD 1200 LT HARDENER LIGHT GREY	7 November 2021	 -
Sectio	$n \in \Delta$	ccidental release measures		

Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

Precautions for safe handling	-	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

Control parameters	
Occupational exposure limits	
None.	
Recommended monitoring procedures	: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

Section 8. Exposi	ure controls/personal protection
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye protection Skin protection	: Chemical splash goggles and face shield.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: nitrile neoprene
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Not available.
Odor	: Amine-like.
рН	: Not applicable.
Melting point	: Not available.
Boiling point	: >37.78°C (>100°F)
Flash point	: Closed cup: 106°C (222.8°F)
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 0.97
Solubility	: Insoluble in the following materials: cold water.

3

Code	00322070	Date of issue	7 November 2021	Version	3	
Product nam	е	SIGMASHIELD 1200 LT HARDENER LIGHT GREY				

# Section 9. Physical and chemical properties

Partition coefficient: n- octanol/water	: Not applicable.	
Auto-ignition temperature	: Not available.	
Decomposition temperature	: Not available.	
Viscosity	: <b>K</b> inematic (40°C (104°F)): >21 mm²/s (>21 cSt)	

### Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials carbon oxides nitrogen oxides Formaldehyde. metal oxide/oxides

### Section 11. Toxicological information

#### Information on toxicological effects

Product/ingredient name	Result	Species	Dose	Exposure
2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine)	LC50 Inhalation Dusts and mists	Rat	420 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	>0.2 g/kg	-
	LD50 Oral	Rat	>0.32 g/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>4178 mg/m <sup>3</sup>	4 hours
-	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-
N-(3-(trimethoxysilyl)propyl) ethylenediamine	LD50 Oral	Rat	2413 mg/kg	-
2,4,6-tris (dimethylaminomethyl) phenol	LD50 Dermal	Rabbit	1.28 g/kg	-
	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-

Conclusion/Summary : Ther

: There are no data available on the mixture itself.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
☑,4,6-tris (dimethylaminomethyl) phenol	Skin - Visible necrosis	Rabbit	-	4 hours	7 days

English (US) Colombia 7/12
----------------------------

	-		
Conclusion/Summary			
Skin	: There are no d	ata available on the mixture itse	elf.
Eyes	: There are no data available on the mixture itself.		
Respiratory	: There are no d	ata available on the mixture itse	elf.
<u>Sensitization</u>			
Product/ingredient name	Route of exposure	Species	Result
₽,4,6-tris (dimethylaminomethyl) phenol	skin	Guinea pig	Sensitizing
Conclusion/Summary			
Skin	: There are no d	ata available on the mixture itse	elf.
Respiratory	: There are no d	ata available on the mixture itse	elf.
<b>Mutagenicity</b>			
Not available.			
Conclusion/Summary Carcinogenicity Not available.	: There are no d	ata available on the mixture itse	elf.
Conclusion/Summary	: There are no d	ata available on the mixture itse	elf.
Reproductive toxicity			
Not available.			
Conclusion/Summary	: There are no d	ata available on the mixture itse	elf.
Teratogenicity			
Not available.			
Conclusion/Summary		ata available on the mixture itse	elf.
Specific target organ toxici	<u>ty (single exposur</u>	<u>e)</u>	

Not available.

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
2,2'-dimethyl-4,4'-methylenebis(cyclohexylamine)	Category 2	-	-

Target organs

: Contains material which causes damage to the following organs: blood, liver, heart, brain.

Contains material which may cause damage to the following organs: kidneys, the nervous system, upper respiratory tract, skin, eyes, adrenal, central nervous system (CNS).

#### Aspiration hazard

Name	Result
benzyl alcohol	ASPIRATION HAZARD - Category 2

English (US)	Colombia	8/12
--------------	----------	------

3

# Section 11. Toxicological information

Information on the likely routes of exposure	:	Not available.
Potential acute health effect	<u>s</u>	
Eye contact	:	Causes serious eye damage.
Inhalation	:	Toxic if inhaled.
Skin contact	:	Causes severe burns. Toxic in contact with skin. May cause an allergic skin reaction.
Ingestion	1	Harmful if swallowed.
Symptoms related to the phy	ysic	al, chemical and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following: pain watering redness
Inhalation	1	No specific data.
Skin contact	:	Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	-	Adverse symptoms may include the following: stomach pains
Delayed and immediate effect	cts	and also chronic effects from short and long term exposure
Conclusion/Summary	:	There are no data available on the mixture itself. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. This product either contains formaldehyde or is capable of releasing formaldehyde above 0.5 ppm under certain conditions. Formaldehyde is a known cancer hazard, a skin sensitizer and a respiratory sensitizer. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
Short term exposure Potential immediate		There are no data available on the mixture itself.
effects		
Potential delayed effects Long term exposure	:	There are no data available on the mixture itself.
Potential immediate effects	:	There are no data available on the mixture itself.

### Section 11. Toxicological information

**Potential delayed effects** : There are no data available on the mixture itself.

#### Potential chronic health effects

Not available.

General	: May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: 📈 known significant effects or critical hazards.

#### Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
SIGMASHIELD 1200 LT HARDENER LIGHT GREY	570.6	349.9	N/A	271.8	0.57
2,2'-dimethyl-4,4'-methylenebis(cyclohexylamine)	500	300	N/A	N/A	0.5
benzyl alcohol	1230	2000	N/A	N/A	1.5
Formaldehyde, polymer with N,N-dimethyl- 1,3-propanediamine and phenol	500	N/A	N/A	N/A	N/A
N-(3-(trimethoxysilyl)propyl)ethylenediamine 2,4,6-tris(dimethylaminomethyl)phenol	2413 1200	N/A 1280	N/A N/A	11 N/A	1.5 N/A

#### Other information :

: Not available.

### Section 12. Ecological information

#### **Ecotoxicity**

Product/ingredient name	Result	Species	Exposure
₽,4,6-tris (dimethylaminomethyl)phenol	Acute LC50 175 mg/l	Fish	96 hours

#### Persistence/degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
penzyl alcohol	-	-	Readily

#### **Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
5	1.8 0.87 0.219	-	low low low

English (US)	Colombia
--------------	----------

3

### Section 12. Ecological information

#### Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.	

**Other adverse effects** : No known significant effects or critical hazards.

### Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible.
	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-
	recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty
	containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	UN	Brazil (ANTT)	IMDG	ΙΑΤΑ
UN number	UN2922	UN2922	UN2922	UN2922
UN proper shipping name	CORROSIVE LIQUID, TOXIC, N.O.S.	CORROSIVE LIQUID, TOXIC, N.O.S.	CORROSIVE LIQUID, TOXIC, N.O.S.	CORROSIVE LIQUID, TOXIC, N.O.S.
	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine))	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine))	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine))	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine))
Transport hazard class(es)	8 (6.1)	8 (6.1)	8 (6.1)	8 (6.1)
Packing group	II	II	II	II
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine))	Not applicable.

Additional information					
UN	: None identified.				
Brazil	: None identified.				
<b>Risk number</b>	: 86				
IMDG	: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.				
ΙΑΤΑ	: The environmentally hazardous substance mark may appear if required by other transportation regulations.				

English (US)	Colombia
--------------	----------

### Section 14. Transport information

Special precautions for user	:	Transport within user's premises: always transport in closed containers that are
		upright and secure. Ensure that persons transporting the product know what to do in
		the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

### Section 15. Regulatory information

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

### Section 16. Other information

	н	ist	o	rv	,
--	---	-----	---	----	---

Date of previous issue	: 6/16/2019
Version	: <b>3</b> EHS
Key to abbreviations	<ul> <li>ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway</li> <li>ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road</li> <li>ATE = Acute Toxicity Estimate</li> <li>BCF = Bioconcentration Factor</li> <li>GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association</li> <li>IMDG = International Maritime Dangerous Goods</li> <li>LogPow = logarithm of the octanol/water partition coefficient</li> <li>MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)</li> <li>RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail</li> <li>UN = United Nations</li> </ul>
References	: ABNT NBR 14725-4: 2014 ANTT - National Land Transportation Agency

Indicates information that has changed from previously issued version.

#### <u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

3