## **SAFETY DATA SHEET**



## Date of issue/Date of revision21 December 2021Version 2

# Section 1. Identification of the substance/mixture and of the company/undertaking

Product code	: 000001185705
Product name	: PPG AQUACOVER 45 (TINTED) BASE L.
Other means of identification	: 00171469; 00190435; 00190436; 00191489; 00249408; 00249409; 00440558; 00440559; 00441134; 00441135
Product type	: Liquid.

<b>Relevant identified u</b>	uses of the substance	or mixture and	uses advised against

Product use	<ul> <li>Coating.</li> <li>Professional applications, Used by spraying.</li> </ul>
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
Supplier's details	: PPG Coatings (Thailand) Co., Ltd. 15 Rama 9 Road, Kwaeng Huamark, Khet Bangkapi, Bangkok 10240 Thailand T: 662-319-4190 #224 F: 662-319-4189
Emergency telephone number (with hours of operation)	: CHEMTREC 001-800-13-203-9987 (CCN 17704)

### Section 2. Hazards identification

Classification of the substance or mixture	<ul> <li>AMMABLE LIQUIDS - Category 4</li> <li>AQUATIC HAZARD (ACUTE) - Category 2</li> <li>AQUATIC HAZARD (LONG-TERM) - Category 2</li> <li>Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 2%</li> </ul>
GHS label elements	
Hazard pictograms	
Signal word	: Warning

### Section 2. Hazards identification

Hazard statements	:	Combustible liquid. Toxic to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Wear protective gloves, protective clothing and eye or face protection. Keep away from flames and hot surfaces. No smoking. Avoid release to the environment.
Response	1	🖉ollect spillage.
Storage	:	Store in a well-ventilated place. Keep cool.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	:	Prolonged or repeated contact may dry skin and cause irritation. Contains isothiazolinones. May cause allergic reaction.

### Section 3. Composition/information on ingredients

: Mixture

CAS number/c	other	<u>identifiers</u>		
CAS number			γ.	NI.

CAS number : Not applicable.		
Ingredient name	%	CAS number
Sobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol 1-(2-butoxy-1-methylethoxy)propan-2-ol tetraamminezinc(2+) carbonate 4,5-dichloro-2-octyl-2H-isothiazol-3-one 3-iodo-2-propynyl butylcarbamate pyrithione zinc	1- <3 1- <3 0.1- <0.3 <0.1 <0.1 <0.1	25265-77-4 29911-28-2 38714-47-5 64359-81-5 55406-53-6 13463-41-7

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### Section 4. First aid measures

Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Product name PPG AQUACOVER 45 (TINTED) BASE L.

### Section 4. First aid measures

Ingestion

: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

Potential acute health effec	<u>ts</u>	
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Defatting to the skin. May cause skin dryness and irritation.
Ingestion	:	No known significant effects or critical hazards.
Over-exposure signs/symp	ton	<u>15</u>
Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation dryness cracking
Ingestion	1	No specific data.
Indication of immediate med	<u>ica</u>	I attention and special treatment needed, if necessary
Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### See toxicological information (Section 11)

### Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Combustible liquid. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides

Date of issue 21 December 2021 Version 2

Product name PPG AQUACOVER 45 (TINTED) BASE L.

### Section 5. Fire-fighting measures

Special protective actions for fire-fighters	-	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions, protecti	ve equipment and emergency procedures
For non-emergency personnel	<ul> <li>No action shall be taken involving any personal risk or without suitable training.</li> <li>Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources.</li> <li>No flares, smoking or flames in hazard area. Avoid breathing vapor or mist.</li> <li>Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.</li> </ul>
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### Methods and materials for containment and cleaning up

Small spill	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

Precautions for safe : handling	Fut on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.
Conditions for safe storage, : including any incompatibilities	Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

Hygiene measures	1	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing.
Environmental exposure controls Individual protection measu		Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Appropriate engineering controls		Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Product name PPG AQUACOVER 45 (TINTED) BASE L.

### Section 8. Exposure controls/personal protection

	• •
Eye protection	: Safety glasses with side shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: For prolonged or repeated handling, use the following type of gloves:
	Recommended: Viton®, butyl rubber, nitrile rubber
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
1	

### Section 9. Physical and chemical properties

		Thailand Page: 6/13
Vapor density	:	
Vapor pressure	1	Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average: 2.79 kPa (20.93 mm Hg) (at 20°C)
Lower and upper explosive (flammable) limits	-	Greatest known range: Lower: 0.6% Upper: 20.4% (1-(2-butoxy-1-methylethoxy) propan-2-ol)
Flammability (solid, gas)	1	liquid
Evaporation rate	1	Highest known value: 0.02 ((2-methoxymethylethoxy)propanol) Weighted average: 0.02compared with butyl acetate
Flash point	1	Closed cup: 81°C (177.8°F)
Boiling point	1	>37.78°C (>100°F)
Melting point	1	May start to solidify at the following temperature: 0°C (32°F) This is based on data for the following ingredient: water. Weighted average: -8.38°C (16.9°F)
рН	1	8
Odor threshold	:	Not available.
Odor	:	Amine-like.
Color	:	Various
Physical state	:	Liquid.
Appearance		

Product name PPG AQUACOVER 45 (TINTED) BASE L.

### Section 9. Physical and chemical properties

	Highest known value: 7.5 (Air = 1) (isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol). Weighted average: 5.17 (Air = 1)	
Relative density	1.18	
Solubility	Partially soluble in the following materials: cold water.	
Partition coefficient: n- octanol/water	Not applicable.	
Auto-ignition temperature Decomposition temperature Viscosity	Lowest known value: 194°C (381.2°F) (1-(2-butoxy-1-methylethoxy)propan-2-ol). Stable under recommended storage and handling conditions (see Section 7). Kinematic (40°C): >21 mm <sup>2</sup> /s	

### Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	<ul> <li>Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides</li> </ul>

### Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
sobutyric acid, monoester with	LD50 Dermal	Rabbit	>15.2 g/kg	-
2,2,4-trimethylpentane-1,3-diol			00	
	LD50 Oral	Rat	6.5 g/kg	-
1-(2-butoxy-1-methylethoxy)propan-	LC50 Inhalation Dusts and mists	Rat	5.4 mg/l	4 hours
2-ol			Ũ	
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	4.05 g/kg	-
4,5-dichloro-2-octyl-2H-isothiazol- 3-one	LC50 Inhalation Dusts and mists	Rat	0.16 mg/l	4 hours
	LD50 Dermal	Rabbit	3.9 g/kg	-
	LD50 Oral	Rat	567 mg/kg	-
3-iodo-2-propynyl butylcarbamate	LC50 Inhalation Dusts and mists	Rat	0.67 mg/l	4 hours
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	1470 mg/kg	-

Thailand Page: 7/13

Date of issue 21 December 2021 Version 2

Product name PPG AQUACOVER 45 (TINTED) BASE L.

### Section 11. Toxicological information

pyrithione zinc	LC50 Inhalation Dusts and mists	Rat	0.14 mg/l	4 hours
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	177 mg/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
3-iodo-2-propynyl butylcarbamate	Eyes - Severe irritant	Rabbit	-	-	-
pyrithione zinc	Eyes - Cornea opacity	Rabbit	4	24 hours	24 hours
Conclusion/Summary					
Skin :	There are no data available	on the mixture	e itself.		
Eyes :	There are no data available	on the mixture	e itself.		
Respiratory :	There are no data available	on the mixture	e itself.		
Sensitization					
Conclusion/Summary					
Skin :	There are no data available	on the mixture	e itself.		
Respiratory :	There are no data available	on the mixture	e itself.		
Mutagenicity					
Conclusion/Summary :	There are no data available	on the mixture	e itself.		
<b>Carcinogenicity</b>					
Conclusion/Summary :	There are no data available	on the mixture	e itself.		
Reproductive toxicity					
Conclusion/Summary :	There are no data available	on the mixture	e itself.		
Teratogenicity					
Conclusion/Summary :	There are no data available	on the mixture	e itself.		
Specific target organ toxicit	t <u>y (single exposure)</u>				

Name		Route of exposure	Target organs
✓,5-dichloro-2-octyl-2H-isothiazol-3-one	Category 3	-	Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Name	•••	Route of exposure	Target organs
	Category 1 Category 1	-	trachea -

#### **Aspiration hazard**

Not available.

#### Information on the likely : Not available. routes of exposure

Thailand Page: 8/13

### Section 11. Toxicological information

#### Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Defatting to the skin. May cause skin dryness and irritation.
Ingestion	: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	<u>fects</u>
General	<ul> <li>Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/ or dermatitis.</li> </ul>
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

#### Numerical measures of toxicity

ŝ

#### Acute toxicity estimates

Route	ATE value
	357925.83 mg/kg 220941.87 mg/kg

#### Other information

Thailand	Page: 9/13

Product name PPG AQUACOVER 45 (TINTED) BASE L.

### Section 11. Toxicological information

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains isothiazolinones. May cause allergic reaction. Avoid contact with skin and clothing.

### Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Sobutyric acid, monoester with 2,2,4-trimethylpentane- 1,3-diol	Acute LC50 33 mg/l	Fish	96 hours
1-(2-butoxy-1-methylethoxy) propan-2-ol	Acute LC50 841 mg/l	Fish	96 hours
4,5-dichloro-2-octyl-2H- isothiazol-3-one	Acute EC50 267.368 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Acute LC50 0.318 mg/l Marine water	Crustaceans - Artemia sp.	48 hours
	Acute LC50 0.0027 mg/l Fresh water	Fish	96 hours
	Chronic NOEC 19.789 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Chronic NOEC 0.00056 mg/l Fresh water	Fish	97 days
3-iodo-2-propynyl butylcarbamate	Acute EC50 0.186 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
-	Acute LC50 0.067 mg/l	Fish	96 hours
	Chronic NOEC 0.049 mg/l	Fish	96 hours
pyrithione zinc	Acute EC50 5.513 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Acute LC50 0.0082 mg/l	Daphnia	48 hours
	Chronic NOEC 1.889 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Chronic NOEC 0.0027 mg/l	Daphnia	21 days

Conclusion/Summary

: There are no data available on the mixture itself.

#### Persistence/degradability

Product/ingredient name	Test	Result	Dose	Inoculum
sobutyric acid, monoester with 2,2,4-trimethylpentane- 1,3-diol	OECD 301B	>76 % - Readily - 28 days	-	-
,	OECD 302B	96 % - Readily - 28 days	-	-
3-iodo-2-propynyl butylcarbamate	-	25 % - Inherent - 28 days	-	-
pyrithione zinc	-	39 % - 28 days	-	-

**Conclusion/Summary** 

: There are no data available on the mixture itself.

### Product name PPG AQUACOVER 45 (TINTED) BASE L.

### Section 12. Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
sobutyric acid, monoester with 2,2,4-trimethylpentane- 1.3-diol	-	-	Readily
1-(2-butoxy-1-methylethoxy) propan-2-ol	-	-	Readily
3-iodo-2-propynyl butylcarbamate	-	-	Inherent
pyrithione zinc	-	50%; < 28 day(s)	Not readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
<b>is</b> obutyric acid, monoester with 2,2,4-trimethylpentane- 1,3-diol	3.2	-	low
1-(2-butoxy-1-methylethoxy)propan-2-ol pyrithione zinc	1.523 0.9		low low

#### Mobility in soil

Soil/water partition coefficient (Koc) Other adverse effects : Not available.

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	VN3082	VN3082	VN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(Nonylphenol, branched, ethoxylated)	(Nonylphenol, branched, ethoxylated)	(Nonylphenol, branched, ethoxylated)
Transport hazard class(es)	9	9	9
Packing group			
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(Nonylphenol, branched, ethoxylated)	Not applicable.

#### **Additional information**

UN	If his product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	If this product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IATA	: In this product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
_	

# **Special precautions for user : Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

### Section 15. Regulatory information

#### Harmful Chemicals List : Listed

- Safety, health and environmental regulations specific for the product
- : No known specific national and/or regional regulations applicable to this product (including its ingredients).

#### **International regulations**

Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants Not listed.

### Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 21 December 2021
Date of previous issue	: 2/26/2021
Version	: 2
Prepared by	: EHS
Key to abbreviations	<ul> <li>ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway</li> <li>ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road</li> <li>ATE = Acute Toxicity Estimate</li> <li>BCF = Bioconcentration Factor</li> <li>GHS = Globally Harmonized System of Classification and Labelling of Chemicals</li> <li>IATA = International Air Transport Association</li> <li>IMDG = International Maritime Dangerous Goods</li> <li>LogPow = logarithm of the octanol/water partition coefficient</li> <li>MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)</li> <li>RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail</li> <li>UN = United Nations</li> </ul>

Indicates information that has changed from previously issued version.

#### Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.