SAFETY DATA SHEET



Date of issue 29 December 2021

Version 4

Section 1. Product and company identification

Product name	1
Product code	1
Other means of identification	:
Product type	:

- SIGMAGUARD CSF 575 HARDENER CLEAR
- : 00171465
- : Not available.
 - Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Coating. Paints. Painting-related materials.

Uses advised against	Reason
Not applicable.	

Supplier's details:	
Supplier	 PPG Industrial do Brasil – Tintas e Vernizes Ltda Via Anhanguera KM 106, Bairro Sao Judas Tadeu Sumare / SP, Brasil 55 19 2103-6000 (Recepção e Portaria)
Email address:	: HazComLatam@ppg.com
Emergency telephone number	: 0800 707 1767 / 0800 707 7022 – Empresa Suatrans Cotec 0800 14 8110 – CEATOX - Centro de Assistência Toxicológica

Section 2. Hazards identification

Classification of the	: CUTE TOXICITY (oral) - Category 4
substance or mixture	ACUTE TOXICITY (dermal) - Category 5
	ACUTE TOXICITY (inhalation) - Category 4
	SKIN CORROSION - Category 1
	SERIOUS EYE DAMAGE - Category 1
	SKIN SENSITIZATION - Category 1
	TOXIC TO REPRODUCTION - Category 2
	AQUATIC HAZARD (LONG-TERM) - Category 3
Target organs	: Contains material which causes damage to the following organs: blood, liver, heart, brain.
	Contains material which may cause damage to the following organs: kidneys, upper respiratory tract, central nervous system (CNS).

Section 2. Hazarda	יכ	dentineation
		Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 1.6%
		Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 4.1%
		Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 43.2%
		Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 23.3%
GHS label elements		
Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	Harmful if swallowed or if inhaled. May be harmful in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. Harmful to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Solution before use. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Avoid breathing vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.
Response	:	F exposed or concerned: Get medical advice or attention. IF INHALED: Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	:	Not applicable.
Disposal	1	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	:	None known.

Section 3. Composition/information on ingredients

Substance/mixture Other means of identification

: Mixture

: Not available.

CAS number/other identifiers

CAS number

: Not applicable.

Ingredient name	%	CAS number
-aminomethyl-3,5,5-trimethylcyclohexylamine	30 - <60	2855-13-2
Phenol, methylstyrenated	20 - <30	68512-30-1
benzyl alcohol	20 - <30	100-51-6
2,4,6-tris(dimethylaminomethyl)phenol	10 - <12.5	90-72-2
salicylic acid	2 - <3	69-72-7
bis[(dimethylamino)methyl]phenol	1 - <2	71074-89-0

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Indication of immediate me	lical attention and special treatment needed, if necessary
Notes to physician Specific treatments	 In case of inhalation of decomposition products in a fire, symptoms may be delayed The exposed person may need to be kept under medical surveillance for 48 hours. No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Potential acute health effec	<u>s</u>
Eye contact	: Causes serious eye damage.
Inhalation	: Harmful if inhaled.
Skin contact	: Causes severe burns. May be harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed.

Section 4. First aid measures

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: $ ot\!$
Unsuitable extinguishing media	: Mone known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions :	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
Methods and materials for cor	ntainment and cleaning up
Small spill :	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 6. A	ccidental release measures
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Conditions for safe storage, including any incompatibilities	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters	
Occupational exposure limit	<u>s</u>
None.	
Recommended monitoring procedures	: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	: Verse only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

4

Section 8. Exposure controls/personal protection

Individual protection measures

Hygiene measures		Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye protection Skin protection	1	Chemical splash goggles and face shield.
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	:	butyl rubber
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	: Liquid.	
Color	: 🕅ear.	
Odor	: Amine-like.	
рН	: Not applicable.	
Melting point	: Not available.	
Boiling point	: >37.78°C (>100°F)	
Flash point	: ℤlosed cup: 100°C (212°F)	
Evaporation rate	: Not available.	
Flammability (solid, gas)	: Not available.	
Lower and upper explosive (flammable) limits	: Not available.	
Vapor pressure	: Not available.	
Vapor density	: Not available.	
Relative density	: 0.99	

Section 9. Physical and chemical properties

_		
Bulk density (g/cm³)	1	4.52
Solubility	:	Insoluble in the following materials: cold water.
Partition coefficient: n- octanol/water	:	Not applicable.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredient	ts.
Chemical stability	: The product is stable.	
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.	
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.	
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following mate carbon oxides nitrogen oxides	erials:

Section 11. Toxicological information

Information on toxicological effects

	Acute	toxicity
--	-------	----------

Product/ingredient name	Result	Species	Dose	Exposure
₿-aminomethyl-	LC50 Inhalation Dusts and mists	Rat	>5.01 mg/l	4 hours
3,5,5-trimethylcyclohexylamine				
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1030 mg/kg	-
Phenol, methylstyrenated	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>4178 mg/m ³	4 hours
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-
2,4,6-tris	LD50 Dermal	Rabbit	1.28 g/kg	-
(dimethylaminomethyl)				
phenol				
	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
salicylic acid	LD50 Oral	Rat	0.891 g/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result		Species	Score	e Ex	oosure	Observation
2,4,6-tris (dimethylaminomethyl) phenol	Skin - Visible ne	crosis	Rabbit	-	4 ho	ours	7 days
<u>Conclusion/Summary</u> Skin Eyes Respiratory <u>Sensitization</u>	: There are no o : There are no o : There are no o	data availa	ble on the mi	xture itse	lf.		
Product/ingredient name	Route of exposure	Species	1		Result		
G-aminomethyl- 3,5,5-trimethylcyclohexylamine 2,4,6-tris (dimethylaminomethyl) phenol	skin skin	Guinea Guinea	0		Sensitizin Sensitizin	•	
Conclusion/Summary Skin Respiratory <u>Mutagenicity</u> Not available.	: There are no o : There are no o						
Conclusion/Summary Carcinogenicity Not available.	: There are no o	data availa	ble on the mi	xture itse	lf.		
Conclusion/Summary Reproductive toxicity Not available.	: There are no o	data availa	ble on the mi	xture itse	lf.		
Conclusion/Summary Teratogenicity Not available.	: There are no o	data availa	ble on the mi	xture itse	lf.		
Conclusion/Summary Specific target organ toxicity Not available.	: There are no o y (single exposu		ble on the mi	xture itse	lf.		
Specific target organ toxicit Not available.	y (repeated expo	o <mark>sure)</mark>					
<u>Target organs</u>	brain.			-	-	-	lood, liver, hear s: kidneys, upp

Aspiration hazard

Section 11. Toxicological information

Name		Result
	benzyl alcohol	ASPIRATION HAZARD - Category 2

Information on the likely routes of exposure	1	Not available.
Potential acute health effects		
Eye contact	÷	Causes serious eye damage.
Inhalation	÷	Harmful if inhaled.
Skin contact	:	Zauses severe burns. May be harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	÷	Harmful if swallowed.
Symptoms related to the physical sector of the sector sect	sic	al, chemical and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following: pain watering redness
Inhalation	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	:	Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	:	Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

vapor concentrations in exce in adverse health effects suc irritation and adverse effects Symptoms and signs include drowsiness and, in extreme some of the above effects by that repeated exposure to or noise can cause greater hea If splashed in the eyes, the I Ingestion may cause nausea known, delayed and immedi	on the mixture itself. Exposure to component solvent ss of the stated occupational exposure limit may result h as mucous membrane and respiratory system on the kidneys, liver and central nervous system. headache, dizziness, fatigue, muscular weakness, cases, loss of consciousness. Solvents may cause absorption through the skin. There is some evidence ganic solvent vapors in combination with constant loud ring loss than expected from exposure to noise alone. quid may cause irritation and reversible damage. , diarrhea and vomiting. This takes into account, where ate effects and also chronic effects of components from posure by oral, inhalation and dermal routes of
---	--

29 December 2021

4

Section 11. Toxicological information

Short term exposure	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
<u>Long term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health eff	ects
Not available.	
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Construction in the	No los acos cincificante effecte en exitical benerale

Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
GMAGUARD CSF 575 HARDENER CLEAR	1338.1	2242.3	N/A	N/A	3.9
3-aminomethyl-3,5,5-trimethylcyclohexylamine	1030	2500	N/A	N/A	N/A
Phenol, methylstyrenated	2500	2500	N/A	N/A	N/A
benzyl alcohol	1230	2000	N/A	N/A	1.5
2,4,6-tris(dimethylaminomethyl)phenol	1200	1280	N/A	N/A	N/A
salicylic acid	891	N/A	N/A	N/A	N/A

Other information

: Not available.

Section 12. Ecological information

Ecotoxicity

Product/ingredient name	Result	Species	Exposure
2,4,6-tris (dimethylaminomethyl)phenol	Acute LC50 175 mg/l	Fish	96 hours
	Acute EC50 1147.57 mg/l Fresh water	Daphnia - Daphnia longispina - Neonate	48 hours
	Chronic NOEC 5.6 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	21 days

Persistence/degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
<mark>b∕e</mark> nzyl alcohol	-	-	Readily

English (US	South America	10/12
-------------	---------------	-------

Section 12. Ecological information

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	0.99	-	low
Phenol, methylstyrenated benzyl alcohol 2,4,6-tris (dimethylaminomethyl)phenol	3.627 0.87 0.219		low low low
salicylic acid	2.21 to 2.26	-	low

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when
	handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	Brazil (ANTT)	IMDG	ΙΑΤΑ
UN number	UN3066	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	8	8	8	8
Packing group	II	II	II	II
Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

UN : None identified.

Section 14. Transport information

Brazil	: None identified.
Risk number	: 80
IMDG	: None identified.
ΙΑΤΑ	: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

History

: No known specific national and/or regional regulations applicable to this product (including its ingredients).

Section 16. Other information

<u>History</u>	
Date of previous issue	: 12/19/2018
Version	: 4
	EHS
Key to abbreviations	 ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail UN = United Nations
References	: ABNT NBR 14725-4: 2014 ANTT - National Land Transportation Agency

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.