SAFETY DATA SHEET

PPG AQUACOVER 20 BASE Z



Date of issue 26 April 2022

Version 4

1. Product and company identification

: PPG AQUACOVER 20 BASE Z **Product name**

Product code : 00440541 **Product type** : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

Uses advised against : Not applicable.

Supplier's details : PPG PMC Japan Co., Ltd.

8F, Shintetsu Bldg., 1-1, Daikaidori 1-chome, Kobe 652-0803

Tel: +81 78 574 2777 Fax: +81 78 576 0035

Emergency telephone

number

: 078 574 2777

2. Hazards identification

GHS Classification ERM CELL MUTAGENICITY - Category 2

CARCINOGENICITY - Category 1A

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 HAZARDOUS TO THE AQUATIC ENVIRONMENT - ACUTE HAZARD - Category 2 HAZARDOUS TO THE AQUATIC ENVIRONMENT - CHRONIC HAZARD -

Category 2

GHS label elements

Hazard pictograms





Signal word

Hazard statements Suspected of causing genetic defects.

May cause cancer.

May cause damage to organs. (respiratory organs, systemic)

May cause damage to organs through prolonged or repeated exposure. (blood

system, immune system, kidneys, respiratory organs)

Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

> Page: 1/13 **Japan**

Product code 00440541 Version 4 Date of issue 26 April 2022

Product name PPG AQUACOVER 20 BASE Z

2. Hazards identification

: Collect spillage. IF exposed or concerned: Call a POISON CENTER or doctor. Response

Storage : Store locked up.

: Dispose of contents and container in accordance with all local, regional, national **Disposal**

and international regulations.

result in classification

Other hazards which do not : Contains isothiazolinones. May cause allergic reaction.

3. Composition/information on ingredients

Substance/mixture : Mixture

CAS number/other identifiers

CAS number : Not applicable. **CSCL** number : Not available.

Ingredient name	%	CAS number	CSCL
rystalline silica, respirable powder (>10 microns)	12.5 - <15	14808-60-7	1-548
Talc containing no asbestos or quartz	3 - <5	14807-96-6	Not available.
barium diboron tetraoxide	3 - <5	13701-59-2	1-40; 9-2405
zinc phosphate	2 - <3	7779-90-0	1-1181; 1-526
Zinc oxide	2 - <3	1314-13-2	1-561
2,2,4-trimethylpentane-1,3-diol monoisobutyrate	2 - <3	25265-77-4	Not available.
crystalline silica (quartz)	1 - <2	14808-60-7	1-548
Distillates (petroleum), hydrotreated heavy naphthenic	0.1 - <0.2	64742-52-5	Not available.
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	<0.1	55965-84-9	5-5235; 9-378

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

4. First aid measures

Description of necessary first aid measures

Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the

eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

If swallowed, seek medical advice immediately and show this container or label. Ingestion

Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

: No known significant effects or critical hazards. Eye contact Inhalation : No known significant effects or critical hazards.

: May cause damage to organs following a single exposure in contact with skin. Skin contact

Japan Page: 2/13 Product code 00440541 Date of issue 26 April 2022 Version 4

Product name PPG AQUACOVER 20 BASE Z

4. First aid measures

Ingestion : May cause damage to organs following a single exposure if swallowed.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon oxides

phosphorus oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Japan Page: 3/13

6. Accidental release measures

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Precautions for safe handling

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage: Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Japan Page: 4/13

8. Exposure controls/personal protection

Ingredient name	Exposure limits
rystalline silica, respirable powder (>10 microns)	Japan Society for Occupational Health (Japan, 3/2021). OEL-C: 0.03 mg/m³ Form: Respirable dust
Talc containing no asbestos or quartz	Japan Society for Occupational Health (Japan, 3/2021).
	OEL-M: 0.5 mg/m³ 8 hours. Form: Respirable dust (Class 1 Dust) OEL-M: 2 mg/m³ 8 hours. Form: Total dust (Class 1 Dust)
Zinc oxide	Japan Society for Occupational Health (Japan, 3/2021). OEL-M: 1 mg/m³ 8 hours. Form: Respirable dust (Class 2 Dust) OEL-M: 4 mg/m³ 8 hours. Form: Total dust (Class 2 Dust)
crystalline silica (quartz)	Japan Society for Occupational Health (Japan, 3/2021).
Distillates (petroleum), hydrotreated heavy naphthenic	OEL-C: 0.03 mg/m³ Form: Respirable dust Japan Society for Occupational Health (Japan, 3/2021). OEL-M: 3 mg/m³ 8 hours. Form: Mist

procedures

Recommended monitoring: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection **Skin protection Hand protection**

: Safety glasses with side shields.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

> Japan Page: 5/13

Product code 00440541 Date of issue 26 April 2022 Version 4

Product name PPG AQUACOVER 20 BASE Z

8. Exposure controls/personal protection

Gloves : For prolonged or repeated handling, use the following type of gloves:

Recommended: nitrile rubber, Chloroprene, Viton®

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection: Respirator selection must be based on known or anticipated exposure levels, the

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary.

9. Physical and chemical properties

Appearance

Physical state : Liquid.

Color : Various

Odor : Amine-like.

Boiling point : >37.78°C (>100°F)

Flash point : Closed cup: 120°C (248°F)

Relative density : 1.31

Solubility: Partially soluble in the following materials: cold water.

Viscosity : Not Applicable

10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

Incompatible materials: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition

products

: Depending on conditions, decomposition products may include the following

materials: carbon oxides phosphorus oxides metal oxide/oxides

Japan Page: 6/13

11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
barium diboron tetraoxide	LC50 Inhalation Dusts and mists	Rat	>3540 mg/m ³	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	0.85 g/kg	-
zinc phosphate	LC50 Inhalation Dusts and mists	Rat	>5.7 mg/l	4 hours
	LD50 Oral	Rat	>5000 mg/kg	-
Zinc oxide	LC50 Inhalation Dusts and mists	Rat	>5700 mg/m ³	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
2,2,4-trimethylpentane-	LD50 Dermal	Rabbit	>15.2 g/kg	-
1,3-diol monoisobutyrate				
	LD50 Oral	Rat	6.5 g/kg	-
Distillates (petroleum), hydrotreated heavy naphthenic	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	_
	LD50 Oral	Rat	15 g/kg	_
reaction mass of: 5-chloro-	LD50 Oral	Rat	53 mg/kg	_
2-methyl-4-isothiazolin-		T tat	oo mg/ng	
3-one [EC no. 247-500-7]				
and 2-methyl-2H-isothiazol-				
3-one [EC no. 220-239-6] (3:				
1)				

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	3.3	Route of exposure	Target organs
ralc containing no asbestos or quartz Zinc oxide	Category 1 Category 1	-	respiratory organs respiratory organs, systemic

Specific target organ toxicity (repeated exposure)

Japan Page: 7/13

Product code 00440541 Date of issue 26 April 2022 Version 4
Product name PPG AQUACOVER 20 BASE Z

11. Toxicological information

Name	Category	Route of exposure	Target organs
▼alc containing no asbestos or quartz zinc phosphate crystalline silica (quartz)	Category 1 Category 1 Category 1	-	respiratory organs blood system immune system, kidneys, respiratory organs

Aspiration hazard

Not available.

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Skin contact: May cause damage to organs following a single exposure in contact with skin.

Ingestion : May cause damage to organs following a single exposure if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
 Inhalation : No specific data.
 Skin contact : No specific data.
 Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

General: May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity: Suspected of causing genetic defects.

Reproductive toxicity: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Japan Page: 8/13

Date of issue 26 April 2022 Version 4

Product name PPG AQUACOVER 20 BASE Z

Product code 00440541

11. Toxicological information

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
PPG AQUACOVER 20 BASE Z	81699.3	81699.3	N/A	N/A	49
barium diboron tetraoxide	2500	2500	N/A	N/A	1.5
Zinc oxide	N/A	2500	N/A	N/A	N/A
2,2,4-trimethylpentane-1,3-diol monoisobutyrate	6500	N/A	N/A	N/A	N/A
Distillates (petroleum), hydrotreated heavy naphthenic	15000	N/A	N/A	N/A	N/A
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	53	50	N/A	0.5	0.05

Other information

Sanding and grinding dusts may be harmful if inhaled. Contains isothiazolinones. May cause allergic reaction.

12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
zinc phosphate	Acute LC50 0.112 mg/l	Fish	96 hours
	Chronic NOEC 0.026 mg/l	Fish	30 days
Zinc oxide	Acute EC50 0.17 mg/l	Algae	72 hours
	Acute EC50 0.481 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Chronic NOEC 0.017 mg/l Fresh water	Algae	72 hours
2,2,4-trimethylpentane- 1,3-diol monoisobutyrate	Acute LC50 33 mg/l	Fish	96 hours
Distillates (petroleum), hydrotreated heavy naphthenic	Acute LC50 >100 mg/l	Fish	96 hours

Persistence/degradability

Product/ingredient name	Test	Result		Dose		Inoculum
2,2,4-trimethylpentane- 1,3-diol monoisobutyrate	OECD 301B	>76 % - Re	adily - 28 days	-		-
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2,2,4-trimethylpentane- 1,3-diol monoisobutyrate	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2,2,4-trimethylpentane- 1,3-diol monoisobutyrate	3.2	-	low

Mobility in soil

Soil/water partition coefficient (K_{oc})

: Not available.

Mobility : Not available.

Japan Page: 9/13

12. Ecological information

Other adverse effects

: No known significant effects or critical hazards.

13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

	UN	IMDG	IATA
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (trizinc bis(orthophosphate),	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (trizinc bis(orthophosphate),	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (trizinc bis(orthophosphate),
	zinc oxide)	zinc oxide)	zinc oxide)
Transport hazard class(es)	9	9	9
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(trizinc bis(orthophosphate), zinc oxide)	Not applicable.

Additional information

UN

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IMDG

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IATA

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg. provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

Japan Page: 10/13 Product code 00440541 Date of issue 26 April 2022 Version 4 **Product name PPG AQUACOVER 20 BASE Z**

15. Regulatory information

Fire Service Law

Category	Substance name/Type	Danger category	Signal word	Designated quantity
Specified flammables	Combustible liquid	Not applicable	Not applicable	2 m³

Pollutant Release and Transfer Registers (PRTR)

Ingredient name	%	Status	Reference number
Foron compounds	≤10	Class 1	405

ISHL

Ordinance on the prevention of the hazard due to specified chemical substances

None of the components are listed.

Substances requiring labelling

Ingredient name	%	Status	Reference number
⊘ rystalline silica	≥10 - ≤20	Listed	165-2
Barium and its water soluble compounds	≤10	Listed	449
Zinc oxide	≤10	Listed	188

Chemicals requiring notification

Ingredient name	%	Status	Reference number
⊘ rystalline silica	≥10 - ≤20	Listed	165-2
Barium and its water soluble compounds	≤10	Listed	449
Zinc oxide	≤10	Listed	188
Mineral oil	≤10	Listed	168

Carcinogen

None of the components are listed.

Mutagen

None of the components are listed.

Corrosive liquid : Not listed

Occupational Safety and

: Øxidizing

Health Law

Regulations on the

: Not listed

Prevention of Tetraalkyl

Lead Poisoning

Harmful Substances

Subject to Obtaining Permission for

: Not listed

Manufacturing

Harmful Substances,

: Not listed

Prohibited for Manufacturing

Dangerous Substances

: Øxidizing

Japan Page: 11/13 Product code 00440541 Version 4 Date of issue 26 April 2022

Product name PPG AQUACOVER 20 BASE Z

15. Regulatory information

Lead regulation : Not listed **Organic solvents** : Not applicable.

poisoning prevention

Poisonous and Deleterious Substances

None of the components are listed.

Chemical Substances Control Law (CSCL)

Ingredient name	%	Status	Reference number
ropane-1,2-diol Isobutyraldehyde	0.308 0.0114	Priority assessment Priority assessment	106 111
Methacrylic acid	0.001045	Priority assessment	35
Acrylonitrile	0.00041013	Priority assessment	39

High Pressure Gas Control

Law

: Not available.

Explosives Control Law

None of the components are listed.

Law concerning prevention : Not available.

of pollution of the ocean

Maritime Safety Law

Notification Regulating Transportation of Dangerous Materials by Sea

None of the components are listed.

Container class

None of the components are listed.

JSOH Carcinogen : Group 1 **List of Specially Controlled**

Industrial Waste

: Not listed

: All components are listed or exempted. **Japan inventory**

Road law : Not available.

16. Other information

History

Date of issue/Date of : 26 April 2022

revision

Date of previous issue : 7/10/2021

Version : 4 : EHS Prepared by

Key to abbreviations : ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

Japan Page: 12/13 Product code 00440541 Date of issue 26 April 2022 Version 4

Product name PPG AQUACOVER 20 BASE Z

16. Other information

IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships,
1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
RID = The Regulations concerning the International Carriage of Dangerous Goods
by Rail
UN = United Nations

▼ Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Japan Page: 13/13