SAFETY DATA SHEET

Date of issue/Date of revision 14 June 2022

Version 8

Section 1. Identification

Product code	: 1114A-A3500/0.49L	
Product identifier	: AMERCOAT 114A OFF WHITE RESIN	
Recommended use and rest	<u>ictions</u>	
Use of the substance/ mixture	: Coating.	
Uses advised against	: Not applicable.	
Supplier's details	: PPG Industries Australia Pty Limited (ABN 82 055 500 939) 14-20 McNaughton Rd CLAYTON Victoria 3168 Tel: (03) 9263 6000 Fax: (03) 9263 6970	
Emergency telephone number	: Australia 1800 883 254 / New Zealand 0800 000 096 For international shipping emergencies: 1-412-391-1618	

Section 2. Hazard(s) identification

Classification of the substance or mixture	: SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
GHS label elements	
Hazard pictograms	
Signal word	: DANGER
Hazard statements	: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Causes damage to organs through prolonged or repeated exposure. (lungs)
Precautionary statement	
Prevention	: Wear protective gloves. Wear eye or face protection. Do not breathe vapour. Wash thoroughly after handling.
Response	: Set medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Not applicable.



Section 2. Hazard(s) identification

Other hazards which do not : None known. result in classification

Section 3. Composition and ingredient information

Substance/mixture

: Mixture

CAS number/other identifiers

CAS number	: Not applicable.
EC number	: Mixture.
Ingredient name	

Ingredient name	CAS number	% (w/w)
s-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	30 - 60
crystalline silica, respirable powder (<10 microns)	14808-60-7	10 - <30
p-tert-butylphenyl 1-(2,3-epoxy)propyl ether	3101-60-8	1 - <10

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment or have an OEL and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

		Demo: 2/41
Ingestion	: No specific data.	
Skin contact	: Adverse symptoms may include the following: irritation redness	
Inhalation	: No specific data.	
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness	
<u>Over-exposure signs</u>	/symptoms	
Ingestion	: No known significant effects or critical hazards.	
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.	
Inhalation	: No known significant effects or critical hazards.	
Eye contact	: Causes serious eye irritation.	
Potential acute health	h effects	
Most important sympt	oms/effects, acute and delayed	

Section 4. First aid measures

Indication of immediate medical attention and special treatment needed, if necessary		
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. 	
Specific treatments	: No specific treatment.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	 Decomposition products may include the following materials: carbon oxides sulfur oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Hazchem code	: •3Z

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency proceduresFor non-emergency
personnel: No action shall be taken involving any personal risk or without suitable training.
Evacuate surrounding areas. Keep unnecessary and unprotected personnel from
entering. Do not touch or walk through spilt material. Avoid breathing vapour or
mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is
inadequate. Put on appropriate personal protective equipment.For emergency responders: If specialised clothing is required to deal with the spillage, take note of any
information in Section 8 on suitable and unsuitable materials. See also the
information in "For non-emergency personnel".Environmental precautions: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains
and sewers. Inform the relevant authorities if the product has caused environmental
pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Product name AMERCOAT 114A OFF WHITE RESIN

Section 6. Accidental release measures

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	
Protective measures	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls and personal protection

Control parameters

controls

Occupational exposure limits s-[4-(2,3-epoxipropoxi)phenyl]propane	DFG MAC-values list (Germany, 10/2021).
p-tert-butylphenyl 1-(2,3-epoxy)propyl ether	Skin sensitiser. DFG MAC-values list (Germany, 10/2021). Skin sensitiser.
Appropriate engineering : If user operations	s generate dust, fumes, gas, vapour or mist, use process

enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

For products that are sprayed, where practicable use a spray booth designed and maintained in accordance with AS/ NZS 4114.

Section 8. Exposure controls and personal protection

Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measure	<u>es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	1	Chemical splash goggles.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	:	butyl rubber
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Restrictions on use	;	Not applicable.

References: Eye protectors should conform to AS/NZS 1336 and AS/NZS 1337. Chemical-resistant gloves should conform to AS/NZS 2161.1. Respiratory protection should conform to AS/NZS 1715 and AS/NZS 1716. Occupational footwear should conform to AS/NZS 2210.

Section 9. Physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: White.
Odour	: Characteristic.
Odour threshold	: Not available.
рН	: Not applicable.
Melting point	: Not available.
Boiling point	: >37.78°C (>100°F)
Flash point	: Closed cup: 93.33°C (200°F)

Section 9. Physical and chemical properties

Evaporation rate	0.02 (butyl acetate = 1)
Flammability (solid, gas)	Not a	vailable.
Lower and upper explosive (flammable) limits	Not a	vailable.
Vapour pressure	0.11	‹Pa (0.8 mm Hg)
Vapour density	Not a	vailable.
Relative density	2.03	
Solubility	Insolu	ble in the following materials: cold water.
Solubility in water	1 g/l	
Partition coefficient: n- octanol/water	Not a	pplicable.
Auto-ignition temperature	Not a	vailable.
Decomposition temperature	Not a	vailable.
Viscosity	Not A	pplicable

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Stable under recommended storage and handling conditions (see Section 7). When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides sulfur oxides metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
bis-[4-(2,3-epoxipropoxi) phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
Conclusion/Summary	: There are no data available on	the mixture itse	lf.	

Irritation/Corrosion

Section 11. Toxicological information

Product/ingredient name	Result		Species	Scor	e	Exposure	Observation
øís-[4-(2,3-epoxipropoxi) phenyl]propane	Eyes - Mild irritan	ıt	Rabbit	-		24 hours	-
	Eyes - Redness o conjunctivae	of the	Rabbit	0.4		24 hours	-
	Skin - Oedema		Rabbit	0.5		4 hours	-
	Skin - Erythema/l		Rabbit	0.8		4 hours	-
	Skin - Mild irritan	t	Rabbit	-		4 hours	-
Conclusion/Summary							
Skin	: There are no d						
Eyes	: There are no d						
Respiratory	: There are no d	ata availat	ole on the mi	xture itse	elt.		
<u>Sensitisation</u>		1					
Product/ingredient name	Route of exposure	Species			Resu	t	
bis-[4-(2,3-epoxipropoxi) phenyl]propane	skin	Mouse			Sensi	tising	
Conclusion/Summary							
Skin	: There are no d	lata availat	le on the mi	xture itse	elf.		
Respiratory	: There are no d	ata availat	ole on the mi	xture itse	elf.		
<u>Mutagenicity</u>							
Not available.							
Conclusion/Summary	: There are no d	ata availab	le on the mi	xture itse	elf.		
Carcinogenicity							
Not available.							
Conclusion/Summary	: There are no d	ata availat	le on the mi	xture itse	elf.		
Reproductive toxicity							
Not available.							
Conclusion/Summary	: There are no d	lata availak	la an tha mi	vturo itor	lt		
	. There are no u	ala avallal		XIULE IISE	<i>.</i>		
<u>Feratogenicity</u>							
Not available.							
Conclusion/Summary	: There are no d	ata availab	le on the mi	xture itse	elf.		
<u>Specific target organ toxici</u>	<u>ty (single exposur</u>	<u>·e)</u>					
Not available.							
<u>Specific target organ toxici</u>	ty (repeated expo	sure)					
Name			Category	1	Route o	of	Target organs

Name		Route of exposure	Target organs
ystalline silica, respirable powder (<10 microns)	Category 1	inhalation	lungs

Aspiration hazard

Not available.

Information on likely routes : Not available. of exposure

Section 11. Toxicological information

Potential acute health effec	'S	-
Eye contact	: Causes serious eye irritation.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.	
Ingestion	: No known significant effects or critical hazards.	

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

	Australia GHS Page: 8/12
Reproductive toxicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
General	: Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Not available.	
Potential chronic health effe	ects
Potential delayed effects	: There are no data available on the mixture itself.
Potential immediate effects	: There are no data available on the mixture itself.
Long term exposure	
Potential immediate effects Potential delayed effects	There are no data available on the mixture itself.There are no data available on the mixture itself.
Short term exposure	
	duration and level of exposure to dust from sanding surfaces or mist from spray applications. This product contains TiO2 which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many PPG products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
Conclusion/Summary	: There are no data available on the mixture itself. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the

Section 11. Toxicological information

Numerical measures of toxicity

Acute toxicity estimates **Product/ingredient name** Oral (mg/ Dermal Inhalation Inhalation Inhalation (vapours) (dusts kg) (mg/kg) (gases) (ppm) (mg/l) and mists) (mg/l)AMERCOAT 114A OFF WHITE RESIN N/A N/A N/A 163.5 N/A bis-[4-(2,3-epoxipropoxi)phenyl]propane 15000 23000 N/A N/A N/A

Section 12. Ecological information

ToxicityProduct/ingredient nameResultSpeciesExposurebis-[4-(2,3-epoxipropoxi)
phenyl]propaneAcute LC50 1.8 mg/l Fresh water
Chronic NOEC 0.3 mg/lDaphnia - daphnia magna
Daphnia48 hours
21 days

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxi) phenyl]propane	-	-	Not readily

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
------------------	---

Section 14. Transport information

	ADG	IMDG	ΙΑΤΑ
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N. O.S. (bis-[4- (2,3-epoxipropoxi)phenyl] propane, p-tert-butylphenyl 1-(2,3-epoxy)propyl ether)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N. O.S. (bis-[4- (2,3-epoxipropoxi)phenyl] propane, p-tert-butylphenyl 1-(2,3-epoxy)propyl ether)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N. O.S. (bis-[4- (2,3-epoxipropoxi)phenyl] propane, p-tert-butylphenyl 1-(2,3-epoxy)propyl ether)
Transport hazard class (es)	9	9	9
Packing group	III		III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane, p-tert- butylphenyl 1-(2,3-epoxy) propyl ether)	Not applicable.

Additional information

/ automai intoini				
ADG	:	The product is not regulated as a dangerous good when transported by road or rail in either an IBC, or in other container types if \leq 500 kg. This product is not regulated as a dangerous good when transported in sizes of \leq 5 L or \leq 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.		
Hazchem code	1	•3Z		
IMDG	1	This product is not regulated as a dangerous good when transported in sizes of \leq 5 L or \leq 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.		
ΙΑΤΑ	1	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.		
Special precautio	ons	s for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.		
Transport in bulk to IMO instrumer		ccording : Not applicable.		

Section 15. Regulatory information

 Standard for the Uniform Scheduling of Medicines and Poisons

 SUSMP
 : Not scheduled

 Model Work Health and Safety Regulations - Scheduled Substances

Section 15. Regulatory information

Ingredient name	<u>Schedule</u>
rystalline silica, respirable powder (<10 microns)	Restricted hazardous chemical [For abrasive blasting at a concentration of greater than 1%]

Australia inventory (AIIC) New Zealand (NZIoC) : All components are listed or exempted.: All components are listed or exempted.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Section 16. Any other relevant information

<u>History</u>	
Date of issue/Date of revision	: 14 June 2022
Date of previous issue	: 10/4/2021
Prepared by	: EHS
Key to abbreviations	: ADG = Australian Dangerous Goods ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) NOHSC = National Occupational Health and Safety Commission SUSMP = Standard Uniform Schedule of Medicine and Poisons UN = United Nations
References	: Not available.
Indicates information th	at has changed from previously issued version.

Indicates information that has changed from previously issued version. <u>Notice to reader</u>

Product name AMERCOAT 114A OFF WHITE RESIN

Section 16. Any other relevant information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.