Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SAFETY DATA SHEET

Date of issue/Date of revision

: 15 June 2022

Version : 1



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: PITT-CHAR XP BASE WHITE PF
Product code	: 000001104885
Product description	:
Product type	: Liquid.
Other means of identification	: 00352601; 00354397
1.2 Relevant identified uses	of the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL Tweemontstraat 104 B-2100 Deurne Belgium Telephone +32-33606311 Fax +32-33606435

e-mail address of person : Product.Stewardship.EMEA@ppg.com

responsible for this SDS

PPG Architectural Coatings UK Ltd, Huddersfield Road, Birstall, West Yorkshire WF17 9XA, Tel: +44 (0) 1924 354000

1.4 Emergency telephone number

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture <u>Classification according to UK CLP/GHS</u> Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Repr. 2, H361d Aquatic Chronic 2, H411

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word

: Warning

English (GB)

Code PITT-CH/	: 000001104885 AR XP BASE WHITE PF	Date of issue/Date of revision	: 15 June 2022
SECTI	ON 2: Hazards identificat	ion	

Hazard statements		Causes skin irritation.
Thazard Statements	1	May cause an allergic skin reaction.
		Causes serious eye irritation.
		Suspected of damaging the unborn child.
		Toxic to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Avoid breathing vapour.
Response	1	Collect spillage.
Storage	1	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
		P202, P280, P273, P261, P391, P501
Supplemental label elements	:	Contains epoxy constituents. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

Mixture :

Product/ingredient name	Identifiers	%	Classification	Туре	
hexaboron dizinc undecaoxide	REACH #: 01-2119691658-19 EC: 235-804-2 CAS: 12767-90-7	≥10 - <25	Eye Irrit. 2, H319 Repr. 2, H361d (oral) Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	[1]	
Dodecanedioic acid, polymer with 2,2'-[1,4-butanediylbis (oxymethylene)]bis[oxirane], (chloromethyl)oxirane, 4,4'- (1-methylethylidene)bis[phenol], nonanedioic acid and 2,2'-oxybis [ethanol]	CAS: 139651-91-5	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	[1]	
Borate(5-), bis[µ- oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen,	REACH #: 01-2119970312-43 CAS: 12046-04-7	≥10 - ≤25	Repr. 2, H361d	[1]	
dihydrate, (T-4)- English (GB)	United I	Kingdom (UK)			

Code: 000001104885Date of issue/Date of revision: 15 JunePITT-CHAR XP BASE WHITE PF				2022	
SECTION 3: Compositio	n/information on i	ngredients			
phosphorous oxychloride, reaction products with propylene oxide	REACH #: 01-2119486772-26 CAS: 1244733-77-4	≥10 - <25	Acute Tox. 4, H302	[1]	
bis-[4-(2,3-epoxipropoxi)phenyl] propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥5.0 - ≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]	

<1.0

Skin Sens. 1B, H317

Aquatic Chronic 3,

See Section 16 for

H412

[1]

 the full text of the H

 statements declared

 above.

 There are no additional ingredients present which, within the current knowledge of the supplier and in the

 concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of

 equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

N,N'-ethane-1,2-diylbis

(12-hydroxyoctadecan-1-amide)

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

REACH #:

01-2119978265-26

EC: 204-613-6

CAS: 123-26-2

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects		
Eye contact	:	Causes serious eye irritation.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Causes skin irritation. May cause an allergic skin reaction.
Ingestion	:	No known significant effects or critical hazards.
Over-exposure signs/sympto	om	<u>15</u>
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	:	Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations

Code : 00000110488 PITT-CHAR XP BASE WHITE	
SECTION 4: First aid	l measures
Skin contact	: Adverse symptoms may include the following: irritation redness reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
4.3 Indication of any immedi	ate medical attention and special treatment needed
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
SECTION 5: Firefigh	ting measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising f	rom the substance or mixture
5.2 Special hazards arising f Hazards from the substance or mixture	 irom the substance or mixture In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazards from the	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being
Hazards from the substance or mixture Hazardous combustion	 In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. Decomposition products may include the following materials: carbon oxides nitrogen oxides phosphorus oxides halogenated compounds
Hazards from the substance or mixture Hazardous combustion products	 In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. Decomposition products may include the following materials: carbon oxides nitrogen oxides phosphorus oxides halogenated compounds

6.1 Personal precautions, protective equipment and emergency procedures					
For non-emergency : personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.				
For emergency responders :	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".				

Code : 00000110488 PITT-CHAR XP BASE WHITE						
SECTION 6: Accidental release measures						
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.					
6.3 Methods and material for	r containment and cleaning up					
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.					
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.					
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.					

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Code: 000001104885Date of issue/Date of revisionPITT-CHAR XP BASE WHITE PF

: 15 June 2022

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
hexaboron dizinc undecaoxide	DNEL	Long term Oral	2.4 mg/kg bw/day	General population	-
	DNEL	Long term Inhalation	8.3 mg/m ³	General population	
	DNEL	Long term Inhalation	22.4 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	1205 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1585 mg/kg bw/day	Workers	Systemic
phosphorous oxychloride,	DNEL	Long term Oral	0.52 mg/kg bw/day	General population	Systemic
reaction products with					
propylene oxide	DNEL	Long term Dermel	1.04 mg/kg bw/day	General population	Svotomio
	DNEL	Long term Dermal Long term Inhalation	1.45 mg/m ³	General population	Systemic Systemic
	DNEL	Short term Oral	2 mg/kg bw/day	General population	
	DNEL	Long term Dermal	2.91 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	5.6 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	8.2 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	22.6 mg/m ³	Workers	Systemic
bis-[4-(2,3-epoxipropoxi)	DNEL	Long term Inhalation	12.25 mg/m ³	Workers	Systemic
phenyl]propane	DINEL	Long term initialation	12.25 mg/m	WUIKEIS	Systemic
phenyipropane	DNEL	Short term Inhalation	12.25 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	3.571 mg/kg bw/day	General	Systemic
				population	- ,
				[Consumers]	
	DNEL	Short term Dermal	3.571 mg/kg bw/day	General	Systemic
				population	,
				[Consumers]	
	DNEL	Long term Oral	0.75 mg/kg bw/day	General	Systemic
		_		population	-
				[Consumers]	
	DNEL	Short term Oral	0.75 mg/kg bw/day	General	Systemic
				population	
				[Consumers]	
	DNEL	Long term Dermal	89.3 µg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.75 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.87 mg/m ³	General population	
	DNEL	Long term Inhalation	4.93 mg/m ³	Workers	Systemic
N,N'-ethane-1,2-diylbis	DNEL	Long term Inhalation	0.83 mg/m³	General population	Local
(12-hydroxyoctadecan-					
1-amide)		Long torm inhelation	$2.25 m a/m^3$	Workers	
	DNEL	Long term Inhalation	3.35 mg/m³	vvoikeis	Local

PNECs

Code	: 000001104885	Date of issue/Date of revision	: 15 June 2022
PITT-CHAR	XP BASE WHITE PF		

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Compartment Detail	Value	Method Detail
		0.006 mg/l 0.001 mg/l 0.996 mg/kg dwt 0.1 mg/kg dwt 0.196 mg/kg dwt 10 mg/l 11 mg/kg	Assessment Factors Assessment Factors Equilibrium Partitioning Equilibrium Partitioning Equilibrium Partitioning Assessment Factors Assessment Factors

8.2 Exposure controls					
Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.	I			
Individual protection measures					
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.				
Eye/face protection <u>Skin protection</u>	: Chemical splash goggles.				
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use as included in the user's risk assessment. butyl rubber	is nt			
Body protection	: Personal protective equipment for the body should be selected based on the task beir performed and the risks involved and should be approved by a specialist before handling this product.	ıg			
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by specialist before handling this product.				
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If worker are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3	rs			
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.				

Code	: 000001104885	Date of issue/Date of revision	: 15 June 2022
PITT-CHAR	XP BASE WHITE PF		

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>		
Physical state	: Liquid.	
Colour	: Off-white.	
Odour	: Aromatic. [Strong]	
Odour threshold	: Not available.	
Melting point/freezing point	: May start to solidify at the following temperature: 8 to 12° based on data for the following ingredient: bis-[4-(2,3-epc	
Initial boiling point and boiling range	: >37.78°C (>100°F)	
Flammability (solid, gas)	: liquid	
Upper/lower flammability or explosive limits	: Not available.	
Flash point	: Closed cup: Not applicable.	
Auto-ignition temperature	: Not available.	
Decomposition temperature	:	
рН	: Not applicable.	
	Not applicable. insoluble in water.	
Viscosity	: Kinematic (40°C): >21 mm ² /s	
Solubility(ies)	- 1	Method

Media Result cold water Not soluble

Miscible with water: No.Partition coefficient: n-octanol/: Not applicable.water

ŝ

Vapour pressure

	Vapour Pressure at 20°C			V	apour pressure at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa
bis-[4-(2,3-epoxipropoxi)phenyl] propane	<0.000075006	<0.00001			
Relative density	: 1.47		-		
Vapour density	: Highe	est known v	alue: 11.7 (Air =	1) (bis-[4-(2,3	-epoxipropoxi)phenyl]propane).
Explosive properties			If is not explosive, rith air is possible.		tion of an explosible mixture of
Oxidising properties Particle characteristics	: Produ	ict does no	t present an oxidi	zing hazard.	
Median particle size	: Not a	pplicable.			

SECTION 10: Stability and reactivity

English (GB)	United Kingdom (UK)	8/15
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposit	ion products.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not	occur.
10.2 Chemical stability	: The product is stable.	
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ing	redients.

SECTION 10: Stability and reactivity							
PITT-CHAR	XP BASE WHITE PF						
Code	: 000001104885	Date of issue/Date of revision	: 15 June 2022				

SECTION 10: Stability and reactivity

Refer to protective measures listed in sections 7 and 8.

10.5 Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides phosphorus oxides halogenated compounds metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
hexaboron dizinc	LC50 Inhalation Dusts and	Rat	>5 mg/l	4 hours
undecaoxide	mists		-	
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Borate(5-), bis[µ-	LD50 Dermal	Rabbit	>2000 mg/kg	-
oxotetraoxodiborato(4-)]-,				
ammonium tetrahydrogen,				
dihydrate, (T-4)-				
	LD50 Oral	Rat	4200 mg/kg	-
phosphorous oxychloride,	LC50 Inhalation Dusts and	Rat	>7 mg/l	4 hours
reaction products with	mists			
propylene oxide				
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	630 to 2000 mg/	-
			kg	
bis-[4-(2,3-epoxipropoxi) phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
N,N'-ethane-1,2-diylbis	LC50 Inhalation Dusts and	Rat	>5.11 mg/l	4 hours
(12-hydroxyoctadecan- 1-amide)	mists			
,	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
PITT-CHAR XP BASE WHITE PF	3963.9	N/A	N/A	N/A	N/A
Borate(5-), bis[µ-oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)-	4200	N/A	N/A	N/A	N/A
phosphorous oxychloride, reaction products with propylene oxide	500	N/A	N/A	N/A	N/A
bis-[4-(2,3-epoxipropoxi)phenyl]propane	15000	23000	N/A	N/A	N/A

Irritation/Corrosion

Code	: 000001104885	Date of issue/Date of revision	: 15 June 2022
PITT-CI	HAR XP BASE WHITE PF		

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
hexaboron dizinc undecaoxide	Eyes - Cornea opacity	Rabbit	33	24 hours 0.083g	74 hours
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
	Skin - Oedema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-
Conclusion/Summary	: Not available.	•		•	
Skin	: There are no data available on	the mixture its	elf.		
Eyes	: There are no data available on the mixture itself.				
Respiratory	: There are no data available on the mixture itself.				
Sensitisation					

Product/ingredient name	Route of exposure		Species		Result	
bis-[4-(2,3-epoxipropoxi) phenyl]propane	skin	Mouse	e	Sensitising		
Conclusion/Summary	•	•				
Skin	: There are no	o data avail	able on the mixture	e itself.		
Respiratory	: There are no data available on the mixture itself.					
Mutagenicity						
Conclusion/Summary Carcinogenicity	: There are no	o data avail	able on the mixture	e itself.		
Conclusion/Summary <u>Reproductive toxicity</u>	: There are no	o data avail	able on the mixture	e itself.		
Broduct/ingradiant name	Matornal	Fortility	Dovelopmental	Spacios	Doso	Exposuro

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
hexaboron dizinc undecaoxide	Positive	Positive	Positive	Rat		90 days; 7 days per week
Conclusion/Summary : There are no data available on the mixture itself.						

Teratogenicity

Conclusion/Summary

There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

ŝ

Not available.

<u>Specific target organ toxicity (repeated exposure)</u> Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	Causes serious eye irritation.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Causes skin irritation. May cause an allergic ski

- **cin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion : No known significant effects or critical hazards.

English (GB)

United Kingdom (UK)

Code	: 000001104885	Date of issue/Date of revision	: 15 June 2022
PITT-CHAR	XP BASE WHITE PF		

SECTION 11: Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
Conclusion/Summary	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: Suspected of damaging the unborn child.

Other information

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
hexaboron dizinc undecaoxide	Acute EC50 76 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 2.17 mg/l	Fish - Salmo gairdneri	96 hours
Borate(5-), bis[µ- oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)-	Acute LC50 >100 mg/l	Fish	96 hours
phosphorous oxychloride, reaction products with propylene oxide	EC50 82 mg/l	Algae	72 hours
English (GB)	United K	ingdom (UK)	11/1

Code	: 000001104885	Date of issue/Date of revision	: 15 June 2022
PITT-CHAR	XP BASE WHITE PF		

SECTION 12: Ecological information

	EC50 131 mg/l	Daphnia	48 hours
	LC50 56.2 mg/l	Fish	96 hours
	NOEC 32 mg/l	Daphnia	48 hours
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - daphnia magna	48 hours
	Chronic NOEC 0.3 mg/l	Daphnia	21 days
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	Acute EC50 29 to 43 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
7	Acute EC50 94 mg/l	Daphnia - Daphnia magna	48 hours
Conclusion/Summary	: Not available.	·	•

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	-	63 % - 28 days	-	-

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxi) phenyl]propane N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	-	-	Not readily Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
hexaboron dizinc undecaoxide	-	60960	high
phosphorous oxychloride, reaction products with propylene oxide	2.68	-	low
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	>6	-	high

12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

Code	: 000001104885	Date of issue/Date of revision	: 15 June 2022
PITT-CHAR	XP BASE WHITE PF		

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods <u>Product</u>	
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

Waste catalogue

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
Packaging	

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	Waste catalogue		
Container	15 01 06 mixed packaging		
Special precautions	 This material and its container must be disposed of in a safe way. Care show taken when handling emptied containers that have not been cleaned or rinsed Empty containers or liners may retain some product residues. Avoid dispersa spilt material and runoff and contact with soil, waterways, drains and sewers. 		

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (hexaboron dizinc undecaoxide, bis-[4- (2,3-epoxipropoxi) phenyl]propane) (hexaboron dizinc undecaoxide, bis-[4- (2,3-epoxipropoxi) phenyl]propane)			
14.3 Transport hazard class(es)	9	9	9	9
14.4 Packing group	III	III	111	111
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	Not applicable.	(hexaboron dizinc undecaoxide, bis-[4- (2,3-epoxipropoxi) phenyl]propane)	Not applicable.

English (GB)

Code : 000001104885 PITT-CHAR XP BASE WHITE PF	Date of issue/Date of revision	: 15 June 2022
SECTION 14: Transport information		

Additional information

Additional into	
ADR/RID	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
Tunnel code	: (-)
ADN	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
14.6 Special pre user	cautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Transport i according to IM	

instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK (GB) /REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category

E2

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration
----------------------------	--

English (GB)	United Kingdom (UK)	14/15
--------------	---------------------	-------

Code	: 000001104885	

Date of issue/Date of revision

: 15 June 2022

PITT-CHAR XP BASE WHITE PF

SECTION 16: Other information

RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Repr. 2, H361d	Calculation method
Aquatic Chronic 2, H411	Calculation method

Full text of abbreviated H statements

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
History	

<u>History</u>

Date of issue/ Date of revision	: 6/15/2022
Date of previous issue	: No previous validation
Prepared by	: EHS
Version	: 1

<u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.