# SAFETY DATA SHEET



#### Conforms to Official Mexican Standard NOM-018-STPS-2015

Date of revision 22 November 2022 Date of issue 22 November 2022

**Version 5** 

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product name : SIGMAZINC 158 PIGMENT GREY

Product code : 00254321

Other means of : Not applicable.

identification

Product type : Powder.

Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

Use of the substance/

mixture

Coating.

Uses advised against : Not applicable.

Manufacturer : PPG Industries, Inc.

One PPG Place Pittsburgh, PA 15272 : (412) 434-4515 (U.S.)

Emergency telephone

<u>number</u>

(514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)

**Technical Phone Number**: 888-977-4762

# **SECTION 2: Hazards identification**

Classification of the substance or mixture

: ACUTE TOXICITY (dermal) - Category 5

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity:

96.7% (oral), 96.7% (dermal)

**GHS label elements** 

Signal word : Warning

**Hazard statements** : H313 - May be harmful in contact with skin.

**Precautionary statements** 

Prevention : Not applicable.

Response : P302 + P312 - IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell.

Storage : Not applicable.

Disposal : Not applicable.

Mexico Page: 1/11

Date of issue 22 November 2022 Version 5

Product code 00254321

### **Product name SIGMAZINC 158 PIGMENT GREY**

# SECTION 2: Hazards identification

result in classification

Other hazards which do not : Sanding and grinding dusts may be harmful if inhaled. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat. Emits toxic fumes when heated.

See toxicological information (Section 11)

# SECTION 3: Composition/information on ingredients

Substance/mixture

: Mixture

**Product name** 

: SIGMAZINC 158 PIGMENT GREY

Other means of identification

: Not applicable.

Ingredient name	%	CAS number
<b>z</b> ínc oxide	≥1.0 - ≤4.1	1314-13-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# SECTION 4: First aid measures

### **Description of necessary first aid measures**

**Eye contact** 

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

**Skin contact** 

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion

If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

# Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** 

: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.

Inhalation

: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.

**Skin contact** 

: May be harmful in contact with skin.

Ingestion

: No known significant effects or critical hazards.

## Over-exposure signs/symptoms

See toxicological information (Section 11)

# Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** 

: No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Mexico Page: 2/11

# SECTION 4: First aid measures

# **SECTION 5: Firefighting measures**

# **Extinguishing media**

Suitable extinguishing media

: Use dry chemical powder.

Unsuitable extinguishing media

: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

Specific hazards arising from the chemical

: May form explosible dust-air mixture if dispersed. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials: metal oxide/oxides

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# SECTION 6: Accidental release measures

# Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and materials for containment and cleaning up

**Small spill** 

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

> Page: 3/11 Mexico

**Product name SIGMAZINC 158 PIGMENT GREY** 

# SECTION 7: Handling and storage

### **Precautions for safe handling**

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid release to the environment. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

: Storage temperature: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# SECTION 8: Exposure controls/personal protection

#### **Control parameters**

С

### Occupational exposure limits

Ingredient name	Exposure limits	
<b>z</b> ínc oxide	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 2 mg/m³ 8 hours. Form: Respirable fraction STEL: 10 mg/m³ 15 minutes. Form: Respirable fraction	

#### Key to abbreviations

= Ceiling Limit = Internal Permissible Exposure Limit **IPEL** TLV

STEL = Short term exposure limit = Threshold Limit Value TWA = Time Weighted Average

### Consult local authorities for acceptable exposure limits.

procedures

**Recommended monitoring**: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Mexico Page: 4/11

Product name SIGMAZINC 158 PIGMENT GREY

# SECTION 8: Exposure controls/personal protection

# Appropriate engineering controls

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

# **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **Individual protection measures**

**Hygiene measures** 

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

# Eye/face protection Skin protection Hand protection

: Safety glasses with side shields.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### **Respiratory protection**

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

**Mexico** 

Page: 5/11

# **SECTION 9: Physical and chemical properties**

#### **Appearance**

**Boiling point** 

Physical state : Solid.

Powder.

Color : Various

Odor : Odorless.

Odor threshold : Not available.

Molecular weight : Not applicable.

pH : Not applicable.

Melting point : Not available.

Flash point : Closed cup: Not applicable.

: Not available.

**Product name SIGMAZINC 158 PIGMENT GREY** 

# **SECTION 9: Physical and chemical properties**

**Auto-ignition temperature** 

Not applicable.

**Decomposition temperature Flammability** 

: Not available. : Not available.

Lower and upper explosive

**Evaporation rate** 

: Not applicable.

(flammable) limits

: Not available. : Not available.

Vapor pressure Vapor density

: Not applicable.

**Relative density** Density (lbs/gal) 7.14 : 59.59

Solubility(ies)

Media Result cold water Not soluble

Solubility in water

: Not available.

Partition coefficient: n-

octanol/water

: Not applicable.

**Viscosity** 

: Kinematic (40°C (104°F)): Not applicable.

**Volatility** 

: 0% (v/v), 0.01% (w/w)

% Solid. (w/w)

99.99

# **SECTION 10: Stability and reactivity**

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** 

: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** 

: When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

Incompatible materials

: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

**Hazardous decomposition** products

: Evolves hydrogen on contact with water. Depending on conditions, decomposition products may include the following materials: metal oxide/oxides

# **SECTION 11: Toxicological information**

### Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
<b>z</b> ínc oxide	LC50 Inhalation Dusts and mists LD50 Dermal	Rat Rat	>5700 mg/m <sup>3</sup> >2000 mg/kg	4 hours
	LD50 Oral	Rat	>5000 mg/kg	-

**Conclusion/Summary** 

: There are no data available on the mixture itself.

**Irritation/Corrosion** 

Mexico Page: 6/11

### **Product name SIGMAZINC 158 PIGMENT GREY**

# **SECTION 11: Toxicological information**

**Conclusion/Summary** 

Skin
 Eyes
 There are no data available on the mixture itself.
 Respiratory
 There are no data available on the mixture itself.
 There are no data available on the mixture itself.

**Sensitization** 

**Conclusion/Summary** 

Skin: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Reproductive toxicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

<u>Target organs</u>: Contains material which may cause damage to the following organs: upper

respiratory tract.

#### **Aspiration hazard**

Not available.

### Information on the likely routes of exposure

#### Potential acute health effects

**Eye contact** : Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the eyes.

**Inhalation** : Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the nose, throat and lungs.

**Skin contact**: May be harmful in contact with skin.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

irritation redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Mexico Page: 7/11

**Product name SIGMAZINC 158 PIGMENT GREY** 

# **SECTION 11: Toxicological information**

### **Conclusion/Summary**

: There are no data available on the mixture itself. Repeated exposure of the eyes to a low level of dust can produce eye irritation. Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

#### **Short term exposure**

**Potential immediate** 

effects

: There are no data available on the mixture itself.

Potential delayed effects

: There are no data available on the mixture itself.

Long term exposure

**Potential immediate** 

: There are no data available on the mixture itself.

effects

Potential delayed effects : There are no data available on the mixture itself.

# Potential chronic health effects

General : Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

# **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	(gases)	(vapors)	Inhalation (dusts and mists) (mg/l)
SIGMAZINC 158 PIGMENT GREY zinc oxide	N/A N/A	2500 2500			N/A N/A

# **SECTION 12: Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
zínc oxide	Acute EC50 0.17 mg/l Acute EC50 0.481 mg/l Fresh water	Algae Daphnia - Daphnia magna -	72 hours 48 hours
		Neonate Algae	72 hours

### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Mexico Page: 8/11

**Product name SIGMAZINC 158 PIGMENT GREY** 

# **SECTION 12: Ecological information**

Other adverse effects

: No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL

PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

# **SECTION 14: Transport information**

	Mexico Classification	IMDG	IATA
UN number	UN3077	UN3077	UN3077
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc powder - zinc dust (stabilized), zinc oxide)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc powder - zinc dust (stabilized), zinc oxide)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc powder - zinc dust (stabilized), zinc oxide)
Transport hazard class(es)	9	9	9
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(Zinc powder - zinc dust (stabilized), zinc oxide)	Not applicable.
Product RQ (lbs) RQ substances	Not applicable. Not applicable.	Not applicable. Not applicable.	Not applicable. Not applicable.

#### **Additional information**

**Mexico** 

: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

**IMDG** 

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. The segregation group has been manually assigned based upon product analysis.

**IATA** 

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Mexico Page: 9/11

Product code 00254321 Date of issue 22 November 2022 Version 5

**Product name SIGMAZINC 158 PIGMENT GREY** 

# SECTION 14: Transport information

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

# **SECTION 15: Regulatory information**

#### **Mexico**

Classification

Flammability: Health: 1 Reactivity: 1

#### International regulations

#### **Montreal Protocol**

Not listed.

#### **Stockholm Convention on Persistent Organic Pollutants**

Not listed.

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

# **SECTION 16: Other information**

# **Hazardous Material Information System (U.S.A.)**

Health: Flammability: 0 Physical hazards:

(\*) - Chronic

effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

**Date of previous issue** : 11/7/2021 Organization that prepared : EHS

the SDS

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not availableSGG = Segregation Group **UN = United Nations** 

Indicates information that has changed from previously issued version.

# **Notice to reader**

Mexico Page: 10/11

Date of issue 22 November 2022 Version 5

**Product name SIGMAZINC 158 PIGMENT GREY** 

# **SECTION 16: Other information**

The information, which is based on the current knowledge of the chemical substance or mixture and applies to appropriate safety precautions for the product, is deemed correct but is not exhaustive and will be used only as a guide.

### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Mexico Page: 11/11