

SAFETY DATA SHEET

Date of issue/Date of revision

: 23 November 2022

Version : 18



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SIGMARINE 48 WHITE

Product code : 00250792

Other means of identification

Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/mixture : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL
Tweemontstraat 104
B-2100 Deurne
Belgium
Telephone +32-33606311
Fax +32-33606435

e-mail address of person responsible for this SDS : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

National advisory body/Poison Centre

National Poison Information Centre at Beaumont Hospital. Tel: +353 1 8092566, email: npicdublin@beaumont.ie

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

STOT SE 3, H336

STOT RE 1, H372

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

Code : 00250792

Date of issue/Date of revision

: 23 November 2022

SIGMARINE 48 WHITE

SECTION 2: Hazards identification

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: Flammable liquid and vapour.
May cause drowsiness or dizziness.
Causes damage to organs through prolonged or repeated exposure.
Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Do not breathe vapour.

Response

: Collect spillage.

Storage

: Store in a well-ventilated place. Keep container tightly closed.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

P210, P273, P260, P391, P403 + P233, P501

Hazardous ingredients

: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Supplemental label elements

: Repeated exposure may cause skin dryness or cracking.
Contains neodecanoic acid, cobalt salt. May produce an allergic reaction.
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: Prolonged or repeated contact may dry skin and cause irritation.

Code : 00250792

SIGMARINE 48 WHITE

Date of issue/Date of revision

: 23 November 2022

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	REACH #: 01-2119458049-33 EC: 919-446-0 CAS: 64742-82-1	≥25 - ≤50	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 (central nervous system (CNS)) (inhalation) Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	EUH066: C ≥ 20%	[1] [2]
2-ethylhexanoic acid, zirconium salt	REACH #: 01-2119979088-21 EC: 245-018-1 CAS: 22464-99-9	≤1.0	Repr. 2, H361d (oral)	-	[1] [2]
neodecanoic acid, cobalt salt	REACH #: 01-2119970733-31 EC: 248-373-0 CAS: 27253-31-2	≤0.30	Acute Tox. 4, H302 Skin Sens. 1, H317 STOT RE 1, H372 (gastrointestinal tract) (oral) Aquatic Chronic 3, H412	ATE [Oral] = 1098 mg/kg	[1] [2]
calcium bis (2-ethylhexanoate)	REACH #: 01-2119978297-19 EC: 205-249-0 CAS: 136-51-6	≤0.30	Eye Dam. 1, H318 Repr. 2, H361d (oral) See Section 16 for the full text of the H statements declared above.	-	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Code : 00250792

Date of issue/Date of revision

: 23 November 2022

SIGMARINE 48 WHITE

SECTION 4: First aid measures

Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	: Defatting to the skin. May cause skin dryness and irritation.
Ingestion	: Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	: Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
--	--

Code : 00250792

Date of issue/Date of revision

: 23 November 2022

SIGMARINE 48 WHITE

SECTION 5: Firefighting measures

Hazardous combustion products : Decomposition products may include the following materials:
carbon oxides
metal oxide/oxides

5.3 Advice for firefighters

Special precautions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

Code : 00250792

SIGMARINE 48 WHITE

Date of issue/Date of revision

: 23 November 2022

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

- : Put on appropriate personal protective equipment (see Section 8). Do not breathe vapour or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

Advice on general occupational hygiene

- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

- : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Code : 00250792

SIGMARINE 48 WHITE

Date of issue/Date of revision

: 23 November 2022

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure limit values
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	NAOSH (Ireland, 8/2018). OELV-8hr: 573 mg/m ³ 8 hours. OELV-8hr: 100 ppm 8 hours.
2-ethylhexanoic acid, zirconium salt	NAOSH (Ireland, 5/2021). [zirconium compounds] OELV-15min: 10 mg/m ³ , (as Zr) 15 minutes. OELV-8hr: 5 mg/m ³ , (as Zr) 8 hours.
neodecanoic acid, cobalt salt	NAOSH (Ireland, 5/2021). [Cobalt and cobalt compounds] Sensitization potential. OELV-8hr: 0.02 mg/m ³ , (as Co) 8 hours.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	DNEL	Long term Inhalation	330 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	44 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	71 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	26 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	26 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	2.5 mg/m ³	General population	Systemic
	DNEL	Long term Oral	2.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	3.25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	5 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	6.49 mg/kg bw/day	Workers	Systemic
2-ethylhexanoic acid, zirconium salt	DNEL	Long term Oral	32 µg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	43 µg/m ³	General population	Local
	DNEL	Long term Inhalation	273.2 µg/m ³	Workers	Local
	DNEL	Long term Oral	0.167 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.167 mg/kg bw/day	General population	Systemic
neodecanoic acid, cobalt salt	DNEL	Long term Dermal	0.333 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.58 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	2.351 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation			
	DNEL	Long term Inhalation			
calcium bis(2-ethylhexanoate)	DNEL	Long term Oral	0.167 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.167 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.333 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.58 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	2.351 mg/m ³	Workers	Systemic

PNECs

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
neodecanoic acid, cobalt salt	-	Fresh water	0.6 µg/l	Sensitivity Distribution
	-	Marine water	2.36 µg/l	Sensitivity Distribution
	-	Sewage Treatment Plant	0.37 mg/l	Assessment Factors
	-	Fresh water sediment	9.5 mg/kg dwt	Sensitivity Distribution
	-	Marine water sediment	9.5 mg/kg dwt	Sensitivity Distribution
	-	Soil	10.9 mg/kg dwt	Sensitivity Distribution

8.2 Exposure controls

Code : 00250792

Date of issue/Date of revision

: 23 November 2022

SIGMARINE 48 WHITE

SECTION 8: Exposure controls/personal protection

Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

- : Safety glasses with side shields. Use eye protection according to EN 166.

Skin protection

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves

- : For prolonged or repeated handling, use the following type of gloves:

Recommended: polyvinyl alcohol (PVA), Viton®

May be used: nitrile rubber

Body protection

- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection

- : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

- : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Code : 00250792

Date of issue/Date of revision

: 23 November 2022

SIGMARINE 48 WHITE

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: Liquid.
Colour	: White.
Odour	: Aromatic. [Slight]
Odour threshold	: Not available.
Melting point/freezing point	: <input checked="" type="checkbox"/> May start to solidify at the following temperature: -43.77°C (-46.8°F) This is based on data for the following ingredient: 1,2,4-trimethylbenzene. Weighted average: -64.13°C (-83.4°F)

Initial boiling point and boiling range

: >37.78°C

Flammability

: Not available.

Upper/lower flammability or explosive limits

: Greatest known range: Lower: 1.4% Upper: 7.6% (Naphtha (petroleum), hydrodesulfurized heavy)

Flash point

: Closed cup: 44°C

Auto-ignition temperature

:

Ingredient name	°C	°F	Method
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	>230	>446	

Decomposition temperature

: Stable under recommended storage and handling conditions (see Section 7).

pH

: Not applicable. insoluble in water.

Viscosity

: Kinematic (room temperature): >400 mm²/s
Kinematic (40°C): >21 mm²/s

Viscosity

: > 100 s (ISO 6mm)

Solubility(ies)

:

Media	Result
<input checked="" type="checkbox"/> cold water	Not soluble

Partition coefficient: n-octanol/ water

: Not applicable.

Vapour pressure

:

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	1.7	0.23				

Evaporation rate

: Highest known value: 0.77 (xylene) Weighted average: 0.5compared with butyl acetate

Relative density

: 1.02

: Highest known value: 4.4 (Air = 1) (nonane). Weighted average: 4.18 (Air = 1)

Explosive properties

: The product itself is not explosive, but the formation of an explosive mixture of vapour or dust with air is possible.

: Product does not present an oxidizing hazard.

Oxidising properties

Particle characteristics

Code : 00250792

Date of issue/Date of revision

: 23 November 2022

SIGMARINE 48 WHITE

SECTION 9: Physical and chemical properties

Median particle size : Not applicable.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) 2-ethylhexanoic acid, zirconium salt	LD50 Oral	Rat	>15000 mg/kg	-
neodecanoic acid, cobalt salt	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	>5 g/kg	-
	LD50 Oral	Rat - Female	1098 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
neodecanoic acid, cobalt salt	skin	Mouse	Sensitising

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary

Code : 00250792

Date of issue/Date of revision

: 23 November 2022

SIGMARINE 48 WHITE

SECTION 11: Toxicological information

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) neodecanoic acid, cobalt salt	Category 1 Category 1	inhalation oral	central nervous system (CNS) gastrointestinal tract

Aspiration hazard

Product/ingredient name	Result
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

Ingestion : Can cause central nervous system (CNS) depression.

Skin contact : Defatting to the skin. May cause skin dryness and irritation.

Eye contact : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

Ingestion : No specific data.

Skin contact : Adverse symptoms may include the following:
irritation
dryness
cracking

Eye contact : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Code : 00250792

Date of issue/Date of revision

: 23 November 2022

SIGMARINE 48 WHITE

SECTION 11: Toxicological information

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Other information : Not available.

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) 2-ethylhexanoic acid, zirconium salt	Chronic NOEC 0.097 mg/l Fresh water Acute LC50 >100 mg/l	Daphnia Fish	21 days 96 hours

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	OECD 301 F 301F Ready Biodegradability - Manometric Respirometry Test	75 % - Readily - 28 days	-	-

Conclusion/Summary : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	-	-	Readily

12.3 Bioaccumulative potential

Code : 00250792

Date of issue/Date of revision

: 23 November 2022

SIGMARINE 48 WHITE

SECTION 12: Ecological information

Not available.

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Code : 00250792

Date of issue/Date of revision

: 23 November 2022

SIGMARINE 48 WHITE

14. Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	(Naphtha (petroleum), hydrodesulfurized heavy, nonane)	Not applicable.

Additional information

ADR/RID : This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.2.3.1.5.2.

Tunnel code : (D/E)

ADN : This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.2.3.1.5.2.

IMDG : This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.3.2.5.

IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorisation](#)

[Annex XIV](#)

None of the components are listed.

[Substances of very high concern](#)

None of the components are listed.

Code : 00250792

Date of issue/Date of revision

: 23 November 2022

SIGMARINE 48 WHITE

SECTION 15: Regulatory information

Annex XVII - Restrictions : Not applicable.
on the manufacture,
placing on the market
and use of certain
dangerous substances,
mixtures and articles

Ozone depleting substances (1005/2009/EU)

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
P5c
E2

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226	On basis of test data
STOT SE 3, H336	Calculation method
STOT RE 1, H372	Calculation method
Aquatic Chronic 2, H411	Calculation method

Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Code : 00250792 SIGMARINE 48 WHITE	Date of issue/Date of revision : 23 November 2022
SECTION 16: Other information	
EUH066	
	Repeated exposure may cause skin dryness or cracking.
Full text of classifications [CLP/GHS]	
Acute Tox. 4 Aquatic Chronic 2 Aquatic Chronic 3 Asp. Tox. 1 Eye Dam. 1 Flam. Liq. 3 Repr. 2 Skin Sens. 1 STOT RE 1 STOT SE 3	ACUTE TOXICITY - Category 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 FLAMMABLE LIQUIDS - Category 3 REPRODUCTIVE TOXICITY - Category 2 SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
History	
Date of issue/ Date of revision	: 23 November 2022
Date of previous issue	: 30 October 2021
Prepared by	: EHS
Version	: 18
Disclaimer	
<i>The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.</i>	