Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

# **SAFETY DATA SHEET**

Date of issue/Date of revision

: 23 February 2023 Version



: 11

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: PSX 700 A RAL 9016 RESIN
Product code	: 00291669
Product type	: Liquid.
Other means of identification	1
Not available.	
1.2 Relevant identified uses of	f the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
1.3 Details of the supplier of the supplier of the supplier of the supplier of the supplication of the sup	he safety data sheet
Sigma Paint Saudi Arabia Ltd.	
PO Box 7509 Dammam 31472	
Saudi Arabia	
Tel: 00966 138 47 31 00 Fax: 00966 138 47 17 34	
Fax. 00900 138 47 17 54	
	: ndpic@sfda.gov.sa
responsible for this SDS	
1.4 Emergency telephone	: 00966 138473100 extn 1001

# number

# **SECTION 2: Hazards identification**

2.1 Classification of the subs	stance or mixture				
Product definition : Mixture					
Classification according to	Regulation (EC) No. 1272/2008 [CLP/GHS]				
₿kin Sens. 1, H317 Aquatic Chronic 3, H412					
The product is classified as h	The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.				
See Section 16 for the full tex	t of the H statements declared above.				
See Section 11 for more deta	ailed information on health effects and symptoms.				
2.2 Label elements					
Hazard pictograms	:				
Signal word	: Warning				
Hazard statements	: May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.				

Date of issue/Date of revision

# **SECTION 2: Hazards identification**

Precautionary statements	
Prevention	: Wear protective gloves. Avoid release to the environment. Avoid breathing vapour.
Response	: Fake off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	<ul> <li>4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane</li> <li>Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate</li> </ul>
Supplemental label elements	: Marning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirem	<u>ients</u>
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB	: ₱his mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Others have a large hits had	New Street

Other hazards which do : None known. not result in classification

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
4,4'- Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane	REACH #: 01-2119959495-22 EC: 500-070-7 CAS: 30583-72-3	≥25 - ≤50	Skin Sens. 1, H317 Aquatic Chronic 3, H412	-	[1]
Reaction mass of bis (1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5	≥0.30 - <2.5	Skin Sens. 1A, H317 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
toluene	REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3	<1.0	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336	-	[1] [2]
		English	(GB) United Arab Er	mirates	2/13

Conforms to Regulation (EC Code : 00291669	, , , ,	Date of issue/Date of revision	: 23 February 2023	
		Date of issue/Date of revision	. 201 ebidary 2023	
PSX 700 A RAL 9016 RESIN	1			
<b>SECTION 3: Compo</b>	sition/information	on ingredients		
	Index: 601-021-00-3	STOT RE 2, H373 Asp. Tox. 1, H304 See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

1 Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

#### SUB codes represent substances without registered CAS Numbers.

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact	:	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	:	If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. **Skin contact** : May cause an allergic skin reaction. Ingestion : No known significant effects or critical hazards. **Over-exposure signs/symptoms** Eye contact : No specific data. Inhalation : No specific data. **Skin contact** : Adverse symptoms may include the following: irritation redness Ingestion : No specific data. 4.3 Indication of any immediate medical attention and special treatment needed Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

Conforms to Regulation (EC	No. 1907/2006 (REACH), Annex II
Code : 00291669 PSX 700 A RAL 9016 RESIN	Date of issue/Date of revision : 23 February 2023
<b>SECTION 5: Firefigh</b>	ting measures
5.1 Extinguishing media Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides
5.3 Advice for firefighters	
Special precautions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

		training.
Special protective	1	Fire-fighters should wear appropriate protective equipment and self-contained breathing
equipment for fire-fighters		apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing
		for fire-fighters (including helmets, protective boots and gloves) conforming to European
		standard EN 469 will provide a basic level of protection for chemical incidents.

# **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	te	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for	co	ntainment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II			
Code : 00291669	Date of issue/Date of revision : 23 February 2023		
PSX 700 A RAL 9016 RESI	N		
SECTION 6: Accide	ental release measures		
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.		
6.4 Reference to other sections	<ul> <li>See Section 1 for emergency contact information.</li> <li>See Section 8 for information on appropriate personal protective equipment.</li> <li>See Section 13 for additional waste treatment information.</li> </ul>		

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

# **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 8.1 Control parameters

**Occupational exposure limits** 

Date of issue/Date of revision

# **SECTION 8: Exposure controls/personal protection**

Product/ingredient name		Exposure limit values	
<b>fo</b> luene		<b>EU OEL (Europe, 1/2022). Absorbed through skin.</b> STEL: 384 mg/m <sup>3</sup> 15 minutes. STEL: 100 ppm 15 minutes. TWA: 192 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.	
Recommended monitoring : procedures	: Reference should be made to monitoring standards, such as the following: Europea Standard EN 689 (Workplace atmospheres - Guidance for the assessment of expose by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.		
8.2 Exposure controls			
	Good general ve contaminants.	ntilation should be sufficient to control worker exposure to airborne	
Individual protection measure	<u>s</u>		
Hygiene measures :	eating, smoking a Appropriate techn Contaminated wo contaminated clo	earms and face thoroughly after handling chemical products, before and using the lavatory and at the end of the working period. niques should be used to remove potentially contaminated clothing. ork clothing should not be allowed out of the workplace. Wash othing before reusing. Ensure that eyewash stations and safety se to the workstation location.	
Eye/face protection : Skin protection	Safety glasses w	ith side shields.	
	worn at all times necessary. Cons during use that the noted that the tim glove manufactur protection time of frequently repeat (breakthrough tim When only brief of (breakthrough tim The user must ch product is the mo as included in the	Int, impervious gloves complying with an approved standard should be when handling chemical products if a risk assessment indicates this is sidering the parameters specified by the glove manufacturer, check he gloves are still retaining their protective properties. It should be ne to breakthrough for any glove material may be different for different rers. In the case of mixtures, consisting of several substances, the f the gloves cannot be accurately estimated. When prolonged or red contact may occur, a glove with a protection class of 6 ne greater than 480 minutes according to EN 374) is recommended. contact is expected, a glove with a protection class of 2 or higher ne greater than 30 minutes according to EN 374) is recommended. heck that the final choice of type of glove selected for handling this best appropriate and takes into account the particular conditions of use, e user's risk assessment.	
	butyl rubber		
	performed and th handling this proc		
Other skin protection	based on the tas	wear and any additional skin protection measures should be selected k being performed and the risks involved and should be approved by a handling this product.	
Respiratory protection :	hazards of the pr are exposed to c certified respirato	tion must be based on known or anticipated exposure levels, the roduct and the safe working limits of the selected respirator. If workers oncentrations above the exposure limit, they must use appropriate, ors. Use a properly fitted, air-purifying or air-fed respirator complying I standard if a risk assessment indicates this is necessary.	

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II				
Code : 00291669	Date of issue/Date of revision : 23 February 2023			
PSX 700 A RAL 9016 RESIN				
SECTION 8: Exposure controls/personal protection				
Environmental exposure : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some				

will be necessary to reduce emissions to acceptable levels.

cases, fume scrubbers, filters or engineering modifications to the process equipment

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

or information on busic physic	
<u>Appearance</u>	
Physical state	: Liquid.
Colour	: White.
Odour	: Aromatic.
Odour threshold	: Not available.
Melting point/freezing point	: May start to solidify at the following temperature: -12.9°C (8.8°F) This is based on data for the following ingredient: 4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane.
Initial boiling point and boiling range	: >37.78°C
Flammability	: Not available.
Upper/lower flammability or explosive limits	: Not available.
Flash point	: Closed cup: 80°C
Auto-ignition temperature	: Not available.
Decomposition temperature	: Stable under recommended storage and handling conditions (see Section 7).
рН	Not applicable. insoluble in water.
Viscosity	: Kinematic (40°C): >21 mm²/s
Solubility(ies)	: · · · · · · · · · · · · · · · · · · ·

Media	Result
cold water	Not soluble
Partition coefficient: n-octai water	: Not applicable.
Vapour pressure	: Not available.
Evaporation rate	: Not available.
Relative density	: 1.45
Explosive properties	: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
Oxidising properties	: Product does not present an oxidizing hazard.
article characteristics	
Median particle size	: Not applicable.

#### 9.2 Other information

No additional information.

<b>Conforms to Regulation (EC)</b>	No. 1907/2006 (REACH), Annex II
Code : 00291669 PSX 700 A RAL 9016 RESIN	Date of issue/Date of revision : 23 February 2023
SECTION 10: Stabilit	ty and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/ oxides

# **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### Acute toxicity

Result	Species	Dose	Exposure
LD50 Dermal	Rat	>3170 mg/kg	-
LD50 Oral	Rat - Male, Female	3230 mg/kg	-
LC50 Inhalation Vapour LD50 Dermal LD50 Oral	Rat Rabbit Rat	49 g/m³ 8.39 g/kg 5580 mg/kg	4 hours - -
	LD50 Dermal LD50 Oral LC50 Inhalation Vapour LD50 Dermal	LD50 Dermal Rat LD50 Oral Rat - Male, Female LC50 Inhalation Vapour Rat LD50 Dermal Rabbit	LD50 DermalRat>3170 mg/kgLD50 OralRat - Male, Female3230 mg/kgLC50 Inhalation Vapour LD50 DermalRat49 g/m³ 8.39 g/kg

Conclusion/Summary	: There are no data available on the mixture itself.
Irritation/Corrosion	
<b>Conclusion/Summary</b>	
Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Sensitisation	
<b>Conclusion/Summary</b>	
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Mutagenicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Carcinogenicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Reproductive toxicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Teratogenicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Specific target organ toxic	<u>ity (single exposure)</u>

ode : 00291669 SX 700 A RAL 9016 RESIN	١	Date of issue	e/Date of revision	: 23 February 202		
ECTION 11: Toxic	ological information	on				
Product/ir	ngredient name	Category	Route of exposure	Target organs		
toluene		Category 3	-	Narcotic effects		
Specific target organ toxi	city (repeated exposure)					
	ngredient name	Category	Route of	Target organs		
Troductin		outegoly	exposure	ranget organis		
toluene		Category 2	-	-		
Aspiration hazard						
	t/ingredient name			Result		
toluene			PIRATION HAZARD			
		A01				
Information on likely routes of exposure	: Not available.					
Potential acute health effe						
Inhalation	: No known significant					
Ingestion	: No known significant		azards.			
Skin contact	: May cause an allergi		_			
Eye contact	: No known significant					
	physical, chemical and to	xicological charac	<u>teristics</u> :			
Inhalation	: No specific data.					
Ingestion	: No specific data.					
Skin contact	: Adverse symptoms n irritation redness	hay include the folic	wing:			
Eye contact	: No specific data.	No specific data.				
Delayed and immediate e	<u>ffects as well as chronic e</u>	ffects from short	and long-term exp	<u>oosure</u>		
Short term exposure						
Potential immediate effects	: Not available.					
Potential delayed effect	ts : Not available.					
Long term exposure						
Potential immediate effects	: Not available.					
Potential delayed effect						
Potential chronic health e	effects					
Not available.						
Conclusion/Summary	: Not available.					
General	: Once sensitized, a se very low levels.	evere allergic reacti	on may occur wher	n subsequently exposed to		
Carcinogenicity	: No known significant	effects or critical h	azards.			
Mutagenicity	: No known significant	effects or critical h	azards.			
Reproductive toxicity	: No known significant	effects or critical h	azards.			
Other information	: Not available.					

### 11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

English (GB) United Arab Emirates

Code : 00291669 PSX 700 A RAL 9016 RESIN Date of issue/Date of revision

# **SECTION 11: Toxicological information**

#### Not available.

#### 11.2.2 Other information

Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
4.4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	LC50 11.5 mg/l	Fish	96 hours
Reaction mass of bis(1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	EC50 1.68 mg/l	Algae	72 hours
······································	LC50 0.9 mg/l	Fish	96 hours

**Conclusion/Summary** : There are no data available on the mixture itself.

#### 12.2 Persistence and degradability

**Conclusion/Summary** : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
voluene	-	-	Readily

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
<b>K</b> luene	2.73	8.32	low

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### **12.6 Endocrine disrupting properties**

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

### SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### **13.1 Waste treatment methods**

Product

Conforms to Regulation (E	C) No. 1907/2006 (REACH), Annex II					
Code : 00291669 PSX 700 A RAL 9016 RESIN	Date of issue/Date of revision       : 23 February 2023         I					
SECTION 13: Disposal considerations						
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.					
Hazardous waste	: Yes.					
European waste catalog	ue (EWC)					
Waste code	Waste designation					
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances					
Packaging						
Methods of disposal	<ul> <li>The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.</li> </ul>					
Type of packaging	European waste catalogue (EWC)					
Container	15 01 06 mixed packaging					
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.					

# **SECTION 14: Transport information**

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### Additional information

ADR/RID	: None identified.
IMDG	: None identified.
ΙΑΤΑ	: None identified.

**14.6 Special precautions for : Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk: Not applicable.according to IMOinstruments

Code : 00291669 PSX 700 A RAL 9016 RESIN Date of issue/Date of revision

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 1907/2006 (REACH)
Annex XIV - List of substances subject to authorisation
Annex XIV
None of the components are listed.
Substances of very high concern
None of the components are listed.
Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles
Other national and international regulations.
Ozone depleting substances (1005/2009/EU)
Not listed.
<b>15.2 Chemical safety</b> : No Chemical Safety Assessment has been carried out.

assessment

**SECTION 16: Other information** 

Indicates information that	has changed from previously is	ssued version.	
Abbreviations and acronyms	<ul> <li>ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number</li> </ul>		
Full text of abbreviated H statements	H304May be fatal if sH315Causes skin irriH317May cause skin irriH317May cause an aH336May cause drowH361Suspected of daH361dSuspected of daH373May cause damH400Very toxic to aqH410Very toxic to aq	Illergic skin reaction. vsiness or dizziness. amaging fertility or the unborn child. amaging the unborn child. nage to organs through prolonged or repeated exposure.	
Full text of classifications [CLP/GHS]	: Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 3 Asp. Tox. 1 Flam. Liq. 2 Repr. 2 Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A STOT RE 2 STOT SE 3	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 ASPIRATION HAZARD - Category 1 FLAMMABLE LIQUIDS - Category 2 REPRODUCTIVE TOXICITY - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1A SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3	
<u>History</u>			

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II					
Code : 00291669		Date of issue/Date of revision	: 23 February 2023		
PSX 700 A RAL 9016 RESI	N				
SECTION 16: Othe	r information				
Date of issue/ Date of revision	: 23 February 2023				
Date of previous issue	: 21 December 2018				
Prepared by	: EHS				
Version	: 11				
Disclaimor					

#### <u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.