SAFETY DATA SHEET



Date of issue/Date of revision28 June 2023Version 2.01

Section 1. Identification				
Product name	: 980 EPOXY CLEAR CATALYST- B			
Product code	: 00462266			
Other means of identification	: Not available.			
Product type	: Liquid.			
Relevant identified uses of the substance or mixture and uses advised against				
Product use	: Professional applications, Used by spraying.			
Use of the substance/ mixture	: 🖉oating.; Hardener.			
Uses advised against	: Not applicable.			
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272			
<u>Emergency telephone</u> <u>number</u>	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)			
Technical Phone Number	: 888-977-4762			

Section 2. Hazards identification

OSHA/HCS status	 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	 SKIN CORROSION - Category 1 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1 TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
	Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 89.8%
GHS label elements	
Hazard pictograms	
Signal word	: Danger

Product name 980 EPOXY CLEAR CATALYST- B

Section 2. Hazards identification

tract) have or face oduct. d out of
or face oduct.
or face oduct.
e DN doctor. ely all ER or ty of ES: nt and
and
1

Section 3. Composition/information on ingredients

: Mixture

Substance/mixture

Product name

: 980 EPOXY CLEAR CATALYST- B

Ingredient name	%	CAS number
Poly[oxy(methyl-1,2-ethanediyl)], α-(2-aminomethylethyl)-ω-	≥50 - ≤57	9046-10-0 (n = 2-6)
(2-aminomethylethoxy)-		
4-nonylphenol, branched	≥20 - ≤33	84852-15-3
2-piperazin-1-ylethylamine	≥5.0 - ≤9.0	140-31-8

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person. Description of necessary first aid measures

Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health eff	ects
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns. May cause an allergic skin reaction.
Ingestion	: Corrosive to the digestive tract. Causes burns.
Over-exposure signs/syn	nptoms
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate m	edical attention and special treatment needed, if necessary
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	No specific treatment

Product name 980 EPOXY CLEAR CATALYST- B

Section 4. First aid measures

Protection of first-aiders
 No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protect	:tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ont	ainment and cleaning up
Small spill Stop leak if without risk. Move containers from spill area. Dilute with if water-soluble. Alternatively, or if water-insoluble, absorb with an ine		Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
		United States Page: 4/14

Product name 980 EPOXY CLEAR CATALYST- B

Section 6. Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	: Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits	
Poly[oxy(methyl-1,2-ethanediyl)], α-(2-aminomethylethyl)-ω-	None.	
(2-aminomethylethoxy)-		
4-nonylphenol, branched	None.	
2-piperazin-1-ylethylamine	None.	

United States

Page: 5/14

Product name 980 EPOXY CLEAR CATALYST- B

Section 8. Exposure controls/personal protection

	Key to abbreviation			
A = Acceptable Maximum Peak ACGIH = American Conference of Governmental Industrial Hygienists. C = Ceiling Limit F = Fume IPEL = Internal Permissible Exposure Limit OSHA = Occupational Safety and Health Administration. R = Respirable Z = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substance		S SR SS STEL TD TLV TWA	 Potential skin absorption Respiratory sensitization Skin sensitization Short term Exposure limit values Total dust Threshold Limit Value Time Weighted Average 	
Consult local authorities for a	acceptable exposure limits.			
Recommended monitoring procedures			nitoring standards. Reference to national mination of hazardous substances will	
Appropriate engineering controls Environmental exposure controls	local exhaust ventilation or other e airborne contaminants below any rEmissions from ventilation or work they comply with the requirements	engineering c recommende process equ of environm ngineering m	uipment should be checked to ensure ental protection legislation. In some nodifications to the process equipment	
Individual protection measur	<u>es</u>			
Hygiene measures	eating, smoking and using the lava	atory and at t used to remo d not be allov ing. Ensure	ove potentially contaminated clothing. wed out of the workplace. Wash	
Eye/face protection	: Chemical splash goggles and face	e shield.		
Skin protection				
Hand protection	worn at all times when handling ch necessary. Considering the paran during use that the gloves are still noted that the time to breakthroug	nemical produ neters specif retaining the h for any glo of mixtures,	ng with an approved standard should be ucts if a risk assessment indicates this is fied by the glove manufacturer, check bir protective properties. It should be ve material may be different for different consisting of several substances, the tely estimated.	
Gloves	: butyl rubber			
Body protection	performed and the risks involved a handling this product.	and should be		
Other skin protection		d and the risl	rotection measures should be selected ks involved and should be approved by a	
Respiratory protection	are exposed to concentrations abo	fe working lin ove the expo ly fitted, air-p assessmen	nits of the selected respirator. If workers sure limit, they must use appropriate, purifying or air-fed respirator complying it indicates this is necessary.	

Section 9. Physical and chemical properties

Appearance

Physical state	:	Liquid.	
Color	:	Clear.	
Odor	1	Amine-like.	
Odor threshold	:	Not available.	
рН	1	Not applicable.	
Melting point	1	Not available.	
Boiling point	1	>37.78°C (>100°F)	
Flash point	1	Closed cup: 98.89°C (210	°F)
Auto-ignition temperature	1	Not available.	
Decomposition temperature	:	Not available.	
Flammability	1	Not available.	
Lower and upper explosive (flammable) limits	1	Not available.	
Evaporation rate	:	Not available.	
Vapor pressure	:	Not available.	
Vapor density	:	Not available.	
Relative density	:	0.95	
Density(lbs / gal)	:	7.93	
		Media	Result
Solubility(ies)	÷	cold water	Not soluble
Partition coefficient: n- octanol/water	1	Not applicable.	
Viscosity	:	Kinematic (40°C (104°F)):	>21 mm²/s (>21 cSt)
Volatility	:	1% (v/v), 0.662% (w/w)	
% Solid. (w/w)	:	99.338	

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Product name 980 EPOXY CLEAR CATALYST- B

Section 10. Stability and reactivity

Hazardous decomposition products

: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Poly[oxy(methyl- 1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	LD50 Dermal	Rat	2980 mg/kg	-
	LD50 Oral	Rat	2885 mg/kg	-
4-nonylphenol, branched	LD50 Dermal	Rabbit	2.14 g/kg	-
	LD50 Oral	Rat	1300 mg/kg	-
2-piperazin-1-ylethylamine	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
	LD50 Dermal	Rabbit	866 mg/kg	-
	LD50 Oral	Rat	2140 mg/kg	-

Conclusion/Summary : Th	ere are no data	available on the	mixture itself.
-------------------------	-----------------	------------------	-----------------

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
4-nonylphenol, branched	Skin - Erythema/Eschar	Rabbit	4	-	-
Conclusion/Summary	-		•		*

Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.

: There are no data available on the mixture itself.

: There are no data available on the mixture itself.

Sensitization

Respiratory

Product/ingredient name	Route of exposure	Species	Result
2-piperazin-1-ylethylamine	skin	Guinea pig	Sensitizing
Conclusion/Summary			
Skin	: There are no dat	ta available on the mixture itself.	
Respiratory	: There are no dat	ta available on the mixture itself.	
<u>Mutagenicity</u>			
Conclusion/Summary	: There are no dat	ta available on the mixture itself.	
Carcinogenicity			
Conclusion/Summary	: There are no dat	ta available on the mixture itself.	
Reproductive toxicity			
Conclusion/Summary	: There are no data	a available on the mixture itself.	
<u>Feratogenicity</u>			
Conclusion/Summary	: There are no data	a available on the mixture itself.	
Specific target organ toxicity	<u>y (single exposure)</u>		
Not available.			

Section 11. Toxicological information

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
2-piperazin-1-ylethylamine	Category 1	inhalation	respiratory tract

```
Target organs
```

: Contains material which causes damage to the following organs: upper respiratory tract, skin, eyes. Contains material which may cause damage to the following organs: kidneys, the

reproductive system, liver, central nervous system (CNS).

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns. May cause an allergic skin reaction.
Ingestion	: Corrosive to the digestive tract. Causes burns.
<u>Over-exposure signs/syn</u>	
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	 Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	 Adverse symptoms may include the following: pain or irritation
	redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations
Delayed and immediate eff	fects and also chronic effects from short and long term exposure
Conclusion/Summary	: There are no data available on the mixture itself. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
<u>Short term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
	United States Page: 9/14

Section 11. Toxicological information

Potential delayed effects	: There are no data available on the mixture itself.
<u>Long term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health effe	ects
General	: Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
980 EPOXY CLEAR CATALYST- B Poly[oxy(methyl-1,2-ethanediyl)], α- (2-aminomethylethyl)-ω-(2-aminomethylethoxy)-	2029.7 2885	2235.5 2980	N/A N/A	N/A N/A	N/A N/A
4-nonylphenol, branched 2-piperazin-1-ylethylamine	1300 2140	2140 866	N/A N/A	N/A N/A	N/A N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Poly[oxy(methyl- 1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	EC50 15 mg/l	Algae	72 hours
4-nonylphenol, branched 2-piperazin-1-ylethylamine	Acute EC50 0.044 mg/l Acute LC50 0.221 mg/l Acute EC50 58 mg/l	Crustaceans - <i>Moina macrocopa</i> Fish Daphnia	48 hours 96 hours 48 hours

Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
2-piperazin-1-ylethylamine	OECD 301F	0 % - Not readily - 28 days	-	-

United States	Page: 10/14

Product name 980 EPOXY CLEAR CATALYST- B

Section 12. Ecological information

Product/ingredient name Aquatic half-life Photolysis Biodegradability		Biodegradability	
Poly[oxy(methyl-			Not readily
1,2-ethanediyl)], α-	-	-	Notreadily
(2-aminomethylethyl)-ω-			
(2-aminomethylethoxy)-			
2-piperazin-1-ylethylamine	-	-	Not readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
4-nonylphenol, branched	5.4	251.19	Low
2-piperazin-1-ylethylamine	-1.48	-	Low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

	DOT	IMDG		IATA
UN number	UN3066	UN3066	UN3066	
UN proper shipping name	PAINT	PAINT	PAINT	
Transport hazard class (es)	8	8	8	
Packing group	11	II	11	
	- -		United States	Page: 11/14

Product name 980 EPOXY CLEAR CATALYST- B

14. Transport information

Environmental hazards	No.	Yes. The environmentally hazardous substance mark is
Marine pollutant substances	Not applicable.	not required. Not applicable.

Additional information

DOT	: None identified.
IMDG	: The marine pollutant mark is not required when transported in sizes of ≤ 5 L or ≤ 5 kg.
ΙΑΤΑ	: The environmentally hazardous substance mark may appear if required by other transportation regulations.
Special pred	autions for user : Transport within user's premises: always transport in closed containers that are

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are active or exempted.

 United States - TSCA 12(b) - Chemical export notification:
 One time notification

 4-nonylphenol, branched
 One time notification

 United States - TSCA 5(a)2 - Proposed significant new use rules:
 Listed

 4-nonylphenol, branched
 Listed

 SARA 302/304
 Not applicable.

 Composition/information on ingredients
 No products were found.

 SARA 311/312
 SARA 311/312

Classification : SKIN CORROSION - Category 1 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1 TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 HNOC - Corrosive to digestive tract

Composition/information on ingredients

Product name 980 EPOXY CLEAR CATALYST- B

Section 15. Regulatory information

Name	%	Classification
Poly[oxy(methyl-1,2-ethanediyl)], α -(2-aminomethylethyl)- ω - (2-aminomethylethoxy)-	≥50 - ≤57	SKIN CORROSION - Category 1C SERIOUS EYE DAMAGE - Category 1
4-nonylphenol, branched	≥20 - ≤33	ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION - Category 1 SERIOUS EYE DAMAGE - Category 1 TOXIC TO REPRODUCTION - Category 2 HNOC - Corrosive to digestive tract
2-piperazin-1-ylethylamine	≥5.0 - ≤9.0	FLAMMABLE LIQUIDS - Category 4 ACUTE TOXICITY (dermal) - Category 3 SKIN CORROSION - Category 1 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1B TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

<u>SARA 313</u>

	Chemical name	CAS number	Concentration
Supplier notification	: 4-nonylphenol, branched	84852-15-3	15 - 40

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

Section 16. Other information

Organization that prepared : EHS

the SDS

Hazardous Material Information System (U.S.A.)
Health : 3 * Flammability : 1 Physical hazards : 0 (*) - Chronic effects
Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.
The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.
National Fire Protection Association (U.S.A.)

Product name 980 EPOXY CLEAR CATALYST- B

Section 16. Other information

Key to abbreviations	: ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	N/A = Not available
	SGG = Segregation Group
	UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.