SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision4 September 2023Version 2.02

Section 1. Identification		
Product name	: 980 EPOXY CLEAR CATALYST- B	
Product code	: 00462266	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses of	the substance or mixture and uses advised against	
Product use	: Professional applications, Used by spraying.	
Use of the substance/ mixture	: Coating.; Hardener.	
Uses advised against	: Not applicable.	
Supplier	 PPG Architectural Coatings Canada, Inc. 1550, rue Ampère, bureau 500 Boucherville (Québec) J4B 7L4 Canada +1 450-655-3121 	
	PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272	
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)	
Technical Phone Number	: 888-977-4762	

Section 2. Hazard identification

Classification of the	: SKIN CORROSION - Category 1 SERIOUS EYE DAMAGE - Category 1
substance or mixture	SKIN SENSITIZATION - Category 1B
	TOXIC TO REPRODUCTION - Category 2
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
	Health Hazards Not Otherwise Classified - Category 1
GHS label elements	
Hazard pictograms	

Product name 980 EPOXY CLEAR CATALYST- B

Section 2. Hazard identification

Signal word	: Danger
Hazard statements	 Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. (respiratory tract) Causes digestive tract burns.
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
Response	: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Store locked up.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Do not taste or swallow. Wash thoroughly after handling. Emits toxic fumes when heated.
	Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 89.8%

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: 980 EPOXY CLEAR CATALYST- B
Other means of	: Not available.
identification	

CAS number/other identifiers

Ingredient name	Synonyms	% (w/w)	CAS number
Poly[oxy(methyl-1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	Poly[oxy(methyl-1,2-ethanediyl)], .alpha (2-aminomethylethyl)omega (2-aminomethylethoxy)-; Poly[oxy(methyl- 1,2-ethanediyl)], alpha- (2-aminomethylethyl)- omega - (2-aminomethylethoxy)-; .alpha.,.omega Diaminopolypropylene glycol; Jeffamine 400; Jeffamine D 600; polyoxypropylenediamine; Diaminopolypropylene glycol; Poly(oxy (methyl-1,2-ethanediyl)), alpha- (2-aminomethylethyl)-omega- (2-aminomethylethoxy)-; poly	30 - 60*	9046-10-0 (n = 2-6)
		Car	nada Page: 2/13

Product name 980 EPOXY CLEAR CATALYST- B

Section 3. Composition/information on ingredients

	- J		
	(oxypropylene)diamine; Poly(oxy(methyl- 1,2-ethanediyl)), .alpha (2-aminomethylethyl)omega (2-aminomethylethoxy)-; JEFFAMINE D- 2000		
4-nonylphenol, branched	Phenol, 4-nonyl-, branched; Branched 4-nonylphenol (mixed isomers); Nonylphenol, 4-branched; N- NONYLPHENOL; Nonylphenol; C9- Branched alkyl phenol; Branched p- nonylphenol; 4-Nonylphenol (branched); Monoalkyl(C3-9)phenol; C9 branched alkyl phenol; Branched 4-nonylphenol	15 - 40	84852-15-3
2-piperazin-1-ylethylamine	1-Piperazineethanamine; 1-(2-Aminoethyl) piperazine; N-(Aminoethyl)piperazine; 2- (1-Piperazinyl) ethylamine; Piperazine, 1- (2-aminoethyl)-; 1-(2-AMINOETHYL)- PIPERAZINE; N- AMINOETHYLPIPERAZINE; 1- (2-AMINOETHYL)PIPERAZIN; 2- (Piperazin-1-yl)ethylamine; 1-Aminoethylpiperazine; PIPERAZINE, N- AMINOETHYL-	5 - 10*	140-31-8

*Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact	 Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact

: Causes serious eye damage.

Product name 980 EPOXY CLEAR CATALYST- B

Section 4. First-aid measures

Inhalation : No known significant effects or critical hazards. Skin contact : Causes severe burns. May cause an allergic skin reaction. Ingestion : Corrosive to the digestive tract. Causes burns. Over-exposure signs/symptoms Eye contact : Adverse symptoms may include the following: pain watering redness Inhalation : Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations Skin contact : Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations Skin contact : Adverse symptoms may include the following: pain or irritation reduces in fetal deaths skeletal malformations Ingestion : Adverse symptoms may include the following: pain or irritation reduced fetal weight increases in fetal deaths skeletal malformations Ingestion : Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations Ingestion : Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations		
Ingestion : Corrosive to the digestive tract. Causes burns. Over-exposure signs/symptoms Eye contact : Adverse symptoms may include the following: pain watering redness Inhalation : Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations Skin contact : Adverse symptoms may include the following: pain or irritation reduced fetal weight increase in fetal deaths skeletal malformations Ingestion : Adverse symptoms may include the following: pain or irritation reduces blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations Ingestion : Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations Ingestion : Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations	Inhalation	: No known significant effects or critical hazards.
Over-exposure signs/symptoms Eye contact : Adverse symptoms may include the following: pain watering redness Inhalation : Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations Skin contact : Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations Ingestion : Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations Ingestion : Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations Ingestion : Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations	Skin contact	: Causes severe burns. May cause an allergic skin reaction.
Eye contact : Adverse symptoms may include the following: pain watering redness Inhalation : Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations Skin contact : Adverse symptoms may include the following: pain or irritation reduced fetal weight increase in fetal deaths skeletal malformations Ingestion : Adverse symptoms may include the following: pain or irritation reduced fetal weight increase in fetal deaths skeletal malformations Ingestion : Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations Ingestion : Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations	Ingestion	: Corrosive to the digestive tract. Causes burns.
pain watering redness Inhalation : Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations Skin contact : Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations Ingestion : Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations Ingestion : Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations	<u>Over-exposure signs/sy</u>	<u>/mptoms</u>
reduced fetal weight increase in fetal deaths skeletal malformations Skin contact : Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations Ingestion : Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations Ingestion : Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations medication of immediate medical attention and special treatment needed, if necessary	Eye contact	pain watering
pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations Ingestion : Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations stomach pains reduced fetal weight increase in fetal deaths skeletal malformations	Inhalation	reduced fetal weight increase in fetal deaths
stomach pains reduced fetal weight increase in fetal deaths skeletal malformations	Skin contact	pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths
	Ingestion	stomach pains reduced fetal weight increase in fetal deaths
	ndication of immediate I Notes to physician	

Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed.
Specific treatments	The exposed person may need to be kept under medical surveillance for 48 hours. No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

: Use an extinguishing agent suitable for the surrounding fire.
: None known.
: In a fire or if heated, a pressure increase will occur and the container may burst.
: Decomposition products may include the following materials: carbon oxides nitrogen oxides

Product name 980 EPOXY CLEAR CATALYST- B

Section 5. Fire-fighting measures

Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protec	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ont	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures
 Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Product name 980 EPOXY CLEAR CATALYST- B

Section 7. Handling and storage

Special precautions	:	Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits	
Poly[oxy(methyl-1,2-ethanediyl)], α -(2-aminomethylethyl)- ω -(2-aminomethylethoxy)-	None.	
4-nonylphenol, branched	None.	
2-piperazin-1-ylethylamine	None.	

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	:	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	<u>es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	1	Chemical splash goggles and face shield.
Skin protection		

Product name 980 EPOXY CLEAR CATALYST- B

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: butyl rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

				Canada	Page: 7/13
Volatility	÷	1% (v/v), 0.662% (w/w)			
Viscosity	1	Kinematic (40°C (104°F)):	>21 mm²/s (>21 cSt)		
Partition coefficient: n- octanol/water	:	Not applicable.			
Solubility(ies)	:	cold water	Not soluble		
		Media	Result		
Density(lbs / gal)	:	7.93			
Relative density	:	0.95			
Vapor density	:	Not available.			
Vapor pressure	:	Not available.			
Evaporation rate	:	Not available.			
Lower and upper explosive flammable) limits	1	Not available.			
Flammability	- 1	Not available.			
Decomposition temperature		Not available.			
Auto-ignition temperature		Not available.			
Flash point		Closed cup: 98.89°C (210	°F)		
Boiling point		>37.78°C (>100°F)			
Melting point	1	Not available.			
рН	:	Not applicable.			
Odor threshold	:	Not available.			
Odor	4	Amine-like.			
Physical state Color		Liquid. Clear.			
Appearance Divisional atom		I tavidal			

Product name 980 EPOXY CLEAR CATALYST- B

Section 9. Physical and chemical properties

: 99.338

% Solid. (w/w)

, · · · · · · · · · · · · · · · · · · ·				
Section 10. Stability and reactivity				
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
Chemical stability	: The product is stable.			
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.			
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.			
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials carbon oxides nitrogen oxides			

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Poly[oxy(methyl- 1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	LD50 Dermal	Rat	2980 mg/kg	-
, , , , , , , , , , , , , , , , , , ,	LD50 Oral	Rat	2885 mg/kg	-
4-nonylphenol, branched	LD50 Dermal LD50 Oral	Rabbit Rat	2.14 g/kg 1300 mg/kg	-
2-piperazin-1-ylethylamine	LC50 Inhalation Dusts and mists LD50 Dermal LD50 Oral	Rat Rabbit Rat	>5 mg/l 866 mg/kg 2140 mg/kg	4 hours - -

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
4-nonylphenol, branched	Skin - Erythema/Eschar	Rabbit	4	-	-
Conclusion/Summary					

Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.

- : There are no data available on the mixture itself.
- Respiratory : There are no data available on the mixture itself.

Sensitization

••••••	Route of exposure	Species	Result
2-piperazin-1-ylethylamine	skin	Guinea pig	Sensitizing

Section 11. Toxicological information

Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Mutagenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Carcinogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Teratogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Specific target organ toxi	<u>city (single exposure)</u>
Not available.	

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
2-piperazin-1-ylethylamine	Category 1	inhalation	respiratory tract

Target organs

: Contains material which causes damage to the following organs: upper respiratory tract, skin, eyes. Contains material which may cause damage to the following organs: kidneys, the reproductive system, liver, central nervous system (CNS).

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns. May cause an allergic skin reaction.
Ingestion	: Corrosive to the digestive tract. Causes burns.

Over-exposure signs/symptoms

Eye contact	 Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Product name 980 EPOXY CLEAR CATALYST- B

Section 11. Toxicological information

Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations
Delayed and immediate effect	ts and also chronic effects from short and long term exposure
Conclusion/Summary	: There are no data available on the mixture itself. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
Short term exposure	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
<u>Long term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health eff	ects
General	: Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Numerical measures of toxic	ity

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)		Inhalation (dusts and mists) (mg/l)
980 EPOXY CLEAR CATALYST- B	2029.7	2235.5	N/A	N/A	N/A
Poly[oxy(methyl-1,2-ethanediyl)], α-	2885	2980	N/A	N/A	N/A
(2-aminomethylethyl)-ω-(2-aminomethylethoxy)-					
4-nonylphenol, branched	1300	2140	N/A	N/A	N/A
2-piperazin-1-ylethylamine	2140	866	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Poly[oxy(methyl- 1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	EC50 15 mg/l	Algae	72 hours
4-nonylphenol, branched 2-piperazin-1-ylethylamine	Acute EC50 0.044 mg/l Acute LC50 0.221 mg/l Acute EC50 58 mg/l	Crustaceans - <i>Moina macrocopa</i> Fish Daphnia	48 hours 96 hours 48 hours

Persistence and degradability

Product/ingredient name	Test	Result		Dose	Inoculum
2-piperazin-1-ylethylamine	OECD 301F	0 % - Not readily - 2	28 days	-	-
Product/ingredient name	Aquatic half-life)	Photolysi	S	Biodegradability
Poly[oxy(methyl- 1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)- 2-piperazin-1-ylethylamine	-		-		Not readily Not readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
4-nonylphenol, branched	5.4	251.19	Low
2-piperazin-1-ylethylamine	-1.48	-	Low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Section 14. Transport information

	TDG	IMDG	IATA
UN number	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class (es)	8	8	8
Packing group	II	II	II
Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	(4-nonylphenol, branched)	(4-nonylphenol, branched)	Not applicable.

Additional information

Section 15	Regulatory information		
Proof of classific statement	Goods Regulations: 2.40-2.42 (Class 8), 2.7 (Marine pollutant mark).		
Transport in bull to IMO instrume	according : Not applicable. Its		
Special precaution	ons for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.		
ΑΤΑ	: The environmentally hazardous substance mark may appear if required by other transportation regulations.		
TDG IMDG	 The marine pollutant mark is not required when transported by road or rail. The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. 		
Auditional inform			

National Inventory List

Canada inventory (DSL)

: All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 3 * Flammability : 1 Physical hazards : 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health : 3 Flammability : 1 Instability : 0

Canada Page: 12/13

Section 16. Other information

Date of issue/Date of revision	4 September 2023
Organization that prepared the SDS	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

✓ Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.