

SAFETY DATA SHEET

Date of issue/Date of revision

: 23 October 2023

Version

: 13



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SIGMAFAST 278 BASE CREAM

Product code : 00328923

Other means of identification

Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/mixture : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL

Tweemontstraat 104

B-2100 Deurne

Belgium

Telephone +32-33606311

Fax +32-33606435

e-mail address of person responsible for this SDS : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Corr. 1B, H314

Eye Dam. 1, H318

Skin Sens. 1, H317

Repr. 2, H361fd

STOT RE 2, H373

Aquatic Acute 1, H400

Aquatic Chronic 1, H410

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Code : 00328923

Date of issue/Date of revision

: 23 October 2023

SIGMAFAST 278 BASE CREAM

SECTION 2: Hazards identification

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: Flammable liquid and vapour.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Suspected of damaging fertility. Suspected of damaging the unborn child.
May cause damage to organs through prolonged or repeated exposure.
Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

: Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Do not breathe vapour.

Response

: Collect spillage.

Storage

: Not applicable.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

P280, P210, P273, P260, P391, P501

Hazardous ingredients

: Bis-[4-(2,3-epoxipropoxy)phenyl]propane
crystalline silica, respirable powder (<10 microns)
4-nonylphenol, branched
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.
Fatty acids, C14-18 and C16-18-unsatd., maleated
maleic anhydride

Supplemental label elements

: Contains epoxy constituents. May produce an allergic reaction.
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Code : 00328923 Date of issue/Date of revision : 23 October 2023
 SIGMAFAST 278 BASE CREAM

SECTION 2: Hazards identification

Other hazards which do not result in classification : Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation.
 May cause endocrine disruption.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Type
1,4-bis-[4-(2,3-epoxipropoxy)phenyl]propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
crystalline silica, respirable powder (<10 microns)	EC: 238-878-4 CAS: 14808-60-7	≥5.0 - <10	STOT RE 1, H372 (inhalation)	-	[1] [2]
xylene	EC: 215-535-7 CAS: 1330-20-7	≥5.0 - ≤10	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1700 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
4-nonylphenol, branched	REACH #: 01-2119510715-45 EC: 284-325-5 CAS: 84852-15-3 Index: 601-053-00-8	≥5.0 - ≤10	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Repr. 2, H361fd Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 1300 mg/kg M [Acute] = 10 M [Chronic] = 10	[1] [3]
1-methoxy-2-propanol	REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 Index: 603-064-00-3	≥1.0 - ≤5.0	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Inhalation (vapours)] = 17.8 mg/l	[1] [2]
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	REACH #: 01-2119485289-22 EC: 271-846-8 CAS: 68609-97-2 Index: 603-103-00-4	≥1.0 - ≤5.0	Skin Irrit. 2, H315 Skin Sens. 1, H317	-	[1]
trizinc bis(orthophosphate)	REACH #:	≤1.0	Aquatic Acute 1, H400	M [Acute] = 1	[1]

Code : 00328923	Date of issue/Date of revision : 23 October 2023
SIGMAFAST 278 BASE CREAM	

SECTION 3: Composition/information on ingredients

	01-2119485044-40 EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6		Aquatic Chronic 1, H410	M [Chronic] = 1	
Fatty acids, C14-18 and C16-18-unsatd., maleated	REACH #: 01-2119978273-29 EC: 288-306-2 CAS: 85711-46-2	≤0.30	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317	-	[1]
maleic anhydride	REACH #: 01-2119472428-31 EC: 203-571-6 CAS: 108-31-6 Index: 607-096-00-9	≤0.10	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372 (respiratory system) (inhalation) EUH071 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 400 mg/kg Skin Sens. 1, H317: C ≥ 0.001%	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Xylene: Several REACH registrations cover the REACH registered substance with xylene isomers, ethylbenzene (and toluene). The other REACH Registrations include: 01-2119555267-33 reaction mass of ethylbenzene and m-xylene and p-xylene, 01-2119486136-34 Aromatic hydrocarbons, C8, 01-2119539452-40 reaction mass of ethylbenzene and xylene.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance of equivalent concern

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Code : 00328923

Date of issue/Date of revision

: 23 October 2023

SIGMAFAST 278 BASE CREAM

SECTION 4: First aid measures

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes severe burns. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : Corrosive to the digestive tract. Causes burns.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
dryness
cracking
blistering may occur
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
stomach pains
reduced foetal weight
increase in foetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Code : 00328923

Date of issue/Date of revision

: 23 October 2023

SIGMAFAST 278 BASE CREAM

SECTION 5: Firefighting measures

Hazardous combustion products : Decomposition products may include the following materials:
carbon oxides
halogenated compounds
metal oxide/oxides

5.3 Advice for firefighters

Special precautions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

Code : 00328923

Date of issue/Date of revision

: 23 October 2023

SIGMAFAST 278 BASE CREAM

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
crystalline silica, respirable powder (<10 microns)	ACGIH TLV (United States, 1/2022). [Silica, crystalline] TWA: 0.025 mg/m ³ 8 hours. Form: Respirable
xylene	EU OEL (Europe, 1/2022). [xylene, mixed isomers pure] Absorbed through skin. STEL: 442 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. TWA: 221 mg/m ³ 8 hours.
1-methoxy-2-propanol	EU OEL (Europe, 1/2022). Absorbed through skin. TWA: 50 ppm 8 hours.

English (GB)

Europe

7/21

Code : 00328923

Date of issue/Date of revision

: 23 October 2023

SIGMAFAST 278 BASE CREAM

SECTION 8: Exposure controls/personal protection

ethylbenzene	<p>STEL: 568 mg/m³ 15 minutes. STEL: 150 ppm 15 minutes. TWA: 375 mg/m³ 8 hours. TWA: 100 ppm 8 hours.</p> <p>EU OEL (Europe, 1/2022). Absorbed through skin. STEL: 884 mg/m³ 15 minutes. STEL: 200 ppm 15 minutes. TWA: 442 mg/m³ 8 hours. TWA: 100 ppm 8 hours.</p>
maleic anhydride	<p>ACGIH TLV (United States, 1/2022). Skin sensitiser. Inhalation sensitiser. TWA: 0.01 mg/m³ 8 hours. Form: Inhalable fraction and vapor</p>

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
1,4-bis-(2,3-epoxypropoxy)phenylpropane	DNEL	Long term Inhalation	12.25 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	12.25 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	3.571 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Dermal	3.571 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Oral	0.75 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Oral	0.75 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Dermal	89.3 µg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic
xylene	DNEL	Long term Dermal	0.75 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.87 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	4.93 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	260 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	260 mg/m ³	General population	Local
	DNEL	Long term Dermal	125 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	65.3 mg/m ³	General population	Systemic
	DNEL	Long term Oral	12.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	221 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	442 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	221 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	442 mg/m ³	Workers	Local
	DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic

Code : 00328923

Date of issue/Date of revision

: 23 October 2023

SIGMAFAST 278 BASE CREAM

SECTION 8: Exposure controls/personal protection

4-nonylphenol, branched	DNEL	Long term Inhalation	65.3 mg/m ³	General population	Local	
	DNEL	Short term Inhalation	260 mg/m ³	General population	Local	
	DNEL	Short term Inhalation	260 mg/m ³	General population	Systemic	
	DNEL	Long term Inhalation	221 mg/m ³	Workers	Local	
	DNEL	Long term Oral	12.5 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	65.3 mg/m ³	General population	Systemic	
	DNEL	Long term Dermal	125 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	221 mg/m ³	Workers	Systemic	
	DNEL	Short term Inhalation	442 mg/m ³	Workers	Local	
	DNEL	Short term Inhalation	442 mg/m ³	Workers	Systemic	
	DNEL	Long term Oral	0.08 mg/kg bw/day	General population	Systemic	
	DNEL	Short term Oral	0.4 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	0.4 mg/m ³	General population	Systemic	
	DNEL	Long term Inhalation	0.5 mg/m ³	Workers	Systemic	
	DNEL	Short term Inhalation	0.8 mg/m ³	General population	Systemic	
	1-methoxy-2-propanol	DNEL	Short term Inhalation	1 mg/m ³	Workers	Systemic
DNEL		Long term Dermal	3.8 mg/kg bw/day	General population	Systemic	
DNEL		Long term Dermal	7.5 mg/kg bw/day	Workers	Systemic	
DNEL		Short term Dermal	7.6 mg/kg bw/day	General population	Systemic	
DNEL		Short term Dermal	15 mg/kg bw/day	Workers	Systemic	
DNEL		Long term Oral	33 mg/kg bw/day	General population	Systemic	
DNEL		Long term Inhalation	43.9 mg/m ³	General population	Systemic	
DNEL		Long term Dermal	78 mg/kg bw/day	General population	Systemic	
DNEL		Long term Dermal	183 mg/kg bw/day	Workers	Systemic	
DNEL		Long term Inhalation	369 mg/m ³	Workers	Systemic	
DNEL		Short term Inhalation	553.5 mg/m ³	Workers	Local	
DNEL		Short term Inhalation	553.5 mg/m ³	Workers	Systemic	
ethylbenzene		DNEL	Long term Oral	1.6 mg/kg bw/day	General population	Systemic
		DNEL	Long term Inhalation	15 mg/m ³	General population	Systemic
		DNEL	Long term Inhalation	77 mg/m ³	Workers	Systemic
		DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic
		DNEL	Short term Inhalation	293 mg/m ³	Workers	Local
	DMEL	Long term Inhalation	442 mg/m ³	Workers	Local	
	DMEL	Short term Inhalation	884 mg/m ³	Workers	Systemic	
	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic	
	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	DNEL	Long term Dermal	0.5 mg/kg bw/day	General population	Systemic
		DNEL	Long term Inhalation	0.87 mg/m ³	General population	Systemic
		DNEL	Long term Dermal	1 mg/kg bw/day	Workers	Systemic
		DNEL	Long term Inhalation	3.6 mg/m ³	Workers	Systemic
		DNEL	Long term Oral	0.83 mg/kg bw/day	General population	Systemic
		DNEL	Long term Inhalation	2.5 mg/m ³	General population	Systemic
		DNEL	Long term Inhalation	5 mg/m ³	Workers	Systemic
	Fatty acids, C14-18 and C16-18-unsatd., maleated	DNEL	Long term Dermal	83 mg/kg bw/day	General population	Systemic
		DNEL	Long term Dermal	83 mg/kg bw/day	Workers	Systemic
DNEL		Long term Oral	1.5 mg/kg bw/day	General population	Systemic	
maleic anhydride		DNEL	Long term Dermal	1.5 mg/kg bw/day	General population	Systemic
		DNEL	Long term Dermal	3 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.4 mg/m ³	Workers	Systemic	
	DNEL	Long term Inhalation	0.4 mg/m ³	Workers	Local	
	DNEL	Long term Inhalation	0.081 mg/m ³	Workers	Local	
	DNEL	Long term Inhalation	0.081 mg/m ³	Workers	Systemic	
	DNEL	Short term Inhalation	0.2 mg/m ³	Workers	Local	
	DNEL	Short term Inhalation	0.2 mg/m ³	Workers	Systemic	

Code : 00328923

Date of issue/Date of revision

: 23 October 2023

SIGMAFAST 278 BASE CREAM

SECTION 8: Exposure controls/personal protection

	DNEL	Long term Inhalation	0.05 mg/m ³	General population	Systemic
	DNEL	Long term Oral	0.06 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.08 mg/m ³	General population	Local
	DNEL	Short term Oral	0.1 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	0.1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.1 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	0.2 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	0.2 mg/kg bw/day	Workers	Systemic

PNECs

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
bis-[4-(2,3-epoxipropoxy)phenyl]propane	-	Fresh water	0.006 mg/l	Assessment Factors
	-	Marine water	0.001 mg/l	Assessment Factors
	-	Fresh water sediment	0.996 mg/kg dwt	Equilibrium Partitioning
	-	Marine water sediment	0.1 mg/kg dwt	Equilibrium Partitioning
	-	Soil	0.196 mg/kg dwt	Equilibrium Partitioning
xylene	-	Sewage Treatment Plant	10 mg/l	Assessment Factors
	-	Secondary Poisoning	11 mg/kg	Assessment Factors
	-	Fresh water	0.327 mg/l	-
	-	Marine water	0.327 mg/l	-
	-	Sewage Treatment Plant	6.58 mg/l	-
1-methoxy-2-propanol	-	Fresh water sediment	12.46 mg/kg dwt	-
	-	Marine water sediment	12.46 mg/kg dwt	-
	-	Soil	2.31 mg/kg	-
	-	Fresh water	10 mg/l	Assessment Factors
	-	Marine water	1 mg/l	Assessment Factors
ethylbenzene	-	Sewage Treatment Plant	100 mg/l	Assessment Factors
	-	Fresh water sediment	41.6 mg/kg	Equilibrium Partitioning
	-	Marine water sediment	4.17 mg/kg	Equilibrium Partitioning
	-	Soil	2.47 mg/kg	Equilibrium Partitioning
	-	Fresh water	0.1 mg/l	Assessment Factors
trizinc bis(orthophosphate)	-	Marine water	0.01 mg/l	Assessment Factors
	-	Sewage Treatment Plant	9.6 mg/l	Assessment Factors
	-	Fresh water sediment	13.7 mg/kg dwt	Equilibrium Partitioning
	-	Marine water sediment	1.37 mg/kg dwt	Equilibrium Partitioning
	-	Soil	2.68 mg/kg dwt	Equilibrium Partitioning
maleic anhydride	-	Secondary Poisoning	20 mg/kg	-
	-	Fresh water	20.6 µg/l	Sensitivity Distribution
	-	Marine water	6.1 µg/l	Sensitivity Distribution
	-	Sewage Treatment Plant	100 µg/l	Assessment Factors
	-	Fresh water sediment	117.8 mg/kg dwt	Sensitivity Distribution
	-	Marine water sediment	56.5 mg/kg dwt	Equilibrium Partitioning
	-	Soil	35.6 mg/kg dwt	Sensitivity Distribution
	-	Fresh water	0.1 mg/l	Assessment Factors
	-	Marine water	0.01 mg/l	Assessment Factors
	-	Sewage Treatment Plant	44.6 mg/l	Assessment Factors
	-	Fresh water sediment	0.334 mg/kg dwt	Equilibrium Partitioning
	-	Marine water sediment	0.033 mg/kg dwt	Equilibrium Partitioning
	-	Soil	0.042 mg/kg dwt	Equilibrium Partitioning

8.2 Exposure controls

Code : 00328923

Date of issue/Date of revision

: 23 October 2023

SIGMAFAST 278 BASE CREAM

SECTION 8: Exposure controls/personal protection

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles and face shield. Use eye protection according to EN 166.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves : butyl rubber

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Code : 00328923

Date of issue/Date of revision

: 23 October 2023

SIGMAFAST 278 BASE CREAM

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Yellow.
- Odour** : Aromatic.
- Odour threshold** : Not available.
- Melting point/freezing point** : May start to solidify at the following temperature: 8 to 12°C (46.4 to 53.6°F) This is based on data for the following ingredient: bis-[4-(2,3-epoxipropoxy)phenyl]propane. Weighted average: -26.43°C (-15.6°F)
- Initial boiling point and boiling range** : >37.78°C
- Flammability** : Not available.
- Upper/lower flammability or explosive limits** : Greatest known range: Lower: 1.48% Upper: 13.74% (1-methoxy-2-propanol)
- Flash point** : Closed cup: 38°C
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
1-methoxy-2-propanol	270	518	

- Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).
- pH** : Not applicable. insoluble in water.
- Viscosity** : Kinematic (40°C): >21 mm²/s
- Solubility(ies)** :

Media	Result
cold water	Not soluble

- Partition coefficient: n-octanol/ water** : Not applicable.

- Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
ethylbenzene	9.3	1.2				

- Evaporation rate** : Highest known value: 0.84 (ethylbenzene) Weighted average: 0.79 compared with butyl acetate
- Relative density** : 1.64
- Vapour density** : Highest known value: 11.7 (Air = 1) (bis-[4-(2,3-epoxipropoxy)phenyl]propane). Weighted average: 8.31 (Air = 1)
- Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
- Oxidising properties** : Product does not present an oxidizing hazard.
- Particle characteristics**
- Median particle size** : Not applicable.

9.2 Other information

Code : 00328923

Date of issue/Date of revision

: 23 October 2023

SIGMAFAST 278 BASE CREAM

SECTION 9: Physical and chemical properties

No additional information.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
bis-[4-(2,3-epoxipropoxy)phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
xylene	LD50 Dermal	Rabbit	1.7 g/kg	-
	LD50 Oral	Rat	4.3 g/kg	-
4-nonylphenol, branched	LD50 Dermal	Rabbit	2.14 g/kg	-
	LD50 Oral	Rat	1300 mg/kg	-
1-methoxy-2-propanol	LC50 Inhalation Vapour	Rat	>7000 ppm	6 hours
	LD50 Dermal	Rabbit	13 g/kg	-
ethylbenzene	LD50 Oral	Rat	5.2 g/kg	-
	LC50 Inhalation Vapour	Rat	17.8 mg/l	4 hours
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	LD50 Dermal	Rabbit	17.8 g/kg	-
	LD50 Oral	Rat	3.5 g/kg	-
trizinc bis(orthophosphate)	LD50 Oral	Rat	17100 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>5.7 mg/l	4 hours
maleic anhydride	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Dermal	Rabbit	2620 mg/kg	-
	LD50 Oral	Rat	400 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Code : 00328923

Date of issue/Date of revision

: 23 October 2023

SIGMAFAST 278 BASE CREAM

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-epoxipropoxy)phenyl]propane xylene 4-nonylphenol, branched	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
	Skin - Oedema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Erythema/Eschar	Rabbit	4	-	-

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
bis-[4-(2,3-epoxipropoxy)phenyl]propane oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	skin skin	Mouse Guinea pig	Sensitising Sensitising

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
xylene 1-methoxy-2-propanol	Category 3 Category 3	- -	Respiratory tract irritation Narcotic effects

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
crystalline silica, respirable powder (<10 microns)	Category 1	inhalation	-
ethylbenzene	Category 2	-	hearing organs
maleic anhydride	Category 1	inhalation	respiratory system

Aspiration hazard

Product/ingredient name	Result
xylene ethylbenzene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Code : 00328923

Date of issue/Date of revision

: 23 October 2023

SIGMAFAST 278 BASE CREAM

SECTION 11: Toxicological information

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : No known significant effects or critical hazards.

Ingestion : Corrosive to the digestive tract. Causes burns.

Skin contact : Causes severe burns. Defatting to the skin. May cause an allergic skin reaction.

Eye contact : Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
stomach pains
reduced foetal weight
increase in foetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
pain or irritation
redness
dryness
cracking
blistering may occur
reduced foetal weight
increase in foetal deaths
skeletal malformations

Eye contact : Adverse symptoms may include the following:
pain
watering
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : Suspected of damaging fertility. Suspected of damaging the unborn child.

Code : 00328923

Date of issue/Date of revision

: 23 October 2023

SIGMAFAST 278 BASE CREAM

SECTION 11: Toxicological information

Other information : Not available.

Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia magna</i>	48 hours
4-nonylphenol, branched	Chronic NOEC 0.3 mg/l Acute EC50 0.044 mg/l	Daphnia Crustaceans - <i>Moina macrocopa</i>	21 days 48 hours
1-methoxy-2-propanol	Acute LC50 0.221 mg/l Acute LC50 23300 mg/l Acute LC50 >4500 mg/l Fresh water	Fish Daphnia Fish	96 hours 48 hours 96 hours
ethylbenzene	Acute EC50 1.8 mg/l Fresh water Chronic NOEC 1 mg/l Fresh water	Daphnia Daphnia - <i>Ceriodaphnia dubia</i>	48 hours -
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. trizinc bis(orthophosphate)	LC50 >100 mg/l Acute LC50 0.112 mg/l Chronic NOEC 0.026 mg/l	Fish Fish Fish	96 hours 96 hours 30 days

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
ethylbenzene	-	79 % - Readily - 10 days	-	-

Conclusion/Summary : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxy)phenyl]propane	-	-	Not readily
xylene	-	-	Readily
ethylbenzene	-	-	Readily

12.3 Bioaccumulative potential

Code : 00328923

Date of issue/Date of revision

: 23 October 2023

SIGMAFAST 278 BASE CREAM

SECTION 12: Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
Xylene	3.12	7.4 to 18.5	Low
4-nonylphenol, branched	5.4	251.19	Low
1-methoxy-2-propanol	<1	-	Low
ethylbenzene	3.6	79.43	Low
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	3.77	-	Low
maleic anhydride	-2.78	-	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

May cause endocrine disruption.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Code : 00328923

Date of issue/Date of revision


: 23 October 2023

SIGMAFAST 278 BASE CREAM

SECTION 13: Disposal considerations

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3470	UN3470	UN3470	UN3470
14.2 UN proper shipping name	PAINT, CORROSIVE, FLAMMABLE	PAINT, CORROSIVE, FLAMMABLE	PAINT, CORROSIVE, FLAMMABLE	PAINT, CORROSIVE, FLAMMABLE
14.3 Transport hazard class(es)	8 (3)	8 (3)	8 (3)	8 (3)
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	 (bis-[4-(2,3-epoxypropoxy)phenyl]propane, 4-nonylphenol, branched)	Not applicable.

Additional information

- ADR/RID** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- Tunnel code** : (D/E)
- ADN** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

Code : 00328923

Date of issue/Date of revision

: 23 October 2023

SIGMAFAST 278 BASE CREAM

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
<input checked="" type="checkbox"/> Endocrine disrupting properties for environment	4-nonylphenol, branched and linear substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, covering also UVCB- and well-defined substances which include any of the individual isomers or a combination thereof	Candidate	ED/169/2012	12/19/2012

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
P5c E1

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

Code : 00328923

Date of issue/Date of revision

: 23 October 2023

SIGMAFAST 278 BASE CREAM

SECTION 16: Other information

IATA = International Air Transport Association

[Full text of abbreviated H statements](#)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

[Full text of classifications \[CLP/GHS\]](#)

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Resp. Sens. 1	RESPIRATORY SENSITISATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

History

Date of issue/ Date of revision : 23 October 2023

English (GB)

Europe

20/21

Code : 00328923

Date of issue/Date of revision

: 23 October 2023

SIGMAFAST 278 BASE CREAM

SECTION 16: Other information

Date of previous issue : 31 October 2022

Prepared by : EHS

Version : 13

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.