

# SAFETY DATA SHEET

Date of issue/Date of revision : 25 October 2023 Version : 9.01



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : AMERCOAT 229T LIGHT TINT RESIN

**Product code** : 00334036

#### Other means of identification

Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications, Used by spraying.

**Use of the substance/  
mixture** : Coating.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

Sigma Paint Saudi Arabia Ltd.  
PO Box 7509  
Dammam 31472  
Saudi Arabia  
Tel: 00966 138 47 31 00  
Fax: 00966 138 47 17 34

**e-mail address of person  
responsible for this SDS** : ndpic@sfda.gov.sa

**1.4 Emergency telephone  
number** : 00966 138473100 extn 1001

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Eye Irrit. 2, H319

Skin Sens. 1, H317

Carc. 2, H351

STOT SE 3, H336

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Code : 00334036

Date of issue/Date of revision

: 25 October 2023

AMERCOAT 229T LIGHT TINT RESIN

## SECTION 2: Hazards identification

### Hazard pictograms

:



### Signal word

: Warning

### Hazard statements

: Flammable liquid and vapour.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of causing cancer.  
Toxic to aquatic life with long lasting effects.

### Precautionary statements

#### Prevention

: Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment.

#### Response

: Collect spillage.

#### Storage

: Store in a well-ventilated place. Keep container tightly closed.

#### Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.  
P280, P210, P273, P391, P403 + P233, P501

### Hazardous ingredients

: heptan-2-one  
2-methoxy-1-methylethyl acetate  
2,2-bis(acryloyloxymethyl)butyl acrylate  
Glycerol, propoxylated, esters with acrylic acid  
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid  
maleic anhydride

### Supplemental label elements

: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

### Special packaging requirements

#### Containers to be fitted with child-resistant fastenings

: Not applicable.

#### Tactile warning of danger

: Not applicable.

### 2.3 Other hazards

#### Product meets the criteria for PBT or vPvB

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### Other hazards which do not result in classification

: Prolonged or repeated contact may dry skin and cause irritation.

Code : 00334036

Date of issue/Date of revision

: 25 October 2023

AMERCOAT 229T LIGHT TINT RESIN

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

: Mixture

| Product/ingredient name  | Identifiers   | %           | Classification   | Specific Conc. Limits, M-factors and ATEs                         | Type    |
|--|---|-------------|--|---|---------|
| heptan-2-one   | REACH #:<br>01-2119902391-49<br>EC: 203-767-1<br>CAS: 110-43-0<br>Index: 606-024-00-3   | ≥10 - ≤25   | Flam. Liq. 3, H226<br>Acute Tox. 4, H302<br>Acute Tox. 4, H332<br>STOT SE 3, H336  | ATE [Oral] = 1600 mg/kg<br>ATE [Inhalation (vapours)] = 16.7 mg/l | [1] [2] |
| 2-methoxy-1-methylethyl acetate  | REACH #:<br>01-2119475791-29<br>EC: 203-603-9<br>CAS: 108-65-6<br>Index: 607-195-00-7   | ≥5.0 - ≤10  | Flam. Liq. 3, H226<br>STOT SE 3, H336  | -   | [1] [2] |
| 2,2-bis(acryloyloxymethyl) butyl acrylate  | REACH #:<br>01-2119489896-11<br>EC: 239-701-3<br>CAS: 15625-89-5<br>Index: 607-111-00-9 | ≥1.0 - ≤5.0 | Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1, H317<br>Carc. 2, H351<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410 | M [Acute] = 1<br>M [Chronic] = 1                                  | [1]     |
| butan-1-ol   | REACH #:<br>01-2119484630-38<br>EC: 200-751-6<br>CAS: 71-36-3<br>Index: 603-004-00-6    | ≥1.0 - <3.0 | Flam. Liq. 3, H226<br>Acute Tox. 4, H302<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>STOT SE 3, H335<br>STOT SE 3, H336            | ATE [Oral] = 790 mg/kg  | [1] [2] |
| (2-methoxymethylethoxy) propanol   | REACH #:<br>01-2119450011-60<br>EC: 252-104-2<br>CAS: 34590-94-8                        | ≥1.0 - ≤5.0 | Not classified.  | -   | [2]     |
| n-butyl acetate  | REACH #:<br>01-2119485493-29<br>EC: 204-658-1<br>CAS: 123-86-4<br>Index: 607-025-00-1   | ≥1.0 - ≤5.0 | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>EUH066  | -   | [1] [2] |
| Glycerol, propoxylated, esters with acrylic acid   | REACH #:<br>01-2119487948-12<br>EC: 500-114-5<br>CAS: 52408-84-1                        | <1.0        | Eye Irrit. 2, H319<br>Skin Sens. 1B, H317  | -   | [1]     |
| 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid | REACH #:<br>01-2119490020-53<br>EC: 500-130-2<br>CAS: 55818-57-0                        | <1.0        | Skin Sens. 1, H317<br>Aquatic Chronic 2, H411  | -   | [1]     |
| propylidynetrimethanol   | REACH #:<br>01-2119486799-10<br>EC: 201-074-9<br>CAS: 77-99-6                           | ≤0.30       | Repr. 2, H361  | -   | [1]     |
| maleic anhydride   | REACH #:  | ≤0.10       | Acute Tox. 4, H302   | ATE [Oral] = 400 mg/kg  | [1] [2] |

Code : 00334036 Date of issue/Date of revision : 25 October 2023  
 AMERCOAT 229T LIGHT TINT RESIN

### SECTION 3: Composition/information on ingredients

|  |   |  |  |   |  |
|--|---|--|--|---|--|
|  | 01-2119472428-31<br>EC: 203-571-6<br>CAS: 108-31-6<br>Index: 607-096-00-9 |  | Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Resp. Sens. 1, H334<br>Skin Sens. 1A, H317<br>STOT RE 1, H372<br>(respiratory system)<br>(inhalation)<br>EUH071<br><b>See Section 16 for<br/>                 the full text of the H<br/>                 statements declared<br/>                 above.</b> | kg<br>Skin Sens. 1, H317: C<br>≥ 0.001% |  |
|--|---|--|--|---|--|

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.  
 In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression.

##### Over-exposure signs/symptoms

Code : 00334036

Date of issue/Date of revision

: 25 October 2023

AMERCOAT 229T LIGHT TINT RESIN

## SECTION 4: First aid measures

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Code : 00334036

Date of issue/Date of revision

: 25 October 2023

AMERCOAT 229T LIGHT TINT RESIN

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Code : 00334036 Date of issue/Date of revision : 25 October 2023  
 AMERCOAT 229T LIGHT TINT RESIN

## SECTION 7: Handling and storage

### 7.2 Conditions for safe storage, including any incompatibilities

: Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name         | Exposure limit values   |
|---------------------------------|---|
| titanium dioxide                | <b>ACGIH TLV (United States, 1/2022).</b><br>TWA: 2.5 mg/m <sup>3</sup> 8 hours. Form: respirable fraction, finescale particles   |
| heptan-2-one                    | <b>ACGIH TLV (United States, 1/2022).</b><br>TWA: 233 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours.  |
| butan-1-ol                      | <b>ACGIH TLV (United States, 1/2022). Notes: 2002 Adoption.</b><br>TWA: 20 ppm 8 hours.   |
| (2-methoxymethylethoxy)propanol | <b>ACGIH TLV (United States, 1/2022). [(2-Methoxymethylethoxy) propanol] Absorbed through skin.</b><br>STEL: 909 mg/m <sup>3</sup> 15 minutes.<br>STEL: 150 ppm 15 minutes.<br>TWA: 606 mg/m <sup>3</sup> 8 hours.<br>TWA: 100 ppm 8 hours. |
| aluminium hydroxide             | <b>ACGIH TLV (United States, 1/2022). [Aluminum, metal and insoluble compounds]</b><br>TWA: 1 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction<br><b>ACGIH TLV (United States).</b><br>TWA: 1 mg/m <sup>3</sup>                         |
| n-butyl acetate                 | <b>ACGIH TLV (United States, 1/2022). [Butyl acetates all isomers]</b><br>STEL: 150 ppm 15 minutes.<br>TWA: 50 ppm 8 hours.   |

### Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Code : 00334036

Date of issue/Date of revision

: 25 October 2023

AMERCOAT 229T LIGHT TINT RESIN

## 8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Chemical splash goggles.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Gloves** : polyethylene butyl rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** :

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid.

**Colour** : Not available.

**Odour** : Characteristic.

**Odour threshold** : Not available.

**Melting point/freezing point** :



Code : 00334036

Date of issue/Date of revision

: 25 October 2023

AMERCOAT 229T LIGHT TINT RESIN

## SECTION 9: Physical and chemical properties

May start to solidify at the following temperature: <-20°C (<-4°F) This is based on data for the following ingredient: heptan-2-one. Weighted average: -47.31°C (-53.2°F)

**Initial boiling point and boiling range** : >37.78°C

**Flammability** : Not available.

**Upper/lower flammability or explosive limits** : Greatest known range: Lower: 1.1% Upper: 14% ((2-methoxymethylethoxy)propanol)

**Flash point** : Closed cup: 42.22°C

**Auto-ignition temperature** :

| Ingredient name                 | °C  | °F    | Method  |
|---------------------------------|-----|-------|---------|
| (2-methoxymethylethoxy)propanol | 207 | 404.6 | EU A.15 |

**Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).

**pH** : Not applicable. insoluble in water.

**Viscosity** : Kinematic (40°C): >21 mm<sup>2</sup>/s

**Solubility(ies)** :

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |

**Water Solubility at room temperature** : 3.6 g/l

**Partition coefficient: n-octanol/ water** : Not applicable.

**Vapour pressure** : 0.43 kPa (3.2 mm Hg)

**Evaporation rate** : 0.4 (butyl acetate = 1)

**Relative density** : 1.38

**Vapour density** : Highest known value: 5.1 (Air = 1) ((2-methoxymethylethoxy)propanol). Weighted average: 4.09 (Air = 1)

**Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

**Oxidising properties** : Product does not present an oxidizing hazard.

### Particle characteristics

**Median particle size** : Not applicable.

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

Code : 00334036

Date of issue/Date of revision

: 25 October 2023

AMERCOAT 229T LIGHT TINT RESIN

## SECTION 10: Stability and reactivity

**10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials:  
carbon oxides metal oxide/oxides

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

| Product/ingredient name   | Result                 | Species | Dose                    | Exposure |
|---|------------------------|---------|-------------------------|----------|
| heptan-2-one  | LC50 Inhalation Vapour | Rat     | 16.7 mg/l               | 4 hours  |
|   | LD50 Dermal            | Rabbit  | 10.206 g/kg             | -        |
|   | LD50 Oral              | Rat     | 1.6 g/kg                | -        |
| 2-methoxy-1-methylethyl acetate   | LC50 Inhalation Vapour | Rat     | 30 mg/l                 | 4 hours  |
|   | LD50 Dermal            | Rabbit  | >5 g/kg                 | -        |
|   | LD50 Oral              | Rat     | 6190 mg/kg              | -        |
| 2,2-bis(acryloyloxymethyl)butyl acrylate  | LD50 Dermal            | Rabbit  | 5170 mg/kg              | -        |
|   | LD50 Oral              | Rat     | 5.19 g/kg               | -        |
|   | LD50 Oral              | Rat     | 24000 mg/m <sup>3</sup> | 4 hours  |
| butan-1-ol  | LC50 Inhalation Vapour | Rat     | 24000 mg/m <sup>3</sup> | 4 hours  |
|   | LD50 Dermal            | Rabbit  | 3400 mg/kg              | -        |
|   | LD50 Oral              | Rat     | 790 mg/kg               | -        |
| (2-methoxymethylethoxy)propanol   | LC50 Inhalation Vapour | Rat     | 500 ppm                 | 4 hours  |
|   | LD50 Dermal            | Rabbit  | 9.5 g/kg                | -        |
|   | LD50 Oral              | Rat     | 5.23 g/kg               | -        |
| n-butyl acetate   | LC50 Inhalation Vapour | Rat     | >21.1 mg/l              | 4 hours  |
|   | LC50 Inhalation Vapour | Rat     | 2000 ppm                | 4 hours  |
|   | LD50 Dermal            | Rabbit  | >17600 mg/kg            | -        |
| Glycerol, propoxylated, esters with acrylic acid  | LD50 Oral              | Rat     | 10.768 g/kg             | -        |
|   | LD50 Dermal            | Rabbit  | >2000 mg/kg             | -        |
|   | LD50 Oral              | Rat     | >5000 mg/kg             | -        |
| Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane, 2-propenoate | LD50 Dermal            | Rat     | >2000 mg/kg             | -        |
|   | LD50 Dermal            | Rabbit  | 10 g/kg                 | -        |
| propylidynetrimethanol  | LD50 Oral              | Rat     | 14000 mg/kg             | -        |
|   | LD50 Oral              | Rabbit  | 2620 mg/kg              | -        |
| maleic anhydride  | LD50 Dermal            | Rabbit  | 400 mg/kg               | -        |
|   | LD50 Oral              | Rat     | 400 mg/kg               | -        |

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Irritation/Corrosion

| Product/ingredient name                  | Result          | Species | Score | Exposure | Observation |
|--|-----------------|---------|-------|----------|-------------|
| 2,2-bis(acryloyloxymethyl)butyl acrylate | Skin - Irritant | Rabbit  | -     | -        | -           |

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

#### Sensitisation

| Product/ingredient name  | Route of exposure | Species | Result      |
|--|-------------------|---------|-------------|
| 2,2-bis(acryloyloxymethyl)butyl acrylate   | skin              | Rabbit  | Sensitising |
| Glycerol, propoxylated, esters with acrylic acid   | skin              | Mouse   | Sensitising |
| 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid | skin              | Mouse   | Sensitising |

**Code** : 00334036 **Date of issue/Date of revision** : 25 October 2023  
 AMERCOAT 229T LIGHT TINT RESIN

## SECTION 11: Toxicological information

### Conclusion/Summary

- Skin** : There are no data available on the mixture itself.  
**Respiratory** : There are no data available on the mixture itself.

### Mutagenicity

- Conclusion/Summary** : There are no data available on the mixture itself.

### Carcinogenicity

- Conclusion/Summary** : There are no data available on the mixture itself.

### Reproductive toxicity

- Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

- Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

| Product/ingredient name         | Category   | Route of exposure | Target organs                |
|---------------------------------|------------|-------------------|------------------------------|
| heptan-2-one                    | Category 3 | -                 | Narcotic effects             |
| 2-methoxy-1-methylethyl acetate | Category 3 | -                 | Narcotic effects             |
| butan-1-ol                      | Category 3 | -                 | Respiratory tract irritation |
| n-butyl acetate                 | Category 3 | -                 | Narcotic effects             |
|                                 | Category 3 | -                 | Narcotic effects             |

### Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs      |
|-------------------------|------------|-------------------|--------------------|
| maleic anhydride        | Category 1 | inhalation        | respiratory system |

### Aspiration hazard

Not available.

- Information on likely routes of exposure** : Not available.

### Potential acute health effects

- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.  
**Ingestion** : Can cause central nervous system (CNS) depression.  
**Skin contact** : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.  
**Eye contact** : Causes serious eye irritation.

### Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : Adverse symptoms may include the following:  
 nausea or vomiting  
 headache  
 drowsiness/fatigue  
 dizziness/vertigo  
 unconsciousness
- Ingestion** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
 irritation  
 redness  
 dryness  
 cracking

Code : 00334036 Date of issue/Date of revision : 25 October 2023  
 AMERCOAT 229T LIGHT TINT RESIN

## SECTION 11: Toxicological information

**Eye contact** : Adverse symptoms may include the following:  
 pain or irritation  
 watering  
 redness

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.

**General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

**Other information** : Not available.

Prolonged or repeated contact may dry skin and cause irritation. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure. The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion may cause nausea, weakness and central nervous system effects. In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact. Avoid contact with skin and clothing.

### **11.2 Information on other hazards**

#### **11.2.1 Endocrine disrupting properties**

Not available.

#### **11.2.2 Other information**

Not available.

## SECTION 12: Ecological information

### **12.1 Toxicity**

| Product/ingredient name                             | Result                          | Species                           | Exposure |
|---|---------------------------------|-----------------------------------|----------|
| heptan-2-one  | Acute LC50 131 mg/l             | Fish                              | 96 hours |
| 2-methoxy-1-methylethyl acetate                     | Acute LC50 134 mg/l Fresh water | Fish - <i>Oncorhynchus mykiss</i> | 96 hours |
| 2,2-bis(acryloyloxymethyl)butyl acrylate            | Acute LC50 0.87 mg/l            | Fish                              | 96 hours |
| butan-1-ol  | Acute LC50 1376 mg/l            | Fish                              | 96 hours |
| (2-methoxymethylethoxy)propanol                     | Acute EC50 1919 mg/l            | Daphnia                           | 48 hours |
| n-butyl acetate                                     | Acute LC50 18 mg/l              | Fish                              | 96 hours |
| Phenol, 4,4'-(1-methylethylidene)bis-, polymer with | Chronic NOEC 0.51 mg/l          | Daphnia                           | 21 days  |

**Code** : 00334036 **Date of issue/Date of revision** : 25 October 2023  
 AMERCOAT 229T LIGHT TINT RESIN

## SECTION 12: Ecological information

|                                     |                                       |      |          |
|-------------------------------------|---------------------------------------|------|----------|
| (chloromethyl)oxirane, 2-propenoate | Fresh water<br>Chronic NOEC 0.25 mg/l | Fish | 33 days  |
| propylidynetrimethanol              | Fresh water<br>Acute LC50 >1000 mg/l  | Fish | 96 hours |

**Conclusion/Summary** : There are no data available on the mixture itself.

### 12.2 Persistence and degradability

| Product/ingredient name         | Test               | Result                   | Dose | Inoculum |
|---------------------------------|--------------------|--------------------------|------|----------|
| heptan-2-one                    | OECD 310           | 69 % - Readily - 28 days | -    | -        |
| 2-methoxy-1-methylethyl acetate | -                  | 83 % - Readily - 28 days | -    | -        |
| n-butyl acetate                 | TEPA and OECD 301D | 83 % - Readily - 28 days | -    | -        |

**Conclusion/Summary** : There are no data available on the mixture itself.

| Product/ingredient name  | Aquatic half-life | Photolysis | Biodegradability |
|--|-------------------|------------|------------------|
| heptan-2-one   | -                 | -          | Readily          |
| 2-methoxy-1-methylethyl acetate  | -                 | -          | Readily          |
| n-butyl acetate  | -                 | -          | Readily          |
| 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid | -                 | -          | Inherent         |

### 12.3 Bioaccumulative potential

| Product/ingredient name  | LogP <sub>ow</sub> | BCF | Potential |
|--|--------------------|-----|-----------|
| heptan-2-one   | 2.26               | -   | Low       |
| 2-methoxy-1-methylethyl acetate  | 1.2                | -   | Low       |
| 2,2-bis(acryloyloxymethyl)butyl acrylate   | 0.67               | -   | Low       |
| butan-1-ol   | 1                  | -   | Low       |
| (2-methoxymethylethoxy)propanol  | 0.004              | -   | Low       |
| n-butyl acetate  | 2.3                | -   | Low       |
| Glycerol, propoxylated, esters with acrylic acid   | 2.52               | -   | Low       |
| 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid | 1.6 to 3           | -   | Low       |
| propylidynetrimethanol   | -0.47              | -   | Low       |
| maleic anhydride   | -2.78              | -   | Low       |

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

**Code** : 00334036 **Date of issue/Date of revision** : 25 October 2023  
 AMERCOAT 229T LIGHT TINT RESIN

## SECTION 12: Ecological information

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

#### European waste catalogue (EWC)

| Waste code | Waste designation              |
|------------|--------------------------------|
| 08 01 99   | wastes not otherwise specified |

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container         | 15 01 06 mixed packaging       |

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

|  | ADR/RID         | IMDG  | IATA   |
|--|-----------------|---|--|
| <b>14.1 UN number or ID number</b>     | UN1263          | UN1263                                      | UN1263   |
| <b>14.2 UN proper shipping name</b>    | PAINT           | PAINT                                       | PAINT  |
| <b>14.3 Transport hazard class(es)</b> | 3               | 3   | 3  |
| <b>14.4 Packing group</b>              | III             | III   | III  |
| <b>14.5 Environmental hazards</b>      | Yes.            | Yes.  | Yes. The environmentally hazardous substance mark is not required. |
| <b>Marine pollutant substances</b>     | Not applicable. | (2,2-bis(acryloyloxymethyl) butyl acrylate) | Not applicable.  |

### Additional information

Code : 00334036 Date of issue/Date of revision : 25 October 2023  
AMERCOAT 229T LIGHT TINT RESIN

## SECTION 14: Transport information

- ADR/RID** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- Tunnel code** : (D/E)
- IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not applicable.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Other national and international regulations.

##### Ozone depleting substances (1005/2009/EU)

Not listed.

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

🔍 Indicates information that has changed from previously issued version.

- Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number
- Full text of abbreviated H statements** : H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.

**Code** : 00334036 **Date of issue/Date of revision** : 25 October 2023  
 AMERCOAT 229T LIGHT TINT RESIN

## SECTION 16: Other information

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H351 Suspected of causing cancer.  
 H361 Suspected of damaging fertility or the unborn child.  
 H372 Causes damage to organs through prolonged or repeated exposure.  
 H400 Very toxic to aquatic life.  
 H410 Very toxic to aquatic life with long lasting effects.  
 H411 Toxic to aquatic life with long lasting effects.  
 EUH066 Repeated exposure may cause skin dryness or cracking.  
 EUH071 Corrosive to the respiratory tract.

### Full text of classifications [CLP/GHS]

: Acute Tox. 4 ACUTE TOXICITY - Category 4  
 Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1  
 Aquatic Chronic 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1  
 Aquatic Chronic 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2  
 Carc. 2 CARCINOGENICITY - Category 2  
 Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1  
 Eye Irrit. 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2  
 Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3  
 Repr. 2 REPRODUCTIVE TOXICITY - Category 2  
 Resp. Sens. 1 RESPIRATORY SENSITISATION - Category 1  
 Skin Corr. 1B SKIN CORROSION/IRRITATION - Category 1B  
 Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2  
 Skin Sens. 1 SKIN SENSITISATION - Category 1  
 Skin Sens. 1A SKIN SENSITISATION - Category 1A  
 Skin Sens. 1B SKIN SENSITISATION - Category 1B  
 STOT RE 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1  
 STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

### History

**Date of issue/ Date of revision** : 25 October 2023

**Date of previous issue** : 23 October 2023

**Prepared by** : EHS

**Version** : 9.01

### Disclaimer

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*