

SAFETY DATA SHEET

Date of issue/Date of revision

: 15 December 2023

Version

: 19



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : PPG VIKOTE 56 ORANGE 3149

Product code : 00155531

Other means of identification

Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/mixture : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL

Tweemontstraat 104

B-2100 Deurne

Belgium

Telephone +32-33606311

Fax +32-33606435

e-mail address of person responsible for this SDS : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : Poison Information Centre; emergency telephone, public + 45 82 12 12 12 (health sector +45 35 31 55 55)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Carc. 1B, H350

Lact., H362

STOT SE 3, H335

STOT SE 3, H336

Aquatic Acute 1, H400

Aquatic Chronic 1, H410

Code : 00155531

Date of issue/Date of revision

: 15 December 2023

PPG VIKOTE 56 ORANGE 3149

SECTION 2: Hazards identification

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word

: **D**anger

Hazard statements

: **H**228, **H**314, **H**332, **H**334, **H**335, **H**350, **H**373, **H**411
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause cancer.
May cause harm to breast-fed children.
Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

: **P**201, **P**203, **P**231, **P**232, **P**233, **P**234, **P**235, **P**240, **P**241, **P**242, **P**243, **P**244, **P**245, **P**246, **P**247, **P**248, **P**249, **P**251, **P**253, **P**254, **P**255, **P**256, **P**257, **P**258, **P**259, **P**261, **P**262, **P**263, **P**264, **P**271, **P**272, **P**273, **P**274, **P**280, **P**281, **P**282, **P**283, **P**284, **P**285, **P**286, **P**287, **P**288, **P**289, **P**290, **P**291, **P**292, **P**293, **P**294, **P**295, **P**296, **P**297, **P**298, **P**299, **P**300, **P**301, **P**302, **P**303, **P**304, **P**305, **P**306, **P**307, **P**308, **P**309, **P**310, **P**311, **P**312, **P**313, **P**314, **P**315, **P**316, **P**317, **P**318, **P**319, **P**320, **P**321, **P**322, **P**323, **P**324, **P**325, **P**326, **P**327, **P**328, **P**329, **P**330, **P**331, **P**332, **P**333, **P**334, **P**335, **P**336, **P**337, **P**338, **P**339, **P**340, **P**341, **P**342, **P**343, **P**344, **P**345, **P**346, **P**347, **P**348, **P**349, **P**350, **P**351, **P**352, **P**353, **P**354, **P**355, **P**356, **P**357, **P**358, **P**359, **P**360, **P**361, **P**362, **P**363, **P**364, **P**365, **P**366, **P**367, **P**368, **P**369, **P**370, **P**371, **P**372, **P**373, **P**374, **P**375, **P**376, **P**377, **P**378, **P**379, **P**380, **P**381, **P**382, **P**383, **P**384, **P**385, **P**386, **P**387, **P**388, **P**389, **P**390, **P**391, **P**392, **P**393, **P**394, **P**395, **P**396, **P**397, **P**398, **P**399, **P**400, **P**401, **P**402, **P**403, **P**404, **P**405, **P**406, **P**407, **P**408, **P**409, **P**410, **P**411, **P**412, **P**413, **P**414, **P**415, **P**416, **P**417, **P**418, **P**419, **P**420, **P**421, **P**422, **P**423, **P**424, **P**425, **P**426, **P**427, **P**428, **P**429, **P**430, **P**431, **P**432, **P**433, **P**434, **P**435, **P**436, **P**437, **P**438, **P**439, **P**440, **P**441, **P**442, **P**443, **P**444, **P**445, **P**446, **P**447, **P**448, **P**449, **P**450, **P**451, **P**452, **P**453, **P**454, **P**455, **P**456, **P**457, **P**458, **P**459, **P**460, **P**461, **P**462, **P**463, **P**464, **P**465, **P**466, **P**467, **P**468, **P**469, **P**470, **P**471, **P**472, **P**473, **P**474, **P**475, **P**476, **P**477, **P**478, **P**479, **P**480, **P**481, **P**482, **P**483, **P**484, **P**485, **P**486, **P**487, **P**488, **P**489, **P**490, **P**491, **P**492, **P**493, **P**494, **P**495, **P**496, **P**497, **P**498, **P**499, **P**500, **P**501, **P**502, **P**503, **P**504, **P**505, **P**506, **P**507, **P**508, **P**509, **P**510, **P**511, **P**512, **P**513, **P**514, **P**515, **P**516, **P**517, **P**518, **P**519, **P**520, **P**521, **P**522, **P**523, **P**524, **P**525, **P**526, **P**527, **P**528, **P**529, **P**530, **P**531, **P**532, **P**533, **P**534, **P**535, **P**536, **P**537, **P**538, **P**539, **P**540, **P**541, **P**542, **P**543, **P**544, **P**545, **P**546, **P**547, **P**548, **P**549, **P**550, **P**551, **P**552, **P**553, **P**554, **P**555, **P**556, **P**557, **P**558, **P**559, **P**560, **P**561, **P**562, **P**563, **P**564, **P**565, **P**566, **P**567, **P**568, **P**569, **P**570, **P**571, **P**572, **P**573, **P**574, **P**575, **P**576, **P**577, **P**578, **P**579, **P**580, **P**581, **P**582, **P**583, **P**584, **P**585, **P**586, **P**587, **P**588, **P**589, **P**590, **P**591, **P**592, **P**593, **P**594, **P**595, **P**596, **P**597, **P**598, **P**599, **P**600, **P**601, **P**602, **P**603, **P**604, **P**605, **P**606, **P**607, **P**608, **P**609, **P**610, **P**611, **P**612, **P**613, **P**614, **P**615, **P**616, **P**617, **P**618, **P**619, **P**620, **P**621, **P**622, **P**623, **P**624, **P**625, **P**626, **P**627, **P**628, **P**629, **P**630, **P**631, **P**632, **P**633, **P**634, **P**635, **P**636, **P**637, **P**638, **P**639, **P**640, **P**641, **P**642, **P**643, **P**644, **P**645, **P**646, **P**647, **P**648, **P**649, **P**650, **P**651, **P**652, **P**653, **P**654, **P**655, **P**656, **P**657, **P**658, **P**659, **P**660, **P**661, **P**662, **P**663, **P**664, **P**665, **P**666, **P**667, **P**668, **P**669, **P**670, **P**671, **P**672, **P**673, **P**674, **P**675, **P**676, **P**677, **P**678, **P**679, **P**680, **P**681, **P**682, **P**683, **P**684, **P**685, **P**686, **P**687, **P**688, **P**689, **P**690, **P**691, **P**692, **P**693, **P**694, **P**695, **P**696, **P**697, **P**698, **P**699, **P**700, **P**701, **P**702, **P**703, **P**704, **P**705, **P**706, **P**707, **P**708, **P**709, **P**710, **P**711, **P**712, **P**713, **P**714, **P**715, **P**716, **P**717, **P**718, **P**719, **P**720, **P**721, **P**722, **P**723, **P**724, **P**725, **P**726, **P**727, **P**728, **P**729, **P**730, **P**731, **P**732, **P**733, **P**734, **P**735, **P**736, **P**737, **P**738, **P**739, **P**740, **P**741, **P**742, **P**743, **P**744, **P**745, **P**746, **P**747, **P**748, **P**749, **P**750, **P**751, **P**752, **P**753, **P**754, **P**755, **P**756, **P**757, **P**758, **P**759, **P**760, **P**761, **P**762, **P**763, **P**764, **P**765, **P**766, **P**767, **P**768, **P**769, **P**770, **P**771, **P**772, **P**773, **P**774, **P**775, **P**776, **P**777, **P**778, **P**779, **P**780, **P**781, **P**782, **P**783, **P**784, **P**785, **P**786, **P**787, **P**788, **P**789, **P**790, **P**791, **P**792, **P**793, **P**794, **P**795, **P**796, **P**797, **P**798, **P**799, **P**800, **P**801, **P**802, **P**803, **P**804, **P**805, **P**806, **P**807, **P**808, **P**809, **P**810, **P**811, **P**812, **P**813, **P**814, **P**815, **P**816, **P**817, **P**818, **P**819, **P**820, **P**821, **P**822, **P**823, **P**824, **P**825, **P**826, **P**827, **P**828, **P**829, **P**830, **P**831, **P**832, **P**833, **P**834, **P**835, **P**836, **P**837, **P**838, **P**839, **P**840, **P**841, **P**842, **P**843, **P**844, **P**845, **P**846, **P**847, **P**848, **P**849, **P**850, **P**851, **P**852, **P**853, **P**854, **P**855, **P**856, **P**857, **P**858, **P**859, **P**860, **P**861, **P**862, **P**863, **P**864, **P**865, **P**866, **P**867, **P**868, **P**869, **P**870, **P**871, **P**872, **P**873, **P**874, **P**875, **P**876, **P**877, **P**878, **P**879, **P**880, **P**881, **P**882, **P**883, **P**884, **P**885, **P**886, **P**887, **P**888, **P**889, **P**890, **P**891, **P**892, **P**893, **P**894, **P**895, **P**896, **P**897, **P**898, **P**899, **P**900, **P**901, **P**902, **P**903, **P**904, **P**905, **P**906, **P**907, **P**908, **P**909, **P**910, **P**911, **P**912, **P**913, **P**914, **P**915, **P**916, **P**917, **P**918, **P**919, **P**920, **P**921, **P**922, **P**923, **P**924, **P**925, **P**926, **P**927, **P**928, **P**929, **P**930, **P**931, **P**932, **P**933, **P**934, **P**935, **P**936, **P**937, **P**938, **P**939, **P**940, **P**941, **P**942, **P**943, **P**944, **P**945, **P**946, **P**947, **P**948, **P**949, **P**950, **P**951, **P**952, **P**953, **P**954, **P**955, **P**956, **P**957, **P**958, **P**959, **P**960, **P**961, **P**962, **P**963, **P**964, **P**965, **P**966, **P**967, **P**968, **P**969, **P**970, **P**971, **P**972, **P**973, **P**974, **P**975, **P**976, **P**977, **P**978, **P**979, **P**980, **P**981, **P**982, **P**983, **P**984, **P**985, **P**986, **P**987, **P**988, **P**989, **P**990, **P**991, **P**992, **P**993, **P**994, **P**995, **P**996, **P**997, **P**998, **P**999, **P**1000

Response

: **R**601, **R**602, **R**603, **R**604, **R**605, **R**606, **R**607, **R**608, **R**609, **R**610, **R**611, **R**612, **R**613, **R**614, **R**615, **R**616, **R**617, **R**618, **R**619, **R**620, **R**621, **R**622, **R**623, **R**624, **R**625, **R**626, **R**627, **R**628, **R**629, **R**630, **R**631, **R**632, **R**633, **R**634, **R**635, **R**636, **R**637, **R**638, **R**639, **R**640, **R**641, **R**642, **R**643, **R**644, **R**645, **R**646, **R**647, **R**648, **R**649, **R**650, **R**651, **R**652, **R**653, **R**654, **R**655, **R**656, **R**657, **R**658, **R**659, **R**660, **R**661, **R**662, **R**663, **R**664, **R**665, **R**666, **R**667, **R**668, **R**669, **R**670, **R**671, **R**672, **R**673, **R**674, **R**675, **R**676, **R**677, **R**678, **R**679, **R**680, **R**681, **R**682, **R**683, **R**684, **R**685, **R**686, **R**687, **R**688, **R**689, **R**690, **R**691, **R**692, **R**693, **R**694, **R**695, **R**696, **R**697, **R**698, **R**699, **R**700, **R**701, **R**702, **R**703, **R**704, **R**705, **R**706, **R**707, **R**708, **R**709, **R**710, **R**711, **R**712, **R**713, **R**714, **R**715, **R**716, **R**717, **R**718, **R**719, **R**720, **R**721, **R**722, **R**723, **R**724, **R**725, **R**726, **R**727, **R**728, **R**729, **R**730, **R**731, **R**732, **R**733, **R**734, **R**735, **R**736, **R**737, **R**738, **R**739, **R**740, **R**741, **R**742, **R**743, **R**744, **R**745, **R**746, **R**747, **R**748, **R**749, **R**750, **R**751, **R**752, **R**753, **R**754, **R**755, **R**756, **R**757, **R**758, **R**759, **R**760, **R**761, **R**762, **R**763, **R**764, **R**765, **R**766, **R**767, **R**768, **R**769, **R**770, **R**771, **R**772, **R**773, **R**774, **R**775, **R**776, **R**777, **R**778, **R**779, **R**780, **R**781, **R**782, **R**783, **R**784, **R**785, **R**786, **R**787, **R**788, **R**789, **R**790, **R**791, **R**792, **R**793, **R**794, **R**795, **R**796, **R**797, **R**798, **R**799, **R**800, **R**801, **R**802, **R**803, **R**804, **R**805, **R**806, **R**807, **R**808, **R**809, **R**810, **R**811, **R**812, **R**813, **R**814, **R**815, **R**816, **R**817, **R**818, **R**819, **R**820, **R**821, **R**822, **R**823, **R**824, **R**825, **R**826, **R**827, **R**828, **R**829, **R**830, **R**831, **R**832, **R**833, **R**834, **R**835, **R**836, **R**837, **R**838, **R**839, **R**840, **R**841, **R**842, **R**843, **R**844, **R**845, **R**846, **R**847, **R**848, **R**849, **R**850, **R**851, **R**852, **R**853, **R**854, **R**855, **R**856, **R**857, **R**858, **R**859, **R**860, **R**861, **R**862, **R**863, **R**864, **R**865, **R**866, **R**867, **R**868, **R**869, **R**870, **R**871, **R**872, **R**873, **R**874, **R**875, **R**876, **R**877, **R**878, **R**879, **R**880, **R**881, **R**882, **R**883, **R**884, **R**885, **R**886, **R**887, **R**888, **R**889, **R**890, **R**891, **R**892, **R**893, **R**894, **R**895, **R**896, **R**897, **R**898, **R**899, **R**900, **R**901, **R**902, **R**903, **R**904, **R**905, **R**906, **R**907, **R**908, **R**909, **R**910, **R**911, **R**912, **R**913, **R**914, **R**915, **R**916, **R**917, **R**918, **R**919, **R**920, **R**921, **R**922, **R**923, **R**924, **R**925, **R**926, **R**927, **R**928, **R**929, **R**930, **R**931, **R**932, **R**933, **R**934, **R**935, **R**936, **R**937, **R**938, **R**939, **R**940, **R**941, **R**942, **R**943, **R**944, **R**945, **R**946, **R**947, **R**948, **R**949, **R**950, **R**951, **R**952, **R**953, **R**954, **R**955, **R**956, **R**957, **R**958, **R**959, **R**960, **R**961, **R**962, **R**963, **R**964, **R**965, **R**966, **R**967, **R**968, **R**969, **R**970, **R**971, **R**972, **R**973, **R**974, **R**975, **R**976, **R**

Code : 00155531 Date of issue/Date of revision : 15 December 2023
PPG VIKOTE 56 ORANGE 3149

SECTION 2: Hazards identification

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Hydrocarbons, C9, aromatics > 0.1% cumene	REACH #: 01-2119455851-35 EC: 918-668-5 CAS: 64742-95-6	≥25 - ≤50	Flam. Liq. 3, H226 Carc. 1B, H350 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	Carc. 1B, H350: C ≥ 10% EUH066: C ≥ 20%	[1]
xylene	EC: 215-535-7 CAS: 1330-20-7	≥10 - ≤25	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1700 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
alkanes, C14-17, chloro	REACH #: 01-2119519269-33 EC: 287-477-0 CAS: 85535-85-9 Index: 602-095-00-X	≥1.0 - ≤5.0	Lact., H362 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH066	M [Acute] = 100 M [Chronic] = 10	[1] [3] [4]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Inhalation (vapours)] = 17.8 mg/l	[1] [2]
1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene	REACH #: 01-2119962189-26 CAS: 911674-82-3 Index: 616-198-00-2	<1.0	Skin Sens. 1, H317 Aquatic Chronic 4, H413	-	[1]
n-butyl methacrylate	REACH #: 01-2119486394-28 EC: 202-615-1 CAS: 97-88-1 Index: 607-033-00-5	<1.0	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335	-	[1] [2]
trizinc bis(orthophosphate)	REACH #: 01-2119485044-40 EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6	≤0.30	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]

Code : 00155531

Date of issue/Date of revision

: 15 December 2023

PPG VIKOTE 56 ORANGE 3149

SECTION 3: Composition/information on ingredients

			See Section 16 for the full text of the H statements declared above.		
--	--	--	---	--	--

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Xylene: Several REACH registrations cover the REACH registered substance with xylene isomers, ethylbenzene (and toluene). The other REACH Registrations include: 01-2119555267-33 reaction mass of ethylbenzene and m-xylene and p-xylene, 01-2119486136-34 Aromatic hydrocarbons, C8, 01-2119539452-40 reaction mass of ethylbenzene and xylene.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation. Defatting to the skin.
- Ingestion** : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness

Code : 00155531

Date of issue/Date of revision

: 15 December 2023

PPG VIKOTE 56 ORANGE 3149

SECTION 4: First aid measures

- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
halogenated compounds
metal oxide/oxides

5.3 Advice for firefighters

Code : 00155531 Date of issue/Date of revision : 15 December 2023
PPG VIKOTE 56 ORANGE 3149

SECTION 5: Firefighting measures

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Code : 00155531

Date of issue/Date of revision

: 15 December 2023

PPG VIKOTE 56 ORANGE 3149

SECTION 7: Handling and storage

Protective measures : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid contact during pregnancy or while nursing. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
xylene	Working Environment Authority (Denmark, 2/2023). [Xylenes, all isomers] Absorbed through skin. TWA: 109 mg/m ³ 8 hours. TWA: 25 ppm 8 hours. STEL: 442 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes.
ethylbenzene	Working Environment Authority (Denmark, 2/2023). Absorbed through skin. Carcinogen. TWA: 217 mg/m ³ 8 hours. TWA: 50 ppm 8 hours. STEL: 434 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes.
n-butyl methacrylate	Working Environment Authority (Denmark, 2/2023). TWA: 145 mg/m ³ 8 hours. TWA: 25 ppm 8 hours.

English (GB)

Denmark

7/20

Code : 00155531

Date of issue/Date of revision

: 15 December 2023

PPG VIKOTE 56 ORANGE 3149

SECTION 8: Exposure controls/personal protection

STEL: 290 mg/m³ 15 minutes.

STEL: 50 ppm 15 minutes.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

Product/ingredient name	Type	Exposure	Value	Population	Effects	
Hydrocarbons, C9, aromatics > 0.1% cumene	DNEL	Long term Inhalation	150 mg/m ³	Workers	Systemic	
	DNEL	Long term Dermal	25 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	32 mg/m ³	General population	Systemic	
	DNEL	Long term Dermal	11 mg/kg bw/day	General population	Systemic	
	xylene	DNEL	Long term Oral	11 mg/kg bw/day	General population	Systemic
		DNEL	Long term Oral	12.5 mg/kg bw/day	General population	Systemic
		DNEL	Long term Inhalation	65.3 mg/m ³	General population	Local
		DNEL	Long term Inhalation	65.3 mg/m ³	General population	Systemic
		DNEL	Long term Dermal	125 mg/kg bw/day	General population	Systemic
		DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic
		DNEL	Long term Inhalation	221 mg/m ³	Workers	Local
		DNEL	Long term Inhalation	221 mg/m ³	Workers	Systemic
		DNEL	Short term Inhalation	260 mg/m ³	General population	Local
		DNEL	Short term Inhalation	260 mg/m ³	General population	Systemic
alkanes, C14-17, chloro	DNEL	Short term Inhalation	442 mg/m ³	Workers	Local	
	DNEL	Short term Inhalation	442 mg/m ³	Workers	Systemic	
	DNEL	Long term Oral	0.58 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	2 mg/m ³	General population	Systemic	
	DNEL	Long term Inhalation	6.7 mg/m ³	Workers	Systemic	
	DNEL	Long term Dermal	28.75 mg/kg bw/day	General population	Systemic	
	ethylbenzene	DNEL	Long term Dermal	47.9 mg/kg bw/day	Workers	Systemic
		DMEL	Long term Inhalation	442 mg/m ³	Workers	Local
		DMEL	Short term Inhalation	884 mg/m ³	Workers	Systemic
		DNEL	Long term Oral	1.6 mg/kg bw/day	General population	Systemic
DNEL		Long term Inhalation	15 mg/m ³	General population	Systemic	
DNEL		Long term Inhalation	77 mg/m ³	Workers	Systemic	
DNEL		Long term Dermal	180 mg/kg bw/day	Workers	Systemic	
DNEL		Short term Inhalation	293 mg/m ³	Workers	Local	
n-butyl methacrylate	DNEL	Long term Dermal	3 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	5 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	66.5 mg/m ³	General population	Systemic	
	DNEL	Long term Inhalation	366.4 mg/m ³	General population	Local	
	DNEL	Long term Inhalation	409 mg/m ³	Workers	Local	
	DNEL	Long term Inhalation	415.9 mg/m ³	Workers	Systemic	
	trizinc bis(orthophosphate)	DNEL	Long term Oral	0.83 mg/kg bw/day	General population	Systemic
		DNEL	Long term Inhalation	2.5 mg/m ³	General population	Systemic
DNEL		Long term Inhalation	5 mg/m ³	Workers	Systemic	
DNEL		Long term Dermal	83 mg/kg bw/day	General population	Systemic	
DNEL		Long term Dermal	83 mg/kg bw/day	Workers	Systemic	

PNECs

Code : 00155531

Date of issue/Date of revision

: 15 December 2023

PPG VIKOTE 56 ORANGE 3149

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
xylene	-	Fresh water	0.327 mg/l	-
	-	Marine water	0.327 mg/l	-
	-	Sewage Treatment Plant	6.58 mg/l	-
	-	Fresh water sediment	12.46 mg/kg dwt	-
	-	Marine water sediment	12.46 mg/kg dwt	-
	-	Soil	2.31 mg/kg	-
ethylbenzene	-	Fresh water	0.1 mg/l	Assessment Factors
	-	Marine water	0.01 mg/l	Assessment Factors
	-	Sewage Treatment Plant	9.6 mg/l	Assessment Factors
	-	Fresh water sediment	13.7 mg/kg dwt	Equilibrium Partitioning
	-	Marine water sediment	1.37 mg/kg dwt	Equilibrium Partitioning
	-	Soil	2.68 mg/kg dwt	Equilibrium Partitioning
trizinc bis(orthophosphate)	-	Secondary Poisoning	20 mg/kg	-
	-	Fresh water	20.6 µg/l	Sensitivity Distribution
	-	Marine water	6.1 µg/l	Sensitivity Distribution
	-	Sewage Treatment Plant	100 µg/l	Assessment Factors
	-	Fresh water sediment	117.8 mg/kg dwt	Sensitivity Distribution
	-	Marine water sediment	56.5 mg/kg dwt	Equilibrium Partitioning
-	Soil	35.6 mg/kg dwt	Sensitivity Distribution	

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Chemical splash goggles. Use eye protection according to EN 166.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves

: For prolonged or repeated handling, use the following type of gloves:

May be used: nitrile rubber

Recommended: polyvinyl alcohol (PVA), Viton®

Code : 00155531

Date of issue/Date of revision

: 15 December 2023

PPG VIKOTE 56 ORANGE 3149

SECTION 8: Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Orange.
- Odour** : Aromatic.
- Odour threshold** : Not available.
- Melting point/freezing point** : May start to solidify at the following temperature: >300°C (>572°F) This is based on data for the following ingredient: Pyrrolo[3,4-c]pyrrole-1,4-dione, 2,5-dihydro-3,6-diphenyl-. Weighted average: -50.98°C (-59.8°F)
- Initial boiling point and boiling range** : >37.78°C
- Flammability** : Not available.
- Upper/lower flammability or explosive limits** : Greatest known range: Lower: 1.4% Upper: 7.6% (Solvent naphtha (petroleum), light aromatic)
- Flash point** : Closed cup: 34°C
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
Pyrrolo[3,4-c]pyrrole-1,4-dione, 2,5-dihydro-3,6-diphenyl-	400	752	

- Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).
- pH** : Not applicable. insoluble in water.
- Viscosity** : Kinematic (40°C): >21 mm²/s
- Solubility(ies)** :

Media	Result
cold water	Not soluble

Code : 00155531

Date of issue/Date of revision

: 15 December 2023

PPG VIKOTE 56 ORANGE 3149

SECTION 9: Physical and chemical properties

Partition coefficient: n-octanol/ water : Not applicable.

Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
ethylbenzene	9.30076	1.2				

Evaporation rate : Highest known value: 0.84 (ethylbenzene) Weighted average: 0.73 compared with butyl acetate

Relative density : 1.03

Vapour density : Highest known value: 4.1 (Air = 1) (1,2,4-trimethylbenzene). Weighted average: 3.88 (Air = 1)

Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

Oxidising properties : Product does not present an oxidizing hazard.

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Code : 00155531

Date of issue/Date of revision

: 15 December 2023

PPG VIKOTE 56 ORANGE 3149

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
Hydrocarbons, C9, aromatics > 0.1% cumene	LD50 Dermal	Rabbit	>3160 mg/kg	-
	LD50 Oral	Rat - Female	3492 mg/kg	-
xylene	LD50 Dermal	Rabbit	1.7 g/kg	-
	LD50 Oral	Rat	4.3 g/kg	-
alkanes, C14-17, chloro	LC50 Inhalation Vapour	Rat	>48.17 g/m ³	1 hours
	LD50 Oral	Rat	>5 g/kg	-
ethylbenzene	LC50 Inhalation Vapour	Rat	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	17.8 g/kg	-
	LD50 Oral	Rat	3.5 g/kg	-
1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene	LC50 Inhalation Dusts and mists	Rat	>5.08 mg/l	4 hours
n-butyl methacrylate	LC50 Inhalation Gas.	Rat	4910 ppm	4 hours
	LC50 Inhalation Vapour	Rat	29000 mg/m ³	4 hours
	LD50 Dermal	Rabbit	10.2 g/kg	-
	LD50 Oral	Rat	16 g/kg	-
trizinc bis(orthophosphate)	LC50 Inhalation Dusts and mists	Rat	>5.7 mg/l	4 hours
	LD50 Oral	Rat	>5000 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitisation

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Hydrocarbons, C9, aromatics > 0.1% cumene	Category 3	-	Respiratory tract irritation
	Category 3	-	Narcotic effects
xylene	Category 3	-	Respiratory tract irritation
n-butyl methacrylate	Category 3	-	Respiratory tract irritation

English (GB)

Denmark

12/20

Code : 00155531 Date of issue/Date of revision : 15 December 2023
PPG VIKOTE 56 ORANGE 3149

SECTION 11: Toxicological information

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs

Aspiration hazard

Product/ingredient name	Result
Hydrocarbons, C9, aromatics > 0.1% cumene xylene ethylbenzene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.

Potential acute health effects

- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.
- Skin contact** : Causes skin irritation. Defatting to the skin.
- Eye contact** : Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Code : 00155531

Date of issue/Date of revision

: 15 December 2023

PPG VIKOTE 56 ORANGE 3149

SECTION 11: Toxicological information

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : May cause harm to breast-fed children.

Other information : Not available.

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
<input checked="" type="checkbox"/> Hydrocarbons, C9, aromatics > 0.1% cumene	EC50 3.2 mg/l LC50 9.2 mg/l	Daphnia Fish	48 hours 96 hours
ethylbenzene	Acute EC50 1.8 mg/l Fresh water Chronic NOEC 1 mg/l Fresh water	Daphnia Daphnia - <i>Ceriodaphnia dubia</i>	48 hours -
1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene	Acute LC50 >100 mg/l	Fish	96 hours
trizinc bis(orthophosphate)	Acute LC50 0.112 mg/l Chronic NOEC 0.026 mg/l	Fish Fish	96 hours 30 days

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
<input checked="" type="checkbox"/> Hydrocarbons, C9, aromatics > 0.1% cumene	-	75 % - Readily - 28 days	-	-
ethylbenzene	-	79 % - Readily - 10 days	-	-

Conclusion/Summary : There are no data available on the mixture itself.

Code : 00155531 Date of issue/Date of revision : 15 December 2023
PPG VIKOTE 56 ORANGE 3149

SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Hydrocarbons, C9, aromatics > 0.1% cumene	-	-	Readily
xylene	-	-	Readily
ethylbenzene	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
xylene	3.12	7.4 to 18.5	Low
alkanes, C14-17, chloro	4.7 to 8.3	-	High
ethylbenzene	3.6	79.43	Low
n-butyl methacrylate	2.99	-	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
xylene	No	N/A	No	No	No	N/A	No
alkanes, C14-17, chloro	SVHC (Candidate)	Specified	Specified	Specified	SVHC (Candidate)	Specified	Specified
ethylbenzene	No	N/A	No	Yes	No	N/A	No
1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene	No	N/A	N/A	No	N/A	N/A	N/A
n-butyl methacrylate	No	N/A	N/A	No	N/A	N/A	N/A

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

Code : 00155531 Date of issue/Date of revision : 15 December 2023
PPG VIKOTE 56 ORANGE 3149

SECTION 13: Disposal considerations

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	☑ (Solvent naphtha (petroleum), light aromatic)	Not applicable.

Additional information

ADR/RID : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Tunnel code : (D/E)
ADN : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
IMDG : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Code : 00155531 Date of issue/Date of revision : 15 December 2023
PPG VIKOTE 56 ORANGE 3149

14. Transport information

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorisation](#)

[Annex XIV](#)

None of the components are listed.

[Substances of very high concern](#)

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
PBT	medium-chain chlorinated paraffins UVCB substances consisting of more than or equal to 80% linear chloroalkanes with carbon chain lengths within the range from C14 to C17	Candidate	D(2021) 4569-DC	7/8/2021
vPvB	medium-chain chlorinated paraffins UVCB substances consisting of more than or equal to 80% linear chloroalkanes with carbon chain lengths within the range from C14 to C17	Candidate	D(2021) 4569-DC	7/8/2021

[Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles](#) : Restricted to professional users.

[Explosive precursors](#) : Not applicable.

[Ozone depleting substances \(1005/2009/EU\)](#)

Not listed.

[Seveso Directive](#)

This product is controlled under the Seveso Directive.

[Danger criteria](#)

Category
P5c E1

[National regulations](#)

[Product registration number](#) : PR-1026035

[Danish fire class](#) : II-1

[Executive Order No. 1795/2015](#)

Ingredient name	Annex I Section A	Annex I Section B
<input checked="" type="checkbox"/> Ethylbenzene Hydrocarbons, C9, aromatics > 0.1% cumene	Listed -	- Carc. 1B, H350

[MAL-code](#) : 4-3

Code : 00155531

Date of issue/Date of revision

: 15 December 2023

PPG VIKOTE 56 ORANGE 3149

SECTION 15: Regulatory information

Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

General: Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 4-3

Application: When spraying in new* booths if the operator is outside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin.

- Air-supplied half mask and eye protection must be worn.

When using scraper or knife, brush, roller, etc. for pre- and post-treatments in cabins or booths of the existing* facility type, if the operator is inside the spray zone.

- Air-supplied half mask, coveralls and eye protection must be worn.

During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Air-supplied full mask and coveralls must be worn.

When spraying in existing* spray booths, if the operator is outside the spray zone.

- Air-supplied full mask, arm protectors and apron must be worn.

During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied full mask must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, coveralls and hood must be worn.

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

Code : 00155531

Date of issue/Date of revision

: 15 December 2023

PPG VIKOTE 56 ORANGE 3149

SECTION 15: Regulatory information

Caution The regulations contain other stipulations in addition to the above.

*See Regulations.

- Restrictions on use** : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.
- List of undesirable substances** : Listed
- Carcinogenic waste** : Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

[Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

Classification	Justification
✔ Flam. Liq. 3, H226	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Carc. 1B, H350	Calculation method
Lact., H362	Calculation method
STOT SE 3, H335	Calculation method
STOT SE 3, H336	Calculation method
Aquatic Acute 1, H400	Calculation method
Aquatic Chronic 1, H410	Calculation method

[Full text of abbreviated H statements](#)

Code : 00155531 **Date of issue/Date of revision** : 15 December 2023
PPG VIKOTE 56 ORANGE 3149

SECTION 16: Other information

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H362	May cause harm to breast-fed children.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.

[Full text of classifications \[CLP/GHS\]](#)

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Aquatic Chronic 4	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 1B	CARCINOGENICITY - Category 1B
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Lact.	REPRODUCTIVE TOXICITY - Effects on or via lactation
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

History

Date of issue/ Date of revision : 15 December 2023

Date of previous issue : 2 November 2022

Prepared by : EHS

Version : 19

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.