Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SAFETY DATA SHEET

Date of issue/Date of revision

: 26 December 2023 Version



: 1.03

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier		
Product name	:	PITT-CHAR NX BASE WHITE PLURAL FEED
Product code	:	00428718
Product type	:	Liquid.
Other means of identification	:	Not available.
1.2 Relevant identified uses	of t	he substance or mixture and uses advised against
Product use	:	Professional applications, Used by spraying.
Use of the substance/ mixture	:	Coating.
Uses advised against	:	Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL Tweemontstraat 104 B-2100 Deurne Belgium Telephone +32-33606311 Fax +32-33606435

e-mail address of person responsible for this SDS

: Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture Classification according to UK CLP/GHS Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Carc. 2, H351 Repr. 2, H361d Aquatic Acute 1, H400 Aquatic Chronic 2, H411 The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended. See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word

: Warning

English (GB)

Code : 00428718	Date of issue/Date of revision	: 26 December 2023
PITT-CHAR NX BASE WHITE PLURAL FEED		

SECTION 2: Hazards identification

Hazard statements	:	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging the unborn child. Very toxic to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Avoid breathing vapour.
Response	:	Collect spillage.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
		P202, P280, P273, P261, P391, P501
Supplemental label elements	1	Contains epoxy constituents. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	er	<u>its</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Туре
Boron zinc hydroxide oxide	REACH #: 01-2119691658-19 CAS: 138265-88-0	≥10 - ≤25	Repr. 2, H361d Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	[1]
Borate(5-), bis[µ- oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)-	REACH #: 01-2119970312-43 EC: 234-521-1 CAS: 12046-04-7	≥10 - ≤25	Repr. 2, H361d	[1]
bis-[4-(2,3-epoxipropoxi)phenyl] propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
phosphorous oxychloride, reaction products with propylene oxide	REACH #: 01-2119486772-26 EC: 807-935-0	≥5.0 - ≤10	Acute Tox. 4, H302	[1]
English (GB)	United F	Kingdom (UK)		2/1

Code : 00428718	Date of issue/Date of revision	: 26 December 2023
PITT-CHAR NX BASE WHITE PLURAL FEED		

SECTION 3: Composition/information on ingredients

•	CAS: 1244733-77-4			
triphenyl phosphate	EC: 204-112-2 CAS: 115-86-6	≥5.0 - ≤10	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
epoxy resin (MW ≤ 700)	REACH #: 01-2119456619-26 EC: 500-033-5 CAS: 25068-38-6	≥1.0 - ≤5.0	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
Cashew, nutshell liq.	EC: 232-355-4 CAS: 8007-24-7	≥1.0 - <3.0	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317	[1]
2,2-bis(acryloyloxymethyl)butyl acrylate	REACH #: 01-2119489896-11 EC: 239-701-3 CAS: 15625-89-5 Index: 607-111-00-9	≥1.0 - ≤4.2	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Carc. 2, H351 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
Quaternary ammonium compounds, benzylbis (hydrogenated tallow alkyl)methyl, chlorides	EC: 263-082-9 CAS: 61789-73-9	≤0.30	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the erapart for at least 10 minutes and seek immediate medical advice. In case of accidental eye contact, avoid direct exposure to the sun or other sour of UV light as severe irritation including burns may result. These reactions can delayed – get medical attention if pain, irritation or blistering occurs after contact Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing 	rces be t.
	irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by personnel.	
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and or use recognised skin cleanser. Do NOT use solvents or thinners.	water
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. person warm and at rest. Do NOT induce vomiting.	Keep
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. may be dangerous to the person providing aid to give mouth-to-mouth resuscita Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	
English (GB)	United Kingdom (UK)	3/16

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

Code : 00428718	Date of issue/Date of revision	: 26 December 2023			
PITT-CHAR NX BASE WHITE PLURAL FEED					

SECTION 4: First aid measures

otential acute health	<u>effects</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/	/symptoms
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	 Decomposition products may include the following materials: carbon oxides nitrogen oxides phosphorus oxides

 5.3 Advice for firefighters

 Special protective actions for fire-fighters

 is a fire. No action shall be taken involving any personal risk or without suitable training.

 English (GB)

 United Kingdom (UK)

halogenated compounds

Code	: 00428718	Date of issue/Date of revision	: 26 December 2023
PITT-CHAR	NX BASE WHITE PLURAL FEED		

SECTION 5: Firefighting measures

Special protective	: Fire-fighters should wear
equipment for fire-fighters	breathing apparatus (SC
	na a al a

r appropriate protective equipment and self-contained CBA) with a full face-piece operated in positive pressure mode

SECTION 6: Accidental release measures

6.1 Personal precautions, prot	tective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for c	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Code	: 00428718	Date of issue/Date of revision	: 26 December 2023
PITT-CHAR I	NX BASE WHITE PLURAL FEED		

SECTION 7: Handling and storage

Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional
	information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
bis-[4-(2,3-epoxipropoxi) phenyl]propane	DNEL	Long term Inhalation	12.25 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	12.25 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	3.571 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Dermal	3.571 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Oral	0.75 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Oral	0.75 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Dermal	89.3 µg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.75 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.87 mg/m ³	General population	
	DNEL	Long term Inhalation	4.93 mg/m ³	Workers	Systemic
phosphorous oxychloride, reaction products with propylene oxide	DNEL	Long term Oral	0.52 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1.04 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	1.45 mg/m ³	General population	
English (GB)		United King	gdom (UK)		6/16

Code : 00428718

Date of issue/Date of revision

: 26 December 2023

PITT-CHAR NX BASE WHITE PLURAL FEED

SECTION 8: Exposure controls/personal protection

	DNEL	Short term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	2.91 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	5.6 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	8.2 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	22.6 mg/m ³	Workers	Systemic
triphenyl phosphate	DNEL	Long term Oral	0.525 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.525 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.91 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	1.05 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	3.7 mg/m ³	Workers	Systemic
epoxy resin (MW ≤ 700)	DNEL	Long term Inhalation	12.25 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	12.25 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	3.571 mg/kg bw/day	General	Systemic
		-		population	-
				[Consumers]	
	DNEL	Short term Dermal	3.571 mg/kg bw/day	General	Systemic
				population	
				[Consumers]	
	DNEL	Long term Oral	0.75 mg/kg bw/day	General	Systemic
				population	
				[Consumers]	
	DNEL	Short term Oral	0.75 mg/kg bw/day	General	Systemic
				population	
				[Consumers]	
Cashew, nutshell liq.	DNEL	Long term Oral	0.75 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.75 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	1.31 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	2.1 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	7.4 mg/m ³	Workers	Systemic
2,2-bis(acryloyloxymethyl) butyl acrylate	DNEL	Long term Inhalation	17.1 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	404 mg/kg bw/day	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Fresh water	0.006 mg/l	Assessment Factors
	Marine water	0.001 mg/l	Assessment Factors
	Fresh water sediment	0.996 mg/kg dwt	Equilibrium Partitioning
	Marine water sediment	0.1 mg/kg dwt	Equilibrium Partitioning
	Soil	0.196 mg/kg dwt	Equilibrium Partitioning
	Sewage Treatment Plant	10 mg/l	Assessment Factors
	Secondary Poisoning	11 mg/kg	Assessment Factors
epoxy resin (MW ≤ 700)	Fresh water	0.006 mg/l	Assessment Factors
	Marine water	0.001 mg/l	Assessment Factors
	Sewage Treatment Plant	10 mg/l	Assessment Factors
	Fresh water sediment	0.996 mg/kg dwt	Equilibrium Partitioning
	Marine water sediment	0.1 mg/kg dwt	Equilibrium Partitioning

8.2 Exposure controls

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Code : 00428718 PITT-CHAR NX BASE WH	Date of issue/Date of revision : 26 December 2023 HITE PLURAL FEED
SECTION 8: Expo	sure controls/personal protection
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	: Chemical splash goggles.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use as included in the user's risk assessment.

		polyethylene butyl rubber
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Off-white.
Odour	: Characteristic.
Odour threshold	: Not available.
Melting point/freezing point	 May start to solidify at the following temperature: 8 to 12°C (46.4 to 53.6°F) This is based on data for the following ingredient: bis-[4-(2,3-epoxipropoxi)phenyl]propane. Weighted average: 7.64°C (45.8°F)
Initial boiling point and boiling range	: >37.78°C (>100°F)
Flammability (solid, gas)	: liquid
Upper/lower flammability or explosive limits	: Not available.
English (GB)	United Kingdom (UK) 8/16

Code	: 00428718	Date of issue/Date of revision

: 26 December 2023

PITT-CHAR NX BASE WHITE PLURAL FEED

SECTION 9: Physical and chemical properties

Flash point

: Closed cup: Not applicable.

Α	uto-ignition temperature :			
	Ingredient name	°C	°F	Method
	2,2-bis(acryloyloxymethyl)butyl acrylate	385	725	EU A.15
p	H : Not app	licable.		

Viscosity	Not applicable. insoluble in water. : Kinematic (40°C): >21 mm²/s
Solubility(ies)	1 · · · · · · · · · · · · · · · · · · ·
Media	Result
cold water	Not soluble

Miscible with water

Partition coefficient: n-octanol/ : Not applicable.

: No.

water

	V	Vapour Pressure at 20°C		V	Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
2,2-bis(acryloyloxymethyl)butyl acrylate	0.00075	0.0001	OECD 104				
Relative density	: 1.5	6					
/apour density	: Hig	hest known	value: 11.7 (Air =	1) (bis-[4-(2,3	-epoxiprop	oxi)phenyl]propane	
Explosive properties		•	elf is not explosive with air is possible	,	ition of an e	explosible mixture	
Dxidising properties Particle characteristics	: Pro	duct does n	ot present an oxic	lizing hazard.			

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides phosphorus oxides halogenated compounds metal oxide/oxides

- Code : 00428718 PITT-CHAR NX BASE WHITE PLURAL FEED
- Date of issue/Date of revision

: 26 December 2023

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Boron zinc hydroxide oxide	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Borate(5-), bis[µ- oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)-	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	4200 mg/kg	-
bis-[4-(2,3-epoxipropoxi) phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
phosphorous oxychloride, reaction products with propylene oxide	LC50 Inhalation Dusts and mists	Rat	>7 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	630 to 2000 mg/ kg	-
triphenyl phosphate	LD50 Dermal LD50 Oral	Rabbit Rat	>7900 mg/kg 3500 mg/kg	-
epoxy resin (MW ≤ 700)	LD50 Dermal LD50 Oral	Rabbit Rat	>2 g/kg >2 g/kg	-
2,2-bis(acryloyloxymethyl) butyl acrylate	LD50 Dermal	Rabbit	5170 mg/kg	-
	LD50 Oral	Rat	5.19 g/kg	-

: There are no data available on the mixture itself.

Conclusion/Summary Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
TT-CHAR NX BASE WHITE PLURAL FEED Borate(5-), bis[µ-oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)-	4574.9 4200	67901.2 N/A	N/A N/A	N/A N/A	N/A N/A
bis-[4-(2,3-epoxipropoxi)phenyl]propane phosphorous oxychloride, reaction products with propylene oxide	15000 500	23000 N/A	N/A N/A	N/A N/A	N/A N/A
triphenyl phosphate Cashew, nutshell liq. 2,2-bis(acryloyloxymethyl)butyl acrylate	3500 500 5190	N/A 1100 5170	N/A N/A N/A	N/A N/A N/A	N/A N/A N/A

Irritation/Corrosion

Result	Species	Score	Exposure	Observation
Eyes - Mild irritant	Rabbit	-	24 hours	-
Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
Skin - Oedema	Rabbit	0.5	4 hours	-
Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
Skin - Mild irritant	Rabbit	-	4 hours	-
Eves - Mild irritant	Rabbit	-	-	-
Skin - Mild irritant	Rabbit	-	-	-
Skin - Irritant	Rabbit	-	-	-
	Eyes - Mild irritant Eyes - Redness of the conjunctivae Skin - Oedema Skin - Erythema/Eschar Skin - Mild irritant Eyes - Mild irritant Skin - Mild irritant	Eyes - Mild irritantRabbitEyes - Redness of the conjunctivaeRabbitSkin - OedemaRabbitSkin - Erythema/EscharRabbitSkin - Mild irritantRabbitEyes - Mild irritantRabbitSkin - Mild irritantRabbit	Eyes - Mild irritantRabbit-Eyes - Redness of the conjunctivaeRabbit0.4Skin - OedemaRabbit0.5Skin - Erythema/EscharRabbit0.8Skin - Mild irritantRabbit-Eyes - Mild irritantRabbit-Skin - Mild irritantRabbit-Skin - Mild irritantRabbit-Skin - Mild irritantRabbit-Skin - Mild irritantRabbit-	Eyes - Mild irritantRabbit-24 hoursEyes - Redness of the conjunctivaeRabbit0.424 hoursSkin - OedemaRabbit0.54 hoursSkin - Erythema/EscharRabbit0.84 hoursSkin - Mild irritantRabbit-4 hoursEyes - Mild irritantRabbitSkin - Mild irritantRabbitSkin - Mild irritantRabbit

Code : 00428718	Date of issue/Date of revision	: 26 December 2023
PITT-CHAR NX BASE WHITE PLURAL FEED		

SECTION 11: Toxicological information

Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.

Respiratory Sensitisation

Product/ingredient name	Route of exposure	Species	Result
bis-[4-(2,3-epoxipropoxi)	skin	Mouse	Sensitising
phenyl]propane			
epoxy resin (MW \leq 700)	skin	Mouse	Sensitising
2,2-bis(acryloyloxymethyl) butyl acrylate	skin	Rabbit	Sensitising
Conclusion/Summary	ļ	ļ	
Skin	: There are no da	ta available on the mixture itself.	
Respiratory		ta available on the mixture itself.	
Mutagenicity			
Conclusion/Summary	: There are no da	ta available on the mixture itself.	
<u>Carcinogenicity</u>			
Conclusion/Summary	: There are no da	ta available on the mixture itself.	
Reproductive toxicity			
Conclusion/Summary <u>Teratogenicity</u>	: There are no da	ta available on the mixture itself.	
Conclusion/Summary	: There are no da	ta available on the mixture itself	
Specific target organ toxicity	<u>/ (single exposure</u>)	
Not available.			
Specific target organ toxicity Not available.	/ (repeated exposi	<u>ıre)</u>	
Aspiration hazard Not available.			
Information on likely routes of exposure	: Not available.		
Potential acute health effects			
Eye contact	: Causes serious	eye irritation.	
Inhalation	: No known signifi	icant effects or critical hazards.	
Skin contact	: Causes skin irrit	ation. May cause an allergic ski	n reaction.
Ingestion	: No known signifi	icant effects or critical hazards.	
Symptoms related to the phys	sical chomical and	toxicological charactoristics	
Eye contact		ms may include the following:	
	pain or irritation watering redness	nis may include the following.	
Inhalation	: Adverse sympto reduced foetal w increase in foeta skeletal malform	al deaths	

Code : 00428718 PITT-CHAR NX BASE WHITE PLURAL FEED	Date of issue/Date of revision	: 26 December 2023			
SECTION 11: Toxicological information					

المحدية بالمحما والمحمد

Skin contact	: Adverse symptoms may include the following: irritation redness reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations

Delayed and immediate eff	ects as well as chronic effects fro	om snort and long-term exposure
Short term exposure		
Detended in successful	Net evelleble	

Potential immediate effects	1	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	1	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effe	ect	<u>S</u>
Not available.		
Conclusion/Summary	:	Not available.
General	1	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	:	Suspected of damaging the unborn child.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Boron zinc hydroxide oxide	Acute LC50 76 mg/l	Daphnia - <i>Daphnia magna</i> straus	48 hours
	Acute LC50 0.452 mg/l	Fish - Trout	96 hours
Borate(5-), bis[µ- oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)-	Acute LC50 >100 mg/l	Fish	96 hours
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia magna</i>	48 hours
	Chronic NOEC 0.3 mg/l	Daphnia	21 days
phosphorous oxychloride, reaction products with propylene oxide	EC50 82 mg/l	Algae	72 hours
	EC50 131 mg/l	Daphnia	48 hours
	LC50 56.2 mg/l	Fish	96 hours
	NOEC 32 mg/l	Daphnia	48 hours
triphenyl phosphate	Acute LC50 0.09 mg/l Fresh water	Daphnia - Water flea - Daphnia magna - Neonate	48 hours
	Chronic NOEC 0.1 mg/l	Algae - Green algae - Desmodesmus subspicatus	3 days
English (GB)	United Kingdo	m (UK)	12/

Code <th::00428718< th=""> Date of issue/Date of revision : 26 December 2023 PITT-CHAR NX BASE WHITE PLURAL FEED </th::00428718<>					
SECTION 12: Ecological information					
epoxy resin (MW ≤ 700)	Acute LC50 1.8 mg/l Chronic NOEC 0.3 mg/l	Daphnia Daphnia		48 hours 21 days	

Fish

butyl acrylate **Conclusion/Summary**

: Not available.

Acute LC50 0.87 mg/l

12.2 Persistence and degradability

2,2-bis(acryloyloxymethyl)

Product/ingredient name	Test	Result		Dose	Inoculum
epoxy resin (MW ≤ 700)	OECD 301F	5 % - 28 days		-	-
Conclusion/Summary	: Not available.				
Product/ingredient name	Aquatic half-life		Photolysis	5	Biodegradability
bis-[4-(2,3-epoxipropoxi) phenyl]propane epoxy resin (MW ≤ 700)	-		-		Not readily Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
phosphorous oxychloride, reaction products with propylene oxide	2.68	-	Low
triphenyl phosphate	4.63	190.55	Low
epoxy resin (MW ≤ 700)	3	31	Low
Cashew, nutshell liq.	>4.78	-	High
2,2-bis(acryloyloxymethyl) butyl acrylate	0.67	-	Low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects	: No known significant effects or critical hazard
----------------------------	---

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment meth	ods
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.
<u>Waste catalogue</u>	

96 hours

- Code : 00428718
- PITT-CHAR NX BASE WHITE PLURAL FEED
- Date of issue/Date of revision

: 26 December 2023

SECTION 13: Disposal considerations

Waste code	Waste designation		
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances		
Packaging			
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.		
Type of packaging	Waste catalogue		
Container	15 01 06 mixed packaging		
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.		

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Boron zinc hydroxide oxide, bis-[4- (2,3-epoxipropoxi) phenyl]propane)			
	(Boron zinc hydroxide oxide, bis-[4- (2,3-epoxipropoxi) phenyl]propane)			
14.3 Transport hazard class(es)	9	9	9	9
14.4 Packing group	III	111	111	Ш
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	Not applicable.	K Boron zinc hydroxide oxide)	Not applicable.
Additional informa	tion			

ADR/RID
This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
Tunnel code
(-)
ADN
This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG
This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG
This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IATA
This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

14.6 Special precautions for user : **Transport within user's premises**: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

Code	: 00428718	Date of issue/Date of revision	: 26 December 2023
PITT-CHAR N	NX BASE WHITE PLURAL FEED		

SECTION 14: Transport information

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria Category E1

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group
	SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification	
Skin Irrit. 2, H315	Calculation method	
Eye Irrit. 2, H319	Calculation method	
Skin Sens. 1, H317	Calculation method	
Carc. 2, H351	Calculation method	
Repr. 2, H361d	Calculation method	
Aquatic Acute 1, H400	Calculation method	
Aquatic Chronic 2, H411	Calculation method	

Full text of abbreviated H statements

<mark>Code</mark> PITT-CHAR	: 00428718 Date of NX BASE WHITE PLURAL FEED	issue/Date of revision	: 26 December 2023
SECTIO	N 16: Other information		
H302	Harmful if swallowed.		1
H312	Harmful in contact with skin.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H318	Causes serious eye damage.		
H319	Causes serious eye irritation.		
H351	Suspected of causing cancer.		
H361d	Suspected of damaging the unborn child.		
H400	Very toxic to aquatic life.		
	Vany taxia ta aquatia lifa with lang lasting off	a et e	

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

: 1.03

Full text of classifications

Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Carc. 2 Eye Dam. 1 Eye Irrit. 2 Repr. 2 Skin Irrit. 2	ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 CARCINOGENICITY - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 REPRODUCTIVE TOXICITY - Category 2 SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
History	
Date of issue/ Date of revision	: 26 December 2023
Date of previous issue	e : 23 October 2023
Prepared by	: EHS

Version

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.