

# SAFETY DATA SHEET

Date of issue/Date of revision

: 13 February 2024

Version

: 5.07



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : MULTIPRIME 4160 GRAY PRIMER

**Product code** : 00407037

#### Other means of identification

Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Consumer applications, Professional applications.

**Use of the substance/  
mixture** : Coating.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Nederland B.V.  
Amsterdamseweg 14  
1422 AD Uithoorn  
Netherlands  
+31 (0)297 541234  
Fax: +31 (0)297 541806

**e-mail address of person  
responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

#### Supplier

+31 (0)20 4075210

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Flam. Liq. 3, H226

Carc. 1B, H350

STOT SE 3, H336

STOT RE 2, H373

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

|                             |            |                                |                    |
|-----------------------------|------------|--------------------------------|--------------------|
| Code                        | : 00407037 | Date of issue/Date of revision | : 13 February 2024 |
| MULTIPRIME 4160 GRAY PRIMER |            |                                |                    |

SECTION 2: Hazards identification

|                                                                                                                                    |   |                                                                                                                                                                                                                                                                                                                                          |
|------------------------------------------------------------------------------------------------------------------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hazard pictograms                                                                                                                  | : |     |
| Signal word                                                                                                                        | : | Danger                                                                                                                                                                                                                                                                                                                                   |
| Hazard statements                                                                                                                  | : | Flammable liquid and vapor.<br>May cause drowsiness or dizziness.<br>May cause cancer.<br>May cause damage to organs through prolonged or repeated exposure.<br>Toxic to aquatic life with long lasting effects.                                                                                                                         |
| <u>Precautionary statements</u>                                                                                                    |   |                                                                                                                                                                                                                                                                                                                                          |
| General                                                                                                                            | : | Keep out of reach of children. If medical advice is needed, have product container or label at hand.                                                                                                                                                                                                                                     |
| Prevention                                                                                                                         | : | Obtain special instructions before use. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapor.                   |
| Response                                                                                                                           | : | Collect spillage. IF exposed or concerned: Get medical advice or attention. IF INHALED: Call a POISON CENTER or doctor if you feel unwell.                                                                                                                                                                                               |
| Storage                                                                                                                            | : | Store locked up. Store in a well-ventilated place. Keep container tightly closed.                                                                                                                                                                                                                                                        |
| Disposal                                                                                                                           | : | Dispose of contents and container in accordance with all local, regional, national and international regulations.<br>P102, P101, P201, P280, P210, P271, P273, P260, P391, P308 + P313, P304 + P312, P405, P403 + P233, P501                                                                                                             |
| Hazardous ingredients                                                                                                              | : | Hydrocarbons, C9, aromatics > 0.1% cumene<br>heptan-2-one<br>solvent naphtha (petroleum), medium aliph.                                                                                                                                                                                                                                  |
| Supplemental label elements                                                                                                        | : | <input checked="" type="checkbox"/> Contains butanone oxime and cobalt bis(2-ethylhexanoate). May produce an allergic reaction.                                                                                                                                                                                                          |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : | Restricted to professional users.                                                                                                                                                                                                                                                                                                        |
| <u>Special packaging requirements</u>                                                                                              |   |                                                                                                                                                                                                                                                                                                                                          |
| Containers to be fitted with child-resistant fastenings                                                                            | : | Yes, applicable.                                                                                                                                                                                                                                                                                                                         |
| Tactile warning of danger                                                                                                          | : | Yes, applicable.                                                                                                                                                                                                                                                                                                                         |
| 2.3 Other hazards                                                                                                                  |   |                                                                                                                                                                                                                                                                                                                                          |
| Product meets the criteria for PBT or vPvB                                                                                         | : | This mixture does not contain any substances that are assessed to be a PBT or a vPvB.                                                                                                                                                                                                                                                    |
| Other hazards which do not result in classification                                                                                | : | Prolonged or repeated contact may dry skin and cause irritation.                                                                                                                                                                                                                                                                         |

|                             |            |                                |                    |
|-----------------------------|------------|--------------------------------|--------------------|
| Code                        | : 00407037 | Date of issue/Date of revision | : 13 February 2024 |
| MULTIPRIME 4160 GRAY PRIMER |            |                                |                    |

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name                             | Identifiers                                                                            | % by weight | Classification                                                                                                                                                                                                                | Specific Conc. Limits, M-factors and ATEs                         | Type    |
|-----------------------------------------------------|----------------------------------------------------------------------------------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------|
| Hydrocarbons, C9, aromatics > 0.1% cumene           | REACH #:<br>01-2119455851-35<br>EC: 918-668-5<br>CAS: 64742-95-6                       | ≥10 - <20   | Flam. Liq. 3, H226<br>Carc. 1B, H350<br>STOT SE 3, H335<br>STOT SE 3, H336<br>Asp. Tox. 1, H304<br>Aquatic Chronic 2, H411<br>EUH066                                                                                          | Carc. 1B, H350: C ≥ 10%<br>EUH066: C ≥ 20%                        | [1]     |
| Wollastonite                                        | EC: 237-772-5<br>CAS: 13983-17-0                                                       | ≥10 - ≤25   | Not classified.                                                                                                                                                                                                               | -                                                                 | [2]     |
| heptan-2-one                                        | REACH #:<br>01-2119902391-49<br>EC: 203-767-1<br>CAS: 110-43-0<br>Index: 606-024-00-3  | ≥5.0 - ≤10  | Flam. Liq. 3, H226<br>Acute Tox. 4, H302<br>Acute Tox. 4, H332<br>STOT SE 3, H336                                                                                                                                             | ATE [Oral] = 1600 mg/kg<br>ATE [Inhalation (vapours)] = 16.7 mg/l | [1] [2] |
| solvent naphtha (petroleum), medium aliph.          | EC: 265-191-7<br>CAS: 64742-88-7<br>Index: 649-405-00-X                                | ≥1.0 - ≤5.0 | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>STOT RE 1, H372 (central nervous system (CNS))<br>Asp. Tox. 1, H304<br>Aquatic Chronic 2, H411<br>EUH066                                                                             | -                                                                 | [1] [2] |
| trizinc bis(orthophosphate)                         | REACH #:<br>01-2119485044-40<br>EC: 231-944-3<br>CAS: 7779-90-0<br>Index: 030-011-00-6 | ≥1.0 - ≤5.0 | Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                                                                                                                                                                              | M [Acute] = 1<br>M [Chronic] = 1                                  | [1]     |
| crystalline silica, respirable powder (<10 microns) | EC: 238-878-4<br>CAS: 14808-60-7                                                       | ≥1.0 - ≤5.0 | STOT RE 1, H372 (inhalation)                                                                                                                                                                                                  | -                                                                 | [1] [2] |
| zinc oxide                                          | REACH #:<br>01-2119463881-32<br>EC: 215-222-5<br>CAS: 1314-13-2<br>Index: 030-013-00-7 | ≥1.0 - ≤5.0 | Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                                                                                                                                                                              | M [Acute] = 1<br>M [Chronic] = 1                                  | [1]     |
| butanone oxime                                      | REACH #:<br>01-2119539477-28<br>EC: 202-496-6<br>CAS: 96-29-7<br>Index: 616-014-00-0   | ≤0.30       | Acute Tox. 3, H301<br>Acute Tox. 4, H312<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Carc. 1B, H350<br>STOT SE 1, H370 (upper respiratory tract)<br>STOT SE 3, H336<br>STOT RE 2, H373 (blood system) | ATE [Oral] = 100 mg/kg<br>ATE [Dermal] = 1100 mg/kg               | [1] [2] |

|                             |            |                                |                    |
|-----------------------------|------------|--------------------------------|--------------------|
| Code                        | : 00407037 | Date of issue/Date of revision | : 13 February 2024 |
| MULTIPRIME 4160 GRAY PRIMER |            |                                |                    |

SECTION 3: Composition/information on ingredients

|                                  |                                                                                       |       |                                                                                                                                                                                                              |               |         |
|----------------------------------|---------------------------------------------------------------------------------------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|---------|
| cobalt bis<br>(2-ethylhexanoate) | REACH #:<br>01-2119524678-29<br>EC: 205-250-6<br>CAS: 136-52-7<br>Index: 607-230-00-6 | <0.10 | Eye Irrit. 2, H319<br>Skin Sens. 1A, H317<br>Repr. 1B, H360FD<br>Aquatic Acute 1, H400<br>Aquatic Chronic 3, H412<br><b>See Section 16 for<br/>the full text of the H<br/>statements declared<br/>above.</b> | M [Acute] = 1 | [1] [2] |
|----------------------------------|---------------------------------------------------------------------------------------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|---------|

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
  - [2] Substance with a workplace exposure limit
- Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:
  - nausea or vomiting
  - headache
  - drowsiness/fatigue
  - dizziness/vertigo
  - unconsciousness

|                             |            |                                |                    |
|-----------------------------|------------|--------------------------------|--------------------|
| Code                        | : 00407037 | Date of issue/Date of revision | : 13 February 2024 |
| MULTIPRIME 4160 GRAY PRIMER |            |                                |                    |

SECTION 4: First aid measures

|                                                                                |                                                                                                                             |
|--------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Skin contact                                                                   | : Adverse symptoms may include the following:<br>irritation<br>dryness<br>cracking                                          |
| Ingestion                                                                      | : No specific data.                                                                                                         |
| 4.3 Indication of any immediate medical attention and special treatment needed |                                                                                                                             |
| Notes to physician                                                             | : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments                                                            | : No specific treatment.                                                                                                    |

SECTION 5: Firefighting measures

|                                                           |                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-----------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 5.1 Extinguishing media                                   |                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Suitable extinguishing media                              | : Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.                                                                                                                                                                                                                                                                                                                                                    |
| Unsuitable extinguishing media                            | : Do not use water jet.                                                                                                                                                                                                                                                                                                                                                                                             |
| 5.2 Special hazards arising from the substance or mixture |                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Hazards from the substance or mixture                     | : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. |
| Hazardous combustion products                             | : Decomposition products may include the following materials:<br>carbon oxides<br>phosphorus oxides<br>halogenated compounds<br>metal oxide/oxides                                                                                                                                                                                                                                                                  |
| 5.3 Advice for firefighters                               |                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Special precautions for fire-fighters                     | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.                                                                                                |
| Special protective equipment for fire-fighters            | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.                                                           |

SECTION 6: Accidental release measures

|                                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 6.1 Personal precautions, protective equipment and emergency procedures |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| For non-emergency personnel                                             | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
| For emergency responders                                                | : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".                                                                                                                                                                                                                                                                      |

|                             |            |                                |                    |
|-----------------------------|------------|--------------------------------|--------------------|
| Code                        | : 00407037 | Date of issue/Date of revision | : 13 February 2024 |
| MULTIPRIME 4160 GRAY PRIMER |            |                                |                    |

SECTION 6: Accidental release measures

|                                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 6.2 Environmental precautions                             | : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.                                                                                                                                                                                                                                                                                           |
| 6.3 Methods and materials for containment and cleaning up |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Small spill                                               | : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.                                                                                                                                                                                                                                                                               |
| Large spill                                               | : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. |
| 6.4 Reference to other sections                           | : See Section 1 for emergency contact information.<br>See Section 8 for information on appropriate personal protective equipment.<br>See Section 13 for additional waste treatment information.                                                                                                                                                                                                                                                                                                                                                                                                                                    |

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

|                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7.1 Precautions for safe handling      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Protective measures                    | : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.<br><br>Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside. |
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

|                             |            |                                |                    |
|-----------------------------|------------|--------------------------------|--------------------|
| Code                        | : 00407037 | Date of issue/Date of revision | : 13 February 2024 |
| MULTIPRIME 4160 GRAY PRIMER |            |                                |                    |

SECTION 7: Handling and storage

**7.2 Conditions for safe storage, including any incompatibilities** : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name                             | Exposure limit values                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Wollastonite                                        | <b>ACGIH TLV (United States, 1/2023).</b><br>TWA: 1 mg/m³ 8 hours. Form: Inhalable fraction<br><b>EU OEL (Europe, 1/2022). Absorbed through skin.</b><br>STEL: 475 mg/m³ 15 minutes.<br>STEL: 100 ppm 15 minutes.<br>TWA: 238 mg/m³ 8 hours.<br>TWA: 50 ppm 8 hours.<br><b>ACGIH TLV (United States).</b><br>TWA: 400 ppm<br><b>ACGIH TLV (United States, 1/2023). [Silica, crystalline]</b><br>TWA: 0.025 mg/m³ 8 hours. Form: Respirable<br><b>IPEL (-).</b><br>TWA: 3 ppm<br>STEL: 9 ppm<br><b>ACGIH TLV (United States, 1/2023). [cobalt and inorganic compounds as Co] Skin sensitizer. Inhalation sensitizer.</b><br>TWA: 0.02 mg/m³, (as Co) 8 hours. |
| heptan-2-one                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| solvent naphtha (petroleum), medium aliph.          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| crystalline silica, respirable powder (<10 microns) |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| butanone oxime                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| cobalt bis(2-ethylhexanoate)                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

|                             |            |                                |                    |
|-----------------------------|------------|--------------------------------|--------------------|
| Code                        | : 00407037 | Date of issue/Date of revision | : 13 February 2024 |
| MULTIPRIME 4160 GRAY PRIMER |            |                                |                    |

SECTION 8: Exposure controls/personal protection

| Product/ingredient name                   | Type | Exposure              | Value              | Population         | Effects  |
|-------------------------------------------|------|-----------------------|--------------------|--------------------|----------|
| Hydrocarbons, C9, aromatics > 0.1% cumene | DNEL | Long term Inhalation  | 150 mg/m³          | Workers            | Systemic |
|                                           | DNEL | Long term Dermal      | 25 mg/kg bw/day    | Workers            | Systemic |
|                                           | DNEL | Long term Inhalation  | 32 mg/m³           | General population | Systemic |
|                                           | DNEL | Long term Dermal      | 11 mg/kg bw/day    | General population | Systemic |
|                                           | DNEL | Long term Oral        | 11 mg/kg bw/day    | General population | Systemic |
|                                           | DNEL | Long term Oral        | 23.32 mg/kg bw/day | General population | Systemic |
|                                           | DNEL | Long term Dermal      | 23.32 mg/kg bw/day | General population | Systemic |
|                                           | DNEL | Long term Dermal      | 54.27 mg/kg bw/day | Workers            | Systemic |
|                                           | DNEL | Long term Inhalation  | 84.31 mg/m³        | General population | Systemic |
|                                           | DNEL | Long term Inhalation  | 394.25 mg/m³       | Workers            | Systemic |
| heptan-2-one                              | DNEL | Short term Inhalation | 1516 mg/m³         | Workers            | Systemic |
|                                           | DNEL | Long term Oral        | 0.83 mg/kg bw/day  | General population | Systemic |
|                                           | DNEL | Long term Inhalation  | 2.5 mg/m³          | General population | Systemic |
|                                           | DNEL | Long term Inhalation  | 5 mg/m³            | Workers            | Systemic |
| trizinc bis(orthophosphate)               | DNEL | Long term Dermal      | 83 mg/kg bw/day    | General population | Systemic |
|                                           | DNEL | Long term Dermal      | 83 mg/kg bw/day    | Workers            | Systemic |
|                                           | DNEL | Long term Inhalation  | 0.5 mg/m³          | Workers            | Local    |
|                                           | DNEL | Long term Oral        | 0.83 mg/kg bw/day  | General population | Systemic |
| zinc oxide                                | DNEL | Long term Inhalation  | 2.5 mg/m³          | General population | Systemic |
|                                           | DNEL | Long term Inhalation  | 5 mg/m³            | Workers            | Systemic |
|                                           | DNEL | Long term Dermal      | 83 mg/kg bw/day    | General population | Systemic |
|                                           | DNEL | Long term Dermal      | 83 mg/kg bw/day    | Workers            | Systemic |
| butanone oxime                            | DMEL | Long term Oral        | 1.6 µg/kg bw/day   | General population | Systemic |
|                                           | DMEL | Long term Dermal      | 4 µg/kg bw/day     | Workers            | Systemic |
|                                           | DMEL | Long term Inhalation  | 4.82 µg/m³         | General population | Systemic |
|                                           | DMEL | Long term Inhalation  | 28 µg/m³           | Workers            | Systemic |
| cobalt bis(2-ethylhexanoate)              | DNEL | Long term Inhalation  | 0.43 mg/m³         | General population | Local    |
|                                           | DNEL | Long term Inhalation  | 0.9 mg/m³          | Workers            | Local    |
|                                           | DNEL | Long term Inhalation  | 37 µg/m³           | General population | Local    |
|                                           | DNEL | Long term Oral        | 175 µg/kg bw/day   | General population | Systemic |
|                                           | DNEL | Long term Inhalation  | 235.1 µg/m³        | Workers            | Local    |

PNECs

| Product/ingredient name      | Type | Compartment Detail     | Value          | Method Detail            |
|------------------------------|------|------------------------|----------------|--------------------------|
| heptan-2-one                 | -    | Fresh water            | 0.0982 mg/l    | Assessment Factors       |
|                              | -    | Marine water           | 0.00982 mg/l   | Assessment Factors       |
|                              | -    | Fresh water sediment   | 1.89 mg/kg     | Equilibrium Partitioning |
|                              | -    | Marine water sediment  | 0.189 mg/kg    | Equilibrium Partitioning |
|                              | -    | Sewage Treatment Plant | 12.5 mg/l      | Assessment Factors       |
| trizinc bis(orthophosphate)  | -    | Soil                   | 0.321 mg/kg    | Equilibrium Partitioning |
|                              | -    | Fresh water            | 20.6 µg/l      | Sensitivity Distribution |
|                              | -    | Marine water           | 6.1 µg/l       | Sensitivity Distribution |
|                              | -    | Sewage Treatment Plant | 100 µg/l       | Assessment Factors       |
|                              | -    | Fresh water sediment   | 117.8 mg/kg dw | Sensitivity Distribution |
| zinc oxide                   | -    | Marine water sediment  | 56.5 mg/kg dw  | Equilibrium Partitioning |
|                              | -    | Soil                   | 35.6 mg/kg dw  | Sensitivity Distribution |
|                              | -    | Fresh water            | 20.6 µg/l      | Sensitivity Distribution |
|                              | -    | Marine water           | 6.1 µg/l       | Sensitivity Distribution |
|                              | -    | Fresh water sediment   | 117 mg/kg dw   | Sensitivity Distribution |
| butanone oxime               | -    | Sewage Treatment Plant | 52 µg/l        | Assessment Factors       |
|                              | -    | Marine water sediment  | 56.5 mg/kg dw  | Assessment Factors       |
|                              | -    | Soil                   | 35.6 mg/kg dw  | Sensitivity Distribution |
|                              | -    | Fresh water            | 0.256 mg/l     | Assessment Factors       |
|                              | -    | Sewage Treatment Plant | 177 mg/l       | Assessment Factors       |
| cobalt bis(2-ethylhexanoate) | -    | Fresh water            | 0.6 µg/l       | Sensitivity Distribution |

|                             |            |                                |                    |
|-----------------------------|------------|--------------------------------|--------------------|
| Code                        | : 00407037 | Date of issue/Date of revision | : 13 February 2024 |
| MULTIPRIME 4160 GRAY PRIMER |            |                                |                    |

| SECTION 8: Exposure controls/personal protection |   |                        |               |                          |
|--------------------------------------------------|---|------------------------|---------------|--------------------------|
|                                                  | - | Marine water           | 2.36 µg/l     | Sensitivity Distribution |
|                                                  | - | Sewage Treatment Plant | 0.37 mg/l     | Assessment Factors       |
|                                                  | - | Fresh water sediment   | 9.5 mg/kg dw  | Sensitivity Distribution |
|                                                  | - | Marine water sediment  | 9.5 mg/kg dw  | Sensitivity Distribution |
|                                                  | - | Soil                   | 10.9 mg/kg dw | Sensitivity Distribution |

8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Chemical splash goggles. Use eye protection according to EN 166.

Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Gloves** : For prolonged or repeated handling, use the following type of gloves:  
  
Recommended: Chloroprene, nitrile rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

**Other skin protection** Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Use with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Wear a respirator conforming to EN140. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Mask type: full-face mask half-face mask Filter type: organic vapor filter (Type A) particulate filter P3 Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

|                             |            |                                |                    |
|-----------------------------|------------|--------------------------------|--------------------|
| Code                        | : 00407037 | Date of issue/Date of revision | : 13 February 2024 |
| MULTIPRIME 4160 GRAY PRIMER |            |                                |                    |

SECTION 8: Exposure controls/personal protection

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

**Physical state** : Liquid.

**Color** : Gray.

**Odor** : Characteristic.

**Odor threshold** : Not available.

**Melting point/freezing point** : May start to solidify at the following temperature: <-20°C (<-4°F) This is based on data for the following ingredient: heptan-2-one. Weighted average: -44.6°C (-48.3°F)

**Initial boiling point and boiling range** : >37.78°C

**Flammability** : Not available.

**Upper/lower flammability or explosive limits** : Greatest known range: Lower: 1.4% Upper: 7.6% (Solvent naphtha (petroleum), light aromatic)

**Flash point** : Closed cup: 42°C

**Auto-ignition temperature** :

| Ingredient name                            | °C   | °F   | Method     |
|--------------------------------------------|------|------|------------|
| Solvent naphtha (petroleum), medium aliph. | >220 | >428 | ASTM E 659 |

**Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).

**pH** : Not applicable. insoluble in water.

**Viscosity** : Kinematic (40°C): >21 mm²/s

**Solubility(ies)** :

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |

**Partition coefficient: n-octanol/ water** : Not applicable.

**Vapor pressure** :

| Ingredient name | Vapor Pressure at 20°C |      |        | Vapor pressure at 50°C |     |        |
|-----------------|------------------------|------|--------|------------------------|-----|--------|
|                 | mm Hg                  | kPa  | Method | mm Hg                  | kPa | Method |
| heptan-2-one    | 6.88                   | 0.92 |        |                        |     |        |

**Evaporation rate** : 0.34 (heptan-2-one) compared with butyl acetate

**Relative density** : 1.39

**Vapor density** : Highest known value: 4.1 (Air = 1) (1,2,4-trimethylbenzene). Weighted average: 3.98 (Air = 1)

**Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapor or dust with air is possible.

**Oxidizing properties** : Product does not present an oxidizing hazard.

|                             |            |                                |                    |
|-----------------------------|------------|--------------------------------|--------------------|
| Code                        | : 00407037 | Date of issue/Date of revision | : 13 February 2024 |
| MULTIPRIME 4160 GRAY PRIMER |            |                                |                    |

SECTION 9: Physical and chemical properties

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.  
Refer to protective measures listed in sections 7 and 8.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:  
oxidizing agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials:  
carbon oxides phosphorus oxides halogenated compounds metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

| Product/ingredient name                    | Result                          | Species      | Dose        | Exposure |
|--------------------------------------------|---------------------------------|--------------|-------------|----------|
| Hydrocarbons, C9, aromatics > 0.1% cumene  | LD50 Dermal                     | Rabbit       | >3160 mg/kg | -        |
|                                            | LD50 Oral                       | Rat - Female | 3492 mg/kg  | -        |
| heptan-2-one                               | LC50 Inhalation Vapor           | Rat          | 16.7 mg/l   | 4 hours  |
|                                            | LD50 Dermal                     | Rabbit       | 10.206 g/kg | -        |
| solvent naphtha (petroleum), medium aliph. | LD50 Oral                       | Rat          | 1.6 g/kg    | -        |
|                                            | LD50 Dermal                     | Rabbit       | >3000 mg/kg | -        |
| trizinc bis(orthophosphate)                | LD50 Oral                       | Rat          | >5000 mg/kg | -        |
|                                            | LC50 Inhalation Dusts and mists | Rat          | >5.7 mg/l   | 4 hours  |
| zinc oxide                                 | LD50 Oral                       | Rat          | >5000 mg/kg | -        |
|                                            | LC50 Inhalation Dusts and mists | Rat          | >5700 mg/m³ | 4 hours  |
| butanone oxime                             | LD50 Dermal                     | Rat          | >2000 mg/kg | -        |
|                                            | LD50 Oral                       | Rat          | >5000 mg/kg | -        |
| cobalt bis(2-ethylhexanoate)               | LD50 Dermal                     | Rabbit       | 1100 mg/kg  | -        |
|                                            | LD50 Oral                       | Rat          | 100 mg/kg   | -        |
|                                            | LD50 Dermal                     | Rabbit       | >5 g/kg     | -        |
|                                            | LD50 Oral                       | Rat          | 3129 mg/kg  | -        |

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary

Skin : There are no data available on the mixture itself.

|                             |            |                                |                    |
|-----------------------------|------------|--------------------------------|--------------------|
| Code                        | : 00407037 | Date of issue/Date of revision | : 13 February 2024 |
| MULTIPRIME 4160 GRAY PRIMER |            |                                |                    |

SECTION 11: Toxicological information

- Eyes : There are no data available on the mixture itself.
- Respiratory : There are no data available on the mixture itself.
- Sensitization
- Conclusion/Summary
- Skin : There are no data available on the mixture itself.
- Respiratory : There are no data available on the mixture itself.
- Mutagenicity
- Conclusion/Summary : There are no data available on the mixture itself.
- Carcinogenicity
- Conclusion/Summary : There are no data available on the mixture itself.
- Reproductive toxicity
- Conclusion/Summary : There are no data available on the mixture itself.
- Teratogenicity
- Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

| Product/ingredient name                    | Category   | Route of exposure | Target organs                |
|--------------------------------------------|------------|-------------------|------------------------------|
| Hydrocarbons, C9, aromatics > 0.1% cumene  | Category 3 | -                 | Respiratory tract irritation |
| heptan-2-one                               | Category 3 | -                 | Narcotic effects             |
| solvent naphtha (petroleum), medium aliph. | Category 3 | -                 | Narcotic effects             |
| butanone oxime                             | Category 1 | -                 | Narcotic effects             |
|                                            | Category 3 | -                 | upper respiratory tract      |
|                                            |            |                   | Narcotic effects             |

Specific target organ toxicity (repeated exposure)

| Product/ingredient name                             | Category   | Route of exposure | Target organs                |
|-----------------------------------------------------|------------|-------------------|------------------------------|
| solvent naphtha (petroleum), medium aliph.          | Category 1 | -                 | central nervous system (CNS) |
| crystalline silica, respirable powder (<10 microns) | Category 1 | inhalation        | -                            |
| butanone oxime                                      | Category 2 | -                 | blood system                 |

Aspiration hazard

| Product/ingredient name                    | Result                         |
|--------------------------------------------|--------------------------------|
| Hydrocarbons, C9, aromatics > 0.1% cumene  | ASPIRATION HAZARD - Category 1 |
| solvent naphtha (petroleum), medium aliph. | ASPIRATION HAZARD - Category 1 |

- Information on the likely routes of exposure : Not available.

Potential acute health effects

- Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Ingestion : Can cause central nervous system (CNS) depression.
- Skin contact : Defatting to the skin. May cause skin dryness and irritation.
- Eye contact : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

|                             |            |                                |                    |
|-----------------------------|------------|--------------------------------|--------------------|
| Code                        | : 00407037 | Date of issue/Date of revision | : 13 February 2024 |
| MULTIPRIME 4160 GRAY PRIMER |            |                                |                    |

SECTION 11: Toxicological information

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                                                                                           |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Inhalation                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | : Adverse symptoms may include the following:<br>nausea or vomiting<br>headache<br>drowsiness/fatigue<br>dizziness/vertigo<br>unconsciousness                             |
| Ingestion                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | : No specific data.                                                                                                                                                       |
| Skin contact                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | : Adverse symptoms may include the following:<br>irritation<br>dryness<br>cracking                                                                                        |
| Eye contact                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | : No specific data.                                                                                                                                                       |
| <u>Delayed and immediate effects and also chronic effects from short and long term exposure</u>                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                                                                                           |
| <u>Short term exposure</u>                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                           |
| Potential immediate effects                                                                                                                                                                                                                                                                                                                                                                                                                                                  | : Not available.                                                                                                                                                          |
| Potential delayed effects                                                                                                                                                                                                                                                                                                                                                                                                                                                    | : Not available.                                                                                                                                                          |
| <u>Long term exposure</u>                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                           |
| Potential immediate effects                                                                                                                                                                                                                                                                                                                                                                                                                                                  | : Not available.                                                                                                                                                          |
| Potential delayed effects                                                                                                                                                                                                                                                                                                                                                                                                                                                    | : Not available.                                                                                                                                                          |
| <u>Potential chronic health effects</u>                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                                                           |
| Not available.                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                                                           |
| Conclusion/Summary                                                                                                                                                                                                                                                                                                                                                                                                                                                           | : Not available.                                                                                                                                                          |
| General                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | : May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. |
| Carcinogenicity                                                                                                                                                                                                                                                                                                                                                                                                                                                              | : May cause cancer. Risk of cancer depends on duration and level of exposure.                                                                                             |
| Mutagenicity                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | : No known significant effects or critical hazards.                                                                                                                       |
| Reproductive toxicity                                                                                                                                                                                                                                                                                                                                                                                                                                                        | : No known significant effects or critical hazards.                                                                                                                       |
| Other information                                                                                                                                                                                                                                                                                                                                                                                                                                                            | : Not available.                                                                                                                                                          |
| Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing. |                                                                                                                                                                           |

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

|                             |            |                                |                    |
|-----------------------------|------------|--------------------------------|--------------------|
| Code                        | : 00407037 | Date of issue/Date of revision | : 13 February 2024 |
| MULTIPRIME 4160 GRAY PRIMER |            |                                |                    |

SECTION 12: Ecological information

| Product/ingredient name                   | Result                  | Species                                  | Exposure |
|-------------------------------------------|-------------------------|------------------------------------------|----------|
| Hydrocarbons, C9, aromatics > 0.1% cumene | EC50 3.2 mg/l           | Daphnia                                  | 48 hours |
| heptan-2-one                              | LC50 9.2 mg/l           | Fish                                     | 96 hours |
| trizinc bis(orthophosphate)               | Acute LC50 131 mg/l     | Fish                                     | 96 hours |
|                                           | Acute LC50 0.112 mg/l   | Fish                                     | 96 hours |
|                                           | Chronic NOEC 0.026 mg/l | Fish                                     | 30 days  |
| zinc oxide                                | Acute EC50 0.17 mg/l    | Algae                                    | 72 hours |
|                                           | Acute EC50 0.481 mg/l   | Daphnia - <i>Daphnia magna</i> - Neonate | 48 hours |
|                                           | Fresh water             |                                          |          |
|                                           | Chronic NOEC 0.017 mg/l | Algae                                    | 72 hours |
|                                           | Fresh water             |                                          |          |

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

| Product/ingredient name                   | Test     | Result                   | Dose | Inoculum |
|-------------------------------------------|----------|--------------------------|------|----------|
| Hydrocarbons, C9, aromatics > 0.1% cumene | -        | 75 % - Readily - 28 days | -    | -        |
| heptan-2-one                              | OECD 310 | 69 % - Readily - 28 days | -    | -        |

Conclusion/Summary : There are no data available on the mixture itself.

| Product/ingredient name                   | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------------------------|-------------------|------------|------------------|
| Hydrocarbons, C9, aromatics > 0.1% cumene | -                 | -          | Readily          |
| heptan-2-one                              | -                 | -          | Readily          |

12.3 Bioaccumulative potential

| Product/ingredient name | LogP <sub>ow</sub> | BCF  | Potential |
|-------------------------|--------------------|------|-----------|
| heptan-2-one            | 2.26               | -    | Low       |
| butanone oxime          | 0.63               | 5.01 | Low       |

12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

|                             |            |                                |                    |
|-----------------------------|------------|--------------------------------|--------------------|
| Code                        | : 00407037 | Date of issue/Date of revision | : 13 February 2024 |
| MULTIPRIME 4160 GRAY PRIMER |            |                                |                    |

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Methods of disposal | : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.            |
| Hazardous waste     | : The classification of the product may meet the criteria for a hazardous waste.                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Packaging           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Methods of disposal | : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.                                                                                                                                                                                                                                                                                                                                           |
| Special precautions | : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. |

14. Transport information

|                                 |                 |                 |                                                                                                                                   |                                                                    |
|---------------------------------|-----------------|-----------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------|
|                                 | ADR/RID         | ADN             | IMDG                                                                                                                              | IATA                                                               |
| 14.1 UN number or ID number     | UN1263          | UN1263          | UN1263                                                                                                                            | UN1263                                                             |
| 14.2 UN proper shipping name    | PAINT           | PAINT           | PAINT                                                                                                                             | PAINT                                                              |
| 14.3 Transport hazard class(es) | 3               | 3               | 3                                                                                                                                 | 3                                                                  |
| 14.4 Packing group              | III             | III             | III                                                                                                                               | III                                                                |
| 14.5 Environmental hazards      | Yes.            | Yes.            | Yes.                                                                                                                              | Yes. The environmentally hazardous substance mark is not required. |
| Marine pollutant substances     | Not applicable. | Not applicable. |  (Solvent naphtha (petroleum), light aromatic) | Not applicable.                                                    |

Additional information

|             |                                                                                                            |
|-------------|------------------------------------------------------------------------------------------------------------|
| ADR/RID     | : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. |
| Tunnel code | : (D/E)                                                                                                    |
| ADN         | : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. |
| IMDG        | : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.                    |

|                             |            |                                |                    |
|-----------------------------|------------|--------------------------------|--------------------|
| Code                        | : 00407037 | Date of issue/Date of revision | : 13 February 2024 |
| MULTIPRIME 4160 GRAY PRIMER |            |                                |                    |

14. Transport information

|                                                              |                                                                                                                                                                                                                     |
|--------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IATA                                                         | : The environmentally hazardous substance mark may appear if required by other transportation regulations.                                                                                                          |
| 14.6 Special precautions for user                            | : <b>Transport within user’s premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. |
| 14.7 Maritime transport in bulk according to IMO instruments | : Not applicable.                                                                                                                                                                                                   |

SECTION 15: Regulatory information

|                                                                                                                                    |                                                        |
|------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|
| 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture                                |                                                        |
| EU Regulation (EC) No. 1907/2006 (REACH)                                                                                           |                                                        |
| Annex XIV - List of substances subject to authorization                                                                            |                                                        |
| Annex XIV                                                                                                                          | None of the components are listed.                     |
| Substances of very high concern                                                                                                    | None of the components are listed.                     |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : Restricted to professional users.                    |
| Explosive precursors                                                                                                               | : Not applicable.                                      |
| Ozone depleting substances (1005/2009/EU)                                                                                          | Not listed.                                            |
| Seveso Directive                                                                                                                   | This product is controlled under the Seveso Directive. |
| Danger criteria                                                                                                                    |                                                        |
| Category                                                                                                                           |                                                        |
| P5c                                                                                                                                |                                                        |
| E2                                                                                                                                 |                                                        |

|                                 |                                                       |
|---------------------------------|-------------------------------------------------------|
| 15.2 Chemical Safety Assessment | : No Chemical Safety Assessment has been carried out. |
|---------------------------------|-------------------------------------------------------|

SECTION 16: Other information

|                                                                                          |
|------------------------------------------------------------------------------------------|
| Indicates information that has changed from previously issued version.                   |
| Abbreviations and acronyms                                                               |
| ATE = Acute Toxicity Estimate                                                            |
| CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] |
| DNEL = Derived No Effect Level                                                           |
| EUH statement = CLP-specific Hazard statement                                            |
| PNEC = Predicted No Effect Concentration                                                 |
| RRN = REACH Registration Number                                                          |
| PBT = Persistent, Bioaccumulative and Toxic                                              |

|                             |            |                                |                    |
|-----------------------------|------------|--------------------------------|--------------------|
| Code                        | : 00407037 | Date of issue/Date of revision | : 13 February 2024 |
| MULTIPRIME 4160 GRAY PRIMER |            |                                |                    |

SECTION 16: Other information

vPvB = Very Persistent and Very Bioaccumulative  
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
IMDG = International Maritime Dangerous Goods  
IATA = International Air Transport Association

Full text of abbreviated H statements

|        |                                                                    |
|--------|--------------------------------------------------------------------|
| H226   | Flammable liquid and vapor.                                        |
| H301   | Toxic if swallowed.                                                |
| H302   | Harmful if swallowed.                                              |
| H304   | May be fatal if swallowed and enters airways.                      |
| H312   | Harmful in contact with skin.                                      |
| H315   | Causes skin irritation.                                            |
| H317   | May cause an allergic skin reaction.                               |
| H318   | Causes serious eye damage.                                         |
| H319   | Causes serious eye irritation.                                     |
| H332   | Harmful if inhaled.                                                |
| H335   | May cause respiratory irritation.                                  |
| H336   | May cause drowsiness or dizziness.                                 |
| H350   | May cause cancer.                                                  |
| H360FD | May damage fertility. May damage the unborn child.                 |
| H370   | Causes damage to organs.                                           |
| H372   | Causes damage to organs through prolonged or repeated exposure.    |
| H373   | May cause damage to organs through prolonged or repeated exposure. |
| H400   | Very toxic to aquatic life.                                        |
| H410   | Very toxic to aquatic life with long lasting effects.              |
| H411   | Toxic to aquatic life with long lasting effects.                   |
| H412   | Harmful to aquatic life with long lasting effects.                 |
| EUH066 | Repeated exposure may cause skin dryness or cracking.              |

Full text of classifications [CLP/GHS]

|                   |                                                                 |
|-------------------|-----------------------------------------------------------------|
| Acute Tox. 3      | ACUTE TOXICITY - Category 3                                     |
| Acute Tox. 4      | ACUTE TOXICITY - Category 4                                     |
| Aquatic Acute 1   | AQUATIC HAZARD (ACUTE) - Category 1                             |
| Aquatic Chronic 1 | AQUATIC HAZARD (LONG-TERM) - Category 1                         |
| Aquatic Chronic 2 | AQUATIC HAZARD (LONG-TERM) - Category 2                         |
| Aquatic Chronic 3 | AQUATIC HAZARD (LONG-TERM) - Category 3                         |
| Asp. Tox. 1       | ASPIRATION HAZARD - Category 1                                  |
| Carc. 1B          | CARCINOGENICITY - Category 1B                                   |
| Eye Dam. 1        | SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1                 |
| Eye Irrit. 2      | SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2                 |
| Flam. Liq. 3      | FLAMMABLE LIQUIDS - Category 3                                  |
| Repr. 1B          | TOXIC TO REPRODUCTION - Category 1B                             |
| Skin Irrit. 2     | SKIN CORROSION/IRRITATION - Category 2                          |
| Skin Sens. 1      | SKIN SENSITIZATION - Category 1                                 |
| Skin Sens. 1A     | SKIN SENSITIZATION - Category 1A                                |
| STOT RE 1         | SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 |
| STOT RE 2         | SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 |
| STOT SE 1         | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1   |
| STOT SE 3         | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3   |

History

|                             |            |                                |                    |
|-----------------------------|------------|--------------------------------|--------------------|
| Code                        | : 00407037 | Date of issue/Date of revision | : 13 February 2024 |
| MULTIPRIME 4160 GRAY PRIMER |            |                                |                    |

SECTION 16: Other information

Date of issue/ Date of revision : 13 February 2024

Date of previous issue : 21 October 2023

Prepared by : EHS

Version : 5.07

Disclaimer

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*