# **SAFETY DATA SHEET**

Date of issue/Date of revision

: 28 February 2024 Version



pPG

: 1.03

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

U	
1.1 Product identifier	
Product name	: SIGMAGUARD CSF 585 BASE BLUE 1
Product code	: 000001099277
Other means of identification	ation
00219192; 00219194; 003 <sup>-</sup>	10817
1.2 Relevant identified use	es of the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/	: Coating.
mixture	
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
1.3 Details of the supplier	of the safety data sheet
Varossieau Suriname NV,	
Mostopowog / Doromoriba	

valussieau Sullianie NV,	
Mastanaweg 4, Paramaribo,	
SURINAME	
Tel: 00597 484447	
Fax: 00597 483785	
e-mail address of person responsible for this SDS	: Product.Stewardship.EMEA@ppg.com

**1.4 Emergency telephone** : 0031 (0)20 4075210 number

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture Product definition : Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411 The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 16 for the full text of the H statements declared above. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements Hazard pictograms



Signal word

: Warning

English (GB)

Code: 000001099277Date of issue/Date of revision: 28 February 2024SIGMAGUARD CSF 585 BASE BLUE 1

# SECTION 2: Hazards identification

SECTION 2. Hazards	
Hazard statements	: Causes skin irritation. May cause an allergic skin reaction.
	Causes serious eye irritation.
	Toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapour. Wash thoroughly after handling.
Response	: Collect spillage.
Storage	: Not applicable.
Disposal	<ul> <li>Dispose of contents and container in accordance with all local, regional, national and international regulations.</li> <li>P280, P273, P261, P264, P391, P501</li> </ul>
Hazardous ingredients	<ul> <li>bis-[4-(2,3-epoxipropoxi)phenyl]propane</li> <li>1,6-Hexanediol, reaction products with epichlorohydrin</li> <li>Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine</li> </ul>
Supplemental label elements	: Contains epoxy constituents. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requiren	<u>nents</u>
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
bis-[4-(2,3-epoxipropoxi) phenyl]propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥25 - ≤50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
1,6-Hexanediol, reaction products with epichlorohydrin	REACH #: 01-2119463471-41 CAS: 933999-84-9	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-	[1]
		English	i (GB) Su	riname	2/14

SECTIC	ON 3: Composition/informa	tion on ingredients	
SIGMAGU	ARD CSF 585 BASE BLUE 1		
Code	: 000001099277	Date of issue/Date of revision	: 28 February 2024

Octadecanoic acid,	REACH #:	<1.0	Skin Sens. 1B, H317	-	[1]
12-hydroxy-, reaction	01-2119979085-27		Aquatic Chronic 3, H412		
products with	EC: 309-629-8				
ethylenediamine	CAS: 100545-48-0				
			See Section 16 for		
			the full text of the H		
			statements declared		
			above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

This mixture contains  $\geq$  1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

#### SUB codes represent substances without registered CAS Numbers.

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	<ul> <li>If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.</li> </ul>
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects	
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sympto	<u>ms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

English (GB)

Code : 000001099277	Date of issue/Date of revision : 28 February 2024
SIGMAGUARD CSF 585 BASE	
SECTION 4: First aid	measures
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
SECTION 5: Firefight	ing measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising fr	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides
5.3 Advice for firefighters	
Special precautions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathin apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to Europea standard EN 469 will provide a basic level of protection for chemical incidents.

6.1 Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.	
6.3 Methods and material for	со	ntainment and cleaning up	
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	

Code	: 000001099277	Date of issue/Date of revision	: 28 February 2024

SIGMAGUARD CSF 585 BASE BLUE 1

#### **SECTION 6: Accidental release measures**

Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 8.1 Control parameters

#### **Occupational exposure limits**

No exposure limit value known.

Code : 000001099277

Date of issue/Date of revision

: 28 February 2024

SIGMAGUARD CSF 585 BASE BLUE 1

**Recommended monitoring** procedures

Reference should be made to monitoring standards, such as the following: European 1 Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
bis-[4-(2,3-epoxipropoxi)phenyl] propane	DNEL	Long term Inhalation	12.25 mg/m <sup>3</sup>	Workers	Systemic
F F	DNEL	Short term Inhalation	12.25 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	3.571 mg/kg bw/	General	Systemic
			day	population [Consumers]	- ,
	DNEL	Short term Dermal	3.571 mg/kg bw/	General	Systemic
	DITLE		day	population [Consumers]	eyetenne
	DNEL	Long term Oral	0.75 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Oral	0.75 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	89.3 µg/kg bw/day	[Consumers] General population	Systemic
	DNEL	Long term Oral	0.5 mg/kg bw/day	General	Systemic
	DNEL	Long term Dermal	0.75 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.87 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	4.93 mg/m <sup>3</sup>	Workers	Systemic
1,6-Hexanediol, reaction products with epichlorohydrin	DNEL	Short term Dermal	13.6 ng/cm <sup>2</sup>	General population	Local
	DNEL	Long term Dermal	13.6 ng/cm²	General population	Local
	DNEL	Short term Dermal	22.6 ng/cm <sup>2</sup>	Workers	Local
	DNEL	Long term Dermal	22.6 ng/cm <sup>2</sup>	Workers	Local
	DNEL	Long term Inhalation	0.27 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	0.44 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Oral	1.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	1.5 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	1.7 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	3 mg/kg bw/day	General	Systemic
	DNEL	Short term Inhalation	5.29 mg/m³	General	Systemic
	DNEL	Long term Inhalation	5.29 mg/m³	General	Systemic
	DNEL	Long term Dermal	6 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	10.57 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	10.57 mg/m <sup>3</sup>	Workers	Systemic
Octadecanoic acid, 12-hydroxy-,	DNEL	Long term Inhalation	0.055 mg/m <sup>3</sup>	General	Local

Code : 000001099277			Date of issue/	: 28 February 2024		
S	SIGMAGUARD CSF 585 BASE BLUE 1					
	reaction products with ethylenediamine				population	
		DNEL	Long term Inhalation	0.308 mg/m <sup>3</sup>	Workers	Local

PNECs				'
Product/ingredient name	Туре	Compartment Detail	Value	Method Detail
bis-[4-(2,3-epoxipropoxi)phenyl] propane	-	Fresh water	0.006 mg/l	Assessment Factors
	- - - - -	Fresh water sediment	0.001 mg/l 0.996 mg/kg dwt 0.1 mg/kg dwt 0.196 mg/kg dwt 10 mg/l 11 mg/kg	Assessment Factors Equilibrium Partitioning Equilibrium Partitioning Equilibrium Partitioning Assessment Factors Assessment Factors

8.2 Exposure controls	
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection meas	ures de la constante de la const
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	: Chemical splash goggles.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Gloves	: butyl rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

Code : 000001099277	7	Date of issue/Date of revision	: 28 February 2024
SIGMAGUARD CSF 585 BAS	E BLUE 1		
Environmental exposure controls		n or work process equipment should uirements of environmental protectior	

will be necessary to reduce emissions to acceptable levels.

cases, fume scrubbers, filters or engineering modifications to the process equipment

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

. I mormation on basic physica	u	na chemical properti	103					
Appearance								
Physical state	1	Liquid.						
Colour	:	Blue.						
Odour	:	Characteristic.						
Odour threshold	:	Not available.						
Melting point/freezing point	:	May start to solidify a based on data for the Weighted average: 3	e following	g ingredie				
Initial boiling point and boiling range	:	>37.78°C						
Flammability	:	Not available.						
Upper/lower flammability or explosive limits	:	Not available.						
Flash point	:	Closed cup: 130°C						
Auto-ignition temperature	:	Not available.						
Decomposition temperature	1	Stable under recomm	nended st	orage an	d handling co	onditions	(see Sec	tion 7).
рН	1	Not applicable. insolu		ter.				
Viscosity	1	Kinematic (40°C): >2						
Viscosity	1	60 - 100 s (ISO 6mm	ı)					
Solubility(ies)	:							
Media		Result						
cold water		Not soluble						
Partition coefficient: n-octanol/ water	:	Not applicable.						
Vapour pressure	:	la se d'antes a	Vapou	ur Pressu	ure at 20°C	Vap	our pres	sure at 50°C
		Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
		bis-[4-(2,3-epoxipropoxi) phenyl]propane	<0.000075006	<0.00001				
Evaporation rate	1	Not available.						
Relative density	4	1.41						
Vapour density		Highest known value						
Explosive properties		The product itself is r vapour or dust with a	ir is possi	ble.		of an exp	olosible n	ixture of
Oxidising properties	4	Product does not pre	sent an o	xidizing h	azard.			
Particle characteristics								
Median particle size	:	Not applicable.						
9.2 Other information								
No additional information.								

Code	: 000001099277	Date of issue/Date of revision	: 28 February 2024
SIGMAGUAR	D CSF 585 BASE BLUE 1		

# **SECTION 10: Stability and reactivity**

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides

## **SECTION 11: Toxicological information**

#### **11.1 Information on toxicological effects**

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
bis-[4-(2,3-epoxipropoxi)phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
1,6-Hexanediol, reaction products with epichlorohydrin	LD50 Dermal	Rat - Male, Female	>2000 mg/kg	-
	LD50 Oral	Rat - Male, Female	2189 mg/kg	-
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	LC50 Inhalation Dusts and mists	Rat	5.05 mg/l	4 hours
	LD50 Oral	Rat	>2000 mg/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the	Rabbit	0.4	24 hours	-
	conjunctivae				
	Skin - Oedema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-

Conclusion/Summary

- : There are no data available on the mixture itself.
- Eyes : There are no data available on the mixture itself.

Respiratory

Skin

: There are no data available on the mixture itself.

#### **Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
bis-[4-(2,3-epoxipropoxi)phenyl]propane Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	skin skin	Mouse Guinea pig	Sensitising Sensitising

#### **Conclusion/Summary**

English (GB)

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 Code : 000001099277 Date of issue/Date of revision : 28 February 2024 SIGMAGUARD CSF 585 BASE BLUE 1 SECTION 11: Toxicological information Skin : There are no data available on the mixture itself. Respiratory : There are no data available on the mixture itself. **Mutagenicity Conclusion/Summary** : There are no data available on the mixture itself. **Carcinogenicity** : There are no data available on the mixture itself. **Conclusion/Summary Reproductive toxicity** : There are no data available on the mixture itself. **Conclusion/Summary Teratogenicity Conclusion/Summary** : There are no data available on the mixture itself. Specific target organ toxicity (single exposure) Not available. Specific target organ toxicity (repeated exposure) Not available. **Aspiration hazard** Not available. Information on likely : Not available. routes of exposure Potential acute health effects Inhalation : No known significant effects or critical hazards. : No known significant effects or critical hazards. Ingestion

: Causes skin irritation. May cause an allergic skin reaction.

Eye contact: Causes serious eye irritation.Symptoms related to the physical, chemical and toxicological characteristics

Inhalation		No specific data.		
Ingestion	÷	No specific data.		
Skin contact	:	Adverse symptoms may include the following: irritation redness		
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness		
Delayed and immediate effects as well as chronic effects from short and long-term exposure				
<u>Short term exposure</u>				
Potential immediate effects	:	Not available.		
Potential delayed effects	:	Not available.		
Long term exposure				
Potential immediate effects	:	Not available.		
Potential delayed effects	:	Not available.		
Potential chronic health effects				

Not available.

**Skin contact** 

**Conclusion/Summary** : Not available.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU)	
2020/878	

Code	÷,	000001099277	Date of issue/Date of revision	1	28 February 2024
SIGMAGUARD CSF 585 BASE BLUE 1					
SECTION 11: Toxicological information					

General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed t very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
Other information	: Not available.
Sanding and grinding dusts	ay be harmful if inhaled.

11.2 Information on other hazards

#### **11.2.1 Endocrine disrupting properties**

Not available.

#### 11.2.2 Other information

Not available.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia</i> <i>magna</i>	48 hours
	Chronic NOEC 0.3 mg/l	Daphnia	21 days
1,6-Hexanediol, reaction products with epichlorohydrin	Acute EC50 47 mg/l Fresh water	Daphnia	48 hours
	Acute LC50 30 mg/l Fresh water	Fish	96 hours
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	Acute EC50 >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 >10 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 >10 mg/l	Fish - Oncorhynchus mykiss	96 hours

Conclusion/Summary

There are no data available on the mixture itself.

#### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
1,6-Hexanediol, reaction products with epichlorohydrin	OECD 301D Ready Biodegradability - Closed Bottle Test	47 % - Not readily - 28 days	-	-
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	301D Ready Biodegradability - Closed Bottle Test	22 % - 28 days	-	-

#### **Conclusion/Summary** : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1,6-Hexanediol, reaction products with epichlorohydrin Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	-	-	Not readily Not readily Inherent

to

 Code
 <th::000001099277</th>
 Date of issue/Date of revision
 : 28 February 2024

 SIGMAGUARD CSF 585 BASE BLUE 1

## **SECTION 12: Ecological information**

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,6-Hexanediol, reaction products with epichlorohydrin	0.822	-	Low
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	>5.86	-	High

#### **12.4 Mobility in soil**

Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
· · · · · · · · · · · · · · · · · · ·	

Hazardous waste : Yes. European waste catalogue (EWC)

Waste code	Waste designation	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	
Packaging		
Methods of disposal		on of waste should be avoided or minimised wherever possible. Waste ould be recycled. Incineration or landfill should only be considered when ot feasible.
Type of packaging		European waste catalogue (EWC)
Container	15 01 06	mixed packaging
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of sp material and runoff and contact with soil, waterways, drains and sewers.	

English (	GB)
-----------	-----

Code: 000001099277Date of issue/Date of revision: 28 February 2024

SIGMAGUARD CSF 585 BASE BLUE 1

## **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi) phenyl]propane)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	Ш	Ш	Ш
14.5 Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Not applicable.

Additional infor	mation			
ADR/RID	This product is not regulated as a dangerous good when transported in sizes of $\leq$ 5 L or $\leq$ 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.			
Tunnel code	: (-)			
IMDG	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.			
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.			
14.6 Special pre user	ecautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.			
14.7 Transport according to IM instruments				

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
<u>EU Regulation (EC) No. 1907/2006 (REACH)</u>
<u>Annex XIV - List of substances subject to authorisation</u>
<u>Annex XIV</u>
None of the components are listed.
<u>Substances of very high concern</u>
None of the components are listed.
<u>Annex XVII - Restrictions</u> : Not applicable.
on the manufacture,
placing on the market

and use of certain dangerous substances, mixtures and articles

Other national and international regulations.

	Date of issue/Date of revision	: 28 February 2024
SIGMAGUARD CSF 585 BASE BLUE 1		
SECTION 15: Regulatory information		
<b>Explosive precursors</b> : Not applicable.		
Ozone depleting substances (1005/2009/EU)		
Not listed.		
Seveso Directive		
This product is controlled under the Seveso Directive.		
Danger criteria		
Category		
E2		
15.2 Chemical safety : No Chemical Safety A	ssessment has been carried out.	
assessment		

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
-	1272/2008]
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classi	fication	Justification
Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411		Calculation method Calculation method Calculation method Calculation method
Full text of abbreviated H statements	H319 Causes serious e H411 Toxic to aquatic li	ergic skin reaction.
Full text of classifications [CLP/GHS]	Aquatic Chronic 3 Eye Irrit. 2 Skin Irrit. 2 Skin Sens. 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1B
<u>History</u>		
Date of issue/ Date of revision	: 28 February 2024	
Date of previous issue	: 15 December 2023	
Prepared by	: EHS	
Version	: 1.03	
<u>Disclaimer</u>		

#### <u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Suriname