



# SAFETY DATA SHEET

Date of issue/Date of revision

: 20 March 2024

Version

: 2.04

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : SIGMARINE 28 GREY

**Product code** : 00445360

#### Other means of identification

Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

**Use of the substance/  
mixture** : Coating.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

Sigma Paint Saudi Arabia Ltd.  
PO Box 7509  
Dammam 31472  
Saudi Arabia  
Tel: 00966 138 47 31 00  
Fax: 00966 138 47 17 34

**e-mail address of person  
responsible for this SDS** : ndpic@sfda.gov.sa

**1.4 Emergency telephone  
number** : 00966 138473100 extn 1001

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Carc. 1B, H350

STOT SE 3, H335

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Code : 00445360

Date of issue/Date of revision

: 20 March 2024

SIGMARINE 28 GREY

## SECTION 2: Hazards identification

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: Flammable liquid and vapour.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause cancer.  
Harmful to aquatic life with long lasting effects.

### Precautionary statements

Prevention

: Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response

: IF exposed or concerned: Get medical advice or attention.

Storage

: Store in a well-ventilated place. Keep container tightly closed.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.  
P202, P280, P210, P308 + P313, P403 + P233, P501

Hazardous ingredients

:  xylene  
butanone oxime

Supplemental label elements

:  Contains 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene, butanone oxime and cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Restricted to professional users.

### Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

### 2.3 Other hazards

Product meets the criteria for PBT or vPvB

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: Prolonged or repeated contact may dry skin and cause irritation.

## SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Code : 00445360

Date of issue/Date of revision

: 20 March 2024

SIGMARINE 28 GREY

### SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7	≥10 - ≤25	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1700 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Inhalation (vapours)] = 17.8 mg/l	[1] [2]
trizinc bis(orthophosphate)	REACH #: 01-2119485044-40 EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6	≤1.0	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene	REACH #: 01-2119962189-26 CAS: 911674-82-3 Index: 616-198-00-2	<1.0	Skin Sens. 1, H317 Aquatic Chronic 4, H413	-	[1] [2]
2-ethylhexanoic acid, zirconium salt	REACH #: 01-2119979088-21 EC: 245-018-1 CAS: 22464-99-9 Index: 607-230-00-6	<0.30	Repr. 1B, H360D	-	[1] [2]
butanone oxime	REACH #: 01-2119539477-28 EC: 202-496-6 CAS: 96-29-7 Index: 616-014-00-0	≤0.30	Acute Tox. 3, H301 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 1B, H350 STOT SE 1, H370 (upper respiratory tract) STOT SE 3, H336 STOT RE 2, H373 (blood system)	ATE [Oral] = 100 mg/kg ATE [Dermal] = 1100 mg/kg	[1] [2]
calcium bis (2-ethylhexanoate)	REACH #: 01-2119978297-19 EC: 205-249-0 CAS: 136-51-6 Index: 607-230-00-6	<0.30	Eye Dam. 1, H318 Repr. 1B, H360D	-	[1]
cobalt bis (2-ethylhexanoate)	REACH #: 01-2119524678-29 EC: 205-250-6 CAS: 136-52-7 Index: 607-230-00-6	<0.10	Eye Irrit. 2, H319 Skin Sens. 1A, H317 Repr. 1B, H360FD Aquatic Acute 1, H400 Aquatic Chronic 3, H412	M [Acute] = 1	[1] [2]

Code : 00445360

Date of issue/Date of revision

: 20 March 2024

SIGMARINE 28 GREY

### SECTION 3: Composition/information on ingredients

			<b>See Section 16 for the full text of the H statements declared above.</b>		
--	--	--	---	--	--

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

This mixture contains  $\geq 1\%$  of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : May cause respiratory irritation.
- Skin contact** : Causes skin irritation. Defatting to the skin.
- Ingestion** : No known significant effects or critical hazards.

##### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Ingestion** : No specific data.

Code : 00445360

Date of issue/Date of revision

: 20 March 2024

SIGMARINE 28 GREY

## SECTION 4: First aid measures

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

Code : 00445360

Date of issue/Date of revision

: 20 March 2024

SIGMARINE 28 GREY

## SECTION 6: Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- 7.2 Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

Code : 00445360

Date of issue/Date of revision

: 20 March 2024

SIGMARINE 28 GREY

## SECTION 7: Handling and storage

See Section 1.2 for Identified uses.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
<p>xylene</p>	<p><b>Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016). [xylene (o, m &amp; p isomers)]</b>                      STEL: 651 mg/m<sup>3</sup> 15 minutes.                      STEL: 150 ppm 15 minutes.                      TWA: 434 mg/m<sup>3</sup> 8 hours.                      TWA: 100 ppm 8 hours.  <b>Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006). [xylene (all isomers)]</b>                      STEL: 150 ppm 15 minutes.                      TWA: 434 mg/m<sup>3</sup> 8 hours.                      STEL: 651 mg/m<sup>3</sup> 15 minutes.                      TWA: 100 ppm 8 hours.  <b>ACGIH TLV (United States, 1/2023). [p-xylene and mixtures containing p-xylene] Ototoxicant.</b>                      TWA: 20 ppm 8 hours.</p>
<p>Talc , not containing asbestiform fibres</p>	<p><b>Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016).</b>                      TWA: 2 mg/m<sup>3</sup> 8 hours. Form: measured as respirable fraction of the aerosol  <b>Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006).</b>                      TWA: 2 mg/m<sup>3</sup> 8 hours.  <b>ACGIH TLV (United States, 1/2023).</b>                      TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable</p>
<p>ethylbenzene</p>	<p><b>Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016).</b>                      STEL: 543 mg/m<sup>3</sup> 15 minutes.                      STEL: 125 ppm 15 minutes.                      TWA: 100 ppm 8 hours.                      TWA: 434 mg/m<sup>3</sup> 8 hours.  <b>Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006).</b>                      STEL: 125 ppm 15 minutes.                      TWA: 434 mg/m<sup>3</sup> 8 hours.                      STEL: 543 mg/m<sup>3</sup> 15 minutes.                      TWA: 100 ppm 8 hours.  <b>ACGIH TLV (United States, 1/2023). Ototoxicant. Notes: Substances for which there is a Biological Exposure Index or Indices 2002 Adoption.</b>                      TWA: 20 ppm 8 hours.</p>
<p>titanium dioxide</p>	<p><b>Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016).</b>                      TWA: 10 mg/m<sup>3</sup> 8 hours.  <b>Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006).</b></p>

Code : 00445360 Date of issue/Date of revision : 20 March 2024  
SIGMARINE 28 GREY

TWA: 10 mg/m<sup>3</sup> 8 hours.  
**ACGIH TLV (United States, 1/2023).**  
TWA: 2.5 mg/m<sup>3</sup> 8 hours. Form: respirable fraction, finescale particles

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

## 8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Chemical splash goggles.

#### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Gloves** : For prolonged or repeated handling, use the following type of gloves:

Not recommended: nitrile rubber  
Recommended: polyvinyl alcohol (PVA), Viton®

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** :



**Code** : 00445360 **Date of issue/Date of revision** : 20 March 2024  
 SIGMARINE 28 GREY

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Grey.
- Odour** : Aromatic.
- Odour threshold** : Not available.
- Melting point/freezing point** : May start to solidify at the following temperature: -94.9°C (-138.8°F) This is based on data for the following ingredient: ethylbenzene. Weighted average: -94.95°C (-138.9°F)
- Initial boiling point and boiling range** : >37.78°C
- Flammability** : Not available.
- Upper/lower flammability or explosive limits** : Greatest known range: Lower: 0.8% Upper: 6.7% (xylene)
- Flash point** : Closed cup: 25°C

#### Auto-ignition temperature

Ingredient name	°C	°F	Method
xylene	432	809.6	

- Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).
- pH** : Not applicable. insoluble in water.
- Viscosity** : Kinematic (40°C): >21 mm<sup>2</sup>/s
- Solubility(ies)** :

Media	Result
cold water	Not soluble

- Partition coefficient: n-octanol/ water** : Not applicable.

#### Vapour pressure

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
ethylbenzene	9.30076	1.2				

- Evaporation rate** : Highest known value: 0.84 (ethylbenzene) Weighted average: 0.78 compared with butyl acetate
- Relative density** : 1.35
- Bulk density ( g/cm<sup>3</sup> )** : 1.466
- Vapour density** : Highest known value: 3.7 (Air = 1) (xylene). Weighted average: 3.7 (Air = 1)
- Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
- Oxidising properties** : Product does not present an oxidizing hazard.
- Particle characteristics**
- Median particle size** : Not applicable.

Code : 00445360

Date of issue/Date of revision

: 20 March 2024

SIGMARINE 28 GREY

## SECTION 9: Physical and chemical properties

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

**10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
xylene	LD50 Dermal	Rabbit	1.7 g/kg	-
	LD50 Oral	Rat	4.3 g/kg	-
ethylbenzene	LC50 Inhalation Vapour	Rat	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	17.8 g/kg	-
	LD50 Oral	Rat	3.5 g/kg	-
trizinc bis(orthophosphate)	LC50 Inhalation Dusts and mists	Rat	>5.7 mg/l	4 hours
	LD50 Oral	Rat	>5000 mg/kg	-
Reaction products of 12-hydroxyoctadecanoic acid and octadecanoic acid and 1,3-phenylenedimethanamine	LC50 Inhalation Dusts and mists	Rat	>5.08 mg/l	4 hours
2-ethylhexanoic acid, zirconium salt	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	>5 g/kg	-
2-butanone oxime	LD50 Dermal	Rabbit	1100 mg/kg	-
	LD50 Oral	Rat	100 mg/kg	-
cobalt bis(2-ethylhexanoate)	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	3129 mg/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

Code : 00445360

Date of issue/Date of revision

: 20 March 2024

SIGMARINE 28 GREY

## SECTION 11: Toxicological information

### Sensitisation

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
xylene butanone oxime	Category 3 Category 1 Category 3	- - -	Respiratory tract irritation upper respiratory tract Narcotic effects

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene butanone oxime	Category 2 Category 2	- -	hearing organs blood system

### Aspiration hazard

Product/ingredient name	Result
xylene ethylbenzene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

**Inhalation** : May cause respiratory irritation.

**Ingestion** : No known significant effects or critical hazards.

**Skin contact** : Causes skin irritation. Defatting to the skin.

**Eye contact** : Causes serious eye irritation.

### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing

**Ingestion** : No specific data.

**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

Code : 00445360 Date of issue/Date of revision : 20 March 2024  
 SIGMARINE 28 GREY

## SECTION 11: Toxicological information

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.

**General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

**Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

**Other information** : Not available.

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
ethylbenzene	Acute EC50 1.8 mg/l Fresh water	Daphnia	48 hours
	Chronic NOEC 1 mg/l Fresh water	Daphnia - <i>Ceriodaphnia dubia</i>	-
trizinc bis(orthophosphate)	Acute LC50 0.112 mg/l	Fish	96 hours
	Chronic NOEC 0.026 mg/l	Fish	30 days
Reaction products of 12-hydroxyoctadecanoic acid and octadecanoic acid and 1,3-phenylenedimethanamine	Acute LC50 >100 mg/l	Fish	96 hours
2-ethylhexanoic acid, zirconium salt	Acute LC50 >100 mg/l	Fish	96 hours

**Conclusion/Summary** : There are no data available on the mixture itself.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
ethylbenzene	-	79 % - Readily - 10 days	-	-

**Conclusion/Summary** : There are no data available on the mixture itself.

Code : 00445360 Date of issue/Date of revision : 20 March 2024  
 SIGMARINE 28 GREY

## SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
xylene	-	-	Readily
ethylbenzene	-	-	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
xylene	3.12	7.4 to 18.5	Low
ethylbenzene	3.6	79.43	Low
butanone oxime	0.63	5.01	Low

### 12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Mobility : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

#### European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Code : 00445360

Date of issue/Date of revision

: 20 March 2024

SIGMARINE 28 GREY

## SECTION 13: Disposal considerations

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	III	III	III
14.5 Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

### Additional information

**ADR/RID** : None identified.

**Tunnel code** : (D/E)

**IMDG** : None identified.

**IATA** : None identified.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not applicable.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU Regulation (EC) No. 1907/2006 (REACH)**

**Annex XIV - List of substances subject to authorisation**

**Annex XIV**

None of the components are listed.

**Substances of very high concern**

None of the components are listed.

Code : 00445360

Date of issue/Date of revision

: 20 March 2024

SIGMARINE 28 GREY

## SECTION 15: Regulatory information

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Restricted to professional users.

### Other national and international regulations.

**Explosive precursors** : Not applicable.

### Ozone depleting substances (1005/2009/EU)

Not listed.

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

### **Abbreviations and acronyms**

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number

### **Full text of abbreviated H statements**

: H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H301 Toxic if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H350 May cause cancer.  
H360D May damage the unborn child.  
H360FD May damage fertility. May damage the unborn child.  
H370 Causes damage to organs.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.  
H413 May cause long lasting harmful effects to aquatic life.

### **Full text of classifications [CLP/GHS]**

: Acute Tox. 3 ACUTE TOXICITY - Category 3  
Acute Tox. 4 ACUTE TOXICITY - Category 4  
Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1  
Aquatic Chronic 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1  
Aquatic Chronic 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3  
Aquatic Chronic 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4  
Asp. Tox. 1 ASPIRATION HAZARD - Category 1  
Carc. 1B CARCINOGENICITY - Category 1B  
Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1  
Eye Irrit. 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2  
Flam. Liq. 2 FLAMMABLE LIQUIDS - Category 2  
Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3  
Repr. 1B REPRODUCTIVE TOXICITY - Category 1B

Code : 00445360

Date of issue/Date of revision

: 20 March 2024

SIGMARINE 28 GREY

## SECTION 16: Other information

Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 1	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

### History

**Date of issue/ Date of revision** : 20 March 2024

**Date of previous issue** : 26 October 2023

**Prepared by** : EHS

**Version** : 2.04

### Disclaimer

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*