

SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision 25 March 2024

Version 1.02

Section 1. Identification

Product name : AquataPoxy A-61 (B-Side)

Product code : 00464343

Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications, Professional applications, Used by spraying.

Use of the substance/
mixture : Coating.

Uses advised against : Not applicable.

Supplier : PPG Architectural Coatings Canada, Inc.
1550, rue Ampère, bureau 500
Boucherville (Québec) J4B 7L4
Canada
+1 450-655-3121

PPG Industries, Inc.
One PPG Place
Pittsburgh, PA 15272

Emergency telephone number : (412) 434-4515 (U.S.)
(514) 645-1320 (Canada)
SETIQ Interior de la República: 800-00-214-00 (México)
SETIQ Ciudad de México: (55) 5559-1588 (México)

Technical Phone Number : 888-977-4762

Section 2. Hazard identification

Classification of the substance or mixture : ACUTE TOXICITY (oral) - Category 4
ACUTE TOXICITY (dermal) - Category 4
SKIN CORROSION - Category 1A
SERIOUS EYE DAMAGE - Category 1
RESPIRATORY SENSITIZATION - Category 1A
SKIN SENSITIZATION - Category 1
TOXIC TO REPRODUCTION - Category 1

GHS label elements

Hazard pictograms :



Section 2. Hazard identification

Signal word : Danger

Hazard statements : Harmful if swallowed or in contact with skin.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May damage fertility or the unborn child.

Precautionary statements

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Wear respiratory protection. Avoid breathing vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Response : IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. If experiencing respiratory symptoms: Call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage : Store locked up.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements : Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Emits toxic fumes when heated. Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 45.7% (oral), 49.1% (dermal), 89.9% (inhalation)

Section 3. Composition/information on ingredients

Substance/mixture : Mixture
Product name : AquataPoxy A-61 (B-Side)
Other means of identification : Not available.

CAS number/other identifiers

| Ingredient name | Synonyms | % (w/w) | CAS number |
|--------------------------------|---|---------|------------|
| 1,3-Cyclohexanedimethanamine | 1,3-bis(aminomethyl)cyclohexane; cyclohexane-1,3-diyl dimethanamine; Cyclohexane, 1,3-bis(aminomethyl)-; Cyclohexane-1,3-diylbis(methylamine); CYCLOHEXANE, 1,3-BIS(AMINOETHYL)-; Cyclohexane-1,3-diylbis (methylamine); 1-[3-(aminomethyl)cyclohexyl] methanamine | 15 - 40 | 2579-20-6 |
| reaction product: bisphenol-A- | epoxy resin; 4,4'-Isopropylidenediphenol, | 7 - 13* | 25068-38-6 |

Section 3. Composition/information on ingredients

| | | | |
|---------------------------------------|---|------------|------------|
| (epichlorhydrin); epoxy resin | oligomeric reaction products with 1-chloro-2,3-epoxypropane; Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane; Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane; phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane; oxirane, (chloromethyl)-, polymer with 4,4'-(1-methylethylidene)bis[phenol]; Bisphenol A, epichlorhydrin polymer; Epichlorhydrin, bisphenol A resin; poly{(4,4'-propane-2,2-diylidiphenol)-co-[2-(chloromethyl)oxirane]}; BADGE; DGEbPA; diglycidyl ether of bisphenol A; bisphenol A diglycidyl ether resin; (bisphenol A)-epichlorhydrin copolymer; poly[4,4'-(1-methylethylidene)bisphenol-co-(chloromethyl)oxirane] | | |
| Mica-group minerals | Mica group minerals; Dimonite; mica; Micatex; Minerals, mica group; Silicate, mica; Silicates (less than 1 % crystalline silica) Mica; Silicates, Mica; Zimwaldite; Roscoelite; Phlogopite | 5 - 10* | 12001-26-2 |
| 2,4,6-tris(dimethylaminomethyl)phenol | Phenol, 2,4,6-tris[(dimethylamino)methyl]-; Phenol, 2,4,6-tris(dimethylaminomethyl)-; 2,4,6-tris((dimethylamino)methyl)phenol; Phenol, 2,4,6-tris{(dimethylamino)methyl}-; 2,4,6-Tris[(dimethylamino)methyl]phenol; 2,4,6-Tri(dimethylaminomethyl)phenol; 2,4,6-Tris(N,N-dimethylaminomethyl)phenol; 2,4,6-Tridimethylaminomethylphenol; TRIS (2,4,6-DIMETHYLAMINOMONOMETHYL)PHENOL; TRIS (2,4,6-DIMETHYLAMINOMETHYL)PHENOL; TRIS[(DIMETHYLAMINO)METHYL]PHENOL, 2,4,6- | 1 - 5* | 90-72-2 |
| glycerol | 1,2,3-Propanetriol; glycerin; Glycerin (mist); Trihydroxypropane; Glycyl alcohol; Glycerin anhydrous; Glycerin mist; glycerol, crude; glycerine, crude; glycerine; E 422; glycerin; propane-1,2,3-triol | 1 - 5* | 56-81-5 |
| Epoxy resin (MW ≤ 700) | reaction product : bisphenol a-(epichlorhydrin) ; epoxy resin (number average molecular weight <= 700) | 0.5 - 1.5* | 25068-38-6 |
| hexahydro-4-methylphthalic anhydride | 1,3-Isobenzofurandione, hexahydro-5-methyl-; 5-Methylhexahydro-1,3-isobenzofurandione; Methylhexahydrophthalic anhydride; 4-Methylcyclohexane-1,2-dicarboxylic | 0.1 - 1* | 19438-60-9 |

Section 3. Composition/information on ingredients

| | | | |
|----------------------------|---|----------|---------|
| tetrahydro-2-furylmethanol | <p>acid anhydride; Hexahydro-5-methyl-1,3-isobenzofurandione; MHHPA; Hexahydromethylphthalic anhydride; 5-Methylhexahydrophthalic anhydride; 3-Methyl-8-oxabicyclo[4.3.0]nonane-7,9-dione; Methyl-hexahydrophthalic acid anhydride; 4-methylcyclohexane-1,2-dicarboxylic anhydride</p> <p>tetrahydro-2-furyl-methanol; tetrahydrofurfuryl alcohol; 2-Furanmethanol, tetrahydro-; 2-TETRAHYDROFURANMETHANOL; 2-(HYDROXYMETHYL) TETRAHYDROFURAN; Tetrahydro-2-furanylmethanol; THFA; Tetrahydro-2-furancarbinol; Tetrahydro-2-furanmethanol; FURFURYL ALCOHOL, TETRAHYDRO-; 2-Hydroxymethyl oxolane</p> | 0.1 - 1* | 97-99-4 |
|----------------------------|---|----------|---------|

*Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Skin contact** : Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
- Ingestion** : Harmful if swallowed.

Section 4. First-aid measures

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
wheezing and breathing difficulties
asthma
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
stomach pains
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

Specific hazards arising from the chemical : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
halogenated compounds

Section 5. Fire-fighting measures

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Section 7. Handling and storage

- Special precautions** : Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|--|---|
| 1,3-Cyclohexanedimethanamine reaction product: bisphenol-A-(epichlorhydrin); epoxy resin Mica-group minerals | None. None. CA Alberta Provincial (Canada, 6/2018). OEL: 3 mg/m ³ 8 hours. Form: Respirable CA British Columbia Provincial (Canada, 6/2022). TWA: 3 mg/m ³ 8 hours. Form: Respirable CA Quebec Provincial (Canada, 6/2022). TWAEV: 3 mg/m ³ 8 hours. Form: Respirable dust. CA Ontario Provincial (Canada, 6/2019). TWA: 3 mg/m ³ 8 hours. Form: Respirable particulate matter. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 6 mg/m ³ 15 minutes. Form: respirable fraction TWA: 3 mg/m ³ 8 hours. Form: respirable fraction |
| 2,4,6-tris(dimethylaminomethyl)phenol glycerol | None. CA Alberta Provincial (Canada, 6/2018). Skin sensitizer. OEL: 10 mg/m ³ 8 hours. Form: Mist CA Quebec Provincial (Canada, 6/2022). TWAEV: 10 mg/m ³ 8 hours. Form: mist CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 mg/m ³ 15 minutes. Form: mist TWA: 10 mg/m ³ 8 hours. Form: mist CA British Columbia Provincial (Canada, |

Section 8. Exposure controls/personal protection

6/2022).

TWA: 3 mg/m³ 8 hours. Form: respirable mistTWA: 10 mg/m³ 8 hours. Form: total mist

None.

None.

None.

Epoxy resin (MW ≤ 700)
hexahydro-4-methylphthalic anhydride
tetrahydro-2-furylmethanol

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles and face shield.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves : nitrile neoprene

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Use an air-fed respirator unless a site-specific assessment determines that an air-fed respirator is not necessary, in which case the results of the risk assessment should be utilized to determine whether respiratory protection is necessary and what type of protection is appropriate. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

| | |
|--|-----------------------------|
| Physical state | : Liquid. |
| Color | : Emerald green. |
| Odor | : Faint odor. |
| Odor threshold | : Not available. |
| pH | : Not applicable. |
| Melting point | : Not available. |
| Boiling point | : >37.78°C (>100°F) |
| Flash point | : Closed cup: 100°C (212°F) |
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Not available. |
| Flammability | : Not available. |
| Lower and upper explosive (flammable) limits | : Not available. |
| Evaporation rate | : Not available. |
| Vapor pressure | : Not available. |
| Vapor density | : Not available. |
| Relative density | : 1.4 |
| Density (lbs / gal) | : 11.68 |

| Media | Result |
|--------------|-------------|
| ☑ Cold water | Not soluble |

| | |
|--|--|
| Partition coefficient: n-octanol/water | : Not applicable. |
| Viscosity | : Kinematic (40°C (104°F)): >21 mm ² /s (>21 cSt) |
| Volatility | : 0% (v/v), 0.128% (w/w) |
| % Solid. (w/w) | : 99.872 |

Section 10. Stability and reactivity

| | |
|------------------------------------|---|
| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8. |
| Incompatible materials | : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids. |
| Hazardous decomposition products | : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|-----------------------|---------|-------------------------|----------|
| 1,3-Cyclohexanedimethanamine reaction product: bisphenol-A-(epichlorhydrin); epoxy resin | LD50 Dermal | Rabbit | 1700 mg/kg | - |
| | LD50 Oral | Rat | 700 mg/kg | - |
| | LD50 Dermal | Rabbit | >2 g/kg | - |
| 2,4,6-tris (dimethylaminomethyl) phenol | LD50 Oral | Rat | >2 g/kg | - |
| | LD50 Dermal | Rabbit | 1.28 g/kg | - |
| glycerol | LD50 Dermal | Rat | 1280 mg/kg | - |
| | LD50 Oral | Rat | 1200 mg/kg | - |
| | LD50 Oral | Rat | 12600 mg/kg | - |
| Epoxy resin (MW ≤ 700) | LD50 Dermal | Rabbit | >2 g/kg | - |
| | LD50 Oral | Rat | >2 g/kg | - |
| hexahydro-4-methylphthalic anhydride | LD50 Oral | Rat | 4.428 g/kg | - |
| | LD50 Oral | Rat | 4.428 g/kg | - |
| tetrahydro-2-furylmethanol | LC50 Inhalation Vapor | Rat | 19630 mg/m ³ | 4 hours |
| | LD50 Dermal | Rabbit | 1.22 g/kg | - |
| | LD50 Oral | Rat | 1600 mg/kg | - |

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|---|--------------------------|---------|-------|-----------------|-------------|
| Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin | Eyes - Mild irritant | Rabbit | - | 100 mg | - |
| | Eyes - Moderate irritant | Rabbit | - | - | - |
| | Skin - Moderate irritant | Rabbit | - | - | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 500 UI | - |
| 2,4,6-tris (dimethylaminomethyl)phenol Epoxy resin (MW ≤ 700) | Skin - Severe irritant | Rabbit | - | 24 hours 2 mg | - |
| | Skin - Visible necrosis | Rabbit | - | 4 hours | 7 days |
| | Eyes - Mild irritant | Rabbit | - | - | - |
| | Skin - Mild irritant | Rabbit | - | - | - |

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitization

| Product/ingredient name | Route of exposure | Species | Result |
|---|-------------------|---------|-------------|
| Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin Epoxy resin (MW ≤ 700) | skin | Mouse | Sensitizing |
| | skin | Mouse | Sensitizing |

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Section 11. Toxicological information

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Target organs

: Contains material which may cause damage to the following organs: kidneys, lungs, mucous membranes, upper respiratory tract, skin, eyes.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

Eye contact

: Causes serious eye damage.

Inhalation

: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin contact

: Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.

Ingestion

: Harmful if swallowed.

Over-exposure signs/symptoms

Eye contact

: Adverse symptoms may include the following:
pain
watering
redness

Inhalation

: Adverse symptoms may include the following:
wheezing and breathing difficulties
asthma
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact

: Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
reduced fetal weight
increase in fetal deaths
skeletal malformations

Section 11. Toxicological information

Ingestion : Adverse symptoms may include the following:
stomach pains
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary : There are no data available on the mixture itself. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

Potential immediate effects : There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Long term exposure

Potential immediate effects : There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : May damage fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

| Product/ingredient name | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|---|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| AquataPoxy A-61 (B-Side) | 992.9 | 1859.1 | N/A | N/A | N/A |
| 1,3-Cyclohexanedimethanamine | 700 | 1700 | N/A | N/A | N/A |
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin | 2500 | 2500 | N/A | N/A | N/A |
| 2,4,6-tris(dimethylaminomethyl)phenol | 1200 | 1280 | N/A | N/A | N/A |
| glycerol | 12600 | N/A | N/A | N/A | N/A |
| Epoxy resin (MW ≤ 700) | 2500 | 2500 | N/A | N/A | N/A |
| hexahydro-4-methylphthalic anhydride | 4428 | N/A | N/A | N/A | N/A |

Section 11. Toxicological information

| | | | | | |
|----------------------------|------|------|-----|-------|-----|
| tetrahydro-2-furylmethanol | 1600 | 1220 | N/A | 19.63 | N/A |
|----------------------------|------|------|-----|-------|-----|

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|---|--|--------------------------------------|---------------------|
| 1,3-Cyclohexanedimethanamine reaction product: bisphenol- A-(epichlorhydrin); epoxy resin 2,4,6-tris (dimethylaminomethyl)phenol Epoxy resin (MW ≤ 700) | LC50 130 mg/l Chronic NOEC 0.3 mg/l | Fish - <i>golden orfe</i> Daphnia | 96 hours 21 days |
| | Acute LC50 175 mg/l | Fish | 96 hours |
| | Acute LC50 1.8 mg/l Chronic NOEC 0.3 mg/l | Daphnia Daphnia | 48 hours 21 days |

Persistence and degradability

| Product/ingredient name | Test | Result | Dose | Inoculum |
|--|-----------|---------------|------|----------|
| Reaction product: bisphenol- A-(epichlorhydrin); epoxy resin Epoxy resin (MW ≤ 700) | OECD 301F | 5 % - 28 days | - | - |
| | OECD 301F | 5 % - 28 days | - | - |

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|--|-------------------|------------|------------------|
| Reaction product: bisphenol- A-(epichlorhydrin); epoxy resin Epoxy resin (MW ≤ 700) | - | - | Not readily |
| | - | - | Not readily |

Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|--|--------------------|-----|-----------|
| 1,3-Cyclohexanedimethanamine reaction product: bisphenol- A-(epichlorhydrin); epoxy resin | 0.783 | - | Low |
| | 2.64 to 3.78 | 31 | Low |
| 2,4,6-tris (dimethylaminomethyl)phenol | 0.219 | - | Low |
| glycerol | -1.76 | - | Low |
| Epoxy resin (MW ≤ 700) | 3 | 31 | Low |
| hexahydro-4-methylphthalic anhydride | 2.09 | - | Low |

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Section 14. Transport information

| | TDG | IMDG | IATA |
|-----------------------------|---|---|---|
| UN number | UN1760 | UN1760 | UN1760 |
| UN proper shipping name | CORROSIVE LIQUID, N.O.S. (1,3-Cyclohexanedimethanamine, 2,4,6-tris(dimethylaminomethyl)phenol) | CORROSIVE LIQUID, N.O.S. (1,3-Cyclohexanedimethanamine, 2,4,6-tris(dimethylaminomethyl)phenol) | CORROSIVE LIQUID, N.O.S. (1,3-Cyclohexanedimethanamine, 2,4,6-tris(dimethylaminomethyl)phenol) |
| Transport hazard class(es) | 8 | 8 | 8 |
| Packing group | II | II | II |
| Environmental hazards | No. | No. | No. |
| Marine pollutant substances | Not applicable. | Not applicable. | Not applicable. |

Additional information

TDG : None identified.

IMDG : None identified.

IATA : None identified.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not applicable.

Proof of classification statement : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.40-2.42 (Class 8).

Section 15. Regulatory information

[National Inventory List](#)

Canada inventory (DSL) : At least one component is not listed.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 3 * Flammability : 1 Physical hazards : 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health : 3 Flammability : 1 Instability : 0

Date of issue/Date of revision 25 March 2024

Organization that prepared the SDS : EHS

Key to abbreviations

: ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
SGG = Segregation Group
UN = United Nations

✔ Indicates information that has changed from previously issued version.

[Disclaimer](#)

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.