SAFETY DATA SHEET



Date of issue 4/10/2024 (month/day/year)

Version 1

Section 1. Chemical product and company identification

Α.	Product name	PSX 700 BAS	E RAL 7030
	Product code	00477299	

B. Relevant identified uses of the substance or mixture and uses advised against

Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
C. Supplier's or Importer's information	: PPG SSC (680-090) 19, Yeocheon-ro 217beon-gil, Nam-gu, Ulsan, Korea Tel: +82-52-210-8222
Email Address	Korea.MSDS@PPG.COM
Emergency telephone number:	: +82-52-210-8331

Section 2. Hazards identification

A. Hazard classification : SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 3 This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

B. GHS label elements, including precautionary statements

Symbol



Signal word	1	Warning
Hazard statements	:	H317 - May cause an allergic skin reaction. H351 - Suspected of causing cancer. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	 P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves, protective clothing and eye or face protection. P273 - Avoid release to the environment. P261 - Avoid breathing vapor.

Korea (GHS) Page: 1/12

Product name PSX 700 BASE RAL 7030

Section	2. Hazard	Is identification
---------	-----------	-------------------

Response	:	 P308 + P313 - IF exposed or concerned: Get medical advice or attention. P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.
Storage	1	Not applicable.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
C. Other hazards which do not result in	:	None known.

classification

Section 3. Composition/information on ingredients

CAS number/other identifiers

CAS number : Not applicable.

Chemical name	Common name	Identifiers	%
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	cyclohexanol, 4,4'-(1-methylethylidene) bis-, polymer with (chloromethyl)oxirane	CAS: 30583-72-3	20 - <30
titanium dioxide bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	TITANIUM DIOXIDE BIS(PENTAMETHYLPIPERIDYL) SEBACATE	CAS: 13463-67-7 CAS: 41556-26-7	10 -<20 1 - <5
iron hydroxide oxide yellow carbon black methyl 1,2,2,6,6-pentamethyl-4-piperidyl	IRON HYDROXIDE OXIDE CARBON BLACK METHYL-(1,2,2,6,6-PENTAMETHYL-	CAS: 51274-00-1 CAS: 1333-86-4 CAS: 82919-37-7	1 - <5 0.1 - <1 0.1 - <1
sebacate methyl alcohol	4-PIPERDIYL) SEBACATE METHYL ALCOHOL	CAS: 67-56-1	0.1 - <1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Α.	Eye contact	:	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
В.	Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
C.	Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
D.	Ingestion	:	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Section 4. First aid measures

E. Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed The exposed person may need to be kept under medical surveillance for 48 hours.	i.
Specific treatments	: No specific treatment.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	-

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Α.	Extinguishing media		
	Suitable extinguishing media	1	Use an extinguishing agent suitable for the surrounding fire.
	Unsuitable extinguishing media	-	None known.
В.	Specific hazards arising from the chemical	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
	Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides
C.	Special equipment for fire-fighting	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
	Fire-fighting procedures	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Section 6. Accidental release measures

 A. Personal precautions, protective equipment and emergency procedures
 No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
 B. Environmental precautions
 Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

C. Methods and materials for containment and cleaning up

Section 6. Accidental release measures

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

	get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist.
--	---

B. Conditions for safe storage, including any incompatibilities
 Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

A. Occupational exposure limits

Ingredient name	Exposure limits
titanium dioxide	Ministry of Employment and Labor
	(Republic of Korea, 1/2020).
	TWA: 10 mg/m ³ 8 hours. Form: total dust
	with less than 1% of free SiO2
iron hydroxide oxide yellow	Ministry of Employment and Labor
	(Republic of Korea, 1/2020). [Iron oxide
	(Fume, as Fe)]
	TWA: 5 mg/m³, (as Fe) 8 hours. Form:
	Fume
	Ministry of Employment and Labor
	(Republic of Korea, 1/2020). [Iron oxide
	as Fe]
	TWA: 5 mg/m³, (as Fe) 8 hours.
carbon black	Ministry of Employment and Labor
	Korea (GHS) Page: 4/12

Product name PSX 700 BASE RAL 7030

Section 8. Exposure controls/personal protection

	methyl alcohol			(Republic of Korea, 1/2020). TWA: 3.5 mg/m ³ 8 hours. Form: inhalable fraction Ministry of Employment and Labor (Republic of Korea, 1/2020). Absorbed through skin. STEL: 250 ppm 15 minutes. TWA: 200 ppm 8 hours.	
	Recommended monitoring procedures	:	Reference should be made to appropria national guidance documents for metho substances will also be required.	•	
В.	Appropriate engineering controls	:	f user operations generate dust, fumes, gas, vapor or mist, use process enclosures, ocal exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.		
	Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		
C.	Personal protective equip	m	ent		

С.

Respiratory protection	 Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Safety glasses with side shields.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: butyl rubber
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Product code 00477299

Product name PSX 700 BASE RAL 7030

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

А.	Appearance		
	Physical state		Liquid.
	Color	÷	Not available.
В.	Odor	÷	
С.	Odor threshold	4	Not available.
D.	рН	4	Not applicable.
Ε.	Melting/freezing point	1	Not available.
F.	Boiling point/boiling range	:	>37.78°C (>100°F)
G.	Flash point	1	Closed cup: Not applicable.
Н.	Evaporation rate	:	Not available.
Т.	Flammability (solid, gas)	:	Not available.
J.	Lower and upper explosive (flammable) limits	:	Not available.
К.	Vapor pressure	1	Not available.
L.	Solubility(ies)	:	Media Result
			cold water Not soluble
	Solubility in water	:	Not available.
М.	Vapor density	:	Not available.
N.	Relative density	1	1.43
Ю. О.	Partition coefficient: n- octanol/water	:	Not applicable.
Ρ.	Auto-ignition temperature	:	Not available.
	-		
Q.	Decomposition temperature	:	Not available.
			Not available. Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)
Q. R.	temperature	:	

Section 10. Stability and reactivity

Α.	Chemical stability	:	The product is stable.
	Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
В.	Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products.
C .	Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
			Korea (GHS) Page: 6/12

Section 10. Stability and reactivity

 D. Hazardous decomposition products
 Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides

Section 11. Toxicological information

A. Information on the likely : Not available. routes of exposure

Potential acute health effects

Inhalation	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Eye contact	: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Inhalation	: No specific data.
Ingestion	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Eye contact	: No specific data.

B. Health hazards

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	LD50 Oral	Rat	3.125 g/kg	-
iron hydroxide oxide yellow	LC50 Inhalation Dusts and mists	Rat	>5.05 mg/l	4 hours
	LD50 Oral	Rat	>10 g/kg	-
carbon black	LD50 Oral	Rat	>10 g/kg	-
methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	LD50 Oral	Rat	3.125 g/kg	-
methyl alcohol	LC50 Inhalation Vapor	Rat	64000 ppm	4 hours
	LD50 Dermal	Rabbit	15800 mg/kg	-
	LD50 Oral	Rat	5600 mg/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.

Sensitization

Korea (Gł	<mark>-IS)</mark> Pa	ge: 7/12
-----------	----------------------	----------

Section 11. Toxicological information

Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Mutagenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
.	
Carcinogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Denne du stine terrisite	
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Teratogenicity	
	. There are no data available on the winter its off
Conclusion/Summary	: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name	Classification	Route of exposure	Target organs
methyl alcohol	Category 1	-	-

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Potential chronic health effects

General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Additional information

Sanding and grinding dusts may be harmful if inhaled. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness.

Product name PSX 700 BASE RAL 7030

Section 11. Toxicological information

Chemical name	Identifiers	GHS Classification
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	CAS: 30583-72-3	SKIN SENSITIZATION - Category 1B
		AQUATIC HAZARD (LONG-TERM) - Category 3
titanium dioxide	CAS: 13463-67-7	CARCINOGENICITY - Category 2
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	CAS: 41556-26-7	SKIN SENSITIZATION - Category 1B
		TOXIC TO REPRODUCTION - Category 2 AQUATIC HAZARD (ACUTE) - Category 1
iron hydroxide oxide yellow	CAS: 51274-00-1	AQUATIC HAZARD (LONG-TERM) - Category 1 Not classified.
carbon black	CAS: 1333-86-4	CARCINOGENICITY - Category 2
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	CAS: 82919-37-7	SKIN SENSITIZATION - Category 1B
		TOXIC TO REPRODUCTION - Category 2
		AQUATIC HAZARD (ACUTE) - Category 1
		AQUATIC HAZARD (LONG-TERM) - Category 1
methyl alcohol	CAS: 67-56-1	FLAMMABLE LIQUIDS - Category 2
-		ACUTE TOXICITY (oral) - Category 3
		ACUTE TOXICITY (dermal) - Category 3
		ACUTE TOXICITY (inhalation) - Category 3
		SPECIFIC TARGET ORGAN TOXICITY (SINGLE
		EXPOSURE) - Category 1
		AQUATIC HAZARD (LONG-TERM) - Category 3

Section 12. Ecological information

A. Ecotoxicity

Product/ingredient name	Result	Species	Exposure
4,4'- Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane	LC50 11.5 mg/l	Fish	96 hours
titanium dioxide iron hydroxide oxide yellow methyl alcohol	Acute LC50 >100 mg/l Fresh water Acute LC50 >100000 mg/l Acute LC50 13 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> Fish Fish	48 hours 96 hours 96 hours

B. Persistence and degradability

Not available.

C. Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
methyl alcohol	-0.77	-	Low

D. Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Korea (GHS) Page: 9/12

Product code 00477299 Product name PSX 700 BASE RAL 7030 Date of issue 4/10/2024 (month/day/year)

Version 1

Section 12. Ecological information

E. <u>Other adverse effects</u> : No known significant effects or critical hazards.

Section 13. Disposal considerations

- A. Disposal methods
 The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- B. Disposal precautions
 This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	IATA
A. UN number	Not regulated.	Not regulated.	Not regulated.
B. UN proper shipping name	-	-	-
C. Transport hazard class(es)	-	-	-
D. Packing group	-	-	-
Environmental hazards	No.	No.	No.
E. Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

- UN : None identified.
- IMDG : None identified.
- IATA : None identified.

F. Special precaution which a user to be aware of or needs to comply with in connection with transport or transportation

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Product code 00477299

Product name PSX 700 BASE RAL 7030

Version 1

Section 15. Regulatory information

Α.	Regulation according to I	SH	<u>A</u>			
	ISHA article 117 (Harmful substances prohibited from manufacture)	:	None of the components are listed.			
	ISHA article 118 (Harmful substances requiring permission)	:	None of the components are listed.			
	Article 2 of Youth Protection Act on Substances Hazardous to Youth	:	It is not allowed to sell to persons under the age of 19.			
	Exposure Limits of Chemical Substances and Physical Factors					
	The following components titanium dioxide iron hydroxide oxide yellow carbon black methyl alcohol		ave an OEL:			
	ISHA Enforcement Regs Annex 19 (Exposure standards established for harmful factors)	:	The following components are listed: methanol			
	ISHA Enforcement Regs Annex 21 (Harmful factors subject to Work Environment Measurement)	:	The following components are listed: titanium dioxide, iron oxide			
	ISHA Enforcement Regs Annex 22 (Harmful Factors Subject to Special Health Check- up)	:	The following components are listed: Iron oxide (dust, fume)			
	Standard of Industrial Safety and Health Annex 12 (Hazardous substances subject to control)	:	The following components are listed: titanium dioxide, iron and its compounds			
В.	Regulation according to (Che	emicals Control Act			
	Article 11 (TRI)	:	The following components are listed: Barium and its compounds			
	Article 18 Prohibited (K- Reach Article 27)	1	None of the components are listed.			
	Article 19 Subject to authorization (K-Reach Article 25)	-	None of the components are listed.			
	Article 20 Restricted (K- Reach Article 27)	1	None of the components are listed.			
	Article 20 Toxic Chemicals (K-Reach Article 20)	:	Not applicable			

Product code 00477299

Date of issue 4/10/2024 (month/day/year)

Product name PSX 700 BASE RAL 7030

Section 15. Regulatory information

	Korea inventory	All components are listed or exempted.	
	Article 39 (Accident Precaution Chemicals)	None of the components are listed.	
C.	Dangerous Materials Safety Management Act	Not applicable.	
D.	Wastes regulation	Dispose of contents and container in accordance with all local, regional, natio and international regulations.	nal
Ε.	Regulation according to e	<u>r foreign laws</u>	

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

Section 16. Other information

A. References	 Korean Ministry of Environment; Chemical Control Act Korean Ministry of Labor; Industrial Safety and Health Act NIER Notice Registry of Toxic Effects of Chemical Substances (RTECS) U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information Retrieval) ECOTOX Database System.
B. Date of issue/Date of revision	: 4/10/2024
C. Version	: 1
Prepared by	: EHS

D. Other

✓ Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.