## **SAFETY DATA SHEET**



### Conforms to Official Mexican Standard NOM-018-STPS-2015

Date of revision 11 April 2024

Version 7

Date of issue 11 April 2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product name	: PITT-TECH PLUS EP DTM ACRYLIC SATIN MIDTONE BASE
Product code	: 00445826
Other means of identification	: Not applicable.
Product type	: Liquid.
Relevant identified uses o	f the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	Not applicable.
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272
<u>Emergency telephone</u> <u>number</u>	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)
Technical Phone Number	: 888-977-4762

## **SECTION 2: Hazards identification**

Classification of the substance or mixture	: CARCINOGENICITY - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 25.1% (oral), 25.1% (dermal), 26.6% (inhalation)
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: H351 - Suspected of causing cancer.
Precautionary statements	

## **SECTION 2: Hazards identification**

Prevention	:	<ul> <li>P201 - Obtain special instructions before use.</li> <li>P202 - Do not handle until all safety precautions have been read and understood.</li> <li>P280 - Wear protective gloves, protective clothing and eye or face protection.</li> </ul>
Response	1	P308 + P313 - IF exposed or concerned: Get medical advice or attention.
Storage	1	P405 - Store locked up.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	:	Contains isothiazolinones. May cause allergic reaction. Emits toxic fumes when heated.
Supplemental label elements (First aid measures):		Photosensitive agents : In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact. In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact.
See toxicological information (Section 11)		

**SECTION 3: Composition/information on ingredients** 

Substance/mixture Product name		Mixture PITT-TECH PLUS EP DTM ACRYLIC SATIN MIDTONE BASE
Other means of identification	:	Not applicable.

Ingredient name	%	CAS number
		13463-67-7 112-34-5 119-61-9

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## **SECTION 4: First aid measures**

#### Description of necessary first aid measures

Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact.</li> </ul>
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

### Product name PITT-TECH PLUS EP DTM ACRYLIC SATIN MIDTONE BASE

## **SECTION 4: First aid measures**

	In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact.		
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.		
Most important symptoms/effects, acute and delayed			
Potential acute health	<u>effects</u>		
Eye contact	: No known significant effects or critical hazards.		
Inhalation	: No known significant effects or critical hazards.		
Skin contact	: No known significant effects or critical hazards.		

**Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

See toxicological information (Section 11)

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

## **SECTION 5: Firefighting measures**

mode.

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

Version 7

## Product name PITT-TECH PLUS EP DTM ACRYLIC SATIN MIDTONE BASE

## **SECTION 6: Accidental release measures**

Personal precautions, protect	ve equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	tainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## **SECTION 7: Handling and storage**

Precautions for safe handling	
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## **SECTION 7: Handling and storage**

Conditions for safe storage,	1	Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in
including any		accordance with local regulations. Store in original container protected from direct
incompatibilities		sunlight in a dry, cool and well-ventilated area, away from incompatible materials
		(see Section 10) and food and drink. Store locked up. Keep container tightly closed
		and sealed until ready for use. Containers that have been opened must be carefully
		resealed and kept upright to prevent leakage. Do not store in unlabeled containers.
		Use appropriate containment to avoid environmental contamination.

## **SECTION 8: Exposure controls/personal protection**

#### Control parameters

Occupational exposure limit	<u>ts</u>			
Ingredient name			Exposure limits	
Manium dioxide 2-(2-butoxyethoxy)ethanol benzophenone			NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 10 mg/m <sup>3</sup> 8 hours. ACGIH TLV (United States, 1/2023). TWA: 10 ppm 8 hours. Form: Inhalable fraction and vapor None.	
		Key to abbreviations		
C = Ceiling Limit IPEL = Internal Permissible Exp	osur	STEL	= Threshold Limit Value	
Consult local authorities fo	r ac	ceptable exposure limits.		
Recommended monitoring procedures	:		opriate monitoring standards. Reference to ethods for the determination of hazardous	
Appropriate engineering controls	:		mes, gas, vapor or mist, use process enclosures gineering controls to keep worker exposure to commended or statutory limits.	
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		
Individual protection measur	res			
Hygiene measures		eating, smoking and using the lavat Appropriate techniques should be u	proughly after handling chemical products, before ory and at the end of the working period. sed to remove potentially contaminated clothing reusing. Ensure that eyewash stations and kstation location.	
Eye/face protection	:	Safety glasses with side shields.		
Skin protection Hand protection	:	be worn at all times when handling of this is necessary. Considering the p check during use that the gloves are should be noted that the time to bre different for different glove manufac several substances, the protection t	ves complying with an approved standard should chemical products if a risk assessment indicates parameters specified by the glove manufacturer, e still retaining their protective properties. It akthrough for any glove material may be sturers. In the case of mixtures, consisting of time of the gloves cannot be accurately	
Gloves	ι.	estimated. polyethylene		
	<u> </u>		Mexico Page: 5/1	

### Product name PITT-TECH PLUS EP DTM ACRYLIC SATIN MIDTONE BASE

## **SECTION 8: Exposure controls/personal protection**

Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

## **SECTION 9: Physical and chemical properties**

<u>Appearance</u>			
Physical state	:	Liquid.	
Color	:	White.	
Odor	:	Characteristic.	
Odor threshold	:	Not available.	
Molecular weight	÷	Not applicable.	
рН	÷	Not available.	
Melting point		Not available.	
Boiling point	1	>37.78°C (>100°F)	
Flash point	4	Closed cup: 95°C (203°F)	
Auto-ignition temperature	:	Not available.	
Decomposition temperature		Not available.	
Flammability	÷	Not available.	
Lower and upper explosive	÷	Not available.	
(flammable) limits Evaporation rate		Not available.	
Vapor pressure		Not available.	
Vapor density		Not available. 1.18	
Relative density		-	
Density(lbs / gal)	÷	9.85	
Solubility(ies)	:	Media	Result
oorability(les)	Ċ	cold water	Partially soluble
Solubility in water	:	Not available.	
Partition coefficient: n- octanol/water	1	Not applicable.	
Viscosity	:	Kinematic (40°C (104°F)):	>21 mm²/s (>21 cSt)
Volatility	÷	62% (v/v), 52.108% (w/w)	
% Solid. (w/w)	1	47.892	

## **SECTION 10: Stability and reactivity**

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous	: Under normal conditions of storage and use, hazardous reactions will not occur.
reactions	
Conditions to avoid	<ul> <li>When exposed to high temperatures may produce hazardous decomposition products.</li> </ul>
	Refer to protective measures listed in sections 7 and 8.
Incompatible materials	<ul> <li>Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.</li> </ul>
Hazardous decomposition	: Depending on conditions, decomposition products may include the following materials
products	carbon oxides metal oxide/oxides

## **SECTION 11: Toxicological information**

### Information on toxicological effects

Acute toxicity

Product/ingredient name	Result		Species	Dose	Exposure
titanium dioxide	LC50 Inha	lation Dusts and m	nists Rat	>6.82 mg/l	4 hours
	LD50 Dern	nal	Rabbit	>5000 mg/kg	-
	LD50 Oral		Rat	>5000 mg/kg	-
2-(2-butoxyethoxy)ethanol	LD50 Dern	nal	Rabbit	2700 mg/kg	-
	LD50 Oral		Rat	4500 mg/kg	-
benzophenone	LD50 Dern LD50 Oral	nal	Rabbit	3.535 g/kg	-
	LD50 Oral		Rat	>10 g/kg	-
Conclusion/Summary	: There a	re no data availabl	e on the mixture i	tself.	
rritation/Corrosion					
Conclusion/Summary					
Skin	: There a	re no data availabl	e on the mixture i	tself.	
Eyes	: There a	re no data availabl	e on the mixture i	tself.	
Respiratory	: There a	re no data availabl	e on the mixture i	tself.	
Sensitization					
Conclusion/Summary					
Skin	: There a	<sup>r</sup> e no data availabl	e on the mixture i	tself.	
Respiratory	: There a	re no data availabl	e on the mixture i	tself.	
<u>Mutagenicity</u>					
Conclusion/Summary	: There a	re no data availabl	e on the mixture i	tself.	
Carcinogenicity					
Conclusion/Summary	: There a	re no data availabl	e on the mixture i	tself.	
Classification					
Product/ingredient name	OSHA	IARC NTP			
titanium dioxide	-	2B -			
benzophenone	-	2B -			

### Product name PITT-TECH PLUS EP DTM ACRYLIC SATIN MIDTONE BASE

## **SECTION 11: Toxicological information**

Carcinogen Classification code: IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

#### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

#### **Teratogenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
benzophenone	Category 2	oral	kidneys, liver

Target organs

: Contains material which may cause damage to the following organs: blood, lungs, liver, upper respiratory tract, skin, central nervous system (CNS).

#### **Aspiration hazard**

Not available.

#### Information on the likely routes of exposure

#### Potential acute health effects

Fotential acute health enect	.5	
Eye contact	1	No known significant effects or critical hazards.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	1	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.
Over-exposure signs/sympt	om	<u>s</u>
Eye contact	:	No specific data.
Inhalation	1	No specific data.
Skin contact	1	No specific data.
Ingestion	:	No specific data.
Delayed and immediate effe	<u>cts</u>	and also chronic effects from short and long term exposure
Conclusion/Summary	:	There are no data available on the mixture itself. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure. The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion may cause nausea, weakness and central nervous system effects. If splashed in the eyes, the liquid may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation

Mexico Page: 8/11

## **SECTION 11: Toxicological information**

	dermal routes of exposure and eye contact.	
<u>Short term exposure</u>		
Potential immediate effects	e are no data available on the mixture itself.	
Potential delayed effects	e are no data available on the mixture itself.	
Long term exposure		
Potential immediate effects	e are no data available on the mixture itself.	
Potential delayed effects	re are no data available on the mixture itself.	
Potential chronic health effe		
General	known significant effects or critical hazards.	
Carcinogenicity	pected of causing cancer. Risk of cancer deper osure.	nds on duration and level of
Mutagenicity	known significant effects or critical hazards.	
Reproductive toxicity	known significant effects or critical hazards.	

#### Numerical measures of toxicity

#### Acute toxicity estimates

	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
TT-TECH PLUS EP DTM ACRYLIC SATIN	226432.3	135859.4	N/A	N/A	N/A
2-(2-butoxyethoxy)ethanol	4500	2700	N/A	N/A	N/A
benzophenone	N/A	3535	N/A	N/A	N/A

## **SECTION 12: Ecological information**

<u>Toxicity</u>			
Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
2-(2-butoxyethoxy)ethanol	1	-	Low
benzophenone	3.18	12.02	Low

#### Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

#### Other adverse effects

: No known significant effects or critical hazards.

Mexico Page: 9/11

#### Product name PITT-TECH PLUS EP DTM ACRYLIC SATIN MIDTONE BASE

## **SECTION 13: Disposal considerations**

 Disposal methods
 The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

## **SECTION 14: Transport information**

	Mexico Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

- Mexico : None identified.
- IMDG : None identified.
- IATA : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Version 7

#### Product name PITT-TECH PLUS EP DTM ACRYLIC SATIN MIDTONE BASE

## **SECTION 15: Regulatory information**

#### **Mexico**

#### Classification

Flammability : 1 Health : 2 Reactivity : 0

#### International regulations

Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

## **SECTION 16: Other information**

Hazardous Material Information System (U.S.A.)

Health : 2 \* Flammability : 1 Physical hazards : 0

(\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Date of previous issue	: 3/22/2024
Organization that prepared the SDS	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

#### Indicates information that has changed from previously issued version.

#### Notice to reader

The information, which is based on the current knowledge of the chemical substance or mixture and applies to appropriate safety precautions for the product, is deemed correct but is not exhaustive and will be used only as a guide.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.