SAFETY DATA SHEET

Date of issue/Date of revision 26 April 2024

Version3.02

Section 1. Identification

Product code	: 00250770
Product name	: SIGMAGUARD CSF 650 BASE REDBROWN
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses	of the substance or mixture and uses advised against
Product use	: Coating. Professional applications, Used by spraying.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
Supplier's details	: PT PPG Coatings Indonesia JI. Rawagelam III No.1 13930 Jakarta Indonesia Tel +62 21 4605710 PMC.Safety@PPG.com
Emergency telephone number	: CHEMTREC 001-803-017-9114 (CCN 17704)

Section 2. Hazards identification

Classification of the substance or mixture	: SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown hazards to the
	aquatic environment: 38.1%

GHS label elements, including precautionary statements

Hazard pictograms	
Signal word	: Warning
Hazard statements	: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
	Indonesia [;] Page: 1/12

Product name SIGMAGUARD CSF 650 BASE REDBROWN

Section 2. Hazards identification

Response	:	: Collect spillage. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advid or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists Get medical advice or attention.			
Storage	:	Not applicable.			
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.			
Other hazards which do not	:	None known.			

result in classification

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
-------------------	-----------

CAS number/other identifiers

CAS number	: Not applicable.
EC number	: Mixture.

Ingredient name	%	CAS number
s-[4-(2,3-epoxipropoxi)phenyl]propane	25- <50	1675-54-3
1,6-bis(2,3-epoxypropoxy)hexane	5- <10	16096-31-4
benzyl alcohol	5- <10	100-51-6
Talc , not containing asbestiform fibres	3- <5	14807-96-6

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SUB codes represent substances without registered CAS Numbers.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health	effects
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Indonesia

² Page: 2/12

Date of issue 26 April 2024

Version 3.02

Section 4. First aid measures

Over-exposure signs/symptoms				
Eye contact	Adverse symptoms may include the following: pain or irritation watering redness			
Inhalation	No specific data.			
Skin contact	Adverse symptoms may include the following: rritation edness			
Ingestion	No specific data.			
Indication of immediate med	attention and special treatment needed, if necessary			
Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.	Э		
Specific treatments	No specific treatment.			
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. may be dangerous to the person providing aid to give mouth-to-mouth resuscita Wash contaminated clothing thoroughly with water before removing it, or wear gloves.			

See toxicological information (Section 11)

Section 5. Fire-fighting measures

	-
Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal	precautions.	protective	equi	pment and	lemergenc	v procedures
<u>i oroonu</u>	productionio		oqui		<u>officiation</u>	F F F C C C C C C C C C C

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and materials for co	ont	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section

Section 7. Handling and storage

Precautions for safe handling		
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

13 for waste disposal.

Section 7. Handling and storage

Conditions for safe storage, :	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in
including any incompatibilities	accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials
	(see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name			Exposure limits	
			Minister of Labor of the Republic of Indonesia (Indonesia, 4/2018). TWA: 2 mg/m ³ 8 hours. Form: respirable particles	
Recommended monitoring procedures	:		riate monitoring standards. Reference to nods for the determination of hazardous	
Appropriate engineering controls	:	Good general ventilation should be su contaminants.	fficient to control worker exposure to airborne	
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		
Individual protection measu	<u>res</u>			
Hygiene measures	:	eating, smoking and using the lavator Appropriate techniques should be use Contaminated work clothing should no	bughly after handling chemical products, before y and at the end of the working period. ed to remove potentially contaminated clothing of be allowed out of the workplace. Wash Ensure that eyewash stations and safety ocation.	
Eye/face protection	:	Chemical splash goggles.		
Skin protection				
Hand protection	:	be worn at all times when handling ch this is necessary. Considering the pa check during use that the gloves are s should be noted that the time to break	s complying with an approved standard should emical products if a risk assessment indicates rameters specified by the glove manufacturer, still retaining their protective properties. It through for any glove material may be rers. In the case of mixtures, consisting of the of the gloves cannot be accurately	
Gloves	:	butyl rubber		
Body protection	:		body should be selected based on the task d and should be approved by a specialist	

Product code 00250770

Version 3.02

Product name SIGMAGUARD CSF 650 BASE REDBROWN

Section 8. Exposure controls/personal protection

-	
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance		
Physical state	:	Liquid.
Color	4	Not available.
Odor	1	Characteristic.
Odor threshold	1	Not available.
рН	1	Not applicable.
Melting point	1	Not available.
Boiling point	:	>37.78°C (>100°F)
Flash point	:	Closed cup: 100°C (212°F)
Evaporation rate	:	Not available.
Flammability/Combustible properties (solid, gas)	1	Not available.
Lower and upper explosive (flammable) limits	:	Greatest known range: Lower: 1.3% Upper: 13% (benzyl alcohol)
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	1.41
Solubility(ies)		Media Result
Solubility(les)	1	old water Not soluble
Partition coefficient: n- octanol/water	:	Not applicable.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Kinematic (40°C): >21 mm²/s
Section 10. Stabili	ty	and reactivity
<u>L</u>		

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.

Product code 00250770 Product name SIGMAGUARD CSF 650 BASE REDBROWN Date of issue 26 April 2024

Version 3.02

Section 10. Stability and reactivity

Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
▶ís-[4-(2,3-epoxipropoxi) phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
benzyl alcohol	LD50 Oral LC50 Inhalation Dusts and mists LD50 Dermal	Rat Rat Rabbit	15000 mg/kg >4178 mg/m ³ 2000 mg/kg	- 4 hours -
	LD50 Oral	Rat	1.23 g/kg	-

Conclusion/Summary : There are no data available on the mixture itself. Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
pís-[4-(2,3-epoxipropoxi)	Eyes - Mild irritant	Rabbit		24 hours	
phenyl]propane		Rabbit	-	24 110015	-
	Eyes - Redness of the	Rabbit	0.4	24 hours	-
	conjunctivae				
	Skin - Edema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-

Conclusion/Summary

Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.

· · · · · · · · · · · · · · · · · · ·	
Respiratory	: There are no data available on the mixture itself.

Sensitization

••••••	Route of exposure	Species	Result
ቓís-[4-(2,3-epoxipropoxi) phenyl]propane	skin	Mouse	Sensitizing

Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Mutagenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Carcinogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.

Section 11. Toxicological information

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
Talc , not containing asbestiform fibres	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure) Not available.

Aspiration hazard

Not available.

Information on the likely	: Not available.
routes of exposure	

Potential acute health effects

Eye contact	: Causes serious eye irritation.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.	
Ingestion	: No known significant effects or critical hazards.	

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effe	<u>cts</u>	and also chronic effects from short and long term exposure
Short term exposure		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	:	There are no data available on the mixture itself.
<u>Long term exposure</u>		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	:	There are no data available on the mixture itself.
Potential chronic health eff	ec	<u>ts</u>
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
		Indonesia [:] Page: 8/1

Section 11. Toxicological information

Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Dermal	11556.53 mg/kg 16686.7 mg/kg 5.7 mg/l

Other information

Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

Section 12. Ecological information

<u>Toxicity</u>			
Product/ingredient name	Result	Species	Exposure
s-[4-(2,3-epoxipropoxi)	Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia magna</i>	48 hours
	Chronic NOEC 0.3 mg/l	Daphnia	21 days

Persistence/degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
▶s-[4-(2,3-epoxipropoxi) phenyl]propane	-	-	Not readily
benzyl alcohol	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,6-bis(2,3-epoxypropoxy)	0.822	-	Low
hexane			
benzyl alcohol	0.87	-	Low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

			
	UN	IMDG	ΙΑΤΑ
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)
Transport hazard class(es)	9	9	9
Packing group	III	III	Ш
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Not applicable.

Additional information

UN	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	
IMDG	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.	
Special preca	autions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	
Transport in	bulk according : Not applicable.	

to IMO instruments

: No known specific national and/or regional regulations applicable to this product

Version 3.02

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

Classification



(including its ingredients).

Law No. 74/2001 - Banned

None of the components are listed.

Law No. 74/2001 - Restricted

None of the components are listed.

Law No. 74/2001 - : Not determined Chemicals that may be used

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 26 April 2024
Date of previous issue	: 5/18/2021
Version	: 3.02
Prepared by	: EHS
Key to abbreviations	 ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

Section 16. Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.