SAFETY DATA SHEET



Version 1.02

Section 1. Product and company identification

6 May 2024

Product name
Product code
Other means of identification
Product type

- : SIGMADUR 550H BASE L 0710CO2170
- : 00323080CO
- : Not available.
 - : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Coating. Paints. Painting-related materials.

Uses advised against	Reason
Not applicable.	

Supplier's details:	
Supplier	 PPG Industries Colombia Ltda Calle 51 # 40-13 Municipio de Itagüí Antioquia, Colombia (57) (4) 3787400 (Porteria)
Email address:	: HazComLatam@ppg.com
Emergency telephone number	: Colombia: 01 8000 916012 (CISPROQUIM) + 571 288 6012 (CISPROQUIM) Ecuador: 1800-59-3005 (CISPROQUIM) Peru: 080-050-847 (CISPROQUIM)

Section 2. Hazards identification

Classification of the substance or mixture	: FLAMMABLE LIQUIDS - Category 3 TOXIC TO REPRODUCTION - Category 2 AQUATIC HAZARD (ACUTE) - Category 3
	AQUATIC HAZARD (LONG-TERM) - Category 3
Target organs	: Contains material which causes damage to the following organs: brain. Contains material which may cause damage to the following organs: upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

GHS label elements

1.02

Section 2. Hazards identification

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	Flammable liquid and vapor. Suspected of damaging fertility or the unborn child. Harmful to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Obtain special instructions before use. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid release to the environment.
Response	:	IF exposed or concerned: Get medical advice or attention.
Storage	:	Store in a well-ventilated place. Keep cool.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	:	Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

CAS number/other identifiers

CAS number : Not applicable.	: Not applicable.		
Ingredient name	%	CAS number	
n-butyl acetate bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	3 - <5 0.2 - <0.5	123-86-4 41556-26-7	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necess	sary first aid measures
Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

English (US) Colombia	
-----------------------	--

Code	003230800	0	Date of issue	6 May 2024	Version	1.02
Product nam	ne	SIGMADUR 550H BASE L 0710CO2	170			

Section 4.	First aid	measures
------------	-----------	----------

Skin contact	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Indication of immediate med	al attention and special treatment needed, if necessary
Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately if large
Specific treatments	quantities have been ingested or inhaled.
	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation
Potential acute health effect	
Eye contact	No known significant effects or critical hazards.
Inhalation	No known significant effects or critical hazards.
Skin contact	Defatting to the skin. May cause skin dryness and irritation.
Ingestion	No known significant effects or critical hazards.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.		

3/11

English (US) Colombia

Code 00323080CO Product name SIGMADU	Dat IR 550H BASE L 0710CO2170	te of issue)	6 May 2024	Version	1.02
Section 6. Accide	ntal release m	easures			
For emergency responders		on 8 on suitable	and unsuitable materia		
Environmental precautions	drains and sewers. I environmental polluti	Inform the relevation (sewers, wat	nd runoff and contact w ant authorities if the pr erways, soil or air). W f released in large qua	oduct has caused ater polluting ma	È
Methods and materials for c	ontainment and cleani	ing up			
Small spill	and explosion-proof Alternatively, or if wa	top leak if without risk. Move containers from spill area. Use spark-proof tools nd explosion-proof equipment. Dilute with water and mop up if water-soluble. Iternatively, or if water-insoluble, absorb with an inert dry material and place in an ppropriate waste disposal container. Dispose of via a licensed waste disposal contractor.			
Large spill	and explosion-proof sewers, water course effluent treatment pla combustible, absorb and place in containe Dispose of via a licer material may pose th	equipment. App es, basements of ant or proceed a ent material e.g. er for disposal a nsed waste disp ne same hazard	iners from spill area. proach release from up or confined areas. Wa s follows. Contain and sand, earth, vermiculi ccording to local regula osal contractor. Conta as the spilled product. Section 13 for waste d	owind. Prevent en sh spillages into a d collect spillage ite or diatomaceo ations (see Sectio aminated absorbe Note: see Sectio	ntry into an with non- ous earth on 13). ent
Section 7. Handli	ng and storage	9			

Precautions for safe handling	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Conditions for safe storage	• Do not store above the following temperature: 50°C (122°E) Store in accordance

Conditions for safe storage,	: Do not store above the following temperature: 50°C (122°F). Store in accordance
including any	with local regulations. Store in a segregated and approved area. Store in original
incompatibilities	container protected from direct sunlight in a dry, cool and well-ventilated area, away
	from incompatible materials (see Section 10) and food and drink. Store locked up.
	Eliminate all ignition sources. Separate from oxidizing materials. Keep container
	tightly closed and sealed until ready for use. Containers that have been opened
	must be carefully resealed and kept upright to prevent leakage. Do not store in
	unlabeled containers. Use appropriate containment to avoid environmental
	contamination. See Section 10 for incompatible materials before handling or use.

6 May 2024

1.02

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name		Exposure limits	
<mark>p</mark> -butyl acetate		ACGIH TLV (United States, 7/2023). [Butyl acetates] STEL: 150 ppm 15 minutes. TWA: 50 ppm 8 hours.	
Recommended monitoring : procedures	Reference should be made to appropri- national guidance documents for meth substances will also be required.	iate monitoring standards. Reference to nods for the determination of hazardous	
Appropriate engineering : controls	contaminants below any recommende	Is to keep worker exposure to airborne ed or statutory limits. The engineering controls concentrations below any lower explosive	
Environmental exposure : controls			
Individual protection measures			
	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.		
Eye protection : Skin protection	Safety glasses with side shields.		
Hand protection :	be worn at all times when handling ch this is necessary. Considering the par check during use that the gloves are s should be noted that the time to break	complying with an approved standard should emical products if a risk assessment indicates rameters specified by the glove manufacturer, still retaining their protective properties. It through for any glove material may be rers. In the case of mixtures, consisting of e of the gloves cannot be accurately	
Gloves :	For prolonged or repeated handling, u	se the following type of gloves:	
	May be used: butyl rubber Not recommended: nitrile rubber		
Body protection :	being performed and the risks involve		
Other skin protection :	Appropriate footwear and any addition	al skin protection measures should be ormed and the risks involved and should be	

English (US)

Colombia

5/11

Code 00323080CO	Date of issue	6 May 2024	Version	1.02
Product name SIGMAD	UR 550H BASE L 0710CO2170			
Section 8. Expos	sure controls/personal p	protection		
Respiratory protection	: Respirator selection must be bas	•		,

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

<u>Appearance</u>			
Physical state	:	Liquid.	
Color	4	Not available.	
Odor	1	Not available.	
рН	1	Not applicable.	
Melting point	1	Not available.	
Boiling point	1	>37.78°C (>100°F)	
Flash point	:	Closed cup: 34°C (93.2°F)	
Evaporation rate	:	Not available.	
Flammability (solid, gas)	:	Not available.	
Lower and upper explosive (flammable) limits	:	Not available.	
Vapor pressure	:	Not available.	
Vapor density	:	Not available.	
Relative density	1	1.46	
Solubility(ies)		Media R	lesult
		cold water N	lot soluble
Partition coefficient: n- octanol/water	:	Not applicable.	
Auto-ignition temperature	:	Not available.	
Decomposition temperature	:	Not available.	
Viscosity	:	Kinematic (40°C (104°F)): >2	21 mm²/s (>21 cSt)
Viscosity	:	> 100 s (ISO 6mm)	

Section 10. Stability and reactivity

· · · · · · · · · · · · · · · · · · ·	English (US) Colombia 6/11			
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.			
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.			
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
Chemical stability	: The product is stable.			
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			

Section 10. Stability and reactivity

Hazardous decomposition products

: Depending on conditions, decomposition products may include the following materials: carbon oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity					
Product/ingredient name	Result	Species	Dose	Exposure	
n-butyl acetate bis(1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate	LC50 Inhalation Vapor LC50 Inhalation Vapor LD50 Dermal LD50 Oral LD50 Oral	Rat Rat Rabbit Rat Rat	>21.1 mg/l 2000 ppm >17600 mg/kg 10.768 g/kg 3.125 g/kg	4 hours 4 hours - -	
Conclusion/Summary Irritation/Corrosion Not available.	: There are no data available o	n the mixture itse	elf.		
Conclusion/Summary					
Skin –	: There are no data available of				
Eyes Respiratory <u>Sensitization</u> Not available.	There are no data available on the mixture itself.There are no data available on the mixture itself.				
Conclusion/Summary					
Skin Respiratory <u>Mutagenicity</u> Not available.	 There are no data available of There are no data available of 				
Conclusion/Summary Carcinogenicity Not available.	: There are no data available o	n the mixture itse	elf.		
Conclusion/Summary <u>Reproductive toxicity</u> Not available.	: There are no data available o	n the mixture itse	elf.		
Conclusion/Summary <u>Teratogenicity</u> Not available.	: There are no data available o	n the mixture itse	elf.		
Conclusion/Summary Specific target organ toxici	: There are no data available of the second state of the second st	n the mixture itse	elf.		

Section 11. Toxicological information

Name		Route of exposure	Target organs
n-butyl acetate	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

Target organs

: Contains material which causes damage to the following organs: brain. Contains material which may cause damage to the following organs: upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Aspiration hazard

Not available.

Information on the likely	:	Not available.
routes of exposure		
Potential acute health effects		
Eye contact	÷	No known significant effects or critical hazards.
Inhalation	÷,	No known significant effects or critical hazards.
Skin contact	:	Defatting to the skin. May cause skin dryness and irritation.
Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the phys	ic	al, chemical and toxicological characteristics
Eye contact	:	No specific data.
Inhalation	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	:	Adverse symptoms may include the following: irritation dryness cracking reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary :	There are no data available on the mixture itself. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
----------------------	--

Short term exposure

Section 11. Toxicological information

Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
<u>Long term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health eff	<u>ects</u>
Not available.	
General	: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/ or dermatitis.

Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	(vapors)	Inhalation (dusts and mists) (mg/l)
n-butyl acetate	10768	N/A	N/A	N/A	N/A
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	3125	N/A	N/A	N/A	N/A

Other information

: Not available.

Section 12. Ecological information

Ecotoxicity

Product/ingredient name	Result	Species	Exposure
n-butyl acetate	Acute LC50 18 mg/l	Fish	96 hours

Persistence/degradability

Product/ingredient name	Test	Result		Dose		Inoculum
n-butyl acetate	TEPA and OECD 301D	83 % - Readily - 28 days		-		-
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
n-butyl acetate	-		-		Readily	/

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
n-butyl acetate	2.3	-	Low

English (US)	Colombia	9/11
--------------	----------	------

Section 12. Ecological information

Mobility in soil

Soil/water partition	
coefficient (Koc)	

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	Brazil (ANTT)	IMDG	ΙΑΤΑ
UN number	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	3	3	3	3
Packing group				III
Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

UN	: None identified.
Brazil	: None identified.
Risk number	: 30
IMDG	: None identified.
ΙΑΤΑ	: None identified.

Code	00323080CO	Date of issue	6 May 2024	Version 1.02
Product nar	ne SIGMADUR 550H	I BASE L 0710CO2170		

Section 14. Transport information

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

Section 16. Other information

History

Date of previous issue Version	: 9/13/2023 : 1.02 EHS
Key to abbreviations	 ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail UN = United Nations
References	: ABNT NBR 14725-4: 2014 ANTT - National Land Transportation Agency

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.