

# SAFETY DATA SHEET



Date of issue/Date of revision

: 10 May 2024

Version

: 1.09

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : DURETHANE DTM NEUTRAL BASE - A  
**Product code** : 00338125  
**Product type** : Liquid.  
**Other means of identification** : Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications.  
**Use of the substance/mixture** : Coating.  
**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL  
Tweemontstraat 104  
B-2100 Deurne  
Belgium  
Telephone +32-33606311  
Fax +32-33606435

**e-mail address of person responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

**Supplier**  
+31 20 4075210

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture  
**Classification according to UK CLP/GHS**  
Flam. Liq. 3, H226  
Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
Skin Sens. 1, H317  
Aquatic Chronic 2, H411

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.  
See Section 16 for the full text of the H statements declared above.  
See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Warning

**Code** : 00338125 **Date of issue/Date of revision** : 10 May 2024  
**DURETHANE DTM NEUTRAL BASE - A**

## SECTION 2: Hazards identification

**Hazard statements** : Flammable liquid and vapour.  
 Causes skin irritation.  
 May cause an allergic skin reaction.  
 Causes serious eye irritation.  
 Toxic to aquatic life with long lasting effects.

### Precautionary statements

**Prevention** : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Avoid breathing vapour.

**Response** : Collect spillage.

**Storage** : Not applicable.

**Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.  
 P280, P210, P273, P261, P391, P501

**Supplemental label elements** : Not applicable.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

### Special packaging requirements

**Containers to be fitted with child-resistant fastenings** : Not applicable.

**Tactile warning of danger** : Not applicable.

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** : Prolonged or repeated contact may dry skin and cause irritation.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
1-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene	REACH #: 01-2119857280-40 EC: 202-681-1 CAS: 98-56-6	$\geq 10$ - $< 20$	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1]
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	$\geq 10$ - $\leq 15$	STOT SE 3, H335 Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	[1] [2]
trizinc bis(orthophosphate)	REACH #: 01-2119485044-40 EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6	$\geq 5.0$ - $\leq 10$	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
heptan-2-one	REACH #: 01-2119902391-49 EC: 203-767-1 CAS: 110-43-0	$\geq 1.0$ - $\leq 4.5$	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H332 STOT SE 3, H336	[1] [2]

**Code** : 00338125 **Date of issue/Date of revision** : 10 May 2024  
**DURETHANE DTM NEUTRAL BASE - A**

### SECTION 3: Composition/information on ingredients

isobutyl isobutyrate	Index: 606-024-00-3 EC: 202-612-5 CAS: 97-85-8	≥1.0 - ≤5.0	Flam. Liq. 3, H226 Aquatic Chronic 3, H412	[1]
reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	EC: 400-830-7 CAS: 104810-48-2 Index: 607-176-00-3	<1.0	Skin Sens. 1B, H317 Aquatic Chronic 2, H411	[1]
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5	≤0.30	Skin Sens. 1A, H317 Repr. 2, H361f Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
zinc oxide	REACH #: 01-2119463881-32 EC: 215-222-5 CAS: 1314-13-2 Index: 030-013-00-7	≤0.30	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
2-hydroxyethyl methacrylate	EC: 212-782-2 CAS: 868-77-9 Index: 607-124-00-X	≤0.30	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 <b>See Section 16 for the full text of the H statements declared above.</b>	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

<b>Code</b> : 00338125	<b>Date of issue/Date of revision</b> : 10 May 2024
<b>DURETHANE DTM NEUTRAL BASE - A</b>	

## SECTION 4: First aid measures

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
phosphorus oxides  
halogenated compounds  
carbonyl halides  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

<b>Code</b> : 00338125	<b>Date of issue/Date of revision</b> : 10 May 2024
<b>DURETHANE DTM NEUTRAL BASE - A</b>	

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

<b>Code</b> : 00338125	<b>Date of issue/Date of revision</b> : 10 May 2024
<b>DURETHANE DTM NEUTRAL BASE - A</b>	

## SECTION 7: Handling and storage

### 7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
n-butyl acetate	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b> STEL: 966 mg/m <sup>3</sup> 15 minutes. STEL: 200 ppm 15 minutes. TWA: 724 mg/m <sup>3</sup> 8 hours. TWA: 150 ppm 8 hours.
heptan-2-one	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b> STEL: 475 mg/m <sup>3</sup> 15 minutes. STEL: 100 ppm 15 minutes. TWA: 237 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.
Product/ingredient name	Exposure indices

**Recommended monitoring procedures** : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
n-butyl acetate	DNEL	Long term Oral	0.0005 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.0005 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.0013 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Dermal	8.8 µg/cm <sup>2</sup>	General population	Local
	DNEL	Long term Dermal	0.017 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	17.6 µg/cm <sup>2</sup>	Workers	Local
	DNEL	Long term Inhalation	0.029 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	300 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	11 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	3.4 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	6 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	7 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	11 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	12 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	35.7 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	48 mg/m <sup>3</sup>	Workers	Systemic

<b>Code</b> : 00338125	<b>Date of issue/Date of revision</b> : 10 May 2024
<b>DURETHANE DTM NEUTRAL BASE - A</b>	

### SECTION 8: Exposure controls/personal protection

heptan-2-one	DNEL	Short term Inhalation	300 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	300 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	300 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	600 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	600 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Oral	23.32 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	23.32 mg/kg bw/day	General population	Systemic
isobutyl isobutyrate	DNEL	Long term Dermal	54.27 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	84.31 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	394.25 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	1516 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Oral	7.86 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	27.34 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	154.77 mg/m <sup>3</sup>	Workers	Systemic
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	DNEL	Long term Dermal	0.5 mg/kg	Workers	Systemic
	DNEL	Long term Inhalation	0.085 mg/m <sup>3</sup>	General population [Consumers]	Systemic
	DNEL	Long term Dermal	0.25 mg/kg	General population [Consumers]	Systemic
	DNEL	Long term Oral	0.025 mg/kg	General population [Consumers]	Systemic
	DNEL	Long term Oral	0.025 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.025 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.085 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	0.25 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.35 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Oral	0.83 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.83 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1.39 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.45 mg/m <sup>3</sup>	General population	Systemic
DNEL	Long term Inhalation	4.9 mg/m <sup>3</sup>	Workers	Systemic	

#### PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
n-butyl acetate	Fresh water	0.18 mg/l	-
	Marine water	0.018 mg/l	-
	Fresh water sediment	0.981 mg/kg	-
	Marine water sediment	0.0981 mg/kg	-
	Sewage Treatment Plant	35.6 mg/l	-
	Soil	0.0903 mg/kg	-
trizinc bis(orthophosphate)	Fresh water	20.6 $\mu$ g/l	Sensitivity Distribution
	Marine water	6.1 $\mu$ g/l	Sensitivity Distribution
	Sewage Treatment Plant	100 $\mu$ g/l	Assessment Factors
	Fresh water sediment	117.8 mg/kg dwt	Sensitivity Distribution
	Marine water sediment	56.5 mg/kg dwt	Equilibrium Partitioning
	Soil	35.6 mg/kg dwt	Sensitivity Distribution
heptan-2-one	Fresh water	0.0982 mg/l	Assessment Factors
	Marine water	0.00982 mg/l	Assessment Factors
	Fresh water sediment	1.89 mg/kg	Equilibrium Partitioning
	Marine water sediment	0.189 mg/kg	Equilibrium Partitioning

**Code** : 00338125 **Date of issue/Date of revision** : 10 May 2024  
**DURETHANE DTM NEUTRAL BASE - A**

## SECTION 8: Exposure controls/personal protection

reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	Sewage Treatment Plant	12.5 mg/l	Assessment Factors
	Soil	0.321 mg/kg	Equilibrium Partitioning
	Fresh water	0.0023 mg/l	-
zinc oxide	Marine water	0.00023 mg/l	-
	Sewage Treatment Plant	10 mg/l	-
	Fresh water sediment	3.06 mg/kg dwt	-
	Marine water sediment	0.306 mg/kg dwt	-
	Soil	2 mg/kg	-
	Fresh water	20.6 $\mu$ g/l	Sensitivity Distribution
	Marine water	6.1 $\mu$ g/l	Sensitivity Distribution
	Fresh water sediment	117 mg/kg dwt	Sensitivity Distribution
	Sewage Treatment Plant	52 $\mu$ g/l	Assessment Factors
	Marine water sediment	56.5 mg/kg dwt	Assessment Factors
Soil	35.6 mg/kg dwt	Sensitivity Distribution	

### 8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Chemical splash goggles.

#### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Gloves** : For prolonged or repeated handling, use the following type of gloves:

Recommended: Chloroprene

May be used: butyl rubber, nitrile rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.



**Code** : 00338125 **Date of issue/Date of revision** : 10 May 2024  
**DURETHANE DTM NEUTRAL BASE - A**

## SECTION 8: Exposure controls/personal protection

- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Wear a respirator conforming to EN140. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Mask type: full-face mask half-face mask Filter type: organic vapour filter (Type A) particulate filter P3 Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Not available.
- Odour** : Characteristic.
- Odour threshold** : Not available.
- Melting point/freezing point** : May start to solidify at the following temperature: <-20°C (<-4°F) This is based on data for the following ingredient: heptan-2-one. Weighted average: -76.92°C (-106.5°F)
- Initial boiling point and boiling range** : >37.78°C (>100°F)
- Flammability (solid, gas)** : liquid
- Upper/lower flammability or explosive limits** : Greatest known range: Lower: 0.9% Upper: 10.5% (4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene)
- Flash point** : Closed cup: 30.56°C (87°F)
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
ethyl 3-ethoxypropionate	377	710.6	

- pH** : Not applicable.  
Not applicable. insoluble in water.

- Viscosity** : Kinematic (40°C): >21 mm<sup>2</sup>/s

- Solubility(ies)** :

Media	Result
cold water	Not soluble

- Miscible with water** : No.

- Partition coefficient: n-octanol/ water** : Not applicable.

- Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
n-butyl acetate	11.25096	1.5	DIN EN 13016-2			

- Relative density** : 1.12

**Code** : 00338125 **Date of issue/Date of revision** : 10 May 2024  
**DURETHANE DTM NEUTRAL BASE - A**

## SECTION 9: Physical and chemical properties

- Vapour density** : Highest known value: 4.97 (Air = 1) (isobutyl isobutyrate). Weighted average: 4.04 (Air = 1)
- Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
- Oxidising properties** : Product does not present an oxidizing hazard.
- Particle characteristics**
- Median particle size** : Not applicable.

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides phosphorus oxides halogenated compounds carbonyl halides metal oxide/oxides

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
4-chloro- $\alpha,\alpha$ -trifluorotoluene	LC50 Inhalation Vapour	Rat	33080 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	>2.7 g/kg	-
	LD50 Oral	Rat	13 g/kg	-
n-butyl acetate	LC50 Inhalation Vapour	Rat	>21.1 mg/l	4 hours
	LC50 Inhalation Vapour	Rat	2000 ppm	4 hours
	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	10.768 g/kg	-
trizinc bis(orthophosphate)	LC50 Inhalation Dusts and mists	Rat	>5.7 mg/l	4 hours
	LD50 Oral	Rat	>5000 mg/kg	-
heptan-2-one	LC50 Inhalation Vapour	Rat	16.7 mg/l	4 hours
	LD50 Dermal	Rabbit	10.206 g/kg	-
isobutyl isobutyrate	LD50 Oral	Rat	1.6 g/kg	-
	LD50 Dermal	Rabbit	>8600 mg/kg	-
	LD50 Oral	Rat	12.8 g/kg	-
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl- $\omega$ -hydroxypoly (oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)	LD50 Dermal	Rat - Male, Female	>2000 mg/kg	-

**Code** : 00338125 **Date of issue/Date of revision** : 10 May 2024  
**DURETHANE DTM NEUTRAL BASE - A**

**SECTION 11: Toxicological information**

propionyloxypoly (oxyethylene)	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	LD50 Dermal	Rat	>3170 mg/kg	-
zinc oxide	LD50 Oral	Rat - Male, Female	3230 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>5700 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
2-hydroxyethyl methacrylate	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	5050 mg/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself.

**Acute toxicity estimates**

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
DURETHANE DTM NEUTRAL BASE - A	41227.1	N/A	N/A	430.3	N/A
4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene	13000	N/A	N/A	33.08	N/A
n-butyl acetate	10768	N/A	N/A	N/A	N/A
heptan-2-one	1600	10206	N/A	16.7	N/A
isobutyl isobutyrate	12800	N/A	N/A	N/A	N/A
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	3230	N/A	N/A	N/A	N/A
2-hydroxyethyl methacrylate	5050	N/A	N/A	N/A	N/A

**Irritation/Corrosion**

**Conclusion/Summary** : Not available.  
**Skin** : There are no data available on the mixture itself.  
**Eyes** : There are no data available on the mixture itself.  
**Respiratory** : There are no data available on the mixture itself.

**Sensitisation****Conclusion/Summary**

**Skin** : There are no data available on the mixture itself.  
**Respiratory** : There are no data available on the mixture itself.

**Mutagenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

**Carcinogenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

**Reproductive toxicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

**Teratogenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

**Specific target organ toxicity (single exposure)**

**Code** : 00338125 **Date of issue/Date of revision** : 10 May 2024  
**DURETHANE DTM NEUTRAL BASE - A**

## SECTION 11: Toxicological information

Product/ingredient name	Category	Route of exposure	Target organs
4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene	Category 3	-	Respiratory tract irritation
n-butyl acetate	Category 3	-	Narcotic effects
heptan-2-one	Category 3	-	Narcotic effects

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
 pain or irritation  
 watering  
 redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
 irritation  
 redness  
 dryness  
 cracking
- Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

- Conclusion/Summary** : Not available.
- General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

**Code** : 00338125 **Date of issue/Date of revision** : 10 May 2024  
**DURETHANE DTM NEUTRAL BASE - A**

## SECTION 11: Toxicological information

**Other information** : Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
n-butyl acetate	Acute LC50 18 mg/l	Fish	96 hours
trizinc bis(orthophosphate)	Acute LC50 0.112 mg/l	Fish	96 hours
	Chronic NOEC 0.026 mg/l	Fish	30 days
heptan-2-one	Acute LC50 131 mg/l	Fish	96 hours
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	Chronic NOEC 0.78 mg/l	Daphnia	21 days
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	EC50 1.68 mg/l	Algae	72 hours
zinc oxide	LC50 0.9 mg/l	Fish	96 hours
	Acute EC50 0.17 mg/l	Algae	72 hours
	Acute EC50 0.481 mg/l Fresh water	Daphnia - Water flea - <i>Daphnia magna</i> - Neonate	48 hours
	Chronic NOEC 0.017 mg/l Fresh water	Algae	72 hours

**Conclusion/Summary** : Not available.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
n-butyl acetate	TEPA and OECD 301D	83 % - Readily - 28 days	-	-
heptan-2-one	OECD 310	69 % - Readily - 28 days	-	-
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	OECD 301B Ready Biodegradability - CO2 Evolution Test	12 % - 28 days	-	-

**Conclusion/Summary** : Not available.

**Code** : 00338125 **Date of issue/Date of revision** : 10 May 2024  
**DURETHANE DTM NEUTRAL BASE - A**

## SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
n-butyl acetate	-	-	Readily
heptan-2-one	-	-	Readily
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	-	-	Not readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
n-butyl acetate	2.3	-	Low
heptan-2-one	2.26	-	Low
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	5.9	-	High
2-hydroxyethyl methacrylate	0.42	-	Low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

**Product**

<b>Code</b> : 00338125	<b>Date of issue/Date of revision</b> : 10 May 2024
<b>DURETHANE DTM NEUTRAL BASE - A</b>	

## SECTION 13: Disposal considerations

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

### Waste catalogue

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	Waste catalogue
Container	15 01 06 mixed packaging

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
<b>14.1 UN number</b>	UN1263	UN1263	UN1263	UN1263
<b>14.2 UN proper shipping name</b>	PAINT	PAINT	PAINT	PAINT
<b>14.3 Transport hazard class(es)</b>	3	3	3	3
<b>14.4 Packing group</b>	III	III	III	III
<b>14.5 Environmental hazards</b>	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
<b>Marine pollutant substances</b>	Not applicable.	Not applicable.	(trizinc bis (orthophosphate))	Not applicable.

### Additional information

- ADR/RID** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- Tunnel code** : (D/E)
- ADN** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

**Code** : 00338125 **Date of issue/Date of revision** : 10 May 2024  
**DURETHANE DTM NEUTRAL BASE - A**

## SECTION 14: Transport information

**14.6 Special precautions for user** : **Transport within user's premises**: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
**UK (GB)/REACH**

### Annex XIV - List of substances subject to authorisation

#### Annex XIV

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

#### Ozone depleting substances

Not listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Seveso Directive

This product is controlled under the Seveso Directive.

#### Danger criteria

#### Category

P5c  
E2

## SECTION 16: Other information

☑ Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
 GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = GB CLP-specific Hazard statement  
 N/A = Not available  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 SGG = Segregation Group  
 vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification

Classification	Justification
Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	On basis of test data Calculation method Calculation method Calculation method Calculation method



<b>Code</b> : 00338125	<b>Date of issue/Date of revision</b> : 10 May 2024
<b>DURETHANE DTM NEUTRAL BASE - A</b>	

**SECTION 16: Other information****Full text of abbreviated H statements**

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Full text of classifications**

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**History**

**Date of issue/ Date of revision** : 10 May 2024

**Date of previous issue** : 12 April 2024

**Prepared by** : EHS

**Version** : 1.09

**Disclaimer**

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*