# SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision 11 May 2024

Version 2.01

## **Section 1. Identification**

: SIGMAGLIDE 790 C HARDENER **Product name** 

**Product code** : 000001198035 Other means of : 00472262

identification

**Product type** : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

**Uses advised against** : Not applicable.

**Supplier** : PPG Architectural Coatings Canada, Inc.

> 1550, rue Ampère, bureau 500 Boucherville (Québec) J4B 7L4

Canada

+1 450-655-3121

PPG Industries. Inc. One PPG Place Pittsburgh, PA 15272 : (412) 434-4515 (U.S.)

**Emergency telephone** number

(514) 645-1320 (Canada)

SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)

**Technical Phone Number** : 888-977-4762

# Section 2. Hazard identification

Classification of the substance or mixture : ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1B GERM CELL MUTAGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 1

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Health Hazards Not Otherwise Classified - Category 1

**GHS** label elements

Canada Page: 1/14

## **Product name SIGMAGLIDE 790 C HARDENER**

## Section 2. Hazard identification

**Hazard pictograms** 







Signal word

: Danger

**Hazard statements** 

: Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction. Suspected of causing genetic defects. May damage fertility or the unborn child. Causes damage to organs. (thymus)

Causes damage to organs through prolonged or repeated exposure. (immune

system)

Causes respiratory tract burns.

#### **Precautionary statements**

**Prevention** 

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Response

: IF exposed or concerned: Call a POISON CENTER or doctor. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage Disposal

: Store locked up.

: Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Supplemental label elements

: This product either contains formaldehyde or is capable of releasing formaldehyde above 0.5 ppm under certain conditions. Formaldehyde is a known cancer hazard, a skin sensitizer and a respiratory sensitizer. Emits toxic fumes when heated. Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 32.1% (oral), 96.8% (dermal), 99.8% (inhalation)

# Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

**Product name** 

: SIGMAGLIDE 790 C HARDENER

Other means of identification

: 00472262

**CAS** number/other identifiers

Canada Page: 2/14

Date of issue 11 May 2024 Version 2.01

Product code 000001198035

**Product name SIGMAGLIDE 790 C HARDENER** 

# Section 3. Composition/information on ingredients

| Ingredient name                            | Synonyms   | % (w/w)  | CAS number     |
|--|--|----------|----------------|
| triacetoxyethylsilane                      | Silanetriol, 1-ethyl-, 1,1,1-triacetate;<br>Silanetriol, ethyl-, triacetate;<br>Ethyltriacetoxysilane; ethylsilanetriyl<br>triacetate; triacetoxy(ethyl)silane; Alkyl<br>(C1-3)acyloxy(C2-20)silane;<br>Ethylsilanetriol, triacetate; Tris(acetyloxy)<br>ethylsilane; SILANE,<br>ETHYLTRIACETOXY-; SILANTRIOL,<br>ETHYL-, TRIACETATE   | 30 - 60* | 17689-77-9     |
| methylsilanetriyl triacetate               | Silanetriol, 1-methyl-, 1,1,1-triacetate; Silanetriol, methyl-, triacetate; Methyltriacetoxysilane; Triacetoxymethylsilane; Silanetriol, methyl-, triacetate, >5% in a non hazardous diluent; Silane, methyltriacetoxy-; Mixture of methyltriacetoxysilane and methyldiacetoxy[1-(ethoxycarbonyl)ethoxy] silane and methylacetoxybis[1-(ethoxycarbonyl)ethoxy]silane; Alkyl(C1-3) acyloxy(C2-20)silane; Methyltrihydroxysilane triacetate; Methylsilanetriol triacetate; METHYLTRIACETROXYSILANE   | 10 - 30* | 4253-34-3      |
| oligomeric ethyl- and methylacetoxysilanes |  | 10 - 30* | Not available. |
| diacetoxydi-tert-butoxysilane              | Acetic acid, 1,1'-dianhydride with silicic acid (H4SiO4) bis(1,1-dimethylethyl) ester; Acetic acid, dianhydride with silicic acid (H4SiO4) bis(1,1-dimethylethyl) ester; Silane, di(tert-butoxy)diacetoxy-; Acetic acid, dianhydride with silicic acid bis (1,1-dimethylethyl) ester; Di-tert-butoxydiacetoxysilane; Diacetyl di-tert-butyl orthosilicate; Alkoxyacetoxysilane; Acetic acid dianhydride with silicic acid (H4SiO4) bis(1,1-dimethylethyl) ester; SILANE, DIACETOXYDI-T-BUTOXY-; Acetic acid, anhydrides, 1,1'-dianhydride with silicic acid (H4SiO4) bis (1,1-dimethylethyl) ester | 1 - 5*   | 13170-23-5     |
| dibutyltin di(acetate)                     | Acetic acid, 1,1'-(dibutylstannylene) ester; Stannane, bis(acetyloxy)dibutyl-; Dibutyltin diacetate; Stannane, diacetoxydibutyl-; bis(Acetyloxy) dibutylstannane; Dibutyltin di [aliphatic monocarboxylate (C2-31)]; Dibytyltin diacetate; TIN DIACETATE, DIBUTYL; din-butyl tin diacetate; Acetic acid, esters, 1,1'-(dibutylstannylene) ester  | 1 - 5*   | 1067-33-0      |

<sup>\*</sup>Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

Canada Page: 3/14

**Product name SIGMAGLIDE 790 C HARDENER** 

## Section 3. Composition/information on ingredients

SUB codes represent substances without registered CAS Numbers.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

## **Description of necessary first aid measures**

**Eye contact**: Check for and remove any contact lenses. Immediately flush eyes with running

water for at least 15 minutes, keeping eyelids open. Seek immediate medical

attention.

**Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

**Ingestion**: If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

## Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : Corrosive to the respiratory system.

**Skin contact**: Causes severe burns. Causes damage to organs following a single exposure in

contact with skin. May cause an allergic skin reaction.

Ingestion : May cause burns to mouth, throat and stomach. Harmful if swallowed. Causes

damage to organs following a single exposure if swallowed.

## Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact** : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Canada Page: 4/14

## **Product name SIGMAGLIDE 790 C HARDENER**

## Section 4. First-aid measures

Ingestion : Adverse symptoms may include the following:

> stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

## Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled. **Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### Extinguishing media

Suitable extinguishing

media

**Unsuitable extinguishing** media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

**Hazardous thermal** decomposition products : In a fire or if heated, a pressure increase will occur and the container may burst.

: Decomposition products may include the following materials: carbon oxides

metal oxide/oxides Formaldehyde.

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

## Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

> Canada Page: 5/14

Date of issue 11 May 2024 Version 2.01

Product code 000001198035

**Product name SIGMAGLIDE 790 C HARDENER** 

## Section 6. Accidental release measures

## **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

## **Small spill**

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

## **Precautions for safe handling**

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

#### **Special precautions**

: Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

# Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Canada Page: 6/14

Date of issue 11 May 2024

Product code 000001198035

**Product name SIGMAGLIDE 790 C HARDENER** 

Version 2.01

## Section 8. Exposure controls/personal protection

## **Control parameters**

## **Occupational exposure limits**

| Ingredient name                            | Exposure limits                         |  |
|--|---|--|
| <b>Irr</b> iacetoxyethylsilane             | None.                                   |  |
| methylsilanetriyl triacetate               | None.                                   |  |
| oligomeric ethyl- and methylacetoxysilanes | None.                                   |  |
| diacetoxydi-tert-butoxysilane              | None.                                   |  |
| dibutyltin di(acetate)                     | CA Alberta Provincial (Canada, 3/2023). |  |
|  | [Tin Organic compounds] Absorbed        |  |
|  | through skin.                           |  |
|  | OEL: 0.2 mg/m³, (as Sn) 15 minutes.     |  |
|  | OEL: 0.1 mg/m³, (as Sn) 8 hours.        |  |
|  | CA British Columbia Provincial (Canada, |  |
|  | 8/2023). [Tin - Organic compounds]      |  |
|  | Absorbed through skin.                  |  |
|  | STEL: 0.2 mg/m³, (as Sn) 15 minutes.    |  |
|  | TWA: 0.1 mg/m³, (as Sn) 8 hours.        |  |
|  | CA Quebec Provincial (Canada, 7/2023).  |  |
|  | [Tin Organic compounds] Absorbed        |  |
|  | through skin.                           |  |
|  | STEV: 0.2 mg/m³, (as Sn) 15 minutes.    |  |
|  | TWAEV: 0.1 mg/m³, (as Sn) 8 hours.      |  |
|  | CA Ontario Provincial (Canada, 6/2019). |  |
|  | [Tin (Organic compounds)] Absorbed      |  |
|  | through skin.                           |  |
|  | TWA: 0.1 mg/m³, (as Sn) 8 hours.        |  |
|  | CA Saskatchewan Provincial (Canada,     |  |
|  | 7/2013). [Tin organic compounds]        |  |
|  | Absorbed through skin.                  |  |
|  | STEL: 0.2 mg/m³, (measured as Sn) 15    |  |
|  | minutes.                                |  |
|  | TWA: 0.1 mg/m³, (measured as Sn) 8      |  |
|  | hours.                                  |  |

## Consult local authorities for acceptable exposure limits.

procedures

**Recommended monitoring**: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Appropriate engineering** controls

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

| Canada |
|--------|
|--------|

**Product name SIGMAGLIDE 790 C HARDENER** 

## Section 8. Exposure controls/personal protection

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Skin protection

: Chemical splash goggles and face shield.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** 

: nitrile neoprene

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# Section 9. Physical and chemical properties

## **Appearance**

Physical state : Liquid. Color : Clear.

Odor : Hydrocarbon. [Strong]

Odor threshold : Not available.

pH : Not applicable.

Melting point : Not available.

Boiling point : >37.78°C (>100°F)

Flash point : Closed cup: 99°C (210.2°F)

Auto-ignition temperature: Not available.Decomposition temperature: Not available.Flammability: Not available.Lower and upper explosive: Not available.

(flammable) limits

Evaporation rate : Not available.

Vapor pressure : Not available.

Vapor density : Not available.

Relative density : 1.16

Canada Page: 8/14

**Product name SIGMAGLIDE 790 C HARDENER** 

## Section 9. Physical and chemical properties

Density (lbs / gal) : 9.68

Solubility(ies) : Media Result

cold water Not soluble

Partition coefficient: n-

octanol/water

: Not applicable.

Viscosity : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

**Volatility** : 72% (v/v), 67.805% (w/w)

% Solid. (w/w) : 32.195

## Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition

products.

Refer to protective measures listed in sections 7 and 8.

**Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

**Hazardous decomposition** 

products

: Depending on conditions, decomposition products may include the following materials:

carbon oxides Formaldehyde. metal oxide/oxides

# **Section 11. Toxicological information**

## Information on toxicological effects

## **Acute toxicity**

| Product/ingredient name      | Result      | Species | Dose       | Exposure |
|------------------------------|-------------|---------|------------|----------|
| triacetoxyethylsilane        | LD50 Oral   | Rat     | 1.462 g/kg |          |
| methylsilanetriyl triacetate | LD50 Oral   | Rat     | 2060 mg/kg | -        |
| dibutyltin di(acetate)       | LD50 Dermal | Rabbit  | 2318 mg/kg | -        |

**Conclusion/Summary** 

: There are no data available on the mixture itself.

**Irritation/Corrosion** 

**Conclusion/Summary** 

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

**Sensitization** 

Skin: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Canada Page: 9/14

## **Product name SIGMAGLIDE 790 C HARDENER**

# **Section 11. Toxicological information**

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Reproductive toxicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

## Specific target organ toxicity (single exposure)

| Name                         | Category   | Route of exposure | Target organs                |
|------------------------------|------------|-------------------|------------------------------|
| methylsilanetriyl triacetate | Category 3 | -                 | Respiratory tract irritation |
| dibutyltin di(acetate)       | Category 1 | oral              | thymus                       |

## Specific target organ toxicity (repeated exposure)

| Name                   | ,          | Route of exposure | Target organs |
|------------------------|------------|-------------------|---------------|
| dibutyltin di(acetate) | Category 1 | -                 | immune system |

**Target organs** 

: Contains material which may cause damage to the following organs: blood, kidneys, liver, bladder, upper respiratory tract, immune system, skin, central nervous system (CNS), eye, lens or cornea.

#### **Aspiration hazard**

Not available.

## Information on the likely routes of exposure

## Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : Corrosive to the respiratory system.

**Skin contact**: Causes severe burns. Causes damage to organs following a single exposure in

contact with skin. May cause an allergic skin reaction.

**Ingestion**: May cause burns to mouth, throat and stomach. Harmful if swallowed. Causes

damage to organs following a single exposure if swallowed.

## **Over-exposure signs/symptoms**

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

reduced fetal weight increase in fetal deaths skeletal malformations

Canada Page: 10/14

## **Product name SIGMAGLIDE 790 C HARDENER**

## **Section 11. Toxicological information**

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion**: Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

#### Delayed and immediate effects and also chronic effects from short and long term exposure

**Conclusion/Summary**: There are no data available on the mixture itself. This product either contains

formaldehyde or is capable of releasing formaldehyde above 0.5 ppm under certain conditions. Formaldehyde is a known cancer hazard, a skin sensitizer and a respiratory sensitizer. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation

and dermal routes of exposure and eye contact.

**Short term exposure** 

**Potential immediate** : There are no data available on the mixture itself.

effects

**Potential delayed effects**: There are no data available on the mixture itself.

Long term exposure

Potential immediate : There are no data available on the mixture itself.

effects

**Potential delayed effects**: There are no data available on the mixture itself.

Potential chronic health effects

General : Causes damage to organs through prolonged or repeated exposure. Once

sensitized, a severe allergic reaction may occur when subsequently exposed to very

low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

Mutagenicity : Suspected of causing genetic defects.Reproductive toxicity : May damage fertility or the unborn child.

## **Numerical measures of toxicity**

## **Acute toxicity estimates**

| Product/ingredient name      | Oral (mg/<br>kg) | Dermal<br>(mg/kg) | Inhalation<br>(gases)<br>(ppm) | Inhalation<br>(vapors)<br>(mg/l) | Inhalation<br>(dusts<br>and mists)<br>(mg/l) |
|------------------------------|------------------|-------------------|--------------------------------|----------------------------------|--|
| SIGMAGLIDE 790 C HARDENER    | 1635.0           | 2440.0            | N/A                            | N/A                              | N/A  |
| triacetoxyethylsilane        | 1462             | N/A               | N/A                            | N/A                              | N/A  |
| methylsilanetriyl triacetate | 2060             | N/A               | N/A                            | N/A                              | N/A  |
| dibutyltin di(acetate)       | N/A              | 2318              | N/A                            | N/A                              | N/A  |

Canada Page: 11/14

**Product name SIGMAGLIDE 790 C HARDENER** 

# **Section 12. Ecological information**

#### **Toxicity**

| Product/ingredient name | Result              | Species | Exposure |
|-------------------------|---------------------|---------|----------|
| ,                       | Acute EC10 3.1 mg/l | Fish    | 72 hours |
|                         | Acute EC50 0.5 mg/l | Algae   | 72 hours |

#### Persistence and degradability

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| dibutyltin di(acetate)  | -                 | -          | Not readily      |

## **Bioaccumulative potential**

Not available.

## **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

# Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL

PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

# Section 14. Transport information

|                             | TDG    | IMDG   | IATA   |
|-----------------------------|--------|--------|--------|
| UN number                   | UN3066 | UN3066 | UN3066 |
| UN proper shipping name     | PAINT  | PAINT  | PAINT  |
| Transport hazard class (es) | 8      | 8      | 8      |
| Packing group               | II     | II     | II     |

Canada Page: 12/14

## **Product name SIGMAGLIDE 790 C HARDENER**

## **Section 14. Transport information**

| <b>Environmental hazards</b> | Yes.                     | Yes.                     | Yes. The environmentally    |
|------------------------------|--------------------------|--------------------------|-----------------------------|
|                              |                          |                          | hazardous substance mark is |
|                              |                          |                          | not required.               |
| Marine pollutant substances  | (dibutyltin di(acetate)) | (dibutyltin di(acetate)) | Not applicable.             |

#### **Additional information**

**TDG** : The marine pollutant mark is not required when transported by road or rail.

**IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

**IATA** : The environmentally hazardous substance mark may appear if required by other transportation

regulations.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

**Proof of classification** 

statement

: Product classified as per the following sections of the Transportation of Dangerous

Goods Regulations: 2.40-2.42 (Class 8), 2.7 (Marine pollutant mark).

# Section 15. Regulatory information

#### **National Inventory List**

Canada inventory (DSL) : All components are listed or exempted.

## **Section 16. Other information**

Hazardous Material Information System (U.S.A.)

Health: Flammability: 1 Physical hazards:

(\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

**National Fire Protection Association (U.S.A.)** 

Health: Flammability: 1 Instability: 2 3

Date of issue/Date of 11 May 2024

revision

Organization that prepared : EHS

the SDS

Canada Page: 13/14

## **Product name SIGMAGLIDE 790 C HARDENER**

## Section 16. Other information

**Key to abbreviations** 

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group

UN = United Nations

## ▼ Indicates information that has changed from previously issued version.

## **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Canada Page: 14/14