# SAFETY DATA SHEET

Date of issue/Date of revision 4 June 2024

**Version 6** 



### **Section 1. Identification**

Product code : 19650-POWDR/20.6K
Product identifier : AMERCOAT 965 POWDER

### Recommended use and restrictions

Use of the substance/

mixture

: Coating.

**Uses advised against** 

: Not applicable.

Supplier's details

: PPG Industries Australia Pty Limited

(ABN 82 055 500 939) 14-20 McNaughton Rd CLAYTON Victoria 3168

Tel: (03) 9263 6000 Fax: (03) 9263 6970

**Emergency telephone** 

number

: Australia 1800 883 254 / New Zealand 0800 000 096 For international shipping emergencies: 1-412-391-1618

# Section 2. Hazard(s) identification

Classification of the substance or mixture : SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

SKIN SENSITISATION - Category 1 CARCINOGENICITY - Category 1

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract

irritation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1

**GHS** label elements

Hazard pictograms :







Signal word : DANGER

Hazard statements : Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage. May cause respiratory irritation.

May cause cancer.

Causes damage to organs through prolonged or repeated exposure. (lungs)

**Precautionary statements** 

**Prevention** 

: Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Do not breathe dust or mist. Wash thoroughly after handling.

Australia GHS Page: 1/12

**Product name AMERCOAT 965 POWDER** 

### Section 2. Hazard(s) identification

Response : IF exposed or concerned: Get medical advice or attention. IF INHALED: Call a

POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Immediately call a POISON CENTER or doctor.

**Storage** : Store in a well-ventilated place. Keep container tightly closed.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Supplemental label

elements

: Not applicable.

Other hazards which do not result in classification

May form explosible dust-air mixture if dispersed. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes,

skin, nose and throat.

# Section 3. Composition and ingredient information

Substance/mixture : Mixture

### **CAS** number/other identifiers

CAS number : Not applicable. EC number : Mixture.

Ingredient name	CAS number	% (w/w)
crystalline silica, respirable powder (<10 microns)	14808-60-7	>60
Cement, portland, chemicals	65997-15-1	10 - <30

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment or have an OEL and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### Section 4. First aid measures

### **Description of necessary first aid measures**

**Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running

water for at least 15 minutes, keeping eyelids open. Seek immediate medical

attention.

**Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show the container or label.

Keep person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

### Potential acute health effects

Eye contactInhalationCauses serious eye damage.May cause respiratory irritation.

**Skin contact** : Causes skin irritation. May cause an allergic skin reaction.

Australia GHS Page: 2/12

Product code 19650-POWDR/20.6K **Version 6** Date of issue 4 June 2024

**Product name AMERCOAT 965 POWDER** 

### Section 4. First aid measures

Ingestion : No known significant effects or critical hazards.

**Over-exposure signs/symptoms** 

**Eye contact** : Adverse symptoms may include the following:

pain watering redness

Inhalation Adverse symptoms may include the following:

respiratory tract irritation

coughing

**Skin contact** : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion Adverse symptoms may include the following:

stomach pains

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** 

: No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Firefighting measures

### **Extinguishing media**

Suitable extinguishing

media

**Unsuitable extinguishing** 

media

Specific hazards arising

from the chemical

**Hazardous thermal** decomposition products

**Special protective actions** 

for fire-fighters

: Use dry chemical powder.

: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

: May form explosible dust-air mixture if dispersed.

: Decomposition products may include the following materials:

metal oxide/oxides

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective** equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Hazchem code : Not applicable.

> **Australia GHS** Page: 3/12

Date of issue 4 June 2024 **Version 6** 

Product code 19650-POWDR/20.6K **Product name AMERCOAT 965 POWDER** 

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

**Small spill** 

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe dust. Do not ingest. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

> **Australia GHS** Page: 4/12

Date of issue 4 June 2024

**Version 6** 

Product code 19650-POWDR/20.6K **Product name AMERCOAT 965 POWDER** 

# Section 7. Handling and storage

including any incompatibilities

Conditions for safe storage, : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls and personal protection

#### **Control parameters**

### Occupational exposure limits

rystalline silica, respirable powder (<10 microns) Safe Work Australia (Australia, 10/2022).

[Silica - Crystalline]

TWA: 0.05 mg/m<sup>3</sup> 8 hours. Form:

Respirable dust

Cement, portland, chemicals Safe Work Australia (Australia, 10/2022).

TWA: 10 mg/m<sup>3</sup> 8 hours.

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

For products that are sprayed, where practicable use a spray booth designed and maintained in accordance with AS/ NZS 4114.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection **Skin protection Hand protection** 

: Chemical splash goggles and face shield.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** : butyl rubber

> **Australia GHS** Page: 5/12

**Product name AMERCOAT 965 POWDER** 

### Section 8. Exposure controls and personal protection

**Body protection** Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist

before handling this product.

Appropriate footwear and any additional skin protection measures should be Other skin protection

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respirator selection must be based on known or anticipated exposure levels, the Respiratory protection

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary.

**Restrictions on use** : Not applicable.

References: Eye protectors should conform to AS/NZS 1336 and AS/NZS 1337. Chemical-resistant gloves should conform to AS/NZS 2161.1. Respiratory protection should conform to AS/NZS 1715 and AS/NZS 1716. Occupational footwear should conform to AS/NZS 2210.

## Section 9. Physical and chemical properties

**Appearance** 

: Solid. Physical state

Powder.

Colour Grey.

Odour Characteristic.

Not available. **Odour threshold** Not applicable. **Melting point** : Not available.

**Boiling point** : Not available.

Flash point Closed cup: Not applicable.

: Not available. **Evaporation rate** Flammability (solid, gas) : Not available. Lower and upper explosive : Not applicable.

(flammable) limits

Vapour pressure : Not available. Vapour density : Not applicable.

**Relative density** 2.75

Media Result Solubility(ies)

cold water Not soluble

Partition coefficient: n-

octanol/water

: Not applicable.

**Auto-ignition temperature** : Not applicable. : Not available. **Decomposition temperature Viscosity** 

: Not Applicable

**Australia GHS** Page: 6/12

**Product name AMERCOAT 965 POWDER** 

## Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** 

: Stable under recommended storage and handling conditions (see Section 7). When exposed to high temperatures may produce hazardous decomposition products.

**Incompatible materials** 

: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

Hazardous decomposition products

 Depending on conditions, decomposition products may include the following materials: metal oxide/oxides

## **Section 11. Toxicological information**

### Information on toxicological effects

#### **Acute toxicity**

Not available.

Conclusion/Summary

**Irritation/Corrosion** 

Not available.

**Conclusion/Summary** 

Skin
: There are no data available on the mixture itself.
Eyes
: There are no data available on the mixture itself.
Respiratory
: There are no data available on the mixture itself.

<u>Sensitisation</u>

Not available.

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

Not available.

**Conclusion/Summary** 

Carcinogenicity

Not available.

: There are no data available on the mixture itself.

: There are no data available on the mixture itself.

Conclusion/Summary

**Reproductive toxicity** 

Not available.

: There are no data available on the mixture itself.

Conclusion/Summary

Teratogenicity

Not available.

: There are no data available on the mixture itself.

Australia GHS Page: 7/12

Product code 19650-POWDR/20.6K **Version 6** Date of issue 4 June 2024

**Product name AMERCOAT 965 POWDER** 

## Section 11. Toxicological information

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Specific target organ toxicity (single exposure)

Name	,	Route of exposure	Target organs
Cement, portland, chemicals	Category 3	-	Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
crystalline silica, respirable powder (<10 microns)	Category 1	inhalation	lungs

### **Aspiration hazard**

Not available.

**Information on likely routes**: Not available.

of exposure

Potential acute health effects

**Eye contact** : Causes serious eye damage. Inhalation : May cause respiratory irritation.

**Skin contact** : Causes skin irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Conclusion/Summary** 

: There are no data available on the mixture itself. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Repeated exposure of the eyes to a low level of dust can produce eye irritation. Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### **Short term exposure**

**Australia GHS** Page: 8/12

**Product name AMERCOAT 965 POWDER** 

## Section 11. Toxicological information

**Potential immediate** 

effects

: There are no data available on the mixture itself.

Potential delayed effects

: There are no data available on the mixture itself.

**Long term exposure** 

**Potential immediate** 

effects

: There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

Not available.

General : Causes damage to organs through prolonged or repeated exposure. Repeated or

prolonged inhalation of dust may lead to chronic respiratory irritation. Once

sensitized, a severe allergic reaction may occur when subsequently exposed to very

low levels.

**Carcinogenicity**: May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.Reproductive toxicity : No known significant effects or critical hazards.

**Numerical measures of toxicity** 

**Acute toxicity estimates** 

N/A

# **Section 12. Ecological information**

### **Toxicity**

Not available.

### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

**Mobility in soil** 

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Australia GHS Page: 9/12

Date of issue 4 June 2024 Version 6

Product code 19650-POWDR/20.6K **Product name AMERCOAT 965 POWDER** 

## Section 13. Disposal considerations

### **Disposal methods**

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	ADG	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

**ADG** : None identified. Hazchem code : Not applicable. **IMDG** : None identified. **IATA** : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

**Australia GHS** Page: 10/12

**Product name AMERCOAT 965 POWDER** 

## **Section 15. Regulatory information**

Standard for the Uniform Scheduling of Medicines and Poisons

SUSMP : Not scheduled

**Model Work Health and Safety Regulations - Scheduled Substances** 

Ingredient name	Schedule
	Restricted hazardous chemical [For abrasive blasting at a concentration of greater than 1%]

Australia inventory (AIIC) : All components are listed or exempted.

New Zealand (NZIoC) : All components are listed or exempted.

**International regulations** 

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

**Montreal Protocol** 

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

# Section 16. Any other relevant information

**History** 

Date of issue/Date of

revision

: 4 June 2024

Date of previous issue : 6/14/2022

Prepared by : EHS

**Key to abbreviations** : ADG = Australian Dangerous Goods

ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
NOHSC = National Occupational Health and Safety Commission
SUSMP = Standard Uniform Schedule of Medicine and Poisons

UN = United Nations

References : Not available.

▼ Indicates information that has changed from previously issued version.

**Notice to reader** 

Australia GHS Page: 11/12

Product code 19650-POWDR/20.6K Date of issue 4 June 2024
Product name AMERCOAT 965 POWDER

## Section 16. Any other relevant information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Australia GHS Page: 12/12

**Version 6**