

SAFETY DATA SHEET



Date of issue/Date of revision

: 4 June 2024

Version

: 1.03

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : DURETHANE MCZ Moisture Cure Zinc Green Component A
Product code : 00348205
Product type : Liquid.
Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications.
Use of the substance/mixture : Coating.
Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL
Tweemontstraat 104
B-2100 Deurne
Belgium
Telephone +32-33606311
Fax +32-33606435

e-mail address of person responsible for this SDS : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

Supplier
+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture
Classification according to UK CLP/GHS
Flam. Liq. 3, H226
Skin Irrit. 2, H315
Eye Irrit. 2, H319
Resp. Sens. 1, H334
Skin Sens. 1, H317
Carc. 1B, H350
STOT SE 3, H335
STOT SE 3, H336
Aquatic Chronic 2, H411

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Code : 00348205 **Date of issue/Date of revision** : 4 June 2024
DURETHANE MCZ Moisture Cure Zinc Green Component A

SECTION 2: Hazards identification

Signal word : Danger
Hazard statements : Flammable liquid and vapour.
 Causes skin irritation.
 May cause an allergic skin reaction.
 Causes serious eye irritation.
 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 May cause respiratory irritation.
 May cause drowsiness or dizziness.
 May cause cancer.
 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Avoid breathing vapour.

Response : Collect spillage.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.
 P280, P210, P273, P261, P391, P501

Supplemental label elements : Contains isocyanates. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Restricted to professional users. As from August 24 2023 adequate training is required before industrial or professional use.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
Hydrocarbons, C9, aromatics > 0.1% cumene	REACH #: 01-2119455851-35 EC: 918-668-5 CAS: 64742-95-6	≥25 - ≤50	Flam. Liq. 3, H226 Carc. 1B, H350 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	[1]
Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol	CAS: 67815-87-6	≥25 - ≤50	Resp. Sens. 1, H334 Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1] [2]

Code : 00348205 **Date of issue/Date of revision** : 4 June 2024
DURETHANE MCZ Moisture Cure Zinc Green Component A

SECTION 3: Composition/information on ingredients

4,4'-methylenediphenyl diisocyanate	REACH #: 01-2119457014-47 EC: 202-966-0 CAS: 101-68-8 Index: 615-005-00-9	≥5.0 - <10	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373	[1] [2]
Isocyanic acid, polymethylenepolyphenylene ester	REACH #: 01-2119457024-46 CAS: 9016-87-9	≥1.0 - ≤5.0	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 (inhalation)	[1] [2]
4-isocyanatosulphonyltoluene	REACH #: 01-2119980050-47 EC: 223-810-8 CAS: 4083-64-1 Index: 615-012-00-7	≥1.0 - ≤5.0	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 STOT SE 3, H335 EUH014	[1] [2]
methylenediphenyl diisocyanate	REACH #: 01-2119457015-45 EC: 247-714-0 CAS: 26447-40-5 Index: 615-005-00-9	<1.0	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 See Section 16 for the full text of the H statements declared above.	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
 [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

Code : 00348205	Date of issue/Date of revision : 4 June 2024
------------------------	---

DURETHANE MCZ Moisture Cure Zinc Green Component A

SECTION 4: First aid measures

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin contact : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.

Ingestion : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness

Inhalation : Adverse symptoms may include the following:
 respiratory tract irritation
 coughing
 wheezing and breathing difficulties
 asthma
 nausea or vomiting
 headache
 drowsiness/fatigue
 dizziness/vertigo
 unconsciousness

Skin contact : Adverse symptoms may include the following:
 irritation
 redness
 dryness
 cracking

Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Code : 00348205	Date of issue/Date of revision : 4 June 2024
------------------------	---

DURETHANE MCZ Moisture Cure Zinc Green Component A

SECTION 5: Firefighting measures

Hazardous combustion products : Decomposition products may include the following materials:
 carbon oxides
 nitrogen oxides
 sulfur oxides
 Cyanate and isocyanate.
 hydrogen cyanide

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Special provisions : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Place in a suitable container. The contaminated area should be cleaned immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): water (45 parts), ethanol or isopropyl alcohol (50 parts) and concentrated (d: 0,880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts) and water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in an unsealed container. Once this stage is reached, close container and dispose of according to local regulations (see section 13). Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the

Code : 00348205 **Date of issue/Date of revision** : 4 June 2024
DURETHANE MCZ Moisture Cure Zinc Green Component A

SECTION 6: Accidental release measures

appropriate authorities in accordance with local regulations.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitisation problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Precautions should be taken to minimise exposure to atmospheric humidity or water. CO₂ will be formed, which, in closed containers, could result in pressurisation.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

Code : 00348205	Date of issue/Date of revision : 4 June 2024
DURETHANE MCZ Moisture Cure Zinc Green Component A	

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure limit values
Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol	EH40/2005 WELs (United Kingdom (UK), 1/2020). [isocyanates, all, except methyl isocyanate] Inhalation sensitiser. STEL: 0.07 mg/m ³ , (as -NCO) 15 minutes. TWA: 0.02 mg/m ³ , (as -NCO) 8 hours.
4,4'-methylenediphenyl diisocyanate	EH40/2005 WELs (United Kingdom (UK), 1/2020). [isocyanates, all, except methyl isocyanate] Inhalation sensitiser. STEL: 0.07 mg/m ³ , (as -NCO) 15 minutes. TWA: 0.02 mg/m ³ , (as -NCO) 8 hours.
Isocyanic acid, polymethylenepolyphenylene ester	EH40/2005 WELs (United Kingdom (UK), 1/2020). [isocyanates, all, except methyl isocyanate] Inhalation sensitiser. STEL: 0.07 mg/m ³ , (as -NCO) 15 minutes. TWA: 0.02 mg/m ³ , (as -NCO) 8 hours.
4-isocyanatosulphonyltoluene	EH40/2005 WELs (United Kingdom (UK), 1/2020). [isocyanates, all, except methyl isocyanate] Inhalation sensitiser. STEL: 0.07 mg/m ³ , (as -NCO) 15 minutes. TWA: 0.02 mg/m ³ , (as -NCO) 8 hours.
methylenediphenyl diisocyanate	EH40/2005 WELs (United Kingdom (UK), 1/2020). [isocyanates, all, except methyl isocyanate] Inhalation sensitiser. STEL: 0.07 mg/m ³ , (as -NCO) 15 minutes. TWA: 0.02 mg/m ³ , (as -NCO) 8 hours.

Product/ingredient name	Exposure indices
-------------------------	------------------

Recommended monitoring procedures : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Hydrocarbons, C9, aromatics > 0.1% cumene 4,4'-methylenediphenyl diisocyanate	DNEL	Long term Inhalation	150 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	25 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	32 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	11 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	11 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.05 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	0.1 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	0.025 mg/m ³	General population	Local
	DNEL	Short term Inhalation	0.05 mg/m ³	[Consumers] General population	Local
	DNEL	Short term Inhalation	0.1 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	0.05 mg/m ³	Workers	Systemic
	DNEL	Short term Dermal	50 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	28.7 mg/cm ²	Workers	Local
	DNEL	Short term Dermal	25 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	0.05 mg/m ³	[Consumers] General population	Systemic
	DNEL	Short term Oral	20 mg/kg bw/day	General population	Systemic
DNEL	Short term Dermal	17.2 mg/cm ²	[Consumers] General population	Local	

Code : 00348205	Date of issue/Date of revision : 4 June 2024
DURETHANE MCZ Moisture Cure Zinc Green Component A	

SECTION 8: Exposure controls/personal protection

Isocyanic acid, polymethylenepolyphenylene ester	DNEL	Long term Inhalation	0.025 mg/m ³	General population [Consumers]	Systemic
	DNEL	Long term Inhalation	0.025 mg/m ³	General population	Local
	DNEL	Short term Inhalation	0.05 mg/m ³	General population	Local
	DNEL	Long term Inhalation	0.05 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	0.1 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	0.05 mg/m ³	Workers	Local
4-isocyanatosulphonyltoluene	DNEL	Short term Inhalation	0.1 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	0.025 mg/m ³	General population [Consumers]	Local
	DNEL	Short term Inhalation	0.05 mg/m ³	General population [Consumers]	Local
	DNEL	Long term Oral	0.46 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.46 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.8 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	0.92 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	3.24 mg/m ³	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
4,4'-methylenediphenyl diisocyanate	Fresh water	1 mg/l	Assessment Factors
	Marine water	0.1 mg/l	Assessment Factors
	Sewage Treatment Plant	1 mg/l	Assessment Factors
	Soil	1 mg/kg dwt	Assessment Factors
Isocyanic acid, polymethylenepolyphenylene ester	Fresh water	1 mg/l	Assessment Factors
	Marine water	0.1 mg/l	Assessment Factors
	Sewage Treatment Plant	1 mg/l	Assessment Factors
	Soil	1 mg/kg dwt	Assessment Factors
4-isocyanatosulphonyltoluene	Fresh water	0.03 mg/l	Assessment Factors
	Marine water	0.003 mg/l	Assessment Factors
	Sewage Treatment Plant	0.4 mg/l	Assessment Factors
	Fresh water sediment	0.172 mg/kg dwt	Equilibrium Partitioning
	Marine water sediment	0.017 mg/kg dwt	Equilibrium Partitioning
	Soil	0.017 mg/kg dwt	Equilibrium Partitioning

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles.

Skin protection

Hand protection :

Code : 00348205	Date of issue/Date of revision : 4 June 2024
------------------------	---

DURETHANE MCZ Moisture Cure Zinc Green Component A

SECTION 8: Exposure controls/personal protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

butyl rubber

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Wear a respirator conforming to EN140. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Mask type: full-face mask half-face mask Filter type: organic vapour filter (Type A) particulate filter P3 Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- Restrictions on use** : Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Green.
- Odour** : Characteristic.
- Odour threshold** : Not available.
- Melting point/freezing point** : May start to solidify at the following temperature: -2.37°C (27.7°F) This is based on data for the following ingredient: 4-isocyanatosulphonyltoluene. Weighted average: -57.64°C (-71.8°F)
- Initial boiling point and boiling range** : >37.78°C (>100°F)
- Flammability (solid, gas)** : liquid
- Upper/lower flammability or explosive limits** : Greatest known range: Lower: 1.4% Upper: 7.6% (Solvent naphtha (petroleum), light aromatic)
- Flash point** : Closed cup: 46.11°C (115°F)
- Auto-ignition temperature** :

Code : 00348205 **Date of issue/Date of revision** : 4 June 2024
DURETHANE MCZ Moisture Cure Zinc Green Component A

SECTION 9: Physical and chemical properties

Ingredient name	°C	°F	Method
Hydrocarbons, C9, aromatics > 0.1% cumene	>400	>752	

pH : Not applicable.
 Not applicable. insoluble in water.

Viscosity : Kinematic (40°C): >21 mm²/s

Solubility(ies) :

Media	Result
cold water	Not soluble

Miscible with water : No.

Partition coefficient: n-octanol/ water : Not applicable.

Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Hydrocarbons, C9, aromatics > 0.1% cumene	1.5	0.2				

Relative density : 1.02

Vapour density : Highest known value: 4.1 (Air = 1) (1,2,4-trimethylbenzene). Weighted average: 4.08 (Air = 1)

Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

Oxidising properties : Product does not present an oxidizing hazard.

Particle characteristics

Median particle size : Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : In a fire, hazardous decomposition products may be produced.
 Refer to protective measures listed in sections 7 and 8.

10.5 Incompatible materials : Keep away from: oxidising agents, strong alkalis, strong acids, amines, alcohols, water.
 Uncontrolled exothermic reactions occur with amines and alcohols.

10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials: Cyanate and isocyanate. carbon oxides nitrogen oxides sulfur oxides hydrogen cyanide

Code : 00348205 **Date of issue/Date of revision** : 4 June 2024
DURETHANE MCZ Moisture Cure Zinc Green Component A

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Hydrocarbons, C9, aromatics > 0.1% cumene 4,4'-methylenediphenyl diisocyanate Isocyanic acid, polymethylenepolyphenylene ester 4-isocyanatosulphonyltoluene methylenediphenyl diisocyanate	LD50 Dermal	Rabbit	>3160 mg/kg	-
	LD50 Oral	Rat - Female	3492 mg/kg	-
	LD50 Oral	Rat	9200 mg/kg	-
	LD50 Dermal	Rabbit	>9400 mg/kg	-
	LD50 Oral	Rat	49 g/kg	-
	LD50 Oral	Rat	2234 mg/kg	-
	LD50 Dermal	Rabbit	>9400 mg/kg	-
LD50 Oral	Rat	>10000 mg/kg	-	

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
DURETHANE MCZ Moisture Cure Zinc Green Component A	N/A	N/A	N/A	N/A	14.9
Hydrocarbons, C9, aromatics > 0.1% cumene	3492	N/A	N/A	N/A	N/A
4,4'-methylenediphenyl diisocyanate	9200	N/A	N/A	N/A	1.5
Isocyanic acid, polymethylenepolyphenylene ester	49000	N/A	N/A	N/A	1.5
4-isocyanatosulphonyltoluene methylenediphenyl diisocyanate	2234	N/A	N/A	N/A	N/A
	N/A	N/A	N/A	11	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
4,4'-methylenediphenyl diisocyanate	Skin - Irritant	Rabbit	-	-	-

Conclusion/Summary : Not available.

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
4,4'-methylenediphenyl diisocyanate methylenediphenyl diisocyanate	Respiratory	Guinea pig	Sensitising
	skin	Mouse	Sensitising
	Respiratory	Guinea pig	Sensitising
	skin	Guinea pig	Sensitising

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Code : 00348205 **Date of issue/Date of revision** : 4 June 2024
DURETHANE MCZ Moisture Cure Zinc Green Component A

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
4,4'-methylenediphenyl diisocyanate	Positive - Inhalation - TC	Rat	0 to 6 mg/m ³	2 years; 5 days per week

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Hydrocarbons, C9, aromatics > 0.1% cumene	Category 3	-	Respiratory tract irritation
4,4'-methylenediphenyl diisocyanate	Category 3	-	Narcotic effects
Isocyanic acid, polymethylenepolyphenylene ester	Category 3	-	Respiratory tract irritation
4-isocyanatosulphonyltoluene	Category 3	-	Respiratory tract irritation
methylenediphenyl diisocyanate	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
4,4'-methylenediphenyl diisocyanate	Category 2	-	-
Isocyanic acid, polymethylenepolyphenylene ester	Category 2	inhalation	-
methylenediphenyl diisocyanate	Category 2	-	-

Aspiration hazard

Product/ingredient name	Result
Hydrocarbons, C9, aromatics > 0.1% cumene	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin contact : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.

Ingestion : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness

Code : 00348205 **Date of issue/Date of revision** : 4 June 2024
DURETHANE MCZ Moisture Cure Zinc Green Component A

SECTION 11: Toxicological information

- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
wheezing and breathing difficulties
asthma
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
- Ingestion** : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Long term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Not available.

- Conclusion/Summary** : Not available.
- General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Hydrocarbons, C9, aromatics > 0.1% cumene	EC50 3.2 mg/l	Daphnia	48 hours
methylenediphenyl diisocyanate	LC50 9.2 mg/l	Fish	96 hours
	Acute LC50 >100 mg/l	Fish	96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Hydrocarbons, C9, aromatics > 0.1% cumene	-	75 % - Readily - 28 days	-	-

Code : 00348205 **Date of issue/Date of revision** : 4 June 2024
DURETHANE MCZ Moisture Cure Zinc Green Component A

SECTION 12: Ecological information

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Hydrocarbons, C9, aromatics > 0.1% cumene	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
4,4'-methylenediphenyl diisocyanate	4.51	-	High
methylenediphenyl diisocyanate	4.51	-	High

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

Waste catalogue

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	Waste catalogue
Container	15 01 06 mixed packaging

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Code : 00348205 **Date of issue/Date of revision** : 4 June 2024
DURETHANE MCZ Moisture Cure Zinc Green Component A

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	☑ (Solvent naphtha (petroleum), light aromatic)	Not applicable.

Additional information

- ADR/RID** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- Tunnel code** : (D/E)
- ADN** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Restricted to professional users. As from August 24 2023 adequate training is required before industrial or professional use.

Seveso Directive

Code : 00348205	Date of issue/Date of revision : 4 June 2024
DURETHANE MCZ Moisture Cure Zinc Green Component A	

SECTION 15: Regulatory information

This product is controlled under the Seveso Directive.

Danger criteria

Category
P5c E2

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms

- : ATE = Acute Toxicity Estimate
- GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = GB CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- SGG = Segregation Group
- vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
Flam. Liq. 3, H226	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Resp. Sens. 1, H334	Calculation method
Skin Sens. 1, H317	Calculation method
Carc. 1B, H350	Calculation method
STOT SE 3, H335	Calculation method
STOT SE 3, H336	Calculation method
Aquatic Chronic 2, H411	Calculation method

Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH014	Reacts violently with water.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications

Code : 00348205 **Date of issue/Date of revision** : 4 June 2024
DURETHANE MCZ Moisture Cure Zinc Green Component A

SECTION 16: Other information

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 1B	CARCINOGENICITY - Category 1B
Carc. 2	CARCINOGENICITY - Category 2
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Resp. Sens. 1	RESPIRATORY SENSITISATION - Category 1
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

History

Date of issue/ Date of revision : 4 June 2024
Date of previous issue : 21 October 2023
Prepared by : EHS
Version : 1.03

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.