## SAFETY DATA SHEET



#### Conforms to Official Mexican Standard NOM-018-STPS-2015

Date of revision 4 June 2024 Date of issue 4 June 2024

**Version 3** 

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product name : AMERCOAT 965 POWDER

Product code : AT965-3P/03
Other means of : Not applicable.

identification

Product type : Powder.

Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

Uses advised against : Not applicable.

Manufacturer : PPG Industries, Inc.

One PPG Place Pittsburgh, PA 15272 : (412) 434-4515 (U.S.)

Emergency telephone : (412) 434-4515 (U.S.)
number (514) 645-1320 (Canada)

SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)

**Technical Phone Number**: 888-977-4762

### **SECTION 2: Hazards identification**

Classification of the substance or mixture

: SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity:

99.8% (oral), 99.8% (dermal), 99.8% (inhalation)

**GHS** label elements

Hazard pictograms







Signal word : Danger

Mexico Page: 1/12

Version 3 Date of issue 4 June 2024

### **Product name AMERCOAT 965 POWDER**

### SECTION 2: Hazards identification

**Hazard statements** 

Product code AT965-3P/03

: H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H335 - May cause respiratory irritation.

H350 - May cause cancer.

H372 - Causes damage to organs through prolonged or repeated exposure.

### **Precautionary statements**

**Prevention** 

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves, protective clothing and eye or face protection.

P271 - Use only outdoors or in a well-ventilated area.

P260 - Do not breathe dust or mist.

P270 - Do not eat, drink or smoke when using this product.

P264 - Wash thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

Response

P308 + P313 - IF exposed or concerned: Get medical advice or attention. P304 + P340, P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor.

**Storage** 

: F405 - Store locked up.

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

**Disposal** 

: P501 - Dispose of contents and container in accordance with all local, regional.

national and international regulations.

result in classification

Other hazards which do not : Sanding and grinding dusts may be harmful if inhaled. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat. Emits toxic fumes when heated.

See toxicological information (Section 11)

### **SECTION 3: Composition/information on ingredients**

Substance/mixture

Mixture

**Product name** 

: AMERCOAT 965 POWDER

Other means of identification

: Not applicable.

Ingredient name	%	CAS number
rystalline silica, respirable powder (<10 microns)	≥50 - ≤75 ≥20 - ≤50	14808-60-7
Cement, portland, chemicals	≥20 - ≥30	65997-15-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Mexico Page: 2/1
------------------

Product code AT965-3P/03 Version 3 Date of issue 4 June 2024

Product name AMERCOAT 965 POWDER

### SECTION 4: First aid measures

### **Description of necessary first aid measures**

: Check for and remove any contact lenses. Immediately flush eyes with running Eye contact

water for at least 15 minutes, keeping eyelids open. Seek immediate medical

attention.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

: If swallowed, seek medical advice immediately and show this container or label. Ingestion

Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

### Potential acute health effects

Eye contact : Causes serious eye damage. Inhalation : May cause respiratory irritation.

: Causes skin irritation. May cause an allergic skin reaction. **Skin contact** 

: No known significant effects or critical hazards. Ingestion

#### Over-exposure signs/symptoms

See toxicological information (Section 11)

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

### **SECTION 5: Firefighting measures**

### **Extinguishing media**

Suitable extinguishing

media

**Unsuitable extinguishing** 

media

: Use dry chemical powder.

: Avoid high pressure media which could cause the formation of a potentially

explosible dust-air mixture.

Specific hazards arising from the chemical **Hazardous thermal** 

decomposition products

: Decomposition products may include the following materials: metal oxide/oxides

: May form explosible dust-air mixture if dispersed.

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk.

Use water spray to keep fire-exposed containers cool.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

> Mexico Page: 3/12

Date of issue 4 June 2024

Version 3

Product code AT965-3P/03

**Product name AMERCOAT 965 POWDER** 

### SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

**Small spill** 

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### **SECTION 7: Handling and storage**

### **Precautions for safe handling**

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe dust. Do not ingest. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Special precautions** 

: Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Mexico Page: 4/12

### **Product name AMERCOAT 965 POWDER**

### **SECTION 7: Handling and storage**

**Advice on general** occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### **SECTION 8: Exposure controls/personal protection**

#### **Control parameters**

C

### Occupational exposure limits

Ingredient name	Exposure limits
rystalline silica, respirable powder (<10 microns)  Cement, portland, chemicals	NOM-010-STPS-2014 (Mexico, 4/2016).  TWA: 0.025 mg/m³ 8 hours. Form: Respirable  NOM-010-STPS-2014 (Mexico, 4/2016).  TWA: 1 mg/m³ 8 hours. Form: Respirable fraction

#### Key to abbreviations

= Ceiling Limit = Internal Permissible Exposure Limit **IPEL** 

STEL = Short term exposure limit TLV = Threshold Limit Value = Time Weighted Average

#### Consult local authorities for acceptable exposure limits.

procedures

**Recommended monitoring**: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

Mexico Page: 5/12

**Product name AMERCOAT 965 POWDER** 

### SECTION 8: Exposure controls/personal protection

: Wash hands, forearms and face thoroughly after handling chemical products, before **Hygiene measures** 

eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

Eye/face protection

**Skin protection Hand protection**  : Chemical splash goggles and face shield.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

estimated.

**Gloves Body protection**  : butyl rubber

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

### **SECTION 9: Physical and chemical properties**

**Appearance** 

**Physical state** : Solid.

Powder.

Color : Gray.

Odor Characteristic. : Not available. **Odor threshold** Not applicable. **Molecular weight** Not applicable. : Not available. **Melting point** 

**Boiling point** Closed cup: Not applicable. Flash point

: Not applicable. **Auto-ignition temperature Decomposition temperature** : Not available. **Flammability** : Not available. Lower and upper explosive

(flammable) limits

: Not applicable.

: Not available.

**Evaporation rate** : Not available. : Not available. Vapor pressure Vapor density : Not applicable.

**Relative density** 2.75

> Mexico Page: 6/12

**Product name AMERCOAT 965 POWDER** 

### **SECTION 9: Physical and chemical properties**

**Density (lbs / gal)** : 22.95

Solubility(ies) Media Result

old water Not soluble

Solubility in water : Not available.

Partition coefficient: n- : Not applicable.

octanol/water

Viscosity : Kinematic (40°C (104°F)): Not applicable.

**Volatility** : 0% (v/v), 0% (w/w)

% Solid. (w/w) : 100

### **SECTION 10: Stability and reactivity**

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

Refer to protective measures listed in sections 7 and 8.

**Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition

products

: Depending on conditions, decomposition products may include the following materials: metal oxide/oxides

### **SECTION 11: Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Not available.

**Conclusion/Summary**: There are no data available on the mixture itself.

Irritation/Corrosion

**Conclusion/Summary** 

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

**Sensitization** 

**Conclusion/Summary** 

Skin: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

Mexico Page: 7/12

### **Product name AMERCOAT 965 POWDER**

### **SECTION 11: Toxicological information**

**Conclusion/Summary**: There are no data available on the mixture itself.

**Classification** 

Product/ingredient name	OSHA	IARC	NTP
grystalline silica, respirable powder (<10 microns)	+	1	Known to be a human carcinogen.

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA:

Not listed/not regulated: -

**Reproductive toxicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name	,	Route of exposure	Target organs
ement, portland, chemicals	Category 3		Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
ystalline silica, respirable powder (<10 microns)	Category 1	inhalation	-

#### **Target organs**

: Contains material which causes damage to the following organs: liver, spleen, bone marrow.

Contains material which may cause damage to the following organs: kidneys, lungs, upper respiratory tract, immune system, skin, eyes.

#### **Aspiration hazard**

Not available.

### Information on the likely routes of exposure

#### Potential acute health effects

Eye contact : Causes serious eye damage.Inhalation : May cause respiratory irritation.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Mexico Page: 8/12

**Product name AMERCOAT 965 POWDER** 

### **SECTION 11: Toxicological information**

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary

: There are no data available on the mixture itself. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Repeated exposure of the eyes to a low level of dust can produce eye irritation. Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

**Short term exposure** 

**Potential immediate** 

effects

: There are no data available on the mixture itself.

**Potential delayed effects** 

: There are no data available on the mixture itself.

Long term exposure

**Potential immediate** 

effects

: There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

**General** 

: Causes damage to organs through prolonged or repeated exposure. Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity

: May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity
Reproductive toxicity

No known significant effects or critical hazards.
No known significant effects or critical hazards.

**Numerical measures of toxicity** 

**Acute toxicity estimates** 

N/A

### **SECTION 12: Ecological information**

#### **Toxicity**

Not available.

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

Mexico Page: 9/12

**Product name AMERCOAT 965 POWDER** 

### **SECTION 12: Ecological information**

**Mobility in soil** 

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

### SECTION 13: Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL

PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

### **SECTION 14: Transport information**

	<b>Mexico Classification</b>	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

### **Additional information**

Mexico: None identified.IMDG: None identified.IATA: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Mexico Page: 10/12

Product code AT965-3P/03 Version 3 Date of issue 4 June 2024

**Product name AMERCOAT 965 POWDER** 

### SECTION 14: Transport information

Transport in bulk according : Not applicable.

to IMO instruments

### **SECTION 15: Regulatory information**

**Mexico** 

Classification

Flammability : 0 Health: 3 Reactivity:

**International regulations** 

**Montreal Protocol** 

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### SECTION 16: Other information

**Hazardous Material Information System (U.S.A.)** 

Health: 3 Flammability: 70 Physical hazards:

(\*) - Chronic

effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

: 1/9/2019 Date of previous issue **Organization that prepared** : EHS

the SDS

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not availableSGG = Segregation Group

UN = United Nations

### Indicates information that has changed from previously issued version.

#### **Notice to reader**

The information, which is based on the current knowledge of the chemical substance or mixture and applies to appropriate safety precautions for the product, is deemed correct but is not exhaustive and will be used only as a quide.

Mexico Page: 11/12

**Product name AMERCOAT 965 POWDER** 

### **SECTION 16: Other information**

### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Mexico Page: 12/12