## **SAFETY DATA SHEET**



#### Conforms to Official Mexican Standard NOM-018-STPS-2015

Date of revision 5 June 2024

Version 8

Date of issue 5 June 2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product name	: MEGASEAL SL Heavy Duty Lt Gray Comp A
Product code	: LR20140901/05
Other means of identification	: Not applicable.
Product type	: Liquid.
Relevant identified uses o	f the substance or mixture and uses advised against
Product use	: Industrial applications.
Use of the substance/ mixture	: Coating.
Uses advised against	: Not applicable.
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)
Technical Phone Number	: 888-977-4762

## **SECTION 2: Hazards identification**

Classification of the substance or mixture	<ul> <li>SKIN IRRITATION - Category 2</li> <li>EYE IRRITATION - Category 2A</li> <li>SKIN SENSITIZATION - Category 1</li> <li>Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity:</li> <li>1.7% (oral), 38.9% (dermal), 95.3% (inhalation)</li> </ul>
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	<ul> <li>H315 - Causes skin irritation.</li> <li>H317 - May cause an allergic skin reaction.</li> <li>H319 - Causes serious eye irritation.</li> </ul>
Precautionary statements	

#### Product name MEGASEAL SL Heavy Duty Lt Gray Comp A

### **SECTION 2: Hazards identification**

Prevention	:	<ul> <li>P280 - Wear protective gloves. Wear eye or face protection.</li> <li>P261 - Avoid breathing vapor.</li> <li>P264 - Wash thoroughly after handling.</li> <li>P272 - Contaminated work clothing should not be allowed out of the workplace.</li> </ul>
Response	:	<ul> <li>P362 + P364 - Take off contaminated clothing and wash it before reuse.</li> <li>P302 + P352 - IF ON SKIN: Wash with plenty of water.</li> <li>P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.</li> <li>P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.</li> <li>Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P337 + P313 - If eye irritation persists: Get medical advice or attention.</li> </ul>
Storage	:	Not applicable.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	:	Contains a substance that may emit formaldehyde if stored beyond its shelf life and/ or during cure at curing temperatures greater than 60C (140F). Emits toxic fumes when heated.
See toxicological information	<u>، رو</u>	Section 11)

See toxicological information (Section 11)

## **SECTION 3: Composition/information on ingredients**

Substance/mixture Product name	: Mixture : MEGASEAL SL Heavy Duty Lt Gray Comp A	
Other means of identification	: Not applicable.	

Ingredient name	%	CAS number
s-[4-(2,3-epoxipropoxi)phenyl]propane	≥50 - ≤75	1675-54-3
Formaldehyde, oligomeric reaction products with 1-chloro-	≥20 - ≤50	9003-36-5
2,3-epoxypropane and phenol		
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	≥10 - ≤20	68609-97-2
titanium dioxide	≥1.0 - ≤5.0	13463-67-7
Formaldehyde, polymer with 1,3-dimethylbenzene	≥1.0 - ≤5.0	26139-75-3
maleic anhydride	<0.10	108-31-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### **SECTION 4: First aid measures**

Description of	f necessary	/ first aid	measures	

	Mexico Page: 2/12
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Product name MEGASEAL SL Heavy Duty Lt Gray Comp A

## **SECTION 4: First aid measures**

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

See toxicological information (Section 11)

Indication of immediate med	ical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

## **SECTION 5: Firefighting measures**

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides Formaldehyde.
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	<ul> <li>Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.</li> </ul>

## **SECTION 6: Accidental release measures**

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
	inadequate. Put on appropriate personal protective equipment.

## Product name MEGASEAL SL Heavy Duty Lt Gray Comp A

## **SECTION 6: Accidental release measures**

For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nt	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## **SECTION 7: Handling and storage**

#### Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	:	Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Product name MEGASEAL SL Heavy Duty Lt Gray Comp A

## **SECTION 8: Exposure controls/personal protection**

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits
pris-[4-(2,3-epoxipropoxi)phenyl]propane	None.
Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol	None.
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	None.
titanium dioxide	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 10 mg/m <sup>3</sup> 8 hours.
Formaldehyde, polymer with 1,3-dimethylbenzene	None.
maleic anhydride	NOM-010-STPS-2014 (Mexico, 4/2016).
•	Skin sensitizer. Inhalation sensitizer.
	TWA: 0.01 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction and vapor

	Rey to appreviations	
C = Ceiling Limit	-	STEL = Short term exposure limit
IPEL = Internal Permissible Expo	sure Limit	TLV = Threshold Limit Value TWA = Time Weighted Average
Consult local authorities for	acceptable exposure limits.	
Recommended monitoring procedures		o appropriate monitoring standards. Reference to for methods for the determination of hazardous red.
Appropriate engineering controls	: Good general ventilation show contaminants.	uld be sufficient to control worker exposure to airborne
Environmental exposure controls	they comply with the requiren cases, fume scrubbers, filters	work process equipment should be checked to ensure nents of environmental protection legislation. In some or engineering modifications to the process to reduce emissions to acceptable levels.

Individual protection measur	es	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	1	Chemical splash goggles.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	1	butyl rubber
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Product name MEGASEAL SL Heavy Duty Lt Gray Comp A

## **SECTION 8: Exposure controls/personal protection**

Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

## **SECTION 9: Physical and chemical properties**

<u>Appearance</u>			
Physical state	:	Liquid.	
Color	:	Gray.	
Odor	:	Characteristic.	
Odor threshold	:	Not available.	
Molecular weight	1	Not applicable.	
рН	÷	Not applicable.	
Melting point		Not available.	
Boiling point		>37.78°C (>100°F)	
Flash point	4	Closed cup: 110°C (230°F)	
Auto-ignition temperature	1	Not available.	
Decomposition temperature	:	Not available.	
Flammability		Not available.	
Lower and upper explosive (flammable) limits	÷	Not available.	
Evaporation rate	:	Not available.	
Vapor pressure	:	Not available.	
Vapor density	:	Not available.	
Relative density	:	1.14	
Density(lbs / gal)	1	9.51	
Colubility/icc)		Media F	Result
Solubility(ies)	1	old water	Not soluble
Solubility in water	:	Not available.	
Partition coefficient: n- octanol/water	1	Not applicable.	
Viscosity	:	Kinematic (40°C (104°F)): >2	21 mm²/s (>21 cSt)
Volatility	1	0% (v/v), 0.002% (w/w)	
% Solid. (w/w)	4	99.998	

## **SECTION 10: Stability and reactivity**

	Mexico Page: 6/12
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Chemical stability	: The product is stable.
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.

#### Product name MEGASEAL SL Heavy Duty Lt Gray Comp A

## **SECTION 10: Stability and reactivity**

Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials carbon oxides halogenated compounds Formaldehyde. metal oxide/oxides

## **SECTION 11: Toxicological information**

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ቓís-[4-(2,3-epoxipropoxi) phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	LD50 Oral	Rat	>10000 mg/kg	-
oxirane, mono[ (C12-14-alkyloxy)methyl] derivs.	LD50 Oral	Rat	17100 mg/kg	-
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
maleic anhydride	LD50 Dermal	Rabbit	2620 mg/kg	-
	LD50 Oral	Rat	400 mg/kg	-

: There are no data available on the mixture itself.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
s-[4-(2,3-epoxipropoxi) phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
	Skin - Edema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-

Conclusion/Summary Skin

: There are no data available on the mixture itself.

Eyes Respiratory There are no data available on the mixture itself.There are no data available on the mixture itself.

**Sensitization** 

Mexico Page: 7/12

Date of issue 5 June 2024

Version 8

#### Product name MEGASEAL SL Heavy Duty Lt Gray Comp A

## **SECTION 11: Toxicological information**

Product/ingredient name	Route of exposure		Species	Result
øís-[4-(2,3-epoxipropoxi) phenyl]propane	skin		Mouse	Sensitizing
oxirane, mono[ (C12-14-alkyloxy)methyl] derivs.	skin		Guinea pig	Sensitizing
Conclusion/Summary				
Skin	: There a	ire no dat	ta available on the mixture itse	elf.
Respiratory	: There a	ire no dat	ta available on the mixture itse	elf.
Mutagenicity				
Conclusion/Summary	: There a	ire no dat	ta available on the mixture itse	elf.
Carcinogenicity				
Conclusion/Summary	: There a	ire no dat	ta available on the mixture itse	elf.
<b>Classification</b>				
Product/ingredient name	OSHA	IARC	NTP	
øis-[4-(2,3-epoxipropoxi) phenyl]propane	-	3	-	
titanium dioxide	- 2B -			
Carcinogen Classificatio	n code:			
IARC: 1, 2A, 2B, 3 NTP: Known to b OSHA: + Not listed/not reg	be a human ca	arcinogen;	Reasonably anticipated to be a hu	man carcinogen
Not listed/list leg				

**Conclusion/Summary** : There are no data available on the mixture itself.

#### **Teratogenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
Formaldehyde, polymer with 1,3-dimethylbenzene	Category 3		Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
maleic anhydride	Category 1	inhalation	respiratory system

Target organs

: Contains material which may cause damage to the following organs: lungs, upper respiratory tract.

#### **Aspiration hazard**

Not available.

#### Information on the likely routes of exposure

#### Potential acute health effects

Eye contact

: Causes serious eye irritation.

## Product name MEGASEAL SL Heavy Duty Lt Gray Comp A

## **SECTION 11: Toxicological information**

Inhalation		No known significant effects or critical hazards.
		0
Skin contact		Causes skin irritation. May cause an allergic skin reaction.
Ingestion		No known significant effects or critical hazards.
Over-exposure signs/sympt		_
Eye contact		Adverse symptoms may include the following: pain or irritation watering redness
Inhalation		No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Delayed and immediate effe	<u>cts</u>	and also chronic effects from short and long term exposure
Conclusion/Summary	:	There are no data available on the mixture itself. This product either contains formaldehyde or is capable of releasing formaldehyde above 0.5 ppm under certain conditions. Formaldehyde is a known cancer hazard, a skin sensitizer and a respiratory sensitizer. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
Short term exposure		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	:	There are no data available on the mixture itself.
Long term exposure		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	:	There are no data available on the mixture itself.
Potential chronic health effe	ects	
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	:	No known significant effects or critical hazards.
Numerical measures of toxic	<u>city</u>	
Acute toxicity estimates		

Product code LR20140901/05		Date of issue	5 June 2024	Vers	ion 8	
Product name MEGASEAL SL Heavy Duty Lt Gray Comp A						
SECTION 11: Toxicological info	ormation					
Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)	
is-[4-(2,3-epoxipropoxi)phenyl]propane oxirane, mono[(C12-14-alkyloxy)methyl] derivs. maleic anhydride	15000 17100 400	23000 N/A 2620	N/A N/A N/A	N/A N/A N/A	N/A N/A N/A	

## **SECTION 12: Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
ofs-[4-(2,3-epoxipropoxi) phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia magna</i>	48 hours
	Chronic NOEC 0.3 mg/l	Daphnia	21 days
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Acute LC50 2.54 mg/l	Fish	96 hours
oxirane, mono[ (C12-14-alkyloxy)methyl] derivs.	LC50 >100 mg/l	Fish	96 hours
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
pís-[4-(2,3-epoxipropoxi) phenyl]propane	-	-	Not readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane	2.7	-	Low
and phenol oxirane, mono[ (C12-14-alkyloxy)methyl] derivs.	3.77	-	Low
maleic anhydride	-2.78	-	Low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

#### Product name MEGASEAL SL Heavy Duty Lt Gray Comp A

## **SECTION 13: Disposal considerations**

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

## **SECTION 14: Transport information**

	Mexico Classification	IMDG	ΙΑΤΑ
UN number	UN3082	UN3082	UN3082
UN proper shipping name			ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl] propane, Epoxy Resin)
Transport hazard class(es)	9	9	9
Packing group			
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Not applicable.

#### **Additional information**

								Mexico	Page: 11	/12
Transport in to IMO instr		•	: Not appli	cable.						
Special pre	caution	s for user	upright a	<b>rt within user'</b> nd secure. Ens t of an accident	ure that per	sons transpo	•			
ΙΑΤΑ	:		0	ulated as a dar gs meet the ge	0 0				0,	
IMDG	:			ulated as a dar gs meet the ge						
Mexico	:	The enviro or ≤5 kg.	onmentally h	azardous subs	tance mark	is not require	d when tra	ansported in	sizes of ≤5	Ĺ

Date of issue 5 June 2024

Version 8

#### Product name MEGASEAL SL Heavy Duty Lt Gray Comp A

### **SECTION 15: Regulatory information**

#### **Mexico**

Classification

Flammability : 1 Health : 2 Reactivity : 1

#### International regulations

**Montreal Protocol** 

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

## SECTION 16: Other information

Hazardous Material Information System (U.S.A.)

Health : 2 \* Flammability : 1 Physical hazards : 1

(\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Date of previous issue Organization that prepared the SDS	: <b>7/4/2021</b> : EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations
🔽 lugali a a ta a din fa mua a ti a m tha a t	has also we al fusion was deviced a second second as

#### Indicates information that has changed from previously issued version.

#### Notice to reader

The information, which is based on the current knowledge of the chemical substance or mixture and applies to appropriate safety precautions for the product, is deemed correct but is not exhaustive and will be used only as a guide.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.