SAFETY DATA SHEET

Safety Data Sheet according to GB/T 16483-2008 and GB/T 17519-2013



Date of issue/Date of revision 11 June 2024

Version 2.02

Product type

Section 1.	Chemical product and company identification
Product code	: 00444891
Product name	: PITT-CHAR XP HARDENER BLACK PF
Product name	: PITT-CHAR XP HARDENER BLACK PF

Product use	 the substance or mixture and uses advised against Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Not applicable.
Supplier's details	: PPG Coatings (Kunshan) Co., Ltd 53 Jinyang Road, Lujia Town, 215331 Kunshan City, Jiangsu Province, P.R. China Tel: 86 512 57678859 Fax: 86 512 57678857
Emergency telephone number (with hours of operation)	: 00 86 532 83889090

: Liquid.

Section 2. Hazards identification

Classification of the substance or mixture according to GB 13690-2009 and GB 30000-2013

Emergency overview Liquid. Black. Characteristic. May be harmful if swallowed or in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. (urinary system) Toxic to aquatic life with long lasting effects. Causes digestive tract burns.

IF exposed or concerned: Get medical advice or attention. IF INHALED: Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. IF ON SKIN (or hair): Immediately call a POISON CENTER or doctor. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Immediately call a POISON CENTER or doctor.

See Section 12 for environmental precautions.

China Page: 1/14

Version 2.02

Product name PITT-CHAR XP HARDENER BLACK PF

Section 2. Hazards identification

Classification of the substance or mixture	 ACUTE TOXICITY (oral) - Category 5 ACUTE TOXICITY (dermal) - Category 5 SKIN CORROSION/IRRITATION - Category 1C SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 17.2% Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 37.2% Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 9.3%
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	 May be harmful if swallowed or in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. (urinary system) Toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
Response	: Collect spillage. IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Storage	: Store locked up.

Date of issue 11 June 2024

Product name PITT-CHAR XP HARDENER BLACK PF

Section 2. Hazards identification

Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Physical and chemical hazards	: No known significant effects or critical hazards.
Health hazards	: May be harmful if swallowed or in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes digestive tract burns.
Symptoms related to the p	physical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations
Delayed and immediate ef	fects and also chronic effects from short and long term exposure
Short term exposure	
Detended inclusionalists	 Net averable

Unort term exposure		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Long term exposure		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Environmental hazards	: Toxic to aquatic life with long lasting effects.	
Other hazards which do not result in classification	: Causes digestive tract burns.	

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

CAS number/other identifiers

CAS number	: Not applicable.
------------	-------------------

Ingredient name	%	CAS number
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	40 - <70	68082-29-1
melamine	10 - <25 1 - <10	108-78-1
4,4'-Isopropylidenediphenol, ethoxylated	1 - <10	32492-61-8 (EO> 4.5 moles)
2,4,6-tris(dimethylaminomethyl)phenol	1 - <10 1 - <10	90-72-2
3,6-diazaoctanethylenediamin	1 - <10	112-24-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Potential acute health effect	s	
Eye contact	:	Causes serious eye damage.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	;	Causes severe burns. May be harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	:	May be harmful if swallowed. Corrosive to the digestive tract. Causes burns.
Over-exposure signs/sympto	on	<u>ns</u>
Eye contact	:	Adverse symptoms may include the following: pain watering redness
Inhalation	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
		Ohima Barra 44

Date of issue 11 June 2024

Product name PITT-CHAR XP HARDENER BLACK PF

Section 4. First aid measures

Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths
	skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

thoroughly with water before removing it, or wear gloves.

Section 6. Accidental release measures

Personal precautions, protect	:tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and materials for co	onta	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal

local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling
 Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
--	---

Date of issue 11 June 2024

Section 8. Exposure controls/personal protection

<u>Control parameters</u>		
Occupational exposure limi	<u>ts</u>	
None.		
Recommended monitoring procedures	:	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	<u>'es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye protection	÷	Chemical splash goggles and face shield.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	1	nitrile neoprene
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Product name PITT-CHAR XP HARDENER BLACK PF

Section 8. Exposure controls/personal protection

Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

<u>Appearance</u>				
Physical state	.iquid.			
Color	Black.			
Odor	Characteristic.			
Boiling point	>37.78°C (>100°F)			
Flash point	Closed cup: Not applicable.			
Lower and upper explosive (flammable) limits	Greatest known range: Lower: 1.1% Upper: 6.4% (3,6-diazaoctanethylenedia	amin)		
Relative density	l.14			
Solubility(ies)	Media Result			
Solubility(les)	cold water Not soluble			
Viscosity	Kinematic (40°C): >21 mm²/s			

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Atty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	LD50 Dermal	Rat	>2000 mg/kg	-
,	LD50 Oral	Rat	>2000 mg/kg	-
melamine	LC50 Inhalation Dusts and mists	Rat	>5190 mg/m ³	4 hours
	LD50 Oral	Rat	3161 mg/kg	-
2,4,6-tris(dimethylaminomethyl) phenol	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
3,6-diazaoctanethylenediamin	LD50 Dermal LD50 Oral	Rabbit Rat	1465 mg/kg 1716 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Atty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Eyes - Severe irritant	Rabbit	-	-	-
	Skin - Irritant	Human	-	-	-

Sensitization

Product/ingredient name	Route of exposure	Species	Result
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	skin	Mouse	Sensitizing
3,6-diazaoctanethylenediamin	skin	Guinea pig	Sensitizing

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Section 11. Toxicological information

Name		Route of exposure	Target organs
melamine	Category 2	-	urinary system

Aspiration hazard

Not available.

Information on the likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	1	Causes serious eye damage.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	1	Causes severe burns. May be harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	:	May be harmful if swallowed. Corrosive to the digestive tract. Causes burns.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	:	Adverse symptoms may include the following: pain watering redness
Inhalation	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	:	Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	:	Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations
Delayed and immediate effect	<u>cts</u>	and also chronic effects from short and long term exposure
Short term exposure		
Potential immediate effects	1	Not available.

Potential delayed effects	4	Not available.
Long term exposure		
Potential immediate effects	1	Not available.
Potential delayed effects	:	Not available.
Potential chronic health eff	<u>ect</u>	<u>s</u>

Product name PITT-CHAR XP HARDENER BLACK PF

Section 11. Toxicological information

General	 May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	 Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
FITT-CHAR XP HARDENER BLACK PF Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	2466.2 2500	2287.6 2500	N/A N/A	N/A N/A	N/A N/A
melamine 2,4,6-tris(dimethylaminomethyl)phenol 3,6-diazaoctanethylenediamin	3161 1200 1716	N/A 1280 1465	N/A N/A N/A	N/A N/A N/A	N/A N/A N/A

Other information

Causes digestive tract burns. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Exposure to amine vapor has been reported to cause transient corneal edema described as blue haze, halo effect, foggy or blurred vision for several hours. This condition is typically temporary and does not cause permanent visual effects. When the proper eye protection specified in Section 8 is worn, exposure is significantly reduced and the condition has not been observed.

Section 12. Ecological information

<u>Toxicity</u>				
Product/ingredient name	Result	Species	Exposure	
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	EC10 1.78 mg/l	Algae	72 hours	
melamine 2,4,6-tris (dimethylaminomethyl)phenol	Acute EC50 200 mg/l Acute LC50 >100 mg/l	Daphnia Daphnia	48 hours 48 hours	
	Acute LC50 >100 mg/l	Fish	96 hours	

Persistence/degradability

Product name PITT-CHAR XP HARDENER BLACK PF

Section 12. Ecological information

Product/ingredient name	Test	Result		Dose		Inoculum
7,4,6-tris (dimethylaminomethyl)phenol	OECD 301D Ready Biodegradability - Closed Bottle Test	4 % - Not re	eadily - 28 days	-		-
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
Atty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 2,4,6-tris (dimethylaminomethyl)phenol	-		-		Not rea	

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
melamine	-1.22	3.8	Low
2,4,6-tris	0.219	-	Low
(dimethylaminomethyl)phenol			
3,6-diazaoctanethylenediamin	-1.66 to -1.4	-	Low

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of issue 11 June 2024

Version 2.02

Section 14. Transport information

	China	UN	IMDG	ΙΑΤΑ
UN number	UN3066	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	8	8	8	8
Packing group	Ш	Ш	Ш	Ш
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	(Polyamide)	Not applicable.

Additional information CN : None identified. UN : None identified. IMDG : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

China inventory (IECSC)	: All components are listed or exempted.
References	 Production Safety Law of the People's Republic of China Code of Occupational Disease Prevention of the People's Republic of China Environmental Protection Law of the People's Republic of China Fire Control Law of the People's Republic of China Regulations on the Control over Safety of Dangerous Chemicals Occupational exposure limits for hazardous agents in the workplace chemical hazardous agents (GBZ2.1) General rule for classification and hazard communication of chemicals (GB13690) Safety data sheet for chemical products - Content and order of sections (GB/ T16483) Guidance on the compilation of safety data sheet for chemical products (GB/ T17519) General rule for preparation of precautionary label for chemicals (GB15258) Safety rules for classification, precautionary labeling and precautionary statements of chemicals (GB30000.2-29)

Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 11 June 2024
Date of previous issue	: 3/20/2024
Version	: 2.02
	EHS
Key to abbreviations	: ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
	ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships,
	1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
	UN = United Nations

✓ Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.