SAFETY DATA SHEET



Date of issue/Date of revision 28 June 2024

Version 3.02

Section 1. Identification of the substance/mixture and of the company/undertaking

Product code : 000001099950

Product name : SIGMAGLIDE 1290 BASE REDBROWN

Other means of : 00332867

identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Coating.

Professional applications, Used by spraying.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

Supplier's details : PPG Coatings (Thailand) Co., Ltd.

15 Rama 9 Road, Kwaeng Huamark, Khet Bangkapi, Bangkok 10240 Thailand

T: 662-319-4190 #224 F: 662-319-4189

Emergency telephone number (with hours of

operation)

: CHEMTREC 001-800-13-203-9987 (CCN 17704)

Section 2. Hazards identification

Classification of the substance or mixture

: FLAMMABLE LIQUIDS - Category 3
ACUTE TOXICITY (dermal) - Category 5
SKIN CORROSION/IRRITATION - Category 3

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

AQUATIC HAZARD (LONG-TERM) - Category 3

Percentage of the mixture consisting of ingredient(s) of unknown acute dermal

toxicity: 91.9%

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the

aquatic environment: 31.2%

GHS label elements

Thailand Page: 1/13

Section 2. Hazards identification

Hazard pictograms







Signal word : Danger

Hazard statements : Flammable liquid and vapor.

May be harmful in contact with skin.

Causes mild skin irritation. Causes serious eye damage.

Causes damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : Wear protective gloves, protective clothing and eye or face protection. Keep away

> from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use nonsparking tools. Take action to prevent static discharges. Keep container tightly closed. Avoid release to the environment. Do not breathe vapor. Do not eat, drink

or smoke when using this product. Wash thoroughly after handling.

: Get medical advice or attention if you feel unwell. IF ON SKIN (or hair): Take off Response

immediately all contaminated clothing. Rinse skin with water. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately

call a POISON CENTER or doctor.

Storage : Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents and container in accordance with all local, regional, national

and international regulations.

result in classification

Other hazards which do not : Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

CAS number/other identifiers

CAS number : Not applicable.

| Ingredient name | % | CAS number |
|------------------------------|-------------------|-----------------------|
| ristobalite (<10 microns) | 10- <20 3 - <5 | 14464-46-1 78-83-1 |
| | | 69430-24-6 |
| octamethylcyclotetrasiloxane | <0.1 | 556-67-2 |

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

| Thailand Pa | age: 2/13 |
|-------------|-----------|
|-------------|-----------|

Product code 000001099950 Date of issue 28 June 2024 Version 3.02

Product name SIGMAGLIDE 1290 BASE REDBROWN

Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with running

water for at least 15 minutes, keeping eyelids open. Seek immediate medical

attention.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact : May be harmful in contact with skin. Causes mild skin irritation. Defatting to the

skin.

Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness dryness cracking

blistering may occur

Ingestion: Adverse symptoms may include the following:

stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

Thailand Page: 3/13

Date of issue 28 June 2024 Version 3.02

Product code 000001099950

Product name SIGMAGLIDE 1290 BASE REDBROWN

Section 4. First aid measures

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media

: Do not use water jet.

Specific hazards arising from the chemical

: Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials: carbon oxides metal oxide/oxides

Formaldehyde.

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

> **Thailand** Page: 4/13

Date of issue 28 June 2024

Product code 000001099950

Product name SIGMAGLIDE 1290 BASE REDBROWN

Version 3.02

Section 6. Accidental release measures

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

including any incompatibilities

Conditions for safe storage, : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

> **Thailand** Page: 5/13

Version 3.02

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|----------------------------|---|
| øristobalite (<10 microns) | Ministry of Labor (Thailand, 8/2017). [crystalline silica] |
| | TWA: 0.025 mg/m³ 8 hours. Form: Respirable dust |
| 2-methylpropan-1-ol | ACGIH TLV (United States, 7/2023). TWA: 152 mg/m³ 8 hours. TWA: 50 ppm 8 hours. |

procedures

Recommended monitoring: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection Skin protection **Hand protection**

: Chemical splash goggles and face shield.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

Gloves

: For prolonged or repeated handling, use the following type of gloves:

Recommended: butyl rubber, nitrile rubber

Thailand Page: 6/13 Product code 000001099950 Date of issue 28 June 2024 Version 3.02

Product name SIGMAGLIDE 1290 BASE REDBROWN

Section 8. Exposure controls/personal protection

Body protection : Personal protective equipment for the body should be selected based on the task

> being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static

discharges, clothing should include anti-static overalls, boots and gloves.

: Appropriate footwear and any additional skin protection measures should be Other skin protection

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respirator selection must be based on known or anticipated exposure levels, the Respiratory protection

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.

Color : Brownish-red. Odor Characteristic. **Odor threshold** : Not available. pН : insoluble in water.

: May start to solidify at the following temperature: <-90°C (<-130°F) This is based on **Melting point**

data for the following ingredient: 2-methylpropan-1-ol.

: >37.78°C (>100°F) **Boiling point**

Flash point : Closed cup: 38°C (100.4°F) [Product does not sustain combustion.]

Evaporation rate : 0.64 (2-methylpropan-1-ol) compared with butyl acetate

Flammability (solid, gas) : liquid

Lower and upper explosive

(flammable) limits

: Not applicable.

Vapor pressure : Highest known value: <1.6 kPa (<12 mm Hg) (at 20°C) (2-methylpropan-1-ol).

Highest known value: 2.55 (Air = 1) (2-methylpropan-1-ol). Vapor density

Relative density 1.14

Media Result Solubility(ies)

cold water Not soluble

Partition coefficient: n-

octanol/water

Not applicable.

Auto-ignition temperature

: Not applicable.

Decomposition temperature :

Stable under recommended storage and handling conditions (see Section 7).

Viscosity : Kinematic (40°C): >21 mm²/s

Viscosity : 30 - <40 s (ISO 6mm)

Thailand Page: 7/13 Product code 000001099950 Date of issue 28 June 2024 Version 3.02

Product name SIGMAGLIDE 1290 BASE REDBROWN

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

Incompatible materials: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

: Depending on conditions, decomposition products may include the following

materials: carbon oxides Formaldehyde. metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|------------------------------|-----------------------|---------|-------------|----------|
| 2 -methylpropan-1-ol | LC50 Inhalation Vapor | Rat | 24.6 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | 2460 mg/kg | - |
| | LD50 Oral | Rat | 2830 mg/kg | - |
| octamethylcyclotetrasiloxane | LC50 Inhalation Vapor | Rat | 36 g/m³ | 4 hours |
| | LD50 Dermal | Rat | >2375 mg/kg | - |
| | LD50 Oral | Rat | >4800 mg/kg | - |

Conclusion/Summary: There are no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary

Skin : There are no data available on the mixture itself.
 Eyes : There are no data available on the mixture itself.
 Respiratory : There are no data available on the mixture itself.

Sensitization

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Thailand Page: 8/13

Product code 000001099950 Date of issue 28 June 2024 Version 3.02

Product name SIGMAGLIDE 1290 BASE REDBROWN

Section 11. Toxicological information

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

| Name | | Route of exposure | Target organs |
|------|--------------------------|-------------------|--|
| 1 . | Category 3 Category 3 | - | Respiratory tract irritation Narcotic effects |

Specific target organ toxicity (repeated exposure)

| Name | 3.3 | Route of exposure | Target organs |
|----------------------------|------------|-------------------|---------------|
| cristobalite (<10 microns) | Category 1 | inhalation | - |

Aspiration hazard

| Name | Result |
|---------------------|--------------------------------|
| 2-methylpropan-1-ol | ASPIRATION HAZARD - Category 2 |

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact : May be harmful in contact with skin. Causes mild skin irritation. Defatting to the

skin.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness dryness cracking

blistering may occur

Ingestion: Adverse symptoms may include the following:

stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

| Thailand Pa |
|-------------|
|-------------|

Product name SIGMAGLIDE 1290 BASE REDBROWN

Section 11. Toxicological information

Short term exposure

Potential immediate

effects

: Not available.

Potential delayed effects

: Not available.

Long term exposure

Potential immediate

effects

: Not available.

Potential delayed effects

: Not available.

Potential chronic health effects

General

: Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

| Route | ATE value |
|-------|---------------------------------|
| | 55156.56 mg/kg 4992.77 mg/kg |

Other information

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C (140F). Avoid contact with skin and clothing.

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|---|---------|---------------------|
| | Acute EC50 1100 mg/l Chronic NOEC 100 mg/l Fresh water | • | 48 hours 21 days |

Conclusion/Summary: There are no data available on the mixture itself.

Persistence/degradability

Not available.

Conclusion/Summary: There are no data available on the mixture itself.

| Thailand Pag | ge: 10/13 |
|--------------|-----------|
|--------------|-----------|

Product name SIGMAGLIDE 1290 BASE REDBROWN

Section 12. Ecological information

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential | |
|------------------------------|--------|-----|-----------|---|
| 2 -methylpropan-1-ol | 1 | - | Low | l |
| octamethylcyclotetrasiloxane | 6.488 | - | High | l |

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | UN | IMDG | IATA |
|-----------------------------|-----------------|-----------------|-----------------|
| UN number | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name | - | - | - |
| Transport hazard class(es) | - | - | - |
| Packing group | - | - | - |
| Environmental hazards | No. | No. | No. |
| Marine pollutant substances | Not applicable. | Not applicable. | Not applicable. |

Additional information

Class 3 is not applicable. Product does not sustain combustion.

UN : None identified.

Thailand Page: 11/13

Product code 000001099950 Date of issue 28 June 2024 Version 3.02

Product name SIGMAGLIDE 1290 BASE REDBROWN

Section 14. Transport information

IMDG : None identified. **IATA** : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

Section 15. Regulatory information

Harmful Chemicals List

Safety, health and environmental regulations specific for the product

Listed

: No known specific national and/or regional regulations applicable to this product (including its ingredients).

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Section 16. Other information

History

Date of issue/Date of

revision

: 28 June 2024

Date of previous issue 6/22/2023

3.02 Version **Prepared by** : EHS

: ADN = European Provisions concerning the International Carriage of Dangerous Key to abbreviations

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations

Thailand Page: 12/13 **Product name SIGMAGLIDE 1290 BASE REDBROWN**

Section 16. Other information

▼ Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Thailand Page: 13/13