

SAFETY DATA SHEET



Date of issue/Date of revision

: 9 July 2024

Version

: 1.05

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : PPG VIKOTE 56 BASE (TINTED)

Product code : 000001166645

Other means of identification

00154010; 00154011; 00392293; 00393323

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

**Use of the substance/
mixture** : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL
Tweemontstraat 104
B-2100 Deurne
Belgium
Telephone +32-33606311
Fax +32-33606435

**e-mail address of person
responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226
Skin Irrit. 2, H315
Eye Irrit. 2, H319
Lact., H362
STOT SE 3, H335
STOT SE 3, H336
Aquatic Acute 1, H400
Aquatic Chronic 1, H410

Code	: 000001166645	Date of issue/Date of revision	: 9 July 2024
PPG VIKOTE 56 BASE (TINTED)			

SECTION 2: Hazards identification

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause harm to breast-fed children. Very toxic to aquatic life with long lasting effects.
Prevention	:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Avoid contact during pregnancy and while nursing.
Response	:	Collect spillage.
Storage	:	Store in a well-ventilated place. Keep container tightly closed.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations. P210, P273, P263, P391, P403 + P233, P501
Hazardous ingredients	:	Hydrocarbons, C9, aromatics < 0.1% cumene alkanes, C14-17, chloro
Supplemental label elements	:	Contains 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene, methyl methacrylate and n-butyl methacrylate. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
<u>Special packaging requirements</u>		
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB	:	This mixture contains substances that are assessed to be a PBT or a vPvB, refer to Section 3.2.
Other hazards which do not result in classification	:	Prolonged or repeated contact may dry skin and cause irritation.

Code	: 000001166645	Date of issue/Date of revision	: 9 July 2024
PPG VIKOTE 56 BASE (TINTED)			

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Hydrocarbons, C9, aromatics < 0.1% cumene	REACH #: 01-2119455851-35 EC: 918-668-5 CAS: 128601-23-0	≥25 - ≤50	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	EUH066: C ≥ 20%	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7	≥10 - ≤25	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1700 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
alkanes, C14-17, chloro	REACH #: 01-2119519269-33 EC: 287-477-0 CAS: 85535-85-9 Index: 602-095-00-X	≥1.0 - ≤5.0	Lact., H362 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH066	M [Acute] = 100 M [Chronic] = 10	[1] [3] [4]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Inhalation (vapours)] = 17.8 mg/l	[1] [2]
2-methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6 Index: 607-195-00-7	≥1.0 - ≤5.0	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene	REACH #: 01-2119962189-26 CAS: 911674-82-3 Index: 616-198-00-2	<1.0	Skin Sens. 1, H317 Aquatic Chronic 4, H413	-	[1] [2]
methyl methacrylate	REACH #: 01-2119452498-28 EC: 201-297-1 CAS: 80-62-6 Index: 607-035-00-6	≤0.30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335	-	[1] [2]
n-butyl methacrylate	REACH #: 01-2119486394-28 EC: 202-615-1 CAS: 97-88-1 Index: 607-033-00-5	≤0.30	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335	-	[1] [2]

Code	: 000001166645	Date of issue/Date of revision	: 9 July 2024
PPG VIKOTE 56 BASE (TINTED)			

SECTION 3: Composition/information on ingredients

			See Section 16 for the full text of the H statements declared above.		
--	--	--	--	--	--

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact : Causes serious eye irritation.
- Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact : Causes skin irritation. Defatting to the skin.
- Ingestion : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

- Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

Code	: 000001166645	Date of issue/Date of revision	: 9 July 2024
PPG VIKOTE 56 BASE (TINTED)			

SECTION 4: First aid measures

	reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness dryness cracking reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	: Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: ☒ Decomposition products may include the following materials: carbon oxides metal oxide/oxides

5.3 Advice for firefighters

Special precautions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Code	: 000001166645	Date of issue/Date of revision	: 9 July 2024
PPG VIKOTE 56 BASE (TINTED)			

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid contact during pregnancy or while nursing. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Code	: 000001166645	Date of issue/Date of revision	: 9 July 2024
PPG VIKOTE 56 BASE (TINTED)			

SECTION 7: Handling and storage

Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
xylene	EU OEL (Europe, 1/2022). [xylene, mixed isomers] Absorbed through skin. STEL: 442 mg/m³ 15 minutes. STEL: 100 ppm 15 minutes. TWA: 221 mg/m³ 8 hours. TWA: 50 ppm 8 hours.
ethylbenzene	EU OEL (Europe, 1/2022). Absorbed through skin. STEL: 884 mg/m³ 15 minutes. STEL: 200 ppm 15 minutes. TWA: 442 mg/m³ 8 hours. TWA: 100 ppm 8 hours.
2-methoxy-1-methylethyl acetate	EU OEL (Europe, 1/2022). Absorbed through skin. STEL: 550 mg/m³ 15 minutes. STEL: 100 ppm 15 minutes. TWA: 275 mg/m³ 8 hours. TWA: 50 ppm 8 hours.
1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene	ACGIH TLV (United States). TWA: 3 mg/m³, (Respirable fraction)
methyl methacrylate	EU OEL (Europe, 1/2022). TWA: 50 ppm 8 hours. STEL: 100 ppm 15 minutes.
n-butyl methacrylate	IPEL (-). TWA: 50 ppm STEL: 75 ppm

Code	: 000001166645	Date of issue/Date of revision	: 9 July 2024
PPG VIKOTE 56 BASE (TINTED)			

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Hydrocarbons, C9, aromatics < 0.1% cumene xylene	DNEL	Long term Dermal	25 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	150 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	11 mg/kg	General population	Systemic
	DNEL	Long term Oral	11 mg/kg	General population	Systemic
	DNEL	Long term Inhalation	32 mg/m³	General population	Systemic
	DNEL	Long term Oral	5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	65.3 mg/m³	General population	Local
	DNEL	Long term Inhalation	65.3 mg/m³	General population	Systemic
	DNEL	Long term Dermal	125 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	221 mg/m³	Workers	Local
	DNEL	Long term Inhalation	221 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	260 mg/m³	General population	Local
	DNEL	Short term Inhalation	260 mg/m³	General population	Systemic
alkanes, C14-17, chloro	DNEL	Short term Inhalation	442 mg/m³	Workers	Local
	DNEL	Short term Inhalation	442 mg/m³	Workers	Systemic
	DNEL	Long term Oral	0.58 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	2 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	6.7 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	28.75 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	47.9 mg/kg bw/day	Workers	Systemic
	DMEL	Long term Inhalation	442 mg/m³	Workers	Local
	DMEL	Short term Inhalation	884 mg/m³	Workers	Systemic
	DNEL	Long term Oral	1.6 mg/kg bw/day	General population	Systemic
ethylbenzene	DNEL	Long term Inhalation	15 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	77 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	293 mg/m³	Workers	Local
	DNEL	Long term Inhalation	33 mg/m³	General population	Local
	DNEL	Long term Inhalation	33 mg/m³	General population	Systemic
	DNEL	Long term Oral	36 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	275 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	320 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	550 mg/m³	Workers	Local
2-methoxy-1-methylethyl acetate	DNEL	Long term Dermal	796 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	1.5 mg/cm²	General population	Local
	DNEL	Long term Dermal	1.5 mg/cm²	General population	Local
	DNEL	Short term Dermal	1.5 mg/cm²	Workers	Local
	DNEL	Long term Dermal	1.5 mg/cm²	Workers	Local
	DNEL	Long term Oral	8.2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	8.2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	13.67 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	74.3 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	74.3 mg/m³	General population	Systemic
methyl methacrylate	DNEL	Long term Inhalation	33 mg/m³	General population	Systemic
	DNEL	Long term Oral	36 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	275 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	320 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	550 mg/m³	Workers	Local
	DNEL	Long term Dermal	796 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	1.5 mg/cm²	General population	Local
	DNEL	Long term Dermal	1.5 mg/cm²	General population	Local
	DNEL	Short term Dermal	1.5 mg/cm²	Workers	Local
	DNEL	Long term Dermal	1.5 mg/cm²	Workers	Local

Code	: 000001166645	Date of issue/Date of revision	: 9 July 2024
PPG VIKOTE 56 BASE (TINTED)			

SECTION 8: Exposure controls/personal protection

n-butyl methacrylate	DNEL	Long term Inhalation	104 mg/m³	General population	Local
	DNEL	Short term Inhalation	208 mg/m³	General population	Local
	DNEL	Long term Inhalation	208 mg/m³	Workers	Local
	DNEL	Long term Inhalation	348.4 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	416 mg/m³	Workers	Local
	DNEL	Long term Dermal	3 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	66.5 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	366.4 mg/m³	General population	Local
	DNEL	Long term Inhalation	409 mg/m³	Workers	Local
	DNEL	Long term Inhalation	415.9 mg/m³	Workers	Systemic

PNECs

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
Xylene	-	Fresh water	0.327 mg/l	-
	-	Marine water	0.327 mg/l	-
	-	Sewage Treatment Plant	6.58 mg/l	-
	-	Fresh water sediment	12.46 mg/kg dwt	-
	-	Marine water sediment	12.46 mg/kg dwt	-
	-	Soil	2.31 mg/kg	-
ethylbenzene	-	Fresh water	0.1 mg/l	Assessment Factors
	-	Marine water	0.01 mg/l	Assessment Factors
	-	Sewage Treatment Plant	9.6 mg/l	Assessment Factors
	-	Fresh water sediment	13.7 mg/kg dwt	Equilibrium Partitioning
	-	Marine water sediment	1.37 mg/kg dwt	Equilibrium Partitioning
	-	Soil	2.68 mg/kg dwt	Equilibrium Partitioning
2-methoxy-1-methylethyl acetate	-	Secondary Poisoning	20 mg/kg	-
	-	Fresh water	0.635 mg/l	-
	-	Marine water	0.0635 mg/l	-
	-	Fresh water sediment	3.29 mg/kg	-
	-	Marine water sediment	0.329 mg/kg	-
	-	Soil	0.29 mg/kg	-
	-	Sewage Treatment Plant	100 mg/l	-

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles. Use eye protection according to EN 166.

Skin protection

Hand protection :

Code	: 000001166645	Date of issue/Date of revision	: 9 July 2024
PPG VIKOTE 56 BASE (TINTED)			

SECTION 8: Exposure controls/personal protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves	:  For prolonged or repeated handling, use the following type of gloves: Recommended: polyvinyl alcohol (PVA), Viton®, butyl rubber May be used: nitrile rubber, Chloroprene
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapor (Type A) and particulate filter P3
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Various
Odor	: Aromatic.
Odor threshold	: Not available.
Melting point/freezing point	:  May start to solidify at the following temperature: -50 to 25°C (-58 to 77°F) This is based on data for the following ingredient: alkanes, C14-17, chloro. Weighted average: -67.39°C (-89.3°F)

Code	: 000001166645	Date of issue/Date of revision	: 9 July 2024
PPG VIKOTE 56 BASE (TINTED)			

SECTION 9: Physical and chemical properties

Initial boiling point and boiling range	: >37.78°C																				
Flammability	: Not available.																				
Upper/lower flammability or explosive limits	: Greatest known range: Lower: 1.4% Upper: 7.6% (Solvent naphtha (petroleum), light aromatic)																				
Flash point	: Closed cup: 34°C																				
Auto-ignition temperature	:																				
<table><tr><th>Ingredient name</th><th>°C</th><th>°F</th><th>Method</th></tr><tr><td>Hydrocarbons, C9, aromatics < 0.1% cumene</td><td>280 to 470</td><td>536 to 878</td><td></td></tr></table>		Ingredient name	°C	°F	Method	Hydrocarbons, C9, aromatics < 0.1% cumene	280 to 470	536 to 878													
Ingredient name	°C	°F	Method																		
Hydrocarbons, C9, aromatics < 0.1% cumene	280 to 470	536 to 878																			
Decomposition temperature	: Stable under recommended storage and handling conditions (see Section 7).																				
pH	: Not applicable.																				
Viscosity	: Kinematic (40°C): >21 mm²/s																				
Solubility(ies)	:																				
<table><tr><th>Media</th><th>Result</th></tr><tr><td>cold water</td><td>Not soluble</td></tr></table>		Media	Result	cold water	Not soluble																
Media	Result																				
cold water	Not soluble																				
Partition coefficient: n-octanol/ water	: Not applicable.																				
Vapor pressure	:																				
<table><tr><th rowspan="2">Ingredient name</th><th colspan="3">Vapor Pressure at 20°C</th><th colspan="3">Vapor pressure at 50°C</th></tr><tr><th>mm Hg</th><th>kPa</th><th>Method</th><th>mm Hg</th><th>kPa</th><th>Method</th></tr><tr><td>Ethylbenzene</td><td>9.30076</td><td>1.2</td><td></td><td></td><td></td><td></td></tr></table>		Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C			mm Hg	kPa	Method	mm Hg	kPa	Method	Ethylbenzene	9.30076	1.2				
Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C																	
	mm Hg	kPa	Method	mm Hg	kPa	Method															
Ethylbenzene	9.30076	1.2																			
Evaporation rate	: Highest known value: 0.84 (ethylbenzene) Weighted average: 0.74compared with butyl acetate																				
Relative density	: 1.04																				
Vapor density	: Highest known value: 4.6 (Air = 1) (2-methoxy-1-methylethyl acetate). Weighted average: 3.95 (Air = 1)																				
Explosive properties	: The product itself is not explosive, but the formation of an explosible mixture of vapor or dust with air is possible.																				
Oxidizing properties	: Product does not present an oxidizing hazard.																				
Particle characteristics																					
Median particle size	: Not applicable.																				

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.

Code	: 000001166645	Date of issue/Date of revision	: 9 July 2024
PPG VIKOTE 56 BASE (TINTED)			

SECTION 10: Stability and reactivity

Refer to protective measures listed in sections 7 and 8.

- 10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:
oxidizing agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials:
carbon oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Hydrocarbons, C9, aromatics < 0.1% cumene	LD50 Dermal	Rabbit - Male, Female	>2000 mg/kg	-
xylene	LD50 Oral	Rat	8400 mg/kg	-
	LD50 Dermal	Rabbit	1.7 g/kg	-
alkanes, C14-17, chloro	LD50 Oral	Rat	4.3 g/kg	-
	LC50 Inhalation Vapor	Rat	>48.17 g/m³	1 hours
ethylbenzene	LD50 Oral	Rat	>5 g/kg	-
	LC50 Inhalation Vapor	Rat	17.8 mg/l	4 hours
2-methoxy-1-methylethyl acetate	LD50 Dermal	Rabbit	17.8 g/kg	-
	LD50 Oral	Rat	3.5 g/kg	-
	LC50 Inhalation Vapor	Rat	30 mg/l	4 hours
1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	6190 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>5.08 mg/l	4 hours
methyl methacrylate	LC50 Inhalation Vapor	Rat	78000 mg/m³	4 hours
	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	7872 mg/kg	-
	LC50 Inhalation Gas.	Rat	4910 ppm	4 hours
	LC50 Inhalation Vapor	Rat	29000 mg/m³	4 hours
	LD50 Dermal	Rabbit	10.2 g/kg	-
n-butyl methacrylate	LD50 Oral	Rat	16 g/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

Route	ATE value
Dermal	10920.55 mg/kg
Inhalation (vapors)	63.6 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

- Conclusion/Summary
- Skin : There are no data available on the mixture itself.
- Eyes : There are no data available on the mixture itself.
- Respiratory : There are no data available on the mixture itself.

Sensitization

Conclusion/Summary

Code	: 000001166645	Date of issue/Date of revision	: 9 July 2024
PPG VIKOTE 56 BASE (TINTED)			

SECTION 11: Toxicological information

Skin : There are no data available on the mixture itself.
Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Hydrocarbons, C9, aromatics < 0.1% cumene	Category 3	-	Respiratory tract irritation
xylene	Category 3	-	Narcotic effects
2-methoxy-1-methylethyl acetate	Category 3	-	Respiratory tract irritation
methyl methacrylate	Category 3	-	Narcotic effects
n-butyl methacrylate	Category 3	-	Respiratory tract irritation
ethylbenzene	Category 2	-	Respiratory tract irritation

Information on the likely routes of exposure : Not available.

Potential acute health effects

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
Ingestion : Can cause central nervous system (CNS) depression.
Skin contact : Causes skin irritation. Defatting to the skin.
Eye contact : Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
Ingestion : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Code	: 000001166645	Date of issue/Date of revision	: 9 July 2024
PPG VIKOTE 56 BASE (TINTED)			

SECTION 11: Toxicological information

- Skin contact** : Adverse symptoms may include the following:
- irritation
 - redness
 - dryness
 - cracking
 - reduced fetal weight
 - increase in fetal deaths
 - skeletal malformations
- Eye contact** : Adverse symptoms may include the following:
- pain or irritation
 - watering
 - redness

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- Conclusion/Summary** : Not available.
- General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : May cause harm to breast-fed children.
- Other information** : Not available.

 Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Code	: 000001166645	Date of issue/Date of revision	: 9 July 2024
PPG VIKOTE 56 BASE (TINTED)			

SECTION 12: Ecological information

Product/ingredient name	Result	Species	Exposure
Hydrocarbons, C9, aromatics < 0.1% cumene ethylbenzene	LC50 9.2 mg/l Acute EC50 1.8 mg/l Fresh water Chronic NOEC 1 mg/l Fresh water	Fish Daphnia	96 hours 48 hours
2-methoxy-1-methylethyl acetate	Acute LC50 134 mg/l Fresh water	Daphnia - <i>Ceriodaphnia dubia</i> Fish - <i>Oncorhynchus mykiss</i>	- 96 hours
1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene	Acute LC50 >100 mg/l	Fish	96 hours

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Hydrocarbons, C9, aromatics < 0.1% cumene ethylbenzene	-	78 % - 28 days	-	-
2-methoxy-1-methylethyl acetate	-	79 % - Readily - 10 days	-	-
	-	83 % - Readily - 28 days	-	-

Conclusion/Summary : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Hydrocarbons, C9, aromatics < 0.1% cumene xylene	-	-	Readily
ethylbenzene	-	-	Readily
2-methoxy-1-methylethyl acetate	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Hydrocarbons, C9, aromatics < 0.1% cumene xylene	3.7 to 4.5 3.12	10 to 2500 7.4 to 18.5	High Low
alkanes, C14-17, chloro	4.7 to 8.3	-	High
ethylbenzene	3.6	79.43	Low
2-methoxy-1-methylethyl acetate	1.2	-	Low
methyl methacrylate	1.38	-	Low
n-butyl methacrylate	2.99	-	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

Code	: 000001166645	Date of issue/Date of revision	: 9 July 2024
PPG VIKOTE 56 BASE (TINTED)			

SECTION 12: Ecological information

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Xylene alkanes, C14-17, chloro	No SVHC (Candidate)	N/A Specified	No Specified	No Specified	No SVHC (Candidate)	N/A Specified	No Specified
ethylbenzene	No	N/A	No	Yes	No	N/A	No
2-methoxy-1-methylethyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene	No	N/A	N/A	No	N/A	N/A	N/A
methyl methacrylate	No	N/A	N/A	No	N/A	N/A	N/A
n-butyl methacrylate	No	N/A	N/A	No	N/A	N/A	N/A

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Code	: 000001166645	Date of issue/Date of revision	: 9 July 2024
PPG VIKOTE 56 BASE (TINTED)			

14. Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	(Solvent naphtha (petroleum), light aromatic)	Not applicable.

Additional information

ADR/RID	: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Tunnel code	: (D/E)
ADN	: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
IMDG	: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
IATA	: The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user	: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
-----------------------------------	---

14.7 Maritime transport in bulk according to IMO instruments	: Not applicable.
--	-------------------

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 1907/2006 (REACH)
Annex XIV - List of substances subject to authorization
Annex XIV
None of the components are listed.
Substances of very high concern

Code	: 000001166645	Date of issue/Date of revision	: 9 July 2024
PPG VIKOTE 56 BASE (TINTED)			

SECTION 15: Regulatory information

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
PBT	medium-chain chlorinated paraffins UVCB substances consisting of more than or equal to 80% linear chloroalkanes with carbon chain lengths within the range from C14 to C17	Candidate	D(2021) 4569-DC	7/8/2021
vPvB	medium-chain chlorinated paraffins UVCB substances consisting of more than or equal to 80% linear chloroalkanes with carbon chain lengths within the range from C14 to C17	Candidate	D(2021) 4569-DC	7/8/2021

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
P5c E1

15.2 Chemical Safety Assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
PBT = Persistent, Bioaccumulative and Toxic
vPvB = Very Persistent and Very Bioaccumulative
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
IMDG = International Maritime Dangerous Goods
IATA = International Air Transport Association

Full text of abbreviated H statements

Code	: 000001166645	Date of issue/Date of revision	: 9 July 2024
PPG VIKOTE 56 BASE (TINTED)			

SECTION 16: Other information

H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H362	May cause harm to breast-fed children.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
Aquatic Chronic 3	AQUATIC HAZARD (LONG-TERM) - Category 3
Aquatic Chronic 4	AQUATIC HAZARD (LONG-TERM) - Category 4
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Lact.	TOXIC TO REPRODUCTION - Effects on or via lactation
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

History

Date of issue/ Date of revision	: 9 July 2024
Date of previous issue	: 11 June 2024
Prepared by	: EHS
Version	: 1.05

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.