SAFETY DATA SHEET



Date of issue 7/17/2024 (month/day/year)

Version 1.01

Section 1. Chemical product and company identification

A. Product name Product code	: SIGMASHIELD 905 BASE GREY 5163 : 00476251	

B. Relevant identified uses of the substance or mixture and uses advised against

Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
C. Supplier's or Importer's information	: PPG SSC (680-090) 19, Yeocheon-ro 217beon-gil, Nam-gu, Ulsan, Korea Tel: +82-52-210-8222 Korea.MSDS@PPG.COM
Email Autress	Kolea.moDo@FFG.COM
Emergency telephone number:	: +82-52-210-8331

Section 2. Hazards identification

A. Hazard classification	: ACUTE TOXICITY (inhalation) - Category 4
	SKIN IRRITATION - Category 2
	EYE IRRITATION - Category 2A
	SKIN SENSITIZATION - Category 1
	CARCINOGENICITY - Category 2
	AQUATIC HAZARD (LONG-TERM) - Category 2
This product is classified in a	accordance with the Industrial Safety and Health Act and the Chemical Control Act

This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

B. GHS label elements, including precautionary statements

Symbol	
Signal word	: Warning
Hazard statements	 H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H332 - Harmful if inhaled. H351 - Suspected of causing cancer. H411 - Toxic to aquatic life with long lasting effects.

Korea (GHS) Page: 1/13

Date of issue 7/17/2024 (month/day/year)

Product name SIGMASHIELD 905 BASE GREY 5163

Section 2. Hazards identification

Precautionary statement	
Prevention	 P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves, protective clothing and eye or face protection. P273 - Avoid release to the environment. P261 - Avoid breathing vapor. P264 - Wash thoroughly after handling.
Response	 P391 - Collect spillage. P308 + P313 - IF exposed or concerned: Get medical advice or attention. P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell. P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
C. Other hazards which do	: None known.

Section 3. Composition/information on ingredients

CAS number/other identifiers

not result in classification

CAS number : Not applicable.

Chemical name	Common name	Identifiers	%
s-[4-(2,3-epoxipropoxi)phenyl]propane	Bisphenol A diglycidyl ether	CAS: 1675-54-3	40 - <50
Talc , not containing asbestiform fibres 1,6-bis(2,3-epoxypropoxy)hexane benzyl alcohol glass, oxide, chemicals titanium dioxide Zinc powder - zinc dust (stabilized)	Talc, non-asbestos form 1,6-HEXANDIOLGLYCIDETHER BENZYL ALCOHOL GLASS OXIDES TITANIUM DIOXIDE ZINC	CAS: 14807-96-6 CAS: 16096-31-4 CAS: 100-51-6 CAS: 65997-17-3 CAS: 13463-67-7 CAS: 7440-66-6	10 -<20 5 - <10 5 - <10 1 - <5 1 - <5 0.1 - <1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Date of issue 7/17/2024 (month/day/year)

Product name SIGMASHIELD 905 BASE GREY 5163

Section 4. First aid measures

Α.	Eye contact	1	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
в.	Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
C.	Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
D.	Ingestion	:	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Е.	Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
	Specific treatments	:	No specific treatment.
	Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

	Ŭ		0
Α.	Extinguishing media		
	Suitable extinguishing media	1	Use an extinguishing agent suitable for the surrounding fire.
	Unsuitable extinguishing media	:	None known.
В.	Specific hazards arising from the chemical	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
	Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon oxides metal oxide/oxides
C.	Special equipment for fire-fighting	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
	Fire-fighting procedures	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Product name SIGMASHIELD 905 BASE GREY 5163

Section 6. Accidental release measures

A. Personal precautions, protective equipment and emergency procedures	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
B. Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
C. Methods and materials for	СС	ontainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Α.	Precautions for safe handling	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
В.	Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Product name SIGMASHIELD 905 BASE GREY 5163

Section 8. Exposure controls/personal protection

A. Occupational exposure limits

^ .			3	
	Ingredient name			Exposure limits
	Palc , not containing asbes glass, oxide, chemicals	stifo	orm fibres	Ministry of Employment and Labor (Republic of Korea, 1/2020). TWA: 2 mg/m ³ 8 hours. Form: fibers Ministry of Employment and Labor (Republic of Korea, 1/2020). [Mineral wool fiber]
	titanium dioxide			TWA: 10 mg/m ³ 8 hours. Form: fibers Ministry of Employment and Labor (Republic of Korea, 1/2020). TWA: 10 mg/m ³ 8 hours. Form: total dust with less than 1% of free SiO2
	Recommended monitoring procedures	:		ate monitoring standards. Reference to ods for the determination of hazardous
в.	Appropriate engineering controls	:	Use only with adequate ventilation. Us ventilation or other engineering control contaminants below any recommended	s to keep worker exposure to airborne
	Environmental exposure controls	:		
С.	Personal protective equip	omo	ent	
	Respiratory protection		hazards of the product and the safe w workers are exposed to concentration appropriate, certified respirators. Use respirator complying with an approved necessary.	n known or anticipated exposure levels, the orking limits of the selected respirator. If s above the exposure limit, they must use a properly fitted, air-purifying or air-fed I standard if a risk assessment indicates this is
	Eye protection		Chemical splash goggles.	
	Hand protection	:	be worn at all times when handling ch this is necessary. Considering the par check during use that the gloves are s should be noted that the time to break	complying with an approved standard should emical products if a risk assessment indicates rameters specified by the glove manufacturer, still retaining their protective properties. It through for any glove material may be rers. In the case of mixtures, consisting of e of the gloves cannot be accurately
	Gloves	1	butyl rubber	
	Body protection	:		body should be selected based on the task d and should be approved by a specialist
	Hygiene measures	:	Wash hands, forearms and face thoro eating, smoking and using the lavator Appropriate techniques should be use Contaminated work clothing should no	oughly after handling chemical products, before y and at the end of the working period. d to remove potentially contaminated clothing of be allowed out of the workplace. Wash Ensure that eyewash stations and safety ocation.
				Korea (GHS) Page: 5/13

Product name SIGMASHIELD 905 BASE GREY 5163

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Κ.	Vapor pressure	÷		Vapor Pressure at 20°C	Vapor pre
J.	Lower and upper explosive (flammable) limits	:	Greatest known range	e: Lower: 1.3% Upper: 13% (be	enzyl alcohol)
Т.	Flammability (solid, gas)	1	Not available.		
н.	Evaporation rate	÷	Not available.		
G.	Flash point	:	Closed cup: Not appli	cable.	
F.	Boiling point/boiling range	ł	>37.78°C (>100°F)		
Ε.	Melting/freezing point	-	Not available.		
D.	рН	÷	Not applicable.		
C.	Odor threshold	1	Not available.		
В.	Odor	1	Characteristic.		
	Color	1	Not available.		
	Physical state	:	Liquid.		
Α.	Appearance				

Ingredient name

			1,6-bis (2,3-epoxypropoxy) hexane	0.067505535	0.009			
L.	Solubility(ies)		Media	Re	sult			
			cold water	No	t soluble			
	Solubility in water	:	Not available.					
М.	Vapor density	1	Not available.					
N.	Relative density	:	1.29					
Ю.	Partition coefficient: n- octanol/water	:	Not applicable.					
Ρ.	Auto-ignition temperature	:						
			Ingredient name		°C	°F	Μ	ethod
			benzyl alcohol		436	816.8		

mm Hg

kPa

Method

Decomposition Q. temperature

- Viscosity
- R. Flow time (ISO 2431)
- Molecular weight S.
- : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)
- : Not available.

: Not available.

: Not applicable.

Vapor pressure at 50°C

Method

kPa

mm

Hg

Date of issue 7/17/2024 (month/day/year)

Version 1.01

Product name SIGMASHIELD 905 BASE GREY 5163

Section 10. Stability and reactivity

Α.	Chemical stability	1	The product is stable.
	Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
В.	Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products.
C.	Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
D.	Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

Section 11. Toxicological information

A. Information on t routes of exposit	he likely : Not available. Jre
Potential acute hea	Ith effects
Inhalation	: Harmful if inhaled.
Ingestion	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Eye contact	: Causes serious eye irritation.
Over-exposure sig	ns/symptoms
Inhalation	: No specific data.
Ingestion	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness

B. Health hazards

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
s-[4-(2,3-epoxipropoxi)phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
benzyl alcohol	LC50 Inhalation Dusts and	Rat	>4178 mg/m ³	4 hours
-	mists			
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-
titanium dioxide	LC50 Inhalation Dusts and	Rat	>6.82 mg/l	4 hours
	mists			
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Zinc powder - zinc dust (stabilized)	LC50 Inhalation Dusts and	Rat	>5.4 mg/l	4 hours
	mists			
	LD50 Oral	Rat	>2000 mg/kg	-
			Korea (GHS)	Page: 7/13

Product name SIGMASHIELD 905 BASE GREY 5163

Section 11. Toxicological information

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-epoxipropoxi)phenyl] propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
	Skin - Edema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-
Conclusion/Summary					

Skin	1	There are no data available on the mixture itself.
Eyes	1	There are no data available on the mixture itself.

: There are no data available on the mixture itself.

: There are no data available on the mixture itself. Respiratory

Sensitization

Product/ingredient name	Route of exposure	Species	Result
bis-[4-(2,3-epoxipropoxi) phenyl]propane	skin	Mouse	Sensitizing
		available on the mixture itself. available on the mixture itself.	
<u>Mutagenicity</u> Conclusion/Summary :	There are no data	available on the mixture itself.	
Carcinogenicity Conclusion/Summary :	There are no data	a available on the mixture itself.	
Reproductive toxicity Conclusion/Summary	There are no data	a available on the mixture itself.	
Teratogenicity Conclusion/Summary	There are no data	a available on the mixture itself.	

Specific target organ toxicity (single exposure)

Name	Classification	Route of exposure	Target organs
Talc , not containing asbestiform fibres	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure) Not available.

Aspiration hazard

Korea (GHS) Page: 8/13

Version 1.01

Product name SIGMASHIELD 905 BASE GREY 5163

Section 11. Toxicological information

Name	Result
benzyl alcohol	ASPIRATION HAZARD - Category 2

Potential chronic health effects

General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Additional information

Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

Chemical name	Identifiers	GHS Classification
bis-[4-(2,3-epoxipropoxi)phenyl]propane	CAS: 1675-54-3	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1B AQUATIC HAZARD (LONG-TERM) - Category 2
Talc , not containing asbestiform fibres	CAS: 14807-96-6	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
1,6-bis(2,3-epoxypropoxy)hexane	CAS: 16096-31-4	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1B AQUATIC HAZARD (LONG-TERM) - Category 3
benzyl alcohol	CAS: 100-51-6	ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 EYE IRRITATION - Category 2A ASPIRATION HAZARD - Category 2
glass, oxide, chemicals	CAS: 65997-17-3	Not classified.
titanium dioxide	CAS: 13463-67-7	CARCINOGENICITY - Category 2
Zinc powder - zinc dust (stabilized)	CAS: 7440-66-6	SUBSTANCES AND MIXTURES, WHICH IN CONTACT WITH WATER, EMIT FLAMMABLE GASES - Category 3 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1

Section 12. Ecological information

A. <u>Ecotoxicity</u>

Product name SIGMASHIELD 905 BASE GREY 5163

Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia magna</i>	48 hours
	Chronic NOEC 0.3 mg/l	Daphnia	21 days
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
Zinc powder - zinc dust (stabilized)	Acute EC50 0.106 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
· · · · ·	Acute EC50 354 µg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Chronic EC10 6.3 µg/l	Daphnia - <i>Daphnia magna -</i> Neonate	21 days
	Chronic LC10 185 µg/l Fresh water	Fish - <i>Oncorhynchus mykiss -</i> Juvenile (Fledgling, Hatchling, Weanling)	30 days

B. Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxi) phenyl]propane	-	-	Not readily
benzyl alcohol	-	-	Readily

C. Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,6-bis(2,3-epoxypropoxy) hexane	0.822	-	Low
benzyl alcohol	0.87	-	Low

D. <u>Mobility in soil</u> Soil/water partition

Soil/water partition : Not available. coefficient (Koc)

E. <u>Other adverse effects</u> : No known significant effects or critical hazards.

Section 13. Disposal considerations

 A. Disposal methods
 : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
 B. Disposal precautions
 : This material and its container must be disposed of in a safe way. Care should be

B. Disposal precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Product name SIGMASHIELD 905 BASE GREY 5163

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ	
A. UN number	UN3082	UN3082	UN3082	
B. UN proper shipping nameENVIRONMENTALLY HAZARDOUS SUBSTAN LIQUID, N.O.S.		ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. EIQUID, N.O.S.		
	(bis-[4-(2,3-epoxipropoxi)(bis-[4-(2,3-epoxipropoxi)phenyl]propane)phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	
C. Transport hazard class(es)	9	9	9	
D. Packing group			III	
Environmental Yes. hazards		Yes.	Yes.	
E. Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Not applicable.	

Additional information

UN	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

F. Special precaution which a user to be aware of or needs to comply with in connection with transport or transportation

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

Α.	Regulation according to ISHA			
	ISHA article 117 (Harmful substances prohibited from manufacture)	: None of the components are listed.		
	ISHA article 118 (Harmful substances requiring permission)	: None of the components are listed.		
	Article 2 of Youth Protection Act on Substances Hazardous to Youth	: It is not allowed to sell to persons under the age of 19		

Exposure Limits of Chemical Substances and Physical Factors

Korea (GHS) Page: 11/13

Version 1.01

Product name SIGMASHIELD 905 BASE GREY 5163

Section 15. Regulatory information

	The following components Talc , not containing asbe glass, oxide, chemicals titanium dioxide		
	ISHA Enforcement Regs Annex 19 (Exposure standards established for harmful factors)	:	None of the components are listed.
	ISHA Enforcement Regs Annex 21 (Harmful factors subject to Work Environment Measurement)	:	The following components are listed: talc / soapstone, titanium dioxide
	ISHA Enforcement Regs Annex 22 (Harmful Factors Subject to Special Health Check- up)	:	The following components are listed: Glass fiber dusts
	Standard of Industrial Safety and Health Annex 12 (Hazardous substances subject to control)	:	The following components are listed: titanium dioxide
В.	Regulation according to (<u>Ch</u>	emicals Control Act
	Article 11 (TRI)	:	None of the components are listed.
	Article 18 Prohibited (K- Reach Article 27)	1	None of the components are listed.
	Article 19 Subject to authorization (K-Reach Article 25)	:	None of the components are listed.
	Article 20 Restricted (K- Reach Article 27)	1	None of the components are listed.
	Article 20 Toxic Chemicals (K-Reach Article 20)	:	Not applicable
	Korea inventory	1	All components are listed or exempted.
	Article 39 (Accident Precaution Chemicals)	1	None of the components are listed.
C.	Dangerous Materials Safety Management Act	-	Not applicable.
D.	Wastes regulation	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Е.	. <u>Regulation according to other foreign laws</u>		
	Safety, health and environmental regulations specific for the product	:	No known specific national and/or regional regulations applicable to this product (including its ingredients).

Product name SIGMASHIELD 905 BASE GREY 5163

Section 16. Other information

Α.	References	:	Korean Ministry of Environment; Chemical Control Act Korean Ministry of Labor; Industrial Safety and Health Act NIER Notice Registry of Toxic Effects of Chemical Substances (RTECS) U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information Retrieval) ECOTOX Database System.
В.	First issue date	:	2/18/2024
С.	Date of issue/Date of revision	1	7/17/2024
D.	Version	1	1.01
	Prepared by	:	EHS

E. Other

✓ Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.