SAFETY DATA SHEET



Date of issue/Date of revision 25 July 2024 Version 6.03

Section 1. Identification		
Product code	: 00254215	
Product name	: SIGMASHIELD 905 BASE BLACK	
Product type	: Liquid.	
Relevant identified uses of the substance or mixture and uses advised against		
Product use	Coating. Professional applications, Used by spraying.	
Supplier's details	: PPG Industries (Singapore) Pte. Ltd., No. 1 Tuas Basin Close, Singapore 638803. Tel +65 68653737	
Emergency telephone number (with hours of operation)	: CHEMTREC +(65)-31581349 (CCN 17704)	

Section 2. Hazards identification

Classification of the	: ACUTE TOXICITY (inhalation) - Category 4
substance or mixture	SKIN CORROSION/IRRITATION - Category 2
	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
	SKIN SENSITIZATION - Category 1
	AQUATIC HAZARD (LONG-TERM) - Category 2

GHS label elements, including precautionary statements		
Hazard pictograms		
Signal word	: Warning	
Hazard statements	 Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. Toxic to aquatic life with long lasting effects. 	
Precautionary statements		
Prevention	: Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapor. Wash thoroughly after handling.	

Singapore	English (US)	Page: 1/12
-----------	--------------	------------

Section 2. Hazards identification

Response	: Collect spillage. IF INHALED: Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Not applicable.
Disposal	: Not applicable.

Other hazards which do not : None known. result in classification

Section 3. Composition/information on ingredients

: Mixture

CAS number/other identifiers

CAS number: Not applicable.EC number: Mixture.		
Ingredient name	%	CAS number
 bis-[4-(2,3-epoxipropoxi)phenyl]propane Talc , not containing asbestiform fibres 1,6-bis(2,3-epoxypropoxy)hexane benzyl alcohol N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) 	25 - <50 10 - <20 5 - <10 5 - <10 0.3 - <1	1675-54-3 14807-96-6 16096-31-4 100-51-6 123-26-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential ac	ute health effec	<u>ts</u>	
Eye conta	ct	: Causes serious eye irritation.	
Singapore	English (US)		Page: 2/12

Section 4. First aid measures

Inhalation	: Harmful if inhaled.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure signs/sym</u>	<u>ptoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

thoroughly with water before removing it, or wear gloves.

Singapore	English (US)	Page: 3/12
-----------	--------------	------------

Product name SIGMASHIELD 905 BASE BLACK

Section 5. Fire-fighting measures

```
Special protective equipment for fire-fighters
```

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protect	<u>tiv</u>	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	-	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Matheada and materials for as	-	sinnent and algoring up

Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in
	which this product is used. Do not get in eyes or on skin or clothing. Do not ingest.
	Avoid breathing vapor or mist. Avoid release to the environment. Use only with
	adequate ventilation. Wear appropriate respirator when ventilation is inadequate.
	Keep in the original container or an approved alternative made from a compatible
	material, kept tightly closed when not in use. Empty containers retain product
	residue and can be hazardous. Do not reuse container.

Section 7. Handling and storage

	-	
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name			Exposure limits		
✓alc , not containing asbestiform fibres N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)			Workplace Safety and Health Act (Singapore, 2/2006). PEL (long term): 2 mg/m ³ 8 hours. ACGIH TLV (United States). TWA: 3 mg/m ³ Form: Respirable TWA: 10 mg/m ³ Form: Total dust		
Recommended monitoring procedures	:	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.			
Appropriate engineering controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.			
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.			
ndividual protection measur	<u>es</u>				
Hygiene measures	:	eating, smoking and using the lavator Appropriate techniques should be use Contaminated work clothing should n	bughly after handling chemical products, before y and at the end of the working period. ed to remove potentially contaminated clothing. ot be allowed out of the workplace. Wash . Ensure that eyewash stations and safety location.		
Eye/face protection	:	Chemical splash goggles.			
Skin protection					

Singapore	English (US)	Page: 5/12
-----------	--------------	------------

Product code 00254215

Product name SIGMASHIELD 905 BASE BLACK

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: butyl rubber
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

Liquid.			
Black.			
Characteristic.			
insoluble in water.			
>37.78°C (>100°F)			
Closed cup: 100°C (212°F)			
0.007 (benzyl alcohol) compared with butyl acetate			
liquid			
▶ Fighest known value: 0.009 kPa (0.07 mm Hg) (at 20°C) (1,6-bis(2,3-epoxypr hexane). Weighted average: 0.002 kPa (0.02 mm Hg) (at 20°C)	ороху)		
Highest known value: 11.7 (Air = 1) (bis-[4-(2,3-epoxipropoxi)phenyl]propane Weighted average: 10.37 (Air = 1)	€).		
1.26			
Media Result			
cold water Not soluble			
Lowest known value: 436°C (816.8°F) (benzyl alcohol).			
Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)			
	 Highest known value: 11.7 (Air = 1) (bis-[4-(2,3-epoxipropoxi)phenyl]propane Weighted average: 10.37 (Air = 1) 1.26 Media Result 		

Singapore	English (US)	Page: 6/12
-----------	--------------	------------

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
pis-[4-(2,3-epoxipropoxi) phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>4178 mg/m ³	4 hours
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	LC50 Inhalation Dusts and mists	Rat	>5.11 mg/l	4 hours
·	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Mild irritant				
	Rabbit	-	24 hours	-
Redness of the ctivae	Rabbit	0.4	24 hours	-
Edema	Rabbit	0.5	4 hours	-
Erythema/Eschar	Rabbit	0.8	4 hours	-
Mild irritant	Rabbit	-	4 hours	-
e E E	ctivae Edema Erythema/Eschar	ctivae Edema Rabbit Erythema/Eschar Rabbit	ctivae Edema Rabbit 0.5 Erythema/Eschar Rabbit 0.8	ctivae Edema Rabbit 0.5 4 hours Erythema/Eschar Rabbit 0.8 4 hours

Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

<u> </u>		
Singapore	English (US)	Page: 7/12

Section 11. Toxicological information

Sensitization

Product/ingredient name	Route of exposure	Species	Result
Interpretended by the set of	skin	Mouse	Sensitizing
Conclusion/Summary			
Skin :	There are no data	available on the mixture itself.	
Respiratory :	There are no data	available on the mixture itself.	
Mutagenicity			
Conclusion/Summary	There are no data	available on the mixture itself.	
Carcinogenicity			
Conclusion/Summary :	There are no data	available on the mixture itself.	
Reproductive toxicity			
Conclusion/Summary :	There are no data	available on the mixture itself.	
Teratogenicity			
Conclusion/Summary :	There are no data	available on the mixture itself.	
Specific target organ toxici	t <u>y (single exposure</u>	<u>e)</u>	

Name		Route of exposure	Target organs
Talc , not containing asbestiform fibres	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure	: Not available.
Potential acute health effect	<u>its</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: Harmful if inhaled.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the pl	nysical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.

Singapore	English (US)	Page: 8/12
-----------	--------------	------------

Section 11. Toxicological information

		0
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Delayed and immediate effe	cts	and also chronic effects from short and long term exposure
<u>Short term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	1	Not available.
Long term exposure		
Potential immediate effects	1	Not available.
Potential delayed effects	:	Not available.
Potential chronic health eff	ect	<u>s</u>
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	:	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Øral	11455.81 mg/kg
Dermal	15623.3 mg/kg
Inhalation (dusts and mists)	4.16 mg/l

Other information

Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

Section 12. Ecological information

ż

Toxicity

Version 6.03

Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia magna</i>	48 hours
	Chronic NOEC 0.3 mg/l	Daphnia	21 days
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	Acute EC50 29 to 43 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 94 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours

Persistence/degradability

Product/ingredient name	Test	Result	Dose	Inoculum
₩,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	-	63 % - 28 days	-	-
Conclusion/Summary	: There are n	o data available on the mixt	ure itself.	

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxi) phenyl]propane benzyl alcohol N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	- - -	-	Not readily Readily Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
	0.822 0.87 >6	-	Low Low High

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Singapore	English (US)
-----------	--------------

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	Kis-[4-(2,3-epoxipropoxi) phenyl]propane)	Kis-[4-(2,3-epoxipropoxi) phenyl]propane)	Kis-[4-(2,3-epoxipropoxi) phenyl]propane)
Transport hazard class(es)	9	9	9
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Not applicable.

Additional information

UN	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.		
IMDG	This product is not regulated as a dangerous good when transported in sizes of \leq 5 L or \leq 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.		
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.		
Special precaution	ns for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.		
Transport in bulk to IMO instrumen	• • • • • • • • • • • • • • • • • • • •		

Singapore	English (US)	Page: 11/12
-----------	--------------	-------------

Section 15. Regulatory information

Singapore - hazardous chemicals under government control

None.

International regulations Montreal Protocol Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

History

Section 16. Other information

History	
Date of issue/Date of revision	: 25 July 2024
Date of previous issue	: 3/28/2024
Version	: 6.03
Prepared by	: EHS
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.