SAFETY DATA SHEET



Date of issue/Date of revision 9 August 2024 Version 3.16

Section 1. Identification		
Product code	: 00243713	
Product name	: SIGMAZINC 158/SIGMAZINC 158 KRA/AMERCOAT 68HS POWDER	
Product type	: Powder.	
Relevant identified uses o	f the substance or mixture and uses advised against	
Product use	Coating. Professional applications, Used by spraying.	
Supplier's details	: PPG Industries (Singapore) Pte. Ltd., No. 1 Tuas Basin Close, Singapore 638803. Tel +65 68653737	
Emergency telephone number (with hours of operation)	: CHEMTREC +(65)-31581349 (CCN 17704)	

Section 2. Hazards identification

Classification of the substance or mixture	:	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
GHS label elements, includin	g	orecautionary statements
Hazard pictograms	:	₩2
Signal word	:	Warning
Hazard statements	:	Very toxic to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Avoid release to the environment.
Response	:	Collect spillage.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Other hazards which do not result in classification	:	May form explosible dust-air mixture if dispersed. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

Singapore	English (GB)	Page: 1/11
-----------	--------------	------------

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

CAS number/other identifiers

CAS number	: Not applicable.
EC number	: Mixture.

Lo number . Mixture.		
Ingredient name	%	CAS number
Zinc powder - zinc dust (stabilized) zinc oxide	50 - 100 3 - <5	7440-66-6 1314-13-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health	<u>n effects</u>
Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/	/symptoms
Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.

Singapore	English (GB)	Page: 2/11
-----------	--------------	------------

Product name SIGMAZINC 158/SIGMAZINC 158 KRA/AMERCOAT 68HS POWDER

Section 4. First aid measures

Indication of immediate med	lical attention and special treatment needed, if necessary	
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.	
Specific treatments	: No specific treatment.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.	

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media Suitable extinguishing : Use dry chemical powder. media Unsuitable extinguishing : Avoid high pressure media which could cause the formation of a potentially media explosible dust-air mixture. Specific hazards arising : May form explosible dust-air mixture if dispersed. This material is very toxic to from the chemical aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. : Decomposition products may include the following materials: Hazardous thermal metal oxide/oxides decomposition products **Special protective actions** : Promptly isolate the scene by removing all persons from the vicinity of the incident if for fire-fighters there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. : Fire-fighters should wear appropriate protective equipment and self-contained **Special protective** breathing apparatus (SCBA) with a full face-piece operated in positive pressure equipment for fire-fighters mode

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Singapore	English (GB)	Page: 3/11
-----------	--------------	------------

Version 3.16

Product name SIGMAZINC 158/SIGMAZINC 158 KRA/AMERCOAT 68HS POWDER

Section 6. Accidental release measures

Methods and material for	containment and cleaning up
Small spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid release to the environment. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Product name SIGMAZINC 158/SIGMAZINC 158 KRA/AMERCOAT 68HS POWDER

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name			Exposure limits
zinc oxide			Workplace Safety and Health Act (Singapore, 2/2006). PEL (long term): 10 mg/m ³ 8 hours. Form: Dust PEL (short term): 10 mg/m ³ 15 minutes. Form: Fume PEL (long term): 5 mg/m ³ 8 hours. Form: Fume
Recommended monitoring procedures	:		riate monitoring standards. Reference to nods for the determination of hazardous
Appropriate engineering controls	:	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.	
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.	
Individual protection measur	<u>'es</u>		
Hygiene measures	:	eating, smoking and using the lavator Appropriate techniques should be use	bughly after handling chemical products, before y and at the end of the working period. ed to remove potentially contaminated clothing. eusing. Ensure that eyewash stations and tation location.
Eye/face protection	:	Safety glasses with side shields.	
Skin protection			
Hand protection	:	be worn at all times when handling ch this is necessary. Considering the pa check during use that the gloves are s should be noted that the time to break	s complying with an approved standard should emical products if a risk assessment indicates rameters specified by the glove manufacturer, still retaining their protective properties. It through for any glove material may be rers. In the case of mixtures, consisting of the of the gloves cannot be accurately
Body protection	:		body should be selected based on the task d and should be approved by a specialist

Product name SIGMAZINC 158/SIGMAZINC 158 KRA/AMERCOAT 68HS POWDER

Section 8. Exposure controls/personal protection

Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	d. vder.	
Colour	ious	
Odour	ourless.	
рН	bluble in water.	
Flash point	sed cup: Not applicable.	
Evaporation rate	available.	
Flammability (solid, gas)	available.	
Vapour pressure	available.	
Vapour density	hest known value: 5.47 (Air = 1) (zinc oxide).	
Relative density	4	
Solubility(ies)	dia Result	
Solubility (ies)	d water Not soluble	
Auto-ignition temperature	available.	
Viscosity	ematic (40°C (104°F)): Not applicable.	

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

Singapore	English (GB)	Page: 6/11
-----------	--------------	------------

Date of issue 9 August 2024

Version 3.16

Product name SIGMAZINC 158/SIGMAZINC 158 KRA/AMERCOAT 68HS POWDER

Section 10. Stability and reactivity

Hazardous decomposition
products: Evolves hydrogen on contact with water. Depending on conditions, decomposition
products may include the following materials: metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient nam	ne	Result	Species	Dose	Exposure
Zinc powder - zinc dust (stabilized)		LC50 Inhalation Dusts and mists	Rat	>5.4 mg/l	4 hours
		LD50 Oral	Rat	>2000 mg/kg	-
zinc oxide		LC50 Inhalation Dusts and mists		>5700 mg/m ³	4 hours
		LD50 Dermal LD50 Oral	Rat Rat	>2000 mg/kg >5000 mg/kg	-
				~3000 mg/kg	-
Conclusion/Summary	-	There are no data available on the	mixture itself.		
Irritation/Corrosion					
Conclusion/Summary	_				
Skin		There are no data available on the			
Eyes		There are no data available on the			
Respiratory	: 7	There are no data available on the	mixture itself.		
<u>Sensitisation</u>					
Conclusion/Summary					
Skin		There are no data available on the	mixture itself.		
Respiratory	10	There are no data available on the	mixture itself.		
<u>Mutagenicity</u>					
Conclusion/Summary	1	There are no data available on the	mixture itself.		
Carcinogenicity					
Conclusion/Summary	:	There are no data available on the	mixture itself.		
Reproductive toxicity					
Conclusion/Summary	1	There are no data available on the	mixture itself.		
Teratogenicity					
Conclusion/Summary	:	There are no data available on the	mixture itself.		
<u>Specific target organ tox</u>	icity	<u>(single exposure)</u>			
Not available.					
Specific target organ tox	icity	(repeated exposure)			
Not available.		- ·			
Aspiration hazard					

Information on likely routes : Not available. of exposure

Version 3.16

Product name SIGMAZINC 158/SIGMAZINC 158 KRA/AMERCOAT 68HS POWDER

Section 11. Toxicological information

Potential acute health effects	
Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the phys	sical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following:

	respiratory tract irritation coughing
Skin contact :	No specific data.
Ingestion :	No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure		
Potential immediate effects	lot available.	
Potential delayed effects	lot available.	
<u>Long term exposure</u>		
Potential immediate effects	lot available.	
Potential delayed effects	lot available.	
Potential chronic health eff		
General	Repeated or prolonged inhalation of dust may lead to chronic respiratory in	ritation.
Carcinogenicity	lo known significant effects or critical hazards.	
Mutagenicity	lo known significant effects or critical hazards.	
Reproductive toxicity	lo known significant effects or critical hazards.	

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Other information

Sanding and grinding dusts may be harmful if inhaled.

ŝ,

Singapore E	English ((GB)
-------------	-----------	------

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Zinc powder - zinc dust (stabilized)	Acute EC50 0.106 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 354 µg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Chronic EC10 6.3 µg/l	Daphnia - <i>Daphnia magna</i> - Neonate	21 days
	Chronic LC10 185 µg/l Fresh water	Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	30 days
zinc oxide	Acute EC50 0.17 mg/l	Algae	72 hours
	Acute EC50 0.481 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
	Chronic NOEC 0.017 mg/l Fresh water	Algae	72 hours
Persistence/degradability Not available. Conclusion/Summary Bioaccumulative potential Not available.	: There are no data available on the m	iixture itself.	
Mobility in soil Soil/water partition coefficient (Koc)	: Not available.		
Other adverse effects	: No known significant effects or critica	al hazards.	
Section 13. Dispo	sal considerations		
Disposal methods	: The generation of waste should be a	voided or minimised wherever po	ssible.

 Disposal methods
 The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. FIGULE Hame SIGMAZINC 150/SIGMAZINC 150 KRA/AMERCOAT 6005 FOW

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	UN3077	UN3077	UN3077
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
	(Zinc powder - zinc dust (stabilized), zinc oxide)	(Zinc powder - zinc dust (stabilized), zinc oxide)	(Zinc powder - zinc dust (stabilized), zinc oxide)
Transport hazard class(es)	9	9	9
Packing group	III	III	Ш
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(Zinc powder - zinc dust (stabilized))	Not applicable.

Additional information

UN	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	
IMDG	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. The segregation group has been manually assigned based upon product analysis.	
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.	
Special precautions for user : Transport within user's premises: always transport in closed containers that are		

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

Singapore - hazardous chemicals under government control

None.

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Singapore English (GB)

Page: 10/11

Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 9 August 2024
Date of previous issue	: 11/20/2022
Version	: 3.16
Prepared by	: EHS
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

✓ Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.