# **SAFETY DATA SHEET**



### The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision 9 August 2024 Version 3.02

Section 1. Identification		
Product name	: SIGMAZINC 158/SIGMAZINC 158 KRA/AMERCOAT 68HS POWDER	
Product code	: 00243713	
Other means of identification	: Not available.	
Product type	: Powder.	
Relevant identified uses of	the substance or mixture and uses advised against	
Product use	: Professional applications, Used by spraying.	
Use of the substance/ mixture	: Coating.	
Uses advised against	: Not applicable.	
Supplier	<ul> <li>PPG Architectural Coatings Canada, Inc. 1550, rue Ampère, bureau 500 Boucherville (Québec) J4B 7L4 Canada +1 450-655-3121</li> </ul>	
	PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272	
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)	
Technical Phone Number	: 888-977-4762	

# Section 2. Hazard identification

Classification of the substance or mixture GHS label elements	: COMBUSTIBLE DUSTS - Category 1
Signal word	: Warning
Hazard statements	: May form combustible dust concentrations in air.
Precautionary statements	
Prevention	: Not applicable.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: Not applicable.

Canada Page: 1/11

Product code 00243713

Version 3.02

### Product name SIGMAZINC 158/SIGMAZINC 158 KRA/AMERCOAT 68HS POWDER

### Section 2. Hazard identification

Supplemental label elements	<ul> <li>Keep container tightly closed. Keep away from heat, sparks, open flames and hot surfaces No smoking. Sanding and grinding dusts may be harmful if inhaled. Prevent dust accumulation. Emits toxic fumes when heated.</li> <li>Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 96.7% (oral), 96.7% (dermal)</li> </ul>
Other hazards which do not result in classification	: None known.

# Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: SIGMAZINC 158/SIGMAZINC 158 KRA/AMERCOAT 68HS POWDER
Other means of identification	: Not available.

### **CAS number/other identifiers**

Ingredient name	Synonyms	% (w/w)	CAS number
zinc oxide	CI 77947; Zinc oxide fume; Zinc peroxide; Zinc, oxide Fume; ZINC OXIDE (ZNO); FLOWERS OF ZINC; zinc oxide, nanoparticles, uncoated; zinc oxide, nanoparticles, coated with [3- (methacryloxy)propyl] trimethoxysilane; C. I. Pigment White 4; Zinc monoxide; Zinc white	1 - 5*	1314-13-2

\*Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

### **Description of necessary first aid measures**

Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Ingestion	<ul> <li>If swallowed, seek medical advice immediately and show this container or label.</li> <li>Keep person warm and at rest. Do NOT induce vomiting.</li> </ul>

### Most important symptoms/effects, acute and delayed Potential acute health effects

Canada Page: 2/11

# Section 4. First-aid measures

Eye contact	<ul> <li>Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.</li> </ul>
Inhalation	<ul> <li>Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.</li> </ul>
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/s	symptoms
Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate	emedical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	No specific treatment.

### **Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical powder.
Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
Specific hazards arising from the chemical	: May form explosible dust-air mixture if dispersed.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

Personal precautions, protec	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	onta	ainment and cleaning up
Small spill	:	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

Precautions for safe handling	
Protective measures :	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general : occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Version 3.02

### Product name SIGMAZINC 158/SIGMAZINC 158 KRA/AMERCOAT 68HS POWDER

# Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
	contamination.

# Section 8. Exposure controls/personal protection

### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits
zínc oxide	CA Alberta Provincial (Canada, 3/2023).
	OEL: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable
	OEL: 10 mg/m³ 15 minutes. Form:
	Respirable
	CA British Columbia Provincial (Canada,
	8/2023).
	STEL: 10 mg/m <sup>3</sup> 15 minutes. Form:
	Respirable
	TWA: 2 mg/m³ 8 hours. Form: Respirable
	CA Quebec Provincial (Canada, 7/2023).
	STEV: 10 mg/m <sup>3</sup> 15 minutes. Form:
	Respirable dust.
	TWAEV: 2 mg/m³ 8 hours. Form:
	Respirable dust.
	CA Ontario Provincial (Canada, 6/2019).
	STEL: 10 mg/m <sup>3</sup> 15 minutes. Form:
	Respirable particulate matter.
	TWA: 2 mg/m³ 8 hours. Form: Respirable
	particulate matter.
	CA Saskatchewan Provincial (Canada,
	7/2013).
	STEL: 10 mg/m <sup>3</sup> 15 minutes. Form:
	respirable dust and fume
	TWA: 2 mg/m³ 8 hours. Form: respirable
	dust and fume

#### Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	:	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

# Section 8. Exposure controls/personal protection

Environmental exposure controls	:	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		
Individual protection measu	<u>ires</u>			
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.		
Eye/face protection	1	Safety glasses with side shields.		
Skin protection				
Hand protection	:	: Chemical-resistant, impervious gloves complying with an approved standard sh be worn at all times when handling chemical products if a risk assessment indic this is necessary. Considering the parameters specified by the glove manufact check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.		
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.		
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.		
<ul> <li>Respiratory protection</li> <li>Respirator selection must be based on known or anticipated exposure level hazards of the product and the safe working limits of the selected respiration workers are exposed to concentrations above the exposure limit, they multiple appropriate, certified respirators. Use a properly fitted, air-purifying or air respirator complying with an approved standard if a risk assessment indication in the safe.</li> </ul>				

# Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Solid.
Color	: Various
Odor	: Odorless.
Odor threshold	: Not available.
рН	: Not applicable.
Melting point	: Not available.
Boiling point	: Not available.
Flash point	: Closed cup: Not applicable.
Auto-ignition temperature	: Not applicable.
Decomposition temperature	: Not available.
Flammability	: Not available.
Lower and upper explosive (flammable) limits	: Not applicable.
Evaporation rate	: Not available.

Canada Page: 6/11

Product code 00243713

### Product name SIGMAZINC 158/SIGMAZINC 158 KRA/AMERCOAT 68HS POWDER

# Section 9. Physical and chemical properties

Vapor pressure	: Not available.				
Vapor density	: Not applicable.	ot applicable.			
Relative density	: 7.14				
Density ( lbs / gal )	: 59.59				
Solubility(ies)	Media	Result			
	. cold water	Not soluble			
Partition coefficient: n- octanol/water	: Not applicable.				
Viscosity	: Kinematic (40°C (1	Kinematic (40°C (104°F)): Not applicable.			
Volatility	: 0% (v/v), 0.01% (w	0% (v/v), 0.01% (w/w)			
% Solid. (w/w)	: 99.99	99.99			

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Evolves hydrogen on contact with water. Depending on conditions, decomposition products may include the following materials: metal oxide/oxides

# Section 11. Toxicological information

### Information on toxicological effects

Acute t	ovicity
Acute i	UXICILY

Product/ingredient name	Result	Species	Dose	Exposure		
zinc oxide	LC50 Inhalation Dusts and mists	Rat	>5700 mg/m <sup>3</sup>	4 hours		
	LD50 Dermal	Rat	>2000 mg/kg	-		
	LD50 Oral	Rat	>5000 mg/kg	-		
Conclusion/Summary	: There are no data available on	the mixture i	tself.	·		
rritation/Corrosion						
Conclusion/Summary						
Skin	: There are no data available on	the mixture i	tself.			
Eyes	: There are no data available on	: There are no data available on the mixture itself.				
Respiratory	: There are no data available on the mixture itself.					
Sensitization						
Skin	: There are no data available on	the mixture i	tself.			
			0	- de Deve		

### Section 11. Toxicological information

Respiratory	: There are no data available on the mixture itself.
<b>Mutagenicity</b>	
Conclusion/Summary	: There are no data available on the mixture itself.
<b>Carcinogenicity</b>	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Reproductive toxicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Teratogenicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Specific target organ toxi	<u>city (single exposure)</u>
Not available.	
Specific target organ toxi	<u>city (repeated exposure)</u>
Not available.	
<u>Target organs</u>	: Contains material which may cause damage to the following organs: upper respiratory tract.
Aspiration hazard	
Not available.	
Information on the likely ro	utes of exposure
Potential acute health effect	<u>:ts</u>
Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symp	u <u>toms</u>

Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary	: There are no data available on the mixture itself. Repeated exposure of the eyes to a low level of dust can produce eye irritation. Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long- term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Section 11. Toxicological information

: There are no data available on the mixture itself.
: There are no data available on the mixture itself.
: There are no data available on the mixture itself.
: There are no data available on the mixture itself.
ects
: Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.

### Numerical measures of toxicity

### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	(gases)	(vapors)	Inhalation (dusts and mists) (mg/l)
SIGMAZINC 158/SIGMAZINC 158 KRA/ AMERCOAT 68HS POWDER zinc oxide	N/A N/A	2500 2500		N/A N/A	N/A N/A

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
zinc oxide	Acute EC50 0.17 mg/l Acute EC50 0.481 mg/l Fresh water	Algae Daphnia - <i>Daphnia magna</i> - Neonate	72 hours 48 hours
	Chronic NOEC 0.017 mg/l Fresh water	Algae	72 hours

### Persistence and degradability

Not available.

### **Bioaccumulative potential**

Not available.

### Mobility in soil

Soil/water partition coefficient (Koc) : Not available.

Canada Page: 9/11

Version 3.02

Product name SIGMAZINC 158/SIGMAZINC 158 KRA/AMERCOAT 68HS POWDER

### Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

# Section 14. Transport information

	TDG	IMDG	ΙΑΤΑ
UN number	UN3077	UN3077	UN3077
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
	(Zinc powder - zinc dust (stabilized), zinc oxide)	(Zinc powder - zinc dust (stabilized), zinc oxide)	(Zinc powder - zinc dust (stabilized), zinc oxide)
Transport hazard class (es)	9	9	9
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	(Zinc powder - zinc dust (stabilized))	(Zinc powder - zinc dust (stabilized))	Not applicable.

#### **Additional information**

TDG	: Non-bulk packages of this product are not regulated as dangerous goods when transported by road or rail.
IMDG	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. The segregation group has been manually assigned based upon product analysis.
ΙΑΤΑ	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
Special prec	cautions for user : Transport within user's premises: always transport in closed containers that are

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments Product code 00243713

Date of issue 9 August 2024

Version 3.02

### Product name SIGMAZINC 158/SIGMAZINC 158 KRA/AMERCOAT 68HS POWDER

### Section 14. Transport information

Proof of classification statement

: Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.43-2.45 (Class 9), 2.7 (Marine pollutant mark).

# Section 15. Regulatory information

National Inventory List

Canada inventory (DSL)

: All components are listed or exempted.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 1 Flammability : 0 Physical hazards : 1

(\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

# The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health : 1 Flamma	ability : 0 Instability : 1
Date of issue/Date of revision	9 August 2024
Organization that prepared the SDS	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

### Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.