SAFETY DATA SHEET



Date of issue 8/9/2024 (month/day/year)

Version 4.07

Section 1. Chemical product and company identification

A. Product name : SIGMAZINC 158 HS PIGMENT GREY (K)

Product code : 00322630

B. Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

Uses advised against: Product is not intended, labelled or packaged for consumer use.

C. Supplier's or Importer's

information

Email Address

: PPG SSC (680-090)

19, Yeocheon-ro 217beon-gil, Nam-gu,

Ulsan, Korea

Tel: +82-52-210-8222 Korea.MSDS@PPG.COM

Emergency telephone

number:

: ₹82-52-210-8331

Section 2. Hazards identification

A. Hazard classification : AQUATIC HAZARD (ACUTE) - Category 1

AQUATIC HAZARD (LONG-TERM) - Category 1

This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

B. GHS label elements, including precautionary statements

Symbol :

*

Signal word : Warning

Hazard statements : H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention: P273 - Avoid release to the environment.

Response : P391 - Collect spillage.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Korea (GHS) Page: 1/11

Product code 00322630 Date of issue 8/9/2024 (month/day/year) Version 4.07 **Product name SIGMAZINC 158 HS PIGMENT GREY (K)**

Section 2. Hazards identification

not result in classification

C. Other hazards which do : May form explosible dust-air mixture if dispersed. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes. skin. nose and throat.

Section 3. Composition/information on ingredients

CAS number/other identifiers

CAS number : Not applicable.

| Chemical name | Common name | Identifiers | % |
|---|-------------|----------------------------------|--------------------|
| Zinc powder - zinc dust (stabilized) zinc oxide | | CAS: 7440-66-6 CAS: 1314-13-2 | 90 - 100 1 - <5 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

A. Eye contact

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

B. Skin contact

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

C. Inhalation

Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

D. Ingestion

: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

E. Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

A. Extinguishing media

Suitable extinguishing media

: Use dry chemical powder.

Unsuitable extinguishing media : Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

Korea (GHS) Page: 2/11

Product name SIGMAZINC 158 HS PIGMENT GREY (K)

Section 5. Fire-fighting measures

- from the chemical
- B. Specific hazards arising: May form explosible dust-air mixture if dispersed. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
 - **Hazardous thermal** decomposition products
- Decomposition products may include the following materials: metal oxide/oxides
- C. Special equipment for fire-fighting
- : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Fire-fighting procedures : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Section 6. Accidental release measures

- A. Personal precautions, protective equipment and emergency procedures
- : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.
- **B. Environmental** precautions
- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
- C. Methods and materials for containment and cleaning up

Small spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

- A. Precautions for safe handling
- Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid release to the environment. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Korea (GHS) Page: 3/11

Product name SIGMAZINC 158 HS PIGMENT GREY (K)

Section 7. Handling and storage

- B. Conditions for safe storage, including any incompatibilities
- : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

A. Occupational exposure limits

| Ingredient name | Exposure limits | |
|-----------------|---|--|
| zinc oxide | Ministry of Employment and Labor (Republic of Korea, 1/2020). | |
| | TWA: 2 mg/m³ 8 hours. Form: Respirable | |
| | dust STEL: 10 mg/m³ 15 minutes. TWA: 5 mg/m³ 8 hours. | |

Recommended monitoring procedures

- Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
- B. Appropriate engineering controls
- Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- C. Personal protective equipment

Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Eye protection Hand protection

- : Safety glasses with side shields.
 - Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Korea (GHS) Page: 4/11

Product name SIGMAZINC 158 HS PIGMENT GREY (K)

Section 8. Exposure controls/personal protection

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

A. Appearance

Physical state : Solid.

Powder.

Color : Various B. Odor Odorless. Not available. C. Odor threshold D. pH Not applicable.

E. Melting/freezing point F. Boiling point/boiling

: Not available. : Not available.

range

G. Flash point

Closed cup: Not applicable.

H. Evaporation rate : Not available. Flammability (solid, gas) : Not available. J. Lower and upper : Not available.

explosive (flammable)

limits

Media

K. Vapor pressure Not available.

L. Solubility(ies) cold water

Not soluble

Result

Solubility in water : Not available. Vapor density Not applicable.

Relative density 7.14

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition : Not applicable.

temperature

Decomposition temperature

: Not available.

Viscosity

Kinematic (40°C (104°F)): Not applicable.

Flow time (ISO 2431) Not available. **Molecular weight** Not applicable.

Korea (GHS) Page: 5/11

Product name SIGMAZINC 158 HS PIGMENT GREY (K)

Section 10. Stability and reactivity

A. Chemical stability

: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

B. Conditions to avoid

: When exposed to high temperatures may produce hazardous decomposition

products.

C. Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

D. Hazardous : Evolves hydrogen on contact with water. Depending on conditions, decomposition

decomposition products products may include the following materials: metal oxide/oxides

Section 11. Toxicological information

A. Information on the likely routes of exposure

: Not available.

Potential acute health effects

Inhalation : Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the nose, throat and lungs.

Ingestion : No known significant effects or critical hazards.Skin contact : No known significant effects or critical hazards.

Eye contact: Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the eyes.

Over-exposure signs/symptoms

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Ingestion : No specific data.

Skin contact : No specific data.

Eye contact : Adverse symptoms may include the following:

irritation redness

B. Health hazards

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--------------------------------------|---------------------------------|------------|----------------------------|----------|
| Zinc powder - zinc dust (stabilized) | LC50 Inhalation Dusts and mists | Rat | >5.4 mg/l | 4 hours |
| | LD50 Oral | Rat | >2000 mg/kg | - |
| zinc oxide | LC50 Inhalation Dusts and mists | Rat | >5700 mg/m ³ | 4 hours |
| | LD50 Dermal LD50 Oral | Rat Rat | >2000 mg/kg >5000 mg/kg | - |

Conclusion/Summary: There are no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary

Korea (GHS) Page: 6/11

Product name SIGMAZINC 158 HS PIGMENT GREY (K)

Section 11. Toxicological information

Skin : There are no data available on the mixture itself.
 Eyes : There are no data available on the mixture itself.
 Respiratory : There are no data available on the mixture itself.

Sensitization

Conclusion/Summary

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary: There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Potential chronic health effects

General : Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Additional information

Sanding and grinding dusts may be harmful if inhaled.

| Chemical name | Identifiers | GHS Classification |
|--------------------------------------|----------------|---|
| Zinc powder - zinc dust (stabilized) | CAS: 7440-66-6 | SUBSTANCES AND MIXTURES, WHICH IN CONTACT WITH WATER, EMIT FLAMMABLE |
| | | GASES - Category 3 AQUATIC HAZARD (ACUTE) - Category 1 |
| zinc oxide | CAS: 1314-13-2 | AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 |

Korea (GHS) Page: 7/11

Product code 00322630 Date of issue 8/9/2024 (month/day/year) Version 4.07
Product name SIGMAZINC 158 HS PIGMENT GREY (K)

Section 12. Ecological information

A. **Ecotoxicity**

| Product/ingredient name | Result | Species | Exposure |
|--------------------------------------|-------------------------------------|---|----------|
| Zinc powder - zinc dust (stabilized) | Acute EC50 0.106 mg/l Fresh water | Algae - Pseudokirchneriella subcapitata | 72 hours |
| | Acute EC50 354 µg/l Fresh water | Daphnia - <i>Daphnia magna</i> | 48 hours |
| | Chronic EC10 6.3 µg/l | Daphnia - <i>Daphnia magna</i> - Neonate | 21 days |
| | Chronic LC10 185 µg/l Fresh water | Fish - <i>Oncorhynchus mykiss</i> - Juvenile (Fledgling, Hatchling, Weanling) | 30 days |
| zinc oxide | Acute EC50 0.17 mg/l | Algae | 72 hours |
| | Acute EC50 0.481 mg/l Fresh water | Daphnia - <i>Daphnia magna</i> - Neonate | 48 hours |
| | Chronic NOEC 0.017 mg/l Fresh water | Algae | 72 hours |

B. Persistence and degradability

Not available.

C. Bioaccumulative potential

Not available.

D. Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

E. Other adverse effects: No known significant effects or critical hazards.

Section 13. Disposal considerations

A. Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

B. Disposal precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Korea (GHS) Page: 8/11

Date of issue 8/9/2024 (month/day/year) Version 4.07

Product name SIGMAZINC 158 HS PIGMENT GREY (K)

Section 14. Transport information

| | UN | IMDG | IATA |
|--------------------------------|--|--|--|
| A. UN number | UN3077 | UN3077 | UN3077 |
| B. UN proper shipping name | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. |
| | (Zinc powder - zinc dust (stabilized), zinc oxide) | (Zinc powder - zinc dust (stabilized), zinc oxide) | (Zinc powder - zinc dust (stabilized), zinc oxide) |
| C. Transport hazard class(es) | 9 | 9 | 9 |
| D. Packing group | III | III | III |
| Environmental hazards | Yes. | Yes. | Yes. |
| E. Marine pollutant substances | Not applicable. | Zinc powder - zinc dust (stabilized)) | Not applicable. |

Additional information

Product code 00322630

UN : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg,

provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IMDG : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg,

provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

The segregation group has been manually assigned based upon product analysis.

in this product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg,

provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

F. Special precaution which a user to be aware of or needs to comply with in connection with transport or transportation

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

A. Regulation according to ISHA

ISHA article 117 : None of the components are listed.

(Harmful substances prohibited from manufacture)

ISHA article 118 : None of the components are listed.

(Harmful substances requiring permission)

Article 2 of Youth Protection : It is not allowed to sell to persons under the age of 19. Act on Substances Hazardous

to Youth

Korea (GHS) Page: 9/11

Product name SIGMAZINC 158 HS PIGMENT GREY (K)

Section 15. Regulatory information

Exposure Limits of Chemical Substances and Physical Factors

The following components have an OEL:

zinc oxide

Annex 19 (Exposure standards established for harmful factors)

ISHA Enforcement Regs

Annex 21 (Harmful factors subject to Work

Environment Measurement)

ISHA Enforcement Regs

Annex 22 (Harmful Factors Subject to Special Health Check-

up)

Standard of Industrial Safety and Health Annex 12 (Hazardous substances subject to

control)

ISHA Enforcement Regs: None of the components are listed.

: The following components are listed: zinc oxide

: The following components are listed: Zinc oxide

: The following components are listed: zinc and its compounds, zinc and its compounds

B. Regulation according to Chemicals Control Act

Article 11 (TRI) : The following components are listed: Zinc and its compounds, Zinc and its

: None of the components are listed.

: None of the components are listed.

: None of the components are listed.

compounds

: Not applicable

Article 18 Prohibited (K-

Reach Article 27)

Article 19 Subject to

authorization (K-Reach

Article 25)

Article 20 Restricted (K-

Reach Article 27)

Article 20 Toxic Chemicals (K-Reach

Article 20)

Korea inventory

Article 39 (Accident

Precaution Chemicals)

C. Dangerous Materials

Safety Management Act

: Class: Class 2 - Combustible Solid

: None of the components are listed.

: All components are listed or exempted.

Item: 5. Metal powder Threshold: 500 kg

Danger category: III

Signal word: Do not allow contact with water.

D. Wastes regulation : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

E. Regulation according to other foreign laws

Korea (GHS) Page: 10/11

Product name SIGMAZINC 158 HS PIGMENT GREY (K)

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

Section 16. Other information

A. References : Korean Ministry of Environment; Chemical Control Act

Korean Ministry of Labor; Industrial Safety and Health Act

NIER Notice

Registry of Toxic Effects of Chemical Substances (RTECS)

U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information

Retrieval) ECOTOX Database System.

B. First issue date : 6/16/2019C. Date of issue/Date of : 8/9/2024

revision

D. Version : 4.07
Prepared by : EHS

E. Other

▼ Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Korea (GHS) Page: 11/11