# SAFETY DATA SHEET

Date of issue/Date of revision : 13 August 2024 Version : 1.03



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : PSX 700 BAS RAL 1021

Product code : 00290879
Product type : Liquid.
Other means of : Not available.

identification

1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

**Uses advised against**: Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL Tweemontstraat 104 B-2100 Deurne Belgium

Telephone +32-33606311 Fax +32-33606435

e-mail address of person responsible for this SDS

: Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

**Supplier** 

+31 20 4075210

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Product definition : Mixture Classification according to UK CLP/GHS

Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word : Warning

**Hazard statements** : May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention**: Wear protective gloves. Avoid release to the environment. Avoid breathing vapour.

English (GB) United Kingdom (UK) 1/13

**PSX 700 BAS RAL 1021** 

### **SECTION 2: Hazards identification**

Response : Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with

plenty of water.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

P280, P273, P261, P362 + P364, P302 + P352, P501

Supplemental label

elements

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

**Special packaging requirements** 

Containers to be fitted

with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according

to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

Other hazards which do not result in classification

: None known.

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Туре
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	REACH #: 01-2119959495-22 EC: 500-070-7 CAS: 30583-72-3	≥25 - ≤50	Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5	≥0.30 - <2.5	Skin Sens. 1A, H317 Repr. 2, H361f Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
methanol	REACH #: 01-2119433307-44 EC: 200-659-6 CAS: 67-56-1 Index: 603-001-00-X	≤0.30	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT SE 1, H370	[1] [2]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

**PSX 700 BAS RAL 1021** 

## **SECTION 3: Composition/information on ingredients**

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

**Eye contact**: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids

apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained

personnel.

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water

or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show the container or label. Keep

person warm and at rest. Do NOT induce vomiting.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear

gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

### Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact** : May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

### Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

# **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

: None known.

### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

English (GB) United Kingdom (UK) 3/13

**PSX 700 BAS RAL 1021** 

# **SECTION 5: Firefighting measures**

Hazardous combustion products

: Decomposition products may include the following materials:

carbon oxides nitrogen oxides

halogenated compounds metal oxide/oxides

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**6.2 Environmental precautions** 

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

English (GB) United Kingdom (UK) 4/13

Code : 13 August 2024 : 00290879 Date of issue/Date of revision

### **PSX 700 BAS RAL 1021**

### **SECTION 7: Handling and storage**

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

### SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### **Occupational exposure limits**

Product/ingredient name	Exposure limit values
methanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.  STEL: 333 mg/m³ 15 minutes.  STEL: 250 ppm 15 minutes.  TWA: 266 mg/m³ 8 hours.  TWA: 200 ppm 8 hours.
Product/ingredient name	Exposure indices

# procedures

**Recommended monitoring**: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
4,4'- Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane	DNEL	Long term Dermal	0.021 mg/cm² skin	Workers	Local
	DNEL DNEL DNEL DNEL DNEL	Short term Dermal Short term Dermal Long term Dermal Long term Dermal Short term Dermal	0.23 mg/cm² skin 21 µg/cm² 21 µg/cm² 21 µg/cm² 0.23 mg/cm²	Workers General population General population Workers Workers	

5/13 English (GB) United Kingdom (UK)

**PSX 700 BAS RAL 1021** 

### **SECTION 8: Exposure controls/personal protection**

	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	0.5 mg/kg bw/day	General population	
	DNEL	Long term Dermal	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	1 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	1 mg/kg bw/day	Workers	Systemic
		· ·			•
	DNEL	Short term Inhalation	1.76 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	1.76 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	3.25 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	3.52 mg/m³	Workers	Systemic
methanol	DNEL	Short term Oral	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	4 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	4 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	20 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	20 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	26 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	26 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	26 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	26 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Inhalation	130 mg/m³	Workers	Local
	DNEL	Long term Inhalation	130 mg/m³	Workers	Local
	DNEL	Short term Inhalation	130 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	130 mg/m³	Workers	Systemic

#### **PNECs**

Product/ingredient name	Compartment Detail	Value	<b>Method Detail</b>
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Fresh water	11.5 µg/l	Assessment Factors
	Marine water	11.5 µg/l	Assessment Factors
	Sewage Treatment Plant	100 mg/l	Assessment Factors
	Fresh water sediment	0.229 mg/kg dwt	-
	Marine water sediment	0.023 mg/kg dwt	Equilibrium Partitioning
	Soil	0.099 mg/kg dwt	Equilibrium Partitioning
methanol	Fresh water	20.8 mg/l	Assessment Factors
	Marine water	2.08 mg/l	Assessment Factors
	Sewage Treatment Plant	100 mg/l	Assessment Factors
	Fresh water sediment	77 mg/kg	Equilibrium Partitioning
	Marine water sediment	7.7 mg/kg	Equilibrium Partitioning
	Soil	100 mg/kg	Assessment Factors

### 8.2 Exposure controls

**Appropriate engineering** controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection Skin protection Hand protection** 

: Safety glasses with side shields.

6/13 English (GB) **United Kingdom (UK)** 

**PSX 700 BAS RAL 1021** 

### **SECTION 8: Exposure controls/personal protection**

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

butvl rubber

**Body protection**: Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before

handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

**Respiratory protection**: Respirator selection must be based on known or anticipated exposure levels, the

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate

filter P3

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### **Appearance**

Physical state : Liquid.
Colour : Various

Odour : Characteristic.
Odour threshold : Not available.

Melting point/freezing point : May start to solidify at the following temperature: -12.9°C (8.8°F) This is based on

data for the following ingredient: 4,4'-Isopropylidenedicyclohexanol, oligomeric

reaction products with 1-chloro-2,3-epoxypropane.

Initial boiling point and

boiling range

: >37.78°C (>100°F)

Flammability (solid, gas)

Upper/lower flammability or

**explosive limits** 

iliquid

: Not available.

Flash point : Closed cup: Not applicable.

**Auto-ignition temperature** :

Ingredient name	°C	°F	Method
(2,3-dihydro-2-oxo-1H-benzimidazol-5-yl)-3-oxo-2-[2-(trifluoromethyl)phenyl]azo]butyramide	290	554	

pH : Not applicable.

English (GB)	United Kingdom (UK)	7/13
Eligiisii (OD)		

**PSX 700 BAS RAL 1021** 

### **SECTION 9: Physical and chemical properties**

Not applicable. insoluble in water.

**Viscosity** Kinematic (40°C): >21 mm<sup>2</sup>/s

Solubility(ies)

Media Result cold water Not soluble

Miscible with water : No.

Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure : Not available.

**Relative density** : 1.18

**Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of

vapour or dust with air is possible.

**Oxidising properties** 

**Particle characteristics** 

: Product does not present an oxidizing hazard.

Median particle size : Not applicable.

### SECTION 10: Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. 10.1 Reactivity

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

: Keep away from the following materials to prevent strong exothermic reactions: 10.5 Incompatible materials

oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/

oxides

# SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	LD50 Dermal	Rat	>3170 mg/kg	-
	LD50 Oral	Rat - Male, Female	3230 mg/kg	-
methanol	LC50 Inhalation Vapour LD50 Dermal LD50 Oral	Rat Rabbit Rat	64000 ppm 15800 mg/kg 5600 mg/kg	4 hours - -

**Conclusion/Summary Acute toxicity estimates** 

: There are no data available on the mixture itself.

8/13 English (GB) United Kingdom (UK)

**PSX 700 BAS RAL 1021** 

### **SECTION 11: Toxicological information**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
PSX 700 BAS RAL 1021 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate methanol	81849.8 3230 100	245549.4 N/A 300	N/A N/A 64000	2455.5 N/A	N/A N/A

#### **Irritation/Corrosion**

**Conclusion/Summary**: Not available.

Skin : There are no data available on the mixture itself.
 Eyes : There are no data available on the mixture itself.
 Respiratory : There are no data available on the mixture itself.

**Sensitisation** 

**Conclusion/Summary** 

Skin: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary** 

Carcinogenicity

There are no data available on the mixture itself.

Conclusion/Summary

Reproductive toxicity

**Conclusion/Summary** 

**Teratogenicity** 

: There are no data available on the mixture itself.

: There are no data available on the mixture itself.

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
methanol	Category 1	-	-

### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

**Information on likely routes**: Not available.

of exposure

### Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

English (GB) United Kingdom (UK) 9/13

**PSX 700 BAS RAL 1021** 

### **SECTION 11: Toxicological information**

Ingestion : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary**: Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Other information : Not available.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
4,4'- Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane Reaction mass of bis (1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	LC50 11.5 mg/l EC50 1.68 mg/l	Fish - Trout Algae	96 hours 72 hours
methanol	LC50 0.9 mg/l Acute LC50 13 mg/l Fresh water	Fish Fish - Trout	96 hours 96 hours

**Conclusion/Summary**: Not available.

### 12.2 Persistence and degradability

**Conclusion/Summary**: Not available.

### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
methanol	-0.77	-	Low

#### 12.4 Mobility in soil

Soil/water partition : Not available.

coefficient (Koc)

English (GB) United Kingdom (UK) 10/13

**PSX 700 BAS RAL 1021** 

### **SECTION 12: Ecological information**

Mobility : Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects**: No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

### **Product**

Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** 

Yes.

#### Waste catalogue

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

#### **Packaging**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	Waste catalogue	
Container	15 01 06	mixed packaging

#### Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

English (GB) United Kingdom (UK) 11/13

**PSX 700 BAS RAL 1021** 

### **SECTION 14: Transport information**

### **Additional information**

ADR/RID : None identified.

: The product is only regulated as a dangerous good when transported in tank vessels. **ADN** 

**IMDG** : None identified. : None identified. **IATA** 

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

### **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture **UK (GB)/REACH**

### Annex XIV - List of substances subject to authorisation

### **Annex XIV**

None of the components are listed.

### **Substances of very high concern**

None of the components are listed.

### Ozone depleting substances

Not listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

### **Seveso Directive**

This product is not controlled under the Seveso Directive.

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and

Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019

No. 720 and amendments

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = GB CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification

Classification	Justification
Skin Sens. 1, H317 Aquatic Chronic 3, H412	Calculation method Calculation method

### Full text of abbreviated H statements

English (GB)	United Kingdom (UK)	12/13
--------------	---------------------	-------

**PSX 700 BAS RAL 1021** 

### **SECTION 16: Other information**

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H361f	Suspected of damaging fertility.
H370	Causes damage to organs.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### **Full text of classifications**

Acute Tox. 3
Aquatic Acute 1
Aquatic Chronic 1
Aquatic Chronic 3
Flam. Liq. 2
ACUTE TOXICITY - Category 3
SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
FLAMMABLE LIQUIDS - Category 2

FLAMMABLE LIQUIDS - CATEGORY 2

Repr. 2 REPRODUCTIVE TOXICITY - Category 2
Skin Sens. 1 SKIN SENSITISATION - Category 1
Skin Sens. 1A SKIN SENSITISATION - Category 1A

STOT SE 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1

#### **History**

Date of issue/ Date of : 13 August 2024

revision

Date of previous issue : 26 June 2024

Prepared by : EHS Version : 1.03

### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

English (GB) United Kingdom (UK) 13/13