SAFETY DATA SHEET

Date of issue/Date of revision : 13 August 2024

Version

: 1



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: PSX 700 CURE 0.2G
Product code	: 000001100597
Other means of identification 00281492	on
1.2 Relevant identified uses	of the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
1.3 Details of the supplier of	the safety data sheet
Sigma Paint Saudi Arabia Ltd PO Box 7509 Dammam 31472 Saudi Arabia Tel: 00966 138 47 31 00 Fax: 00966 138 47 17 34	
e-mail address of person responsible for this SDS	: ndpic@sfda.gov.sa
1.4 Emergency telephone	: 00966 138473100 extn 1001

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

 Product definition
 : Mixture

 Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

 Flam. Liq. 3, H226

 Acute Tox. 4, H302

 Skin Corr. 1B, H314

 Eye Dam. 1, H318

Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360FD STOT SE 2, H371 STOT RE 2, H373 Aquatic Chronic 2, H411

number

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Code : 000001100597 PSX 700 CURE 0.2G	Date of issue/Date of revision: 13 August 2024
SECTION 2: Hazards	dentification
Hazard pictograms	
	Danger
Hazard statements	Flammable liquid and vapour. Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing genetic defects. May damage fertility. May damage the unborn child. May cause damage to organs. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Do not breathe vapour.
Response	Collect spillage.
Storage	Not applicable.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations. P280, P210, P273, P260, P391, P501
Hazardous ingredients	3-aminopropyltriethoxysilane dibutylbis(pentane-2,4-dionato-O,O')tin
Supplemental label elements	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Restricted to professional users.
Special packaging requirem	<u>nts</u>
Containers to be fitted with child-resistant fastenings	Not applicable.
Tactile warning of danger	Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB	This mixture does not contain any substances that are assessed to be a PBT or a vPv
Other hazards which do not result in classification	Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation.

: 000001100597 Code

Date of issue/Date of revision

: 13 August 2024

PSX 700 CURE 0.2G

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
3-aminopropyltriethoxysilane	REACH #: 01-2119480479-24 EC: 213-048-4 CAS: 919-30-2 Index: 612-108-00-0	≥90	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317	ATE [Oral] = 1570 mg/ kg	[1]
dibutylbis(pentane- 2,4-dionato-O,O')tin	REACH #: 01-2119557817-24 EC: 245-152-0 CAS: 22673-19-4 Index: 650-056-00-0	≥5.0 - <10	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360FD STOT SE 1, H370 STOT RE 1, H372 (immune system) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 1864 mg/ kg M [Acute] = 1 M [Chronic] = 1	[1] [2]
ethanol	REACH #: 01-2119457610-43 EC: 200-578-6 CAS: 64-17-5 Index: 603-002-00-5	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Eye Irrit. 2, H319 See Section 16 for the full text of the H	-	[1] [2]
			statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

		English (GB)	United Arab Emirates	3/15
Protection of first-aiders	:	suspected that fumes are still prese self-contained breathing apparatus.	ny personal risk or without suitable tra nt, the rescuer should wear an appro It may be dangerous to the person p Wash contaminated clothing thoroug	priate mask or providing aid to
Ingestion	:	If swallowed, seek medical advice in person warm and at rest. Do NOT i	mmediately and show the container o nduce vomiting.	r label. Keep
Skin contact		Remove contaminated clothing and or use recognised skin cleanser. Do	shoes. Wash skin thoroughly with so NOT use solvents or thinners.	ap and water
Inhalation	:		varm and at rest. If not breathing, if br irs, provide artificial respiration or oxy	
Eye contact	:		enses. Immediately flush eyes with rus open. Seek immediate medical atter	

Code : 000001100597 PSX 700 CURE 0.2G Date of issue/Date of revision

: 13 August 2024

SECTION 4: First aid measures

otential acute health	
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns. May cause damage to organs following a single exposure in contact with skin. Defatting to the skin. May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed. Corrosive to the digestive tract. Causes burns. May cause damage to organs following a single exposure if swallowed.
<u>)ver-exposure signs/</u>	'symptoms
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness dryness cracking blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
5.2 Special hazards arising f	rom the substance or mixture
Hazards from the substance or mixture	: Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

English (GB)	United Arab Emirates

Code	: 000001100597	Date of issue/Date of revision	: 13 August 2024
PSX 700 CURE 0.2G			

SECTION 5: Firefighting measures

•	
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides Formaldehyde.
5.3 Advice for firefighters	
Special precautions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures For non-emergency personnel No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. For emergency responders If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions
 Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
6.4 Reference to other sections	 See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

Code : 000001100597

Date of issue/Date of revision

: 13 August 2024

PSX 700 CURE 0.2G

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
dibutylbis(pentane-2,4-dionato-O,O')tin	 Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016). [tin organic compounds] Absorbed through skin. STEL: 0.2 mg/m³, (as Sn) 15 minutes. TWA: 0.1 mg/m³, (as Sn) 8 hours. Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006). [tin (organic compounds)] Absorbed through skin. TWA: 0.1 mg/m³, (as Sn) 8 hours. STEL: 0.2 mg/m³, (as Sn) 8 hours.
	English (GB) United Arab Emirates 6/15

code : 0000011005	7	Date of issue/Date of revision	: 13 August 2024			
PSX 700 CURE 0.2G			C C			
ethanol		 ACGIH TLV (United States). Absorbed through skin. STEL: 0.2 mg/m³ ACGIH TLV (United States, 7/2023). [Tin, organic compounds] Absorbed through skin. TWA: 0.1 mg/m³, (as Sn) 8 hours. STEL: 0.2 mg/m³, (as Sn) 15 minutes. Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016). STEL: 1000 ppm 15 minutes. STEL: 1880 mg/m³ 15 minutes. ACGIH TLV (United States, 7/2023). Notes: 1996 Adoption Refers to Appendix A Carcinogens. STEL: 1000 ppm 15 minutes. 				
Recommended monitoring procedures	Standard EN 689 by inhalation to ch strategy) Europea application and us biological agents) requirements for th agents) Referenc	be made to monitoring standards, such as the (Workplace atmospheres - Guidance for the emical agents for comparison with limit value an Standard EN 14042 (Workplace atmosphere e of procedures for the assessment of expose European Standard EN 482 (Workplace atmosphere he performance of procedures for the measure to national guidance documents for method stances will also be required.	assessment of exposure es and measurement eres - Guide for the sure to chemical and nospheres - General rement of chemical			
.2 Exposure controls						
Appropriate engineering controls	other engineering recommended or	quate ventilation. Use process enclosures, lo controls to keep worker exposure to airborne statutory limits. The engineering controls als ncentrations below any lower explosive limits lent.	e contaminants below an o need to keep gas,			
Individual protection meas	<u>ures</u>					
Hygiene measures	eating, smoking an Appropriate techni Contaminated wor contaminated clot	arms and face thoroughly after handling cher nd using the lavatory and at the end of the wo iques should be used to remove potentially c rk clothing should not be allowed out of the w hing before reusing. Ensure that eyewash st to the workstation location.	orking period. ontaminated clothing. orkplace. Wash			
Eye/face protection Skin protection	: Chemical splash g	goggles and face shield.				
Hand protection	worn at all times w necessary. Considuring use that the noted that the time glove manufacture protection time of frequently repeate (breakthrough time When only brief co (breakthrough time The user must che product is the mos	t, impervious gloves complying with an approvent in the parameters specified by the glove egloves are still retaining their protective properts to breakthrough for any glove material may ers. In the case of mixtures, consisting of severe gloves cannot be accurately estimated. Note the gloves cannot be accurately estimated. Note contact may occur, a glove with a protection of e greater than 480 minutes according to EN 33 eck that the final choice of type of glove select appropriate and takes into account the part user's risk assessment.	essment indicates this is manufacturer, check berties. It should be be different for different veral substances, the When prolonged or n class of 6 374) is recommended. class of 2 or higher 74) is recommended. cted for handling this			

Code : 000001100593	Date of issue/Date of revision : 13 August 2024
PSX 700 CURE 0.2G	
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>								
Physical state		Liquid.						
Colour		Colourless.						
Odour	4	Amine-like.						
Odour threshold		Not available.						
Melting point/freezing point	•	May start to solidify a data for the following average: 4.61°C (40.	ingredier					
Initial boiling point and boiling range	:	>37.78°C						
Flammability	:	Not available.						
Upper/lower flammability or explosive limits	:	Greatest known rang	e: Lower:	3.3% Up	oper: 19% (et	hanol)		
Flash point	:	Closed cup: 47°C						
Auto-ignition temperature	:	Ingredient name		°C	°F		Nethod	
		dibutylbis(pentane-2,4-dio	onato-O,O')t	in 400	752	E	U A.15	
Decomposition temperature	:	Stable under recomm	nended st	orage an	d handling co	nditions	(see Sec	tion 7).
рН	:	Not applicable.						
Viscosity	:	Kinematic (40°C): >2	1 mm²/s					
Viscosity	4	60 - 100 s (ISO 6mm	ı)					
Solubility(ies)	4							
Media		Result						
cold water		Not soluble						
Partition coefficient: n-octanol/ water	:	Not applicable.						
Vapour pressure	;	Ingredient name	Vapoι	ır Pressı	ire at 20°C	Vap	our press	sure at 50°C
		Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
		ethanol	42.94865	5.7				
Evaporation rate		1.7 (ethanol) compar	l ed with by	itvl aceta	te			
Relative density		0.96		alyr acela				
				11	ted Arels Fr			0/4 5
		Engl	lish (GB)	Un	ited Arab En	iirates		8/15

 Code
 <th::000001100597</th>
 Date of issue/Date of revision
 : 13 August 2024

 PSX 700 CURE 0.2G

SECTION 9: Physical and chemical properties

Bulk density (g/cm ³)	: 0.963
Vapour density	: Highest known value: 1.6 (Air = 1) (ethanol).
Explosive properties	 The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
Oxidising properties	: Product does not present an oxidizing hazard.
Particle characteristics	
Median particle size	: Not applicable.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity				
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
10.2 Chemical stability	: The product is stable.			
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.			
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.			
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides. Formaldehyde, metal oxide/oxides			

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
3-aminopropyltriethoxysilane	LC50 Inhalation Dusts and	Rat	>7.35 mg/l	4 hours
	mists LD50 Dermal	Rabbit	4 g/kg	-
	LD50 Oral	Rat	1.57 g/kg	-
dibutylbis(pentane-2,4-dionato-O,O')tin	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1864 mg/kg	-
ethanol	LC50 Inhalation Vapour	Rat	124700 mg/m ³	4 hours
	LD50 Dermal	Rat	17100 mg/kg	-
	LD50 Oral	Rat	7 g/kg	-
Conclusion/Summary : There ar	e no data available on the mixtu	re itself.		
Irritation/Corrosion				
Conclusion/Summary				
Skin : There are	e no data available on the mixtur	e itself.		
Eyes : There are	e no data available on the mixtur	e itself.		
Respiratory : There are	e no data available on the mixtur	e itself.		
<u>Sensitisation</u>				

Code	: 000001100597	Date of issue/Date of revision	: 13 August 2024
PSX 700 (CURE 0.2G		

SECTION 11: Toxicological information

Product/ingr	redient name	Route of exposure		Result
3-aminopropyltriethoxysilar	ne	skin	Guinea pig	Sensitising
Conclusion/Summary Skin Respiratory	: There are no data : There are no data	a available on the mi a available on the mi		
<u>Mutagenicity</u> Conclusion/Summary	: There are no data	a available on the mi	xture itself	
Carcinogenicity Conclusion/Summary	: There are no data			
Reproductive toxicity Conclusion/Summary	: There are no data			
<u>Feratogenicity</u> Conclusion/Summary	: There are no data			
-	igredient name	Catego	ry Route of exposure	Target organs
nformation on likely outes of exposure	: Not available.			
Potential acute health effe	<u>ects</u>			
Inhalation	: No known signific	ant effects or critica	hazards.	
Ingestion	damage to organs	s following a single e	e digestive tract. Cause exposure if swallowed.	
Skin contact	contact with skin.	Defatting to the ski	mage to organs followir n. May cause an allergi	
Eye contact	: Causes serious e			
Symptoms related to the Inhalation	 physical, chemical and : Adverse symptom reduced foetal we increase in foetal skeletal malforma 	ns may include the fo ight deaths		
Ingestion	: Adverse symptom stomach pains reduced foetal we increase in foetal skeletal malforma	ight deaths	bllowing:	
Skin contact	: Adverse symptom pain or irritation redness dryness cracking blistering may occ reduced foetal we increase in foetal skeletal malforma	cur ight deaths	ollowing:	
Eye contact	: Adverse symptom pain watering redness	ns may include the fo	bllowing:	
Delayed and immediate e	ffects as well as chron	ic effects from sho	rt and long-term expo	<u>osure</u>
Short term exposure				
		English (GB)	United Arab Emirate	es 10/1

English (GB) United Arab Emirates

Code	: 000001100597	Date of issue/Date of revision	: 13 August 2024
PSX 700 CUP	RE 0.2G		

SECTION 11: Toxicological information

		5
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effe	ct	<u>s</u>
Not available.		
Conclusion/Summary	:	Not available.
General	:	May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	Suspected of causing genetic defects.
Reproductive toxicity	:	May damage fertility. May damage the unborn child.
Other information	:	Not available.

Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
3-aminopropyltriethoxysilane ethanol	Acute LC50 >934 mg/l Acute EC50 7640 mg/l Fresh water	Fish Daphnia - <i>Daphnia</i> <i>magna</i>	96 hours 48 hours

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

Conclusion/Summary : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
ethanol	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
3-aminopropyltriethoxysilane ethanol	1.7 -0.35	3.4	Low Low
Culdion	-0.00		LOW

English (GB) United Arab Emirates

Code	: 000001100597	Date of issue/Date of revision	: 13 August 2024
PSX 700 CUF	RE 0.2G		

SECTION 12: Ecological information

12.4 Mobility in soil	
Soil/water partition coefficient (K _{oc})	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC)

Waste code	Waste designation waste paint and varnish containing organic solvents or other hazardous substances		
08 01 11*			
ackaging			
Methods of disposal	 The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. 		
Type of packaging	European waste catalogue (EWC)		
Container	15 01 06 mixed packaging		
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly		

drains and sewers.

internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways,

Code : 000001100597

Date of issue/Date of revision :

: 13 August 2024

PSX 700 CURE 0.2G

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	UN3470	UN3470	UN3470
14.2 UN proper shipping name	PAINT, CORROSIVE, FLAMMABLE	PAINT, CORROSIVE, FLAMMABLE	Paint, corrosive, flammable
14.3 Transport hazard class(es)	8 (3)	8 (3)	8 (3)
14.4 Packing group	11	П	11
14.5 Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(dibutylbis(pentane- 2,4-dionato-O,O')tin)	Not applicable.

Additional information

ADR/RID	: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Tunnel code	: (D/E)
IMDG	: The marine pollutant mark is not required when transported in sizes of \leq 5 L or \leq 5 kg.
ΙΑΤΑ	: The environmentally hazardous substance mark may appear if required by other transportation regulations.
14.6 Special pred user	cautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Transport ir according to IMC instruments	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
Toxic to reproduction	dibutylbis(pentane-2,4-dionato-O,O')tin	Candidate	D(2020) 4578-DC	6/25/2020
Annex XVII - Restriction on the manufacture, placing on the market and use of certain dangerous substances mixtures and articles				

Date of issue/Date of revision

: 13 August 2024

Code : 000001100597

PSX 700 CURE 0.2G

SECTION 15: Regulatory information

Other national and international regulations.Explosive precursors: Not applicable.Ozone depleting substances (1005/2009/EU)Not listed.

15.2 Chemical safety

: No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

Indicates information that	has changed from previous	ly issued versio	n.	
Abbreviations and acronyms	: ATE = Acute Toxicity E CLP = Classification, L 1272/2008] DNEL = Derived No Et EUH statement = CLP PNEC = Predicted No RRN = REACH Regist	abelling and Pa fect Level -specific Hazar Effect Concent		
Full text of abbreviated H statements	: H225 Highly flamm H226 Flammable I H302 Harmful if sw H314 Causes seve H317 May cause a H318 Causes seric H319 Causes seric H341 Suspected o H360FD May damage H370 Causes dam H371 May cause d H372 Causes dam H373 May cause d H400 Very toxic to H410 Very toxic to	able liquid and quid and vapou /allowed. ere skin burns a n allergic skin r ous eye damage ous eye irritation f causing genet e fertility. May da age to organs. amage to organs t amage to organs t	ur. and eye damage. reaction. e. n. tic defects. amage the unborn child.	e.
Full text of classifications [CLP/GHS]	: Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Eye Dam. 1 Eye Irrit. 2 Flam. Liq. 2 Flam. Liq. 3 Muta. 2 Repr. 1B Skin Corr. 1B Skin Corr. 1B Skin Corr. 1C Skin Sens. 1 STOT RE 1 STOT RE 2 STOT SE 1 STOT SE 2	SHORT-T LONG-TE SERIOUS SERIOUS FLAMMAE FLAMMAE GERM CE REPRODI SKIN COF SKIN COF SKIN SEN SPECIFIC EXPOSUF SPECIFIC EXPOSUF SPECIFIC EXPOSUF	OXICITY - Category 4 ERM (ACUTE) AQUATIC HAZARD - Cate RM (CHRONIC) AQUATIC HAZARD - Cate RM (CHRONIC) AQUATIC HAZARD - Cate RM (CHRONIC) AQUATIC HAZARD - Cate EYE DAMAGE/EYE IRRITATION - Cate EYE DAMAGE/EYE IRRITATION - Cate EYE DAMAGE/EYE IRRITATION - Cate BLE LIQUIDS - Category 2 BLE LIQUIDS - Category 3 ELL MUTAGENICITY - Category 18 RROSION/IRRITATION - Category 18 RROSION/IRRITATION - Category 18 RROSION/IRRITATION - Category 18 RROSION/IRRITATION - Category 10 SITISATION - Category 1 CARGET ORGAN TOXICITY - REPEATI RE - Category 1 C TARGET ORGAN TOXICITY - REPEATI RE - Category 2 C TARGET ORGAN TOXICITY - SINGLE RE - Category 1 C TARGET ORGAN TOXICITY - SINGLE RE - Category 1	itegory 1 itegory 2 gory 1 gory 2 ED
<u>History</u> Date of issue/ Date of revision	: 13 August 2024			
	Er	nglish (GB)	United Arab Emirates	14/15

Conforms to Regulation (I 2020/878	EC) No. 1907/2006 (REACH), A	nnex II, as amended by Commissio	n Regulation (EU)
Code : 000001100	597	Date of issue/Date of revision	: 13 August 2024
PSX 700 CURE 0.2G			
SECTION 16: Othe	r information		
Date of previous issue	: No previous validation		
Prepared by	: EHS		

Version

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

: 1