

# SAFETY DATA SHEET



Date of issue/Date of revision : 13 August 2024 Version : 22.01

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : SIGMAPRIME 700 BASE REDBROWN

**Product code** : 00267439

#### Other means of identification

Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

**Use of the substance/mixture** : Coating.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL  
Tweemontstraat 104  
B-2100 Deurne  
Belgium  
Telephone +32-33606311  
Fax +32-33606435

**e-mail address of person responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : Poison Information Centre; emergency telephone, public + 45 82 12 12 12 (health sector +45 35 31 55 55)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

STOT RE 1, H372

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Code : 00267439

Date of issue/Date of revision

: 13 August 2024

SIGMAPRIME 700 BASE REDBROWN

## SECTION 2: Hazards identification

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

#### Hazard pictograms



#### Signal word

: Danger

#### Hazard statements

: Flammable liquid and vapour.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Causes damage to organs through prolonged or repeated exposure.  
Harmful to aquatic life with long lasting effects.

#### Precautionary statements

##### Prevention

: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Do not breathe vapour.

##### Response

: Get medical advice/attention if you feel unwell.

##### Storage

: Not applicable.

##### Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

P280, P210, P273, P260, P314, P501

#### Hazardous ingredients

crystalline silica, respirable powder (<10 microns)  
Epoxy Resin (700<MW<=1100)  
Phenol, methylstyrenated  
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.  
Cashew, nutshell liq.

#### Supplemental label elements

: Not applicable.

#### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

#### Special packaging requirements

##### Containers to be fitted with child-resistant fastenings

: Not applicable.

##### Tactile warning of danger

: Not applicable.

### 2.3 Other hazards

#### Product meets the criteria for PBT or vPvB

: This mixture contains substances that are assessed to be a PBT or a vPvB, refer to Section 3.2.

#### Other hazards which do not result in classification

: Prolonged or repeated contact may dry skin and cause irritation. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F.

Code : 00267439 Date of issue/Date of revision : 13 August 2024  
SIGMAPRIME 700 BASE REDBROWN

## SECTION 2: Hazards identification

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

| Product/ingredient name                             | Identifiers   | % by weight | Classification   | Specific Conc. Limits, M-factors and ATEs                         | Type    |
|---|---|-------------|--|---|---------|
| crystalline silica, respirable powder (<10 microns) | EC: 238-878-4<br>CAS: 14808-60-7  | ≥10 - ≤25   | STOT RE 1, H372 (inhalation)   | -   | [1] [2] |
| Epoxy Resin (700<MW ≤1100)                          | CAS: 25036-25-3   | ≥10 - ≤25   | Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1, H317  | -   | [1]     |
| xylene  | REACH #:<br>01-2119488216-32<br>EC: 215-535-7<br>CAS: 1330-20-7                         | ≥10 - ≤18   | Flam. Liq. 3, H226<br>Acute Tox. 4, H312<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412 | ATE [Dermal] = 1700 mg/kg<br>ATE [Inhalation (vapours)] = 11 mg/l | [1] [2] |
| Phenol, methylstyrenated                            | REACH #:<br>01-2119555274-38<br>EC: 270-966-8<br>CAS: 68512-30-1                        | ≥1.0 - ≤5.0 | Skin Irrit. 2, H315<br>Skin Sens. 1, H317<br>Aquatic Chronic 3, H412   | -   | [1] [3] |
| Solvent naphtha (petroleum), heavy arom. Nota(s) P  | REACH #:<br>01-2119451097-39<br>EC: 265-198-5<br>CAS: 64742-94-5<br>Index: 649-424-00-3 | ≥1.0 - ≤5.0 | STOT SE 3, H336<br>Asp. Tox. 1, H304<br>Aquatic Chronic 2, H411<br>EUH066  | -   | [1]     |
| oxirane, mono[(C12-14-alkyloxy)methyl] derivs.      | REACH #:<br>01-2119485289-22<br>EC: 271-846-8<br>CAS: 68609-97-2<br>Index: 603-103-00-4 | ≥1.0 - ≤5.0 | Skin Irrit. 2, H315<br>Skin Sens. 1, H317  | -   | [1]     |
| 1-methoxy-2-propanol                                | REACH #:<br>01-2119457435-35<br>EC: 203-539-1<br>CAS: 107-98-2<br>Index: 603-064-00-3   | ≥1.0 - ≤5.0 | Flam. Liq. 3, H226<br>STOT SE 3, H336  | -   | [1] [2] |
| ethylbenzene  | REACH #:<br>01-2119489370-35<br>EC: 202-849-4<br>CAS: 100-41-4<br>Index: 601-023-00-4   | ≥1.0 - ≤5.0 | Flam. Liq. 2, H225<br>Acute Tox. 4, H332<br>STOT RE 2, H373 (hearing organs)<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412                             | ATE [Inhalation (vapours)] = 17.8 mg/l                            | [1] [2] |
| Cashew, nutshell liq.                               | EC: 232-355-4<br>CAS: 8007-24-7   | ≤1.6        | Acute Tox. 4, H302<br>Acute Tox. 4, H312<br>Skin Irrit. 2, H315  | ATE [Oral] = 500 mg/kg<br>ATE [Dermal] = 1100                     | [1]     |

Code : 00267439 Date of issue/Date of revision : 13 August 2024  
 SIGMAPRIME 700 BASE REDBROWN

### SECTION 3: Composition/information on ingredients

|  |   |             |   | mg/kg   |         |
|--|---|-------------|---|---|---------|
| Urea, polymer with formaldehyde, butylated | CAS: 68002-19-7   | ≥1.0 - ≤5.0 | Eye Dam. 1, H318<br>Skin Sens. 1, H317  | -   | [1]     |
| 2-methylpropan-1-ol                        | REACH #:<br>01-2119484609-23<br>EC: 201-148-0<br>CAS: 78-83-1<br>Index: 603-108-00-1  | ≤1.3        | Aquatic Chronic 4, H413<br><br>Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>STOT SE 3, H335<br>STOT SE 3, H336  | -   | [1] [2] |
| 4-methylpentan-2-one                       | REACH #:<br>01-2119473980-30<br>EC: 203-550-1<br>CAS: 108-10-1<br>Index: 606-004-00-4 | ≤0.30       | Flam. Liq. 2, H225<br>Acute Tox. 4, H332<br>Eye Irrit. 2, H319<br>Carc. 2, H351<br>STOT SE 3, H336<br>EUH066<br><b>See Section 16 for the full text of the H statements declared above.</b> | ATE [Inhalation (vapours)] = 11 mg/l<br>EUH066: C ≥ 20% | [1] [2] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Xylene: Several REACH registrations cover the REACH registered substance with xylene isomers, ethylbenzene (and toluene). The other REACH Registrations include: 01-211955267-33 reaction mass of ethylbenzene and m-xylene and p-xylene, 01-2119486136-34 Aromatic hydrocarbons, C8, 01-2119539452-40 reaction mass of ethylbenzene and xylene.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

- Eye contact** : Causes serious eye irritation.

Code : 00267439 Date of issue/Date of revision : 13 August 2024  
SIGMAPRIME 700 BASE REDBROWN

## SECTION 4: First aid measures

- Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.  
**Ingestion** : No known significant effects or critical hazards.

### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
nitrogen oxides  
halogenated compounds  
metal oxide/oxides  
Formaldehyde.

### 5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Code : 00267439

Date of issue/Date of revision

: 13 August 2024

SIGMAPRIME 700 BASE REDBROWN

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Code : 00267439

Date of issue/Date of revision

: 13 August 2024

SIGMAPRIME 700 BASE REDBROWN

## SECTION 7: Handling and storage

### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name                             | Exposure limit values   |
|---|---|
| crystalline silica, respirable powder (<10 microns) | <b>Working Environment Authority (Denmark, 2/2023). Carcinogen.</b><br>TWA: 0.1 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction<br>STEL: 0.2 mg/m <sup>3</sup> 15 minutes. Form: Respirable fraction   |
| xylene  | TWA: 0.3 mg/m <sup>3</sup> 8 hours. Form: total<br>STEL: 0.6 mg/m <sup>3</sup> 15 minutes. Form: total<br><b>Working Environment Authority (Denmark, 2/2023). [xylen, alle isomere] Absorbed through skin.</b><br>TWA: 109 mg/m <sup>3</sup> 8 hours.<br>TWA: 25 ppm 8 hours.<br>STEL: 442 mg/m <sup>3</sup> 15 minutes.<br>STEL: 100 ppm 15 minutes. |
| 1-methoxy-2-propanol                                | <b>Working Environment Authority (Denmark, 2/2023). [1-methoxy-2-propanol] Absorbed through skin.</b><br>TWA: 185 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours.<br>STEL: 568 mg/m <sup>3</sup> 15 minutes.<br>STEL: 150 ppm 15 minutes.  |
| ethylbenzene  | <b>Working Environment Authority (Denmark, 2/2023). Absorbed through skin. Carcinogen.</b><br>TWA: 217 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours.<br>STEL: 434 mg/m <sup>3</sup> 15 minutes.<br>STEL: 100 ppm 15 minutes.   |
| 2-methylpropan-1-ol                                 | <b>Working Environment Authority (Denmark, 2/2023). [butanol, alle isomere] Absorbed through skin.</b><br>CEIL: 150 mg/m <sup>3</sup>   |



Code : 00267439

Date of issue/Date of revision

: 13 August 2024

SIGMAPRIME 700 BASE REDBROWN

## SECTION 8: Exposure controls/personal protection

4-methylpentan-2-one

CEIL: 50 ppm

**Working Environment Authority (Denmark, 2/2023). Absorbed through skin.**

TWA: 83 mg/m<sup>3</sup> 8 hours.

TWA: 20 ppm 8 hours.

STEL: 208 mg/m<sup>3</sup> 15 minutes.

STEL: 50 ppm 15 minutes.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs

| Product/ingredient name                            | Type                     | Exposure              | Value                    | Population         | Effects            |
|--|--------------------------|-----------------------|--------------------------|--------------------|--------------------|
| Xylene   | DNEL                     | Long term Oral        | 5 mg/kg bw/day           | General population | Systemic           |
|  | DNEL                     | Long term Inhalation  | 65.3 mg/m <sup>3</sup>   | General population | Local              |
|  | DNEL                     | Long term Inhalation  | 65.3 mg/m <sup>3</sup>   | General population | Systemic           |
|  | DNEL                     | Long term Dermal      | 125 mg/kg bw/day         | General population | Systemic           |
|  | DNEL                     | Long term Dermal      | 212 mg/kg bw/day         | Workers            | Systemic           |
|  | DNEL                     | Long term Inhalation  | 221 mg/m <sup>3</sup>    | Workers            | Local              |
|  | DNEL                     | Long term Inhalation  | 221 mg/m <sup>3</sup>    | Workers            | Systemic           |
|  | DNEL                     | Short term Inhalation | 260 mg/m <sup>3</sup>    | General population | Local              |
|  | DNEL                     | Short term Inhalation | 260 mg/m <sup>3</sup>    | General population | Systemic           |
|  | DNEL                     | Short term Inhalation | 442 mg/m <sup>3</sup>    | Workers            | Local              |
|  | DNEL                     | Short term Inhalation | 442 mg/m <sup>3</sup>    | Workers            | Systemic           |
|  | Phenol, methylstyrenated | DNEL                  | Long term Oral           | 0.2 mg/kg bw/day   | General population |
| DNEL   |                          | Long term Inhalation  | 0.348 mg/m <sup>3</sup>  | General population | Systemic           |
| DNEL   |                          | Long term Inhalation  | 1.41 mg/m <sup>3</sup>   | Workers            | Systemic           |
| DNEL   |                          | Long term Dermal      | 1.67 mg/kg bw/day        | General population | Systemic           |
| DNEL   |                          | Long term Dermal      | 3.5 mg/kg bw/day         | Workers            | Systemic           |
| DNEL   |                          | Long term Oral        | 0.03 mg/kg bw/day        | General population | Systemic           |
| Solvent naphtha (petroleum), heavy arom. Nota(s) P | DNEL                     | Long term Dermal      | 0.28 mg/kg bw/day        | General population | Systemic           |
|  | DNEL                     | Long term Inhalation  | 0.69 mg/m <sup>3</sup>   | General population | Local              |
|  | DNEL                     | Long term Inhalation  | 0.69 mg/m <sup>3</sup>   | General population | Systemic           |
|  | DNEL                     | Long term Dermal      | 0.95 mg/kg bw/day        | Workers            | Systemic           |
|  | DNEL                     | Long term Inhalation  | 2.31 mg/m <sup>3</sup>   | Workers            | Local              |
|  | DNEL                     | Long term Inhalation  | 2.31 mg/m <sup>3</sup>   | Workers            | Systemic           |
|  | DNEL                     | Short term Oral       | 25.6 mg/kg bw/day        | General population | Systemic           |
|  | DNEL                     | Short term Inhalation | 143.5 mg/m <sup>3</sup>  | General population | Local              |
|  | DNEL                     | Short term Inhalation | 160.23 mg/m <sup>3</sup> | Workers            | Local              |
|  | DNEL                     | Short term Inhalation | 226 mg/m <sup>3</sup>    | General population | Systemic           |
|  | DNEL                     | Short term Inhalation | 384 mg/m <sup>3</sup>    | Workers            | Systemic           |
|  | DNEL                     | Long term Oral        | 0.5 mg/kg bw/day         | General population | Systemic           |
| oxirane, mono[(C12-14-alkyloxy)methyl] derivs.     | DNEL                     | Long term Dermal      | 0.5 mg/kg bw/day         | General population | Systemic           |
|  | DNEL                     | Long term Inhalation  | 0.87 mg/m <sup>3</sup>   | General population | Systemic           |
|  | DNEL                     | Long term Dermal      | 1 mg/kg bw/day           | Workers            | Systemic           |
|  | DNEL                     | Long term Inhalation  | 3.6 mg/m <sup>3</sup>    | Workers            | Systemic           |
|  | DNEL                     | Long term Oral        | 33 mg/kg bw/day          | General population | Systemic           |
| 1-methoxy-2-propanol                               | DNEL                     | Long term Oral        | 33 mg/kg bw/day          | General population | Systemic           |



Code : 00267439

Date of issue/Date of revision

: 13 August 2024

SIGMAPRIME 700 BASE REDBROWN

## SECTION 8: Exposure controls/personal protection

|                       |                       |                       |                         |                    |          |
|-----------------------|-----------------------|-----------------------|-------------------------|--------------------|----------|
| ethylbenzene          | DNEL                  | Long term Inhalation  | 43.9 mg/m <sup>3</sup>  | General population | Systemic |
|                       | DNEL                  | Long term Dermal      | 78 mg/kg bw/day         | General population | Systemic |
|                       | DNEL                  | Long term Dermal      | 183 mg/kg bw/day        | Workers            | Systemic |
|                       | DNEL                  | Long term Inhalation  | 369 mg/m <sup>3</sup>   | Workers            | Systemic |
|                       | DNEL                  | Short term Inhalation | 553.5 mg/m <sup>3</sup> | Workers            | Local    |
|                       | DNEL                  | Short term Inhalation | 553.5 mg/m <sup>3</sup> | Workers            | Systemic |
|                       | DMEL                  | Long term Inhalation  | 442 mg/m <sup>3</sup>   | Workers            | Local    |
|                       | DMEL                  | Short term Inhalation | 884 mg/m <sup>3</sup>   | Workers            | Systemic |
|                       | DNEL                  | Long term Oral        | 1.6 mg/kg bw/day        | General population | Systemic |
|                       | DNEL                  | Long term Inhalation  | 15 mg/m <sup>3</sup>    | General population | Systemic |
| Cashew, nutshell liq. | DNEL                  | Long term Inhalation  | 77 mg/m <sup>3</sup>    | Workers            | Systemic |
|                       | DNEL                  | Long term Dermal      | 180 mg/kg bw/day        | Workers            | Systemic |
|                       | DNEL                  | Short term Inhalation | 293 mg/m <sup>3</sup>   | Workers            | Local    |
|                       | DNEL                  | Long term Oral        | 0.75 mg/kg bw/day       | General population | Systemic |
|                       | DNEL                  | Long term Dermal      | 0.75 mg/kg bw/day       | General population | Systemic |
| 2-methylpropan-1-ol   | DNEL                  | Long term Inhalation  | 1.31 mg/m <sup>3</sup>  | General population | Systemic |
|                       | DNEL                  | Long term Dermal      | 2.1 mg/kg bw/day        | Workers            | Systemic |
|                       | DNEL                  | Long term Inhalation  | 7.4 mg/m <sup>3</sup>   | Workers            | Systemic |
|                       | DNEL                  | Long term Inhalation  | 55 mg/m <sup>3</sup>    | General population | Local    |
| 4-methylpentan-2-one  | DNEL                  | Long term Inhalation  | 310 mg/m <sup>3</sup>   | Workers            | Local    |
|                       | DNEL                  | Long term Dermal      | 4.2 mg/kg bw/day        | General population | Systemic |
|                       | DNEL                  | Long term Dermal      | 11.8 mg/kg bw/day       | Workers            | Systemic |
|                       | DNEL                  | Long term Inhalation  | 14.7 mg/m <sup>3</sup>  | General population | Local    |
|                       | DNEL                  | Long term Inhalation  | 14.7 mg/m <sup>3</sup>  | General population | Systemic |
|                       | DNEL                  | Long term Inhalation  | 83 mg/m <sup>3</sup>    | Workers            | Local    |
|                       | DNEL                  | Long term Inhalation  | 83 mg/m <sup>3</sup>    | Workers            | Systemic |
|                       | DNEL                  | Short term Inhalation | 155.2 mg/m <sup>3</sup> | General population | Local    |
|                       | DNEL                  | Short term Inhalation | 155.2 mg/m <sup>3</sup> | General population | Systemic |
|                       | DNEL                  | Short term Inhalation | 208 mg/m <sup>3</sup>   | Workers            | Local    |
| DNEL                  | Short term Inhalation | 208 mg/m <sup>3</sup> | Workers                 | Systemic           |          |
| DNEL                  | Long term Oral        | 4.2 mg/kg bw/day      | General population      | Systemic           |          |

### PNECs

| Product/ingredient name | Type | Compartment Detail     | Value           | Method Detail            |
|-------------------------|------|------------------------|-----------------|--------------------------|
| xylene                  | -    | Fresh water            | 0.327 mg/l      | -                        |
|                         | -    | Marine water           | 0.327 mg/l      | -                        |
|                         | -    | Sewage Treatment Plant | 6.58 mg/l       | -                        |
|                         | -    | Fresh water sediment   | 12.46 mg/kg dwt | -                        |
|                         | -    | Marine water sediment  | 12.46 mg/kg dwt | -                        |
| 1-methoxy-2-propanol    | -    | Soil                   | 2.31 mg/kg      | -                        |
|                         | -    | Fresh water            | 10 mg/l         | Assessment Factors       |
|                         | -    | Marine water           | 1 mg/l          | Assessment Factors       |
|                         | -    | Sewage Treatment Plant | 100 mg/l        | Assessment Factors       |
|                         | -    | Fresh water sediment   | 41.6 mg/kg      | Equilibrium Partitioning |
| ethylbenzene            | -    | Marine water sediment  | 4.17 mg/kg      | Equilibrium Partitioning |
|                         | -    | Soil                   | 2.47 mg/kg      | Equilibrium Partitioning |
|                         | -    | Fresh water            | 0.1 mg/l        | Assessment Factors       |
|                         | -    | Marine water           | 0.01 mg/l       | Assessment Factors       |
|                         | -    | Sewage Treatment Plant | 9.6 mg/l        | Assessment Factors       |
| 2-methylpropan-1-ol     | -    | Fresh water sediment   | 13.7 mg/kg dwt  | Equilibrium Partitioning |
|                         | -    | Marine water sediment  | 1.37 mg/kg dwt  | Equilibrium Partitioning |
|                         | -    | Soil                   | 2.68 mg/kg dwt  | Equilibrium Partitioning |
|                         | -    | Secondary Poisoning    | 20 mg/kg        | -                        |
|                         | -    | Fresh water            | 0.4 mg/l        | Assessment Factors       |
|                         | -    | Marine water           | 0.04 mg/l       | Assessment Factors       |
|                         | -    | Sewage Treatment Plant | 10 mg/l         | Assessment Factors       |
|                         | -    | Fresh water sediment   | 1.56 mg/kg dwt  | Equilibrium Partitioning |

Code : 00267439 Date of issue/Date of revision : 13 August 2024  
SIGMAPRIME 700 BASE REDBROWN

## SECTION 8: Exposure controls/personal protection

|                      |   |                        |                 |                          |
|----------------------|---|------------------------|-----------------|--------------------------|
| 4-methylpentan-2-one | - | Marine water sediment  | 0.156 mg/kg dwt | -                        |
|                      | - | Soil                   | 0.076 mg/kg dwt | Equilibrium Partitioning |
|                      | - | Fresh water            | 0.6 mg/l        | Assessment Factors       |
|                      | - | Marine water           | 0.06 mg/l       | Assessment Factors       |
|                      | - | Sewage Treatment Plant | 27.5 mg/l       | Assessment Factors       |
|                      | - | Fresh water sediment   | 8.27 mg/kg      | Equilibrium Partitioning |
|                      | - | Marine water sediment  | 0.83 mg/kg      | Equilibrium Partitioning |
|                      | - | Soil                   | 1.3 mg/kg       | Equilibrium Partitioning |

### 8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Chemical splash goggles. Use eye protection according to EN 166.

#### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Gloves** : butyl rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Code : 00267439 Date of issue/Date of revision : 13 August 2024  
SIGMAPRIME 700 BASE REDBROWN

## SECTION 8: Exposure controls/personal protection

- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Brownish-red.
- Odour** : Aromatic.
- Odour threshold** : Not available.
- Melting point/freezing point** : May start to solidify at the following temperature: -14°C (6.8°F) This is based on data for the following ingredient: Phenol, methylstyrenated. Weighted average: -73.24°C (-99.8°F)
- Initial boiling point and boiling range** : >37.78°C
- Flammability** : Not available.
- Upper/lower flammability or explosive limits** : Greatest known range: Lower: 1.48% Upper: 13.74% (1-methoxy-2-propanol)
- Flash point** : Closed cup: 27°C
- Auto-ignition temperature** :

| Ingredient name                          | °C         | °F         | Method     |
|--|------------|------------|------------|
| Solvent naphtha (petroleum), heavy arom. | 220 to 250 | 428 to 482 | ASTM E 659 |

- Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).
- pH** : Not applicable. insoluble in water.
- Viscosity** : Kinematic (40°C): >21 mm<sup>2</sup>/s
- Solubility(ies)** :

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |

- Partition coefficient: n-octanol/ water** : Not applicable.

- Vapour pressure** :

| Ingredient name   | Vapour Pressure at 20°C |      |                | Vapour pressure at 50°C |     |        |
|-------------------|-------------------------|------|----------------|-------------------------|-----|--------|
|                   | mm Hg                   | kPa  | Method         | mm Hg                   | kPa | Method |
| Methylpropan-1-ol | <12.00102               | <1.6 | DIN EN 13016-2 |                         |     |        |

Code : 00267439 Date of issue/Date of revision : 13 August 2024  
SIGMAPRIME 700 BASE REDBROWN

## SECTION 9: Physical and chemical properties

- Evaporation rate** : Highest known value: 0.84 (ethylbenzene) Weighted average: 0.78 compared with butyl acetate
- Relative density** : 1.52
- Vapour density** : Highest known value: 3.7 (Air = 1) (xylene). Weighted average: 3.55 (Air = 1)
- Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
- Oxidising properties** : Product does not present an oxidizing hazard.
- Particle characteristics**
- Median particle size** : Not applicable.

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds Formaldehyde. metal oxide/oxides

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

| Product/ingredient name                            | Result                          | Species | Dose        | Exposure |
|--|---------------------------------|---------|-------------|----------|
| Epoxy Resin (700<MW<=1100)                         | LD50 Dermal                     | Rat     | >2000 mg/kg | -        |
|  | LD50 Oral                       | Rat     | >2000 mg/kg | -        |
| xylene   | LD50 Dermal                     | Rabbit  | 1.7 g/kg    | -        |
|  | LD50 Oral                       | Rat     | 4.3 g/kg    | -        |
| Phenol, methylstyrenated                           | LD50 Dermal                     | Rabbit  | >2000 mg/kg | -        |
|  | LD50 Oral                       | Rat     | >2000 mg/kg | -        |
| Solvent naphtha (petroleum), heavy arom. Nota(s) P | LC50 Inhalation Dusts and mists | Rat     | >5.2 mg/l   | 4 hours  |
|  | LD50 Oral                       | Rat     | >5 g/kg     | -        |
| oxirane, mono[(C12-14-alkyloxy)methyl] derivs.     | LD50 Oral                       | Rat     | 17100 mg/kg | -        |
| 1-methoxy-2-propanol                               | LC50 Inhalation Vapour          | Rat     | >7000 ppm   | 6 hours  |
|  | LD50 Dermal                     | Rabbit  | 13 g/kg     | -        |
|  | LD50 Oral                       | Rat     | 5.2 g/kg    | -        |
| ethylbenzene                                       | LC50 Inhalation Vapour          | Rat     | 17.8 mg/l   | 4 hours  |
|  | LD50 Dermal                     | Rabbit  | 17.8 g/kg   | -        |

Code : 00267439 Date of issue/Date of revision : 13 August 2024  
SIGMAPRIME 700 BASE REDBROWN

## SECTION 11: Toxicological information

|                      |  |                                       |   |                             |
|----------------------|--|---------------------------------------|---|-----------------------------|
| 2-methylpropan-1-ol  | LD50 Oral<br>LC50 Inhalation Vapour  | Rat<br>Rat                            | 3.5 g/kg<br>24.6 mg/l   | -<br>4 hours                |
| 4-methylpentan-2-one | LD50 Dermal<br>LD50 Oral<br>LC50 Inhalation Vapour<br>LD50 Dermal<br>LD50 Oral | Rabbit<br>Rat<br>Rat<br>Rabbit<br>Rat | 2460 mg/kg<br>2830 mg/kg<br>11 mg/l<br>>5000 mg/kg<br>2.08 g/kg | -<br>-<br>4 hours<br>-<br>- |

**Conclusion/Summary** : There are no data available on the mixture itself.

### Acute toxicity estimates

| Route                                  | ATE value                                    |
|--|--|
| Oral<br>Dermal<br>Inhalation (vapours) | 39651.47 mg/kg<br>13258.5 mg/kg<br>91.2 mg/l |

### Irritation/Corrosion

| Product/ingredient name | Result                   | Species | Score | Exposure        | Observation |
|-------------------------|--------------------------|---------|-------|-----------------|-------------|
| Xylene                  | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 mg | -           |

### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Sensitisation

| Product/ingredient name                        | Route of exposure | Species    | Result      |
|--|-------------------|------------|-------------|
| oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | skin              | Guinea pig | Sensitising |

### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

| Product/ingredient name                            | Category   | Route of exposure | Target organs                |
|--|------------|-------------------|------------------------------|
| Xylene   | Category 3 | -                 | Respiratory tract irritation |
| Solvent naphtha (petroleum), heavy arom. Nota(s) P | Category 3 | -                 | Narcotic effects             |
| 1-methoxy-2-propanol                               | Category 3 | -                 | Narcotic effects             |
| 2-methylpropan-1-ol                                | Category 3 | -                 | Respiratory tract irritation |
| 4-methylpentan-2-one                               | Category 3 | -                 | Narcotic effects             |
|  | Category 3 | -                 | Narcotic effects             |

### Specific target organ toxicity (repeated exposure)

|              |         |       |
|--------------|---------|-------|
| English (GB) | Denmark | 13/22 |
|--------------|---------|-------|

Code : 00267439 Date of issue/Date of revision : 13 August 2024  
 SIGMAPRIME 700 BASE REDBROWN

## SECTION 11: Toxicological information

| Product/ingredient name                             | Category   | Route of exposure | Target organs  |
|---|------------|-------------------|----------------|
| crystalline silica, respirable powder (<10 microns) | Category 1 | inhalation        | -              |
| ethylbenzene  | Category 2 | -                 | hearing organs |

### Aspiration hazard

| Product/ingredient name  | Result   |
|--|--|
| xylene<br>Solvent naphtha (petroleum), heavy arom. Nota(s) P<br>ethylbenzene | ASPIRATION HAZARD - Category 1<br>ASPIRATION HAZARD - Category 1<br>ASPIRATION HAZARD - Category 1 |

Information on likely routes of exposure : Not available.

### Potential acute health effects

- Inhalation : No known significant effects or critical hazards.
- Ingestion : No known significant effects or critical hazards.
- Skin contact : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Eye contact : Causes serious eye irritation.

### Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation : No specific data.
- Ingestion : No specific data.
- Skin contact : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Eye contact : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

- Potential immediate effects : Not available.
- Potential delayed effects : Not available.

#### Long term exposure

- Potential immediate effects : Not available.
- Potential delayed effects : Not available.

### Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

**General** : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.



Code : 00267439 Date of issue/Date of revision : 13 August 2024  
SIGMAPRIME 700 BASE REDBROWN

## SECTION 11: Toxicological information

**Reproductive toxicity** : No known significant effects or critical hazards.

**Other information** : Not available.

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F. Avoid contact with skin and clothing.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

| Product/ingredient name  | Result  | Species   | Exposure                                    |
|--|---|---|---|
| ☑ Solvent naphtha (petroleum), heavy arom. Nota(s) P<br>oxirane, mono[(C12-14-alkyloxy)methyl] derivs.<br>1-methoxy-2-propanol | NOEL 0.48 mg/l Fresh water<br>LC50 >100 mg/l<br>Acute LC50 23300 mg/l<br>Acute LC50 >4500 mg/l<br>Fresh water | Daphnia<br>Fish<br>Daphnia<br>Fish                | 21 days<br>96 hours<br>48 hours<br>96 hours |
| ethylbenzene   | Acute EC50 1.8 mg/l Fresh<br>water<br>Chronic NOEC 1 mg/l Fresh<br>water                                      | Daphnia<br>Daphnia -<br><i>Ceriodaphnia dubia</i> | 48 hours<br>-                               |
| 2-methylpropan-1-ol<br>4-methylpentan-2-one  | Acute EC50 1100 mg/l<br>Acute LC50 >179 mg/l  | Daphnia<br>Fish                                   | 48 hours<br>96 hours                        |

**Conclusion/Summary** : There are no data available on the mixture itself.

### 12.2 Persistence and degradability

| Product/ingredient name                | Test           | Result   | Dose   | Inoculum |
|--|----------------|--|--------|----------|
| ☑ ethylbenzene<br>4-methylpentan-2-one | -<br>OECD 301F | 79 % - Readily - 10 days<br>83 % - Readily - 28 days | -<br>- | -<br>-   |

**Conclusion/Summary** : There are no data available on the mixture itself.

| Product/ingredient name                          | Aquatic half-life | Photolysis  | Biodegradability              |
|--|-------------------|-------------|-------------------------------|
| ☑ xylene<br>ethylbenzene<br>4-methylpentan-2-one | -<br>-<br>-       | -<br>-<br>- | Readily<br>Readily<br>Readily |

### 12.3 Bioaccumulative potential

Code : 00267439 Date of issue/Date of revision : 13 August 2024  
SIGMAPRIME 700 BASE REDBROWN

## SECTION 12: Ecological information

| Product/ingredient name                            | LogP <sub>ow</sub> | BCF         | Potential |
|--|--------------------|-------------|-----------|
| xylene   | 3.12               | 7.4 to 18.5 | Low       |
| Phenol, methylstyrenated                           | 3.627              | -           | Low       |
| Solvent naphtha (petroleum), heavy arom. Nota(s) P | 2.8 to 6.5         | -           | High      |
| oxirane, mono[(C12-14-alkyloxy)methyl] derivs.     | 3.77               | -           | Low       |
| 1-methoxy-2-propanol                               | <1                 | -           | Low       |
| ethylbenzene                                       | 3.6                | 79.43       | Low       |
| Cashew, nutshell liq.                              | >4.78              | -           | High      |
| 2-methylpropan-1-ol                                | 1                  | -           | Low       |
| 4-methylpentan-2-one                               | 1.9                | -           | Low       |

### 12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Mobility : Not available.

### 12.5 Results of PBT and vPvB assessment

| Product/ingredient name                            | PBT | P   | B   | T   | vPvB                | vP        | vB        |
|--|-----|-----|-----|-----|---------------------|-----------|-----------|
| epoxy Resin (700<MW <=1100)                        | No  | N/A | N/A | No  | N/A                 | N/A       | N/A       |
| xylene   | No  | N/A | No  | No  | No                  | N/A       | No        |
| Phenol, methylstyrenated                           | No  | N/A | N/A | No  | SVHC<br>(Candidate) | Specified | Specified |
| Solvent naphtha (petroleum), heavy arom. Nota(s) P | No  | N/A | N/A | No  | N/A                 | N/A       | N/A       |
| oxirane, mono[(C12-14-alkyloxy)methyl] derivs.     | No  | N/A | N/A | No  | N/A                 | N/A       | N/A       |
| 1-methoxy-2-propanol                               | No  | N/A | N/A | No  | N/A                 | N/A       | N/A       |
| ethylbenzene                                       | No  | N/A | No  | Yes | No                  | N/A       | No        |
| Cashew, nutshell liq.                              | No  | N/A | N/A | No  | N/A                 | N/A       | N/A       |
| Urea, polymer with formaldehyde, butylated         | No  | N/A | N/A | No  | N/A                 | N/A       | N/A       |
| 2-methylpropan-1-ol                                | No  | N/A | N/A | No  | N/A                 | N/A       | N/A       |
| 4-methylpentan-2-one                               | No  | N/A | N/A | No  | N/A                 | N/A       | N/A       |

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

Code : 00267439 Date of issue/Date of revision : 13 August 2024  
SIGMAPRIME 700 BASE REDBROWN

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

#### European waste catalogue (EWC)

| Waste code | Waste designation   |
|------------|---|
| 08 01 11*  | waste paint and varnish containing organic solvents or other hazardous substances |

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container         | 15 01 06 mixed packaging       |

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

|                                 | ADR/RID         | ADN             | IMDG            | IATA            |
|---------------------------------|-----------------|-----------------|-----------------|-----------------|
| 14.1 UN number or ID number     | UN1263          | UN1263          | UN1263          | UN1263          |
| 14.2 UN proper shipping name    | PAINT           | PAINT           | PAINT           | PAINT           |
| 14.3 Transport hazard class(es) | 3               | 3               | 3               | 3               |
| 14.4 Packing group              | III             | III             | III             | III             |
| 14.5 Environmental hazards      | No.             | Yes.            | No.             | No.             |
| Marine pollutant substances     | Not applicable. | Not applicable. | Not applicable. | Not applicable. |

### Additional information

Code : 00267439 Date of issue/Date of revision : 13 August 2024  
SIGMAPRIME 700 BASE REDBROWN

## SECTION 14: Transport information

**ADR/RID** : None identified.  
**Tunnel code** : (D/E)  
**ADN** : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.  
**IMDG** : None identified.  
**IATA** : None identified.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not applicable.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

| Intrinsic property | Ingredient name  | Status    | Reference number | Date of revision |
|--------------------|--|-----------|------------------|------------------|
| vPvB               | Oligomerisation and alkylation reaction products of 2-phenylpropene and phenol | Candidate | D(2023) 8585-DC  | 1/23/2024        |

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

**Explosive precursors** : This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

#### Ozone depleting substances (1005/2009/EU)

Not listed.

#### Seveso Directive

This product is controlled under the Seveso Directive.

##### Danger criteria

| Category |
|----------|
| P5c      |

#### National regulations

**Product registration number** : PR-2360107

**Danish fire class** : II-1

Code : 00267439

Date of issue/Date of revision

: 13 August 2024

SIGMAPRIME 700 BASE REDBROWN

## SECTION 15: Regulatory information

### Executive Order No. 1795/2015

| Ingredient name            | Annex I Section A | Annex I Section B |
|----------------------------|-------------------|-------------------|
| Quartz (SiO <sub>2</sub> ) | Listed            | -                 |
| ethylbenzene               | Listed            | -                 |

**MAL-code** : 3-6

**Protection based on MAL** : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 3-6

**Application:** When using scraper or knife, brush, roller etc. for pre- and post-treatments in a spray booth where the operator is outside the spray zone and when working in similar new\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. When spraying in new\* booths and cabins with non-atomizing guns.

- Protective clothing must be worn.

During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents. When using scraper or knife, brush, roller, etc. for pre- and post-treatments in cabins or booths of the existing\* facility type, if the operator is inside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin.

- Air-supplied half mask, protective clothing and eye protection must be worn.

When spraying in new\* booths if the operator is outside the spray zone.

- Air-supplied half mask and eye protection must be worn.

When spraying in existing\* spray booths, if the operator is outside the spray zone. During non-atomising spraying in existing\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied full mask and protective clothing must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, protective clothing and hood must be worn.

Code : 00267439

Date of issue/Date of revision

: 13 August 2024

SIGMAPRIME 700 BASE REDBROWN

## SECTION 15: Regulatory information

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

- Restrictions on use** : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.
- List of undesirable substances** : Not listed
- Carcinogenic waste** : Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

[Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)



|                                     |  |
|-------------------------------------|--|
| <b>Code</b> : 00267439              | <b>Date of issue/Date of revision</b> : 13 August 2024 |
| <b>SIGMAPRIME 700 BASE REDBROWN</b> |  |

**SECTION 16: Other information**

| <b>Classification</b>   | <b>Justification</b>  |
|---|---|
| Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1, H317<br>STOT RE 1, H372<br>Aquatic Chronic 3, H412 | On basis of test data<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method |

**Full text of abbreviated H statements**

|  |   |
|--|---|
| <p><input checked="" type="checkbox"/> H225<br/>H226<br/>H302<br/>H304<br/>H312<br/>H315<br/>H317<br/>H318<br/>H319<br/>H332<br/>H335<br/>H336<br/>H351<br/>H372<br/>H373</p> <p>H411<br/>H412<br/>H413<br/>EUH066</p> | <p>Highly flammable liquid and vapour.<br/>Flammable liquid and vapour.<br/>Harmful if swallowed.<br/>May be fatal if swallowed and enters airways.<br/>Harmful in contact with skin.<br/>Causes skin irritation.<br/>May cause an allergic skin reaction.<br/>Causes serious eye damage.<br/>Causes serious eye irritation.<br/>Harmful if inhaled.<br/>May cause respiratory irritation.<br/>May cause drowsiness or dizziness.<br/>Suspected of causing cancer.<br/>Causes damage to organs through prolonged or repeated exposure.<br/>May cause damage to organs through prolonged or repeated exposure.<br/>Toxic to aquatic life with long lasting effects.<br/>Harmful to aquatic life with long lasting effects.<br/>May cause long lasting harmful effects to aquatic life.<br/>Repeated exposure may cause skin dryness or cracking.</p> |
|--|---|

**Full text of classifications [CLP/GHS]**

|  |   |
|--|---|
| <p><input checked="" type="checkbox"/> Acute Tox. 4<br/>Aquatic Chronic 2<br/>Aquatic Chronic 3<br/>Aquatic Chronic 4<br/>Asp. Tox. 1<br/>Carc. 2<br/>Eye Dam. 1<br/>Eye Irrit. 2<br/>Flam. Liq. 2<br/>Flam. Liq. 3<br/>Skin Irrit. 2<br/>Skin Sens. 1<br/>STOT RE 1</p> <p>STOT RE 2</p> <p>STOT SE 3</p> | <p>ACUTE TOXICITY - Category 4<br/>LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2<br/>LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3<br/>LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4<br/>ASPIRATION HAZARD - Category 1<br/>CARCINOGENICITY - Category 2<br/>SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1<br/>SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2<br/>FLAMMABLE LIQUIDS - Category 2<br/>FLAMMABLE LIQUIDS - Category 3<br/>SKIN CORROSION/IRRITATION - Category 2<br/>SKIN SENSITISATION - Category 1<br/>SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1<br/>SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2<br/>SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3</p> |
|--|---|

**History**

|  |                  |
|--|------------------|
| <b>Date of issue/ Date of revision</b> | : 13 August 2024 |
| <b>Date of previous issue</b>          | : 12 August 2024 |
| <b>Prepared by</b>                     | : EHS            |

**Code** : 00267439

**Date of issue/Date of revision**

: 13 August 2024

**SIGMAPRIME 700 BASE REDBROWN**

## **SECTION 16: Other information**

**Version** : 22.01

### **Disclaimer**

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*