## SAFETY DATA SHEET



Date of issue

22 August 2024

Version 6.01

# Section 1. Product and company identification

Product name : SIGMAGUARD 603 BASE

Product code : 00319943
Other means of identification : Not available.

Product type : Liquid.

#### Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** 

Coating. Paints. Painting-related materials.

Uses advised against	Reason
Not applicable.	

#### Supplier's details:

Supplier : PPG Industries Colombia Ltda

Calle 51 # 40-13 Municipio de Itagüí Antioquia, Colombia (57) (4) 3787400 (Porteria)

Email address: : HazComLatam@ppg.com

**Emergency telephone number** 

Colombia: 01 8000 916012 (CISPROQUIM)

+ 571 288 6012 (CISPROQUIM) Ecuador: 1800-59-3005 (CISPROQUIM) Peru: 080-050-847 (CISPROQUIM)

### Section 2. Hazards identification

Classification of the substance or mixture

: SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A

AQUATIC HAZARD (ACUTE) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 2

Target organs : Contains material which causes damage to the following organs: blood, liver, heart,

brain.

Contains material which may cause damage to the following organs: kidneys, lungs, cardiovascular system, upper respiratory tract, skin, eyes, central nervous system

(CNS).

Code Date of issue 00319943 22 August 2024 Version 6.01

**Product name** SIGMAGUARD 603 BASE

### Section 2. Hazards identification

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 38%

#### **GHS** label elements

**Hazard pictograms** 







Signal word : Danger

**Hazard statements** Causes skin irritation.

> May cause an allergic skin reaction. Causes serious eye irritation.

May cause cancer.

Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention** : Obtain special instructions before use. Wear protective gloves, protective clothing

and eye or face protection. Avoid release to the environment. Avoid breathing

vapor. Wash thoroughly after handling.

: Collect spillage. IF exposed or concerned: Get medical advice or attention. Take Response

off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice or attention.

: Not applicable. **Storage** 

**Disposal** : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Other hazards which do not : None known.

result in classification

### Section 3. Composition/information on ingredients

Substance/mixture : Mixture Other means of

identification

: Not available.

#### **CAS** number/other identifiers

**CAS** number : Not applicable.

Ingredient name	%	CAS number
5/8-[4-(2,3-epoxipropoxi)phenyl]propane   5/8-[4-(2,3-epoxipropoxip	30 - <60	1675-54-3
1,6-bis(2,3-epoxypropoxy)hexane	7 - <10	16096-31-4
benzyl alcohol	7 - <10	100-51-6
Talc , not containing asbestiform fibres	3 - <5	14807-96-6
titanium dioxide	3 - <5	13463-67-7
crystalline silica, respirable powder (>10 microns)	0.1 - < 0.2	14808-60-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

English (US)	Colombia	2/12

Product name SIGMAGUARD 603 BASE

## Section 3. Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact**: Remove contact lenses, irrigate copiously with clean, fresh water, holding the

eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

**Ingestion**: If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Specific treatments

: Treat symptomatically. Contact poison treatment specialist immediately if large

: quantities have been ingested or inhaled.

No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising

from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water

contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal : Decomposition products : carbon oxid

Decomposition products may include the following materials: carbon oxides

metal oxide/oxides

English (US) Colombia 3/12

**Product name SIGMAGUARD 603 BASE** 

### Section 5. Fire-fighting measures

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions**: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

**Precautions for safe** handling

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

English (US) Colombia 4/12

**Product name SIGMAGUARD 603 BASE** 

# Section 7. Handling and storage

including any incompatibilities

Conditions for safe storage, : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

Ingredient name	Exposure limits
▼alc , not containing asbestiform fibres titanium dioxide	ACGIH TLV (United States, 7/2023).  TWA: 2 mg/m³ 8 hours. Form: Respirable  ACGIH TLV (United States, 7/2023).  TWA: 2.5 mg/m³ 8 hours. Form: respirable fraction, finescale particles

**Recommended monitoring** procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Appropriate engineering** controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye protection** Skin protection **Hand protection**  : Chemical splash goggles.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** : butyl rubber

English (US) Colombia 5/12

**Product name** SIGMAGUARD 603 BASE

### Section 8. Exposure controls/personal protection

: Personal protective equipment for the body should be selected based on the task **Body protection** 

being performed and the risks involved and should be approved by a specialist

before handling this product. Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

: Respirator selection must be based on known or anticipated exposure levels, the **Respiratory protection** 

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary.

## Section 9. Physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Color : Gray.

Odor : Characteristic. Ha Not applicable. **Melting point** : Not available.

: >37.78°C (>100°F) **Boiling point** 

Flash point : Closed cup: 100°C (212°F)

**Evaporation rate**  Not available. : Not available. Flammability (solid, gas) Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available. Vapor density Not available.

Relative density 1.4

Media Result Solubility(ies)

cold water Not soluble

Partition coefficient: n-

octanol/water

: Not applicable.

**Auto-ignition temperature** : 300°C (572°F) **Decomposition temperature** : Not available.

**Viscosity** : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

**Viscosity** : 60 - 100 s (ISO 6mm)

### Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

English (US) Colombia 6/12

Product name SIGMAGUARD 603 BASE

### Section 10. Stability and reactivity

**Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.

**Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

## Section 11. Toxicological information

### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
bis-[4-(2,3-epoxipropoxi) phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>4178 mg/m³	4 hours
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-

# Conclusion/Summary Irritation/Corrosion

: There are no data available on the mixture itself.

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
	Skin - Edema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-

#### **Conclusion/Summary**

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

#### **Sensitization**

3	Route of exposure	Species	Result
bis-[4-(2,3-epoxipropoxi) phenyl]propane	skin	Mouse	Sensitizing

#### **Conclusion/Summary**

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

#### **Mutagenicity**

Not available.

English (US) Colombia 7/12

Product name SIGMAGUARD 603 BASE

### Section 11. Toxicological information

**Conclusion/Summary** 

: There are no data available on the mixture itself.

**Carcinogenicity** 

Not available.

**Conclusion/Summary** 

: There are no data available on the mixture itself.

**Classification** 

Product/ingredient name	OSHA	IARC	NTP
bis-[4-(2,3-epoxipropoxi) phenyl]propane	-	3	-
titanium dioxide	-	2B	- Known to be a human carsing an
crystalline silica, respirable powder (>10 microns)	+	'	Known to be a human carcinogen.

#### Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

#### Reproductive toxicity

Not available.

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

Not available.

**Conclusion/Summary**: There are no data available on the mixture itself.

#### Specific target organ toxicity (single exposure)

Name	, , , , , , , , , , , , , , , , , , ,	Route of exposure	Target organs
Talc , not containing asbestiform fibres	Category 3		Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Target organs**

: Contains material which causes damage to the following organs: blood, liver, heart, brain.

Contains material which may cause damage to the following organs: kidneys, lungs, cardiovascular system, upper respiratory tract, skin, eyes, central nervous system (CNS).

#### **Aspiration hazard**

Name	Result
benzyl alcohol	ASPIRATION HAZARD - Category 2

Information on the likely routes of exposure

: Not available.

Potential acute health effects

English (US) Colombia	8/12
-----------------------	------

SIGMAGUARD 603 BASE **Product name** 

### Section 11. Toxicological information

: Causes serious eye irritation. Eye contact

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes skin irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

> irritation redness

Ingestion : No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

#### **Conclusion/Summary**

: There are no data available on the mixture itself. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from shortterm and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

#### Short term exposure

**Potential immediate** 

: There are no data available on the mixture itself.

**Potential delayed effects** 

: There are no data available on the mixture itself.

Long term exposure

Potential immediate

: There are no data available on the mixture itself.

effects

effects

**Potential delayed effects** : There are no data available on the mixture itself.

Potential chronic health effects

English (US) Colombia 9/12

Product name SIGMAGUARD 603 BASE

### Section 11. Toxicological information

Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

**Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.Reproductive toxicity : No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
SIGMAGUARD 603 BASE	11602.4	23000	N/A	N/A	5.7
bis-[4-(2,3-epoxipropoxi)phenyl]propane	15000		N/A	N/A	N/A
benzyl alcohol	1230		N/A	N/A	1.5

Other information : Not available.

# **Section 12. Ecological information**

#### **Ecotoxicity**

Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - daphnia magna	48 hours
titanium dioxide	Chronic NOEC 0.3 mg/l Acute LC50 >100 mg/l Fresh water	Daphnia Daphnia - <i>Daphnia magna</i>	21 days 48 hours

#### Persistence/degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxi) phenyl]propane	-	-	Not readily
benzyl alcohol	-	-	Readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
1,6-bis(2,3-epoxypropoxy)	0.822	-	Low
hexane benzyl alcohol	0.87	-	Low

#### **Mobility in soil**

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

	English (US)	Colombia	10/12
--	--------------	----------	-------

Code 00319943 Date of issue 22 August 2024 Version 6.01 **Product name** SIGMAGUARD 603 BASE

# Section 13. Disposal considerations

### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	UN	Brazil (ANTT)	IMDG	IATA
UN number	UN3082	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(bis-[4- (2,3-epoxipropoxi) phenyl]propane)	(bis-[4- (2,3-epoxipropoxi) phenyl]propane)	(bis-[4- (2,3-epoxipropoxi) phenyl]propane)	(bis-[4- (2,3-epoxipropoxi) phenyl]propane)
Transport hazard class(es)	9	9	9	9
Packing group	III	III	III	III
Environmental hazards	Yes.	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	Not applicable.	(bis-[4- (2,3-epoxipropoxi) phenyl]propane)	Not applicable.

#### Additional information

UN

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**Brazil** 

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Risk number

: 90

**IMDG** 

This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg. provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**IATA** 

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

English (US) Colombia 11/12 Code 22 August 2024 00319943 Date of issue Version 6.01

**Product name SIGMAGUARD 603 BASE** 

### Section 14. Transport information

Transport in bulk according : Not applicable.

to IMO instruments

### Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

: No known specific national and/or regional regulations applicable to this product (including its ingredients).

### **Section 16. Other information**

### **History**

Date of previous issue : 12/20/2023

**Version** : 6.01 **EHS** 

Key to abbreviations : ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations

References : ABNT NBR 14725-4: 2014

ANTT - National Land Transportation Agency

Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

English (US) Colombia 12/12