# **SAFETY DATA SHEET**

Safety Data Sheet according to GB/T 16483-2008 and GB/T 17519-2013



Date of issue/Date of revision 22 August 2024

Version 3.01

Section 1. Chemical product and company identification

Product code	: 000001099408
Product name	: SIGMAGUARD 603 BASE GREY 5163
Product name	: SIGMAGUARD 603 BASE GREY 5163
Other means of identification	: 00267448; 00319943
Product type	: Liquid.
Relevant identified uses o	f the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Not applicable.
Supplier's details	: PPG Coatings (Kunshan) Co., Ltd 53 Jinyang Road, Lujia Town, 215331 Kunshan City, Jiangsu Province, P.R. China Tel: 86 512 57678859 Fax: 86 512 57678857
Emergency telephone number (with hours of operation)	: 00 86 532 83889090

### Section 2. Hazards identification

Classification of the substance or mixture according to GB 13690-2009 and GB 30000-2013

#### Emergency overview

Liquid. Gray. Characteristic. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life. Toxic to aquatic life. Toxic to aquatic life with long lasting effects. If skin irritation or rash occurs: Get medical advice or attention. If eye irritation persists: Get medical advice or attention. See Section 12 for environmental precautions.

SERIOUS ETE DAMAGE/ ETE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 AQUATIC HAZARD (ACUTE) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 2	Classification of the substance or mixture	AQUATIC HAZARD (ACUTE) - Category 2
---	--	-------------------------------------

### Section 2. Hazards identification

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 38%

GHS label elements Hazard pictograms				
Signal word	: Warning			
Hazard statements	: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.			
Precautionary statements				
Prevention	: Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.			
Response	: Collect spillage. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.			
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.			
Storage	: Not applicable.			
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.			
Physical and chemical hazards	: No known significant effects or critical hazards.			
Health hazards	: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.			
Symptoms related to the ph	vsical, chemical and toxicological characteristics			
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness			
Inhalation	: No specific data.			
Skin contact	: Adverse symptoms may include the following: irritation redness			
Ingestion	: No specific data.			
Delayed and immediate effe	Delayed and immediate effects and also chronic effects from short and long term exposure			

#### Short term exposure

China Page: 2/12

### Section 2. Hazards identification

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Environmental hazards	: Toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Other hazards which do not result in classification	: None known.

### Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: 00267448; 00319943
identification	

#### CAS number/other identifiers

CAS number : Not applicable.		
Ingredient name	%	CAS number
bis-[4-(2,3-epoxipropoxi)phenyl]propane	40 - <70	1675-54-3
1,6-bis(2,3-epoxypropoxy)hexane	1 - <10	16096-31-4
benzyl alcohol	1 - <10	100-51-6
Talc, not containing asbestiform fibres	1 - <10	14807-96-6

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### Section 4. First aid measures

**Description of necessary first aid measures** 

Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

### Potential acute health effects

#### Section 4. First aid measures Eye contact : Causes serious eye irritation. Inhalation : No known significant effects or critical hazards. Skin contact : Causes skin irritation. May cause an allergic skin reaction. Ingestion : No known significant effects or critical hazards. **Over-exposure signs/symptoms** Eye contact : Adverse symptoms may include the following: pain or irritation watering redness Inhalation : No specific data. **Skin contact** : Adverse symptoms may include the following: irritation redness Ingestion : No specific data. Indication of immediate medical attention and special treatment needed, if necessary : Treat symptomatically. Contact poison treatment specialist immediately if large Notes to physician quantities have been ingested or inhaled. : No specific treatment. **Specific treatments Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures					
Extinguishing media	xtinguishing media				
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.				
Unsuitable extinguishing media	: None known.				
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.				
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides				
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.				
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.				

Product name SIGMAGUARD 603 BASE GREY 5163

## Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.	
Methods and materials for co	ont	ainment and cleaning up	
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas.	

Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

Precautions for safe handling	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Version 3.01

## Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name			Exposure limits	
			<b>GBZ 2.1 (China, 11/2022).</b> PC-TWA: 1 mg/m <sup>3</sup> 8 hours. Form: respirable dust PC-TWA: 3 mg/m <sup>3</sup> 8 hours. Form: total dust	
Recommended monitoring procedures	:		riate monitoring standards. Reference to nods for the determination of hazardous	
Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.		
Environmental exposure controls	:	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		
ndividual protection measur	<u>es</u>			
<ul> <li>Hygiene measures</li> <li>Wash hands, forearms and face thoroughly after handling chemical products, eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated cl Contaminated work clothing should not be allowed out of the workplace. Was contaminated clothing before reusing. Ensure that eyewash stations and safe showers are close to the workstation location.</li> </ul>			y and at the end of the working period. ed to remove potentially contaminated clothing. ot be allowed out of the workplace. Wash Ensure that eyewash stations and safety	
Eye protection	: Chemical splash goggles.			
Skin protection				
Hand protection	-	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.		
Gloves	:	butyl rubber		
Body protection	:		body should be selected based on the task d and should be approved by a specialist	
Other skin protection	:		nal skin protection measures should be formed and the risks involved and should be ing this product.	
Respiratory protection	:	hazards of the product and the safe w workers are exposed to concentration appropriate, certified respirators. Use	n known or anticipated exposure levels, the orking limits of the selected respirator. If is above the exposure limit, they must use a properly fitted, air-purifying or air-fed d standard if a risk assessment indicates this is	

### Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	luid.	
Color	ay.	
Odor	aracteristic.	
Boiling point	7.78°C (>100°F)	
Flash point	osed cup: 100°C (212°F)	
Lower and upper explosive (flammable) limits	eatest known range: Lower: 1.3% Upper: 1	3% (benzyl alcohol)
Relative density	l de la constante de	
Solubility(ies)	edia Result	
Solubility(les)	ld water Not soluble	
Auto-ignition temperature	0°C (572°F)	
Auto-ignition temperature Viscosity	0°C (572°F) nematic (40°C): >21 mm²/s	

Section 10. Stability and reactivity			
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.		
Chemical stability	: The product is stable.		
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.		
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.		
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.		
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides		

### Section 11. Toxicological information

#### Information on toxicological effects

**Acute toxicity** Product/ingredient name Result **Species Exposure** Dose bis-[4-(2,3-epoxipropoxi)phenyl] Rabbit 23000 mg/kg LD50 Dermal propane 15000 mg/kg LD50 Oral Rat >4178 mg/m<sup>3</sup> benzyl alcohol LC50 Inhalation Dusts Rat 4 hours and mists LD50 Dermal Rabbit 2000 mg/kg LD50 Oral Rat 1.23 g/kg

Irritation/Corrosion

China Page: 7/12

#### Product code 000001099408

#### Date of issue 22 August 2024 Ve

Version 3.01

Product name SIGMAGUARD 603 BASE GREY 5163

## Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
	Skin - Edema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-

#### **Sensitization**

••••••	Route of exposure	Species	Result
bis-[4-(2,3-epoxipropoxi) phenyl]propane	skin	Mouse	Sensitizing

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
Talc , not containing asbestiform fibres	Category 3		Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Name	Result	
benzyl alcohol	ASPIRATION HAZARD - Category 2	

## Information on the likely routes of exposure

: Not available.

Potential acute health effects		
Eye contact	:	Causes serious eye irritation.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Causes skin irritation. May cause an allergic skin reaction.
Ingestion	:	No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Version 3.01

### Section 11. Toxicological information

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure Short term exposure **Potential immediate** : Not available. effects **Potential delayed effects** : Not available. Long term exposure **Potential immediate** : Not available. effects Potential delayed effects : Not available. Potential chronic health effects General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. Carcinogenicity : No known significant effects or critical hazards. : No known significant effects or critical hazards. **Mutagenicity** : No known significant effects or critical hazards. **Reproductive toxicity**

#### Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	<b>(</b> J	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
SIGMAGUARD 603 BASE GREY 5163 bis-[4-(2,3-epoxipropoxi)phenyl]propane benzyl alcohol	11602.4 15000 1230	23000	N/A N/A N/A	-	5.7 N/A 1.5

#### **Other information**

Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

### Section 12. Ecological information

<u>Toxicity</u>			
Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia magna</i>	48 hours
	Chronic NOEC 0.3 mg/l	Daphnia	21 days

#### Persistence/degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxi) phenyl]propane	-	-	Not readily
benzyl alcohol	-	-	Readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
1,6-bis(2,3-epoxypropoxy) hexane	0.822	-	Low
benzyl alcohol	0.87	-	Low

Mobility in soil Soil/water partition coefficient (Koc)	: Not available.
Other adverse effects	: No known significant effects or critical hazards.

## Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and
	runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

#### Product code 000001099408

Product name SIGMAGUARD 603 BASE GREY 5163

### Section 14. Transport information

	China	UN	IMDG	ΙΑΤΑ
UN number	UN3082	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(bis-[4- (2,3-epoxipropoxi) phenyl]propane)	(bis-[4- (2,3-epoxipropoxi) phenyl]propane)	(bis-[4- (2,3-epoxipropoxi) phenyl]propane)	(bis-[4- (2,3-epoxipropoxi) phenyl]propane)
Transport hazard class(es)	9	9	9	9
Packing group	Ш	111	111	Ш
Environmental hazards	Yes.	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	Not applicable.	(bis-[4- (2,3-epoxipropoxi) phenyl]propane)	Not applicable.

#### **Additional information**

CN	: None identified.
UN	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
Special preca	utions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according	1	Not applicable.
to IMO instruments		

## Section 15. Regulatory information

China inventory (IECSC)	: All components are listed or exempted.
References	<ul> <li>Production Safety Law of the People's Republic of China Code of Occupational Disease Prevention of the People's Republic of China Environmental Protection Law of the People's Republic of China Fire Control Law of the People's Republic of China Regulations on the Control over Safety of Dangerous Chemicals Occupational exposure limits for hazardous agents in the workplace chemical hazardous agents (GBZ2.1) General rule for classification and hazard communication of chemicals (GB13690) Safety data sheet for chemical products - Content and order of sections (GB/ T16483) Guidance on the compilation of safety data sheet for chemical products (GB/</li> </ul>

### Section 15. Regulatory information

T17519)

General rule for preparation of precautionary label for chemicals (GB15258) Safety rules for classification, precautionary labeling and precautionary statements of chemicals (GB30000.2-29)

### Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 22 August 2024
Date of previous issue	: 12/15/2023
Version	: 3.01
	EHS
Key to abbreviations	<ul> <li>ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail</li> </ul>
	UN = United Nations

**V** Indicates information that has changed from previously issued version.

#### Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.