SAFETY DATA SHEET



Date of issue 9/3/2024 (month/day/year)

Version 3.01

Section 1. Chemical product and company identification

A. Product name : SIGMASHIELD 1200 LT HARDENER BLACK Product code : 000001087813

Other means of identification 00271467

Relevant identified uses o	elevant identified uses of the substance or mixture and uses advised against					
Product use	:	Professional applications, Used by spraying.				
Use of the substance/ mixture	:	Hardener.; Coating.				
Uses advised against	:	Product is not intended, labelled or packaged for consumer use.				
Supplier's or Importer's information	:	PPG SSC (680-090) 19, Yeocheon-ro 217beon-gil, Nam-gu, Ulsan, Korea Tel: +82-52-210-8222 Korea.MSDS@PPG.COM				
Emergency telephone number:	:	+82-52-210-8331				
	Product use Use of the substance/ mixture Uses advised against Supplier's or Importer's information Email Address Emergency telephone	Product use:Use of the substance/ mixture:Uses advised against:Supplier's or Importer's information:Email Address Emergency telephone:				

Section 2. Hazards identification

A. Hazard classification	: CORROSIVE TO METALS - Category 1
	ACUTE TOXICITY (oral) - Category 4
	ACUTE TOXICITY (dermal) - Category 3
	ACUTE TOXICITY (inhalation) - Category 3
	SKIN CORROSION - Category 1A
	SERIOUS EYE DAMAGE - Category 1
	SKIN SENSITIZATION - Category 1
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
	AQUATIC HAZARD (LONG-TERM) - Category 2
This product is closelfied in	economic with the Industrial Sefety and Legith Act and the Chemical Control Act

This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

B. GHS label elements, including precautionary statements



Korea (GHS) Page: 1/13

Date of issue 9/3/2024 (month/day/year)

Product name SIGMASHIELD 1200 LT HARDENER BLACK

Section 2. Hazards identification

	Hazard statements		 H290 - May be corrosive to metals. H302 - Harmful if swallowed. H311 + H331 - Toxic in contact with skin or if inhaled. H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H373 - May cause damage to organs through prolonged or repeated exposure. H411 - Toxic to aquatic life with long lasting effects.
	Precautionary statements	5	
	Prevention	:	 P280 - Wear protective gloves, protective clothing and eye or face protection. P234 - Keep only in original packaging. P273 - Avoid release to the environment. P260 - Do not breathe vapor. P270 - Do not eat, drink or smoke when using this product. P264 - Wash thoroughly after handling.
	Response		 P391 - Collect spillage. P390 - Absorb spillage to prevent material damage. P304 + P340, P310 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. P301 + P310, P330, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353, P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. P363 - Wash contaminated clothing before reuse. P302 + P312, P352 - IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
	Storage	:	Not applicable.
	Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
) .	Other hazards which do not result in	:	None known.

not result in classification

С

Section 3. Composition/information on ingredients

CAS number/other identifiers

```
CAS number
```

: Not applicable.

Chemical name	Common name	Identifiers	%
2,2'-dimethyl-4,4'-methylenebis	3,3'-Dimethyl-4,4'-	CAS: 6864-37-5	70 -
(cyclohexylamine)	diaminodicyclohexylmethane		<80
benzyl alcohol	BENZYL ALCOHOL	CAS: 100-51-6	5 - <10
Formaldehyde polymer with N,N-	Formaldehyde, polymer with N,N-	CAS: 445498-00-0	5 - <10
dimethyl-1,3-propanediamine and phenol	dimethyl-1,3-propanediamine and phenol		
N-(3-(trimethoxysilyl)propyl)	N-(3-(trimethoxysilyl)propyl)	CAS: 1760-24-3	1 - <5
ethylenediamine	ethylenediamine		
2,4,6-tris(dimethylaminomethyl)phenol	2,4,6-tris(dimethylaminomethyl)phenol	CAS: 90-72-2	1 - <5
		Korea (GHS)	Page: 2/13

Product code 000001087813	Date of issue 9/3/2024 (month/day/year)	Version 3.01				
Product name SIGMASHIELD 1200 LT HARDENER BLACK						
Section 3. Composition/information on ingredients						
carbon black	CARBON BLACK CAS: 1333-8	6-4 0.1 - <1				

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Α.	Eye contact	:	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
В.	Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
C.	Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
D.	Ingestion	:	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Е.	Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
	Specific treatments	1	No specific treatment.
	Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Α.	Extinguishing media		
	Suitable extinguishing media	1	Use an extinguishing agent suitable for the surrounding fire.
	Unsuitable extinguishing media	-	None known.
В.	Specific hazards arising from the chemical	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
	Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides Formaldehyde.

Korea (GHS) Page: 3/13

Product name SIGMASHIELD 1200 LT HARDENER BLACK

Section 5. Fire-fighting measures

C.	Special equipment for fire-fighting	-	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
	Fire-fighting procedures	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Section 6. Accidental release measures

A. Personal precautions, protective equipment and emergency procedures	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
B. Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
C. Methods and materials for	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Absorb spillage to prevent material damage. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Absorb spillage to prevent material damage. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

A. Precautions for safe handling
 Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Absorb spillage to prevent material damage.

Product name SIGMASHIELD 1200 LT HARDENER BLACK

Section 7. Handling and storage

В.	Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a corrosion resistant container with a resistant inner liner. Store locked up. Keep away from metals. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
----	--	---

Section 8. Exposure controls/personal protection

A. Occupational exposure limits

	Ingredient name			Exposure limits
	carbon black			Ministry of Employment and Labor (Republic of Korea, 1/2020). TWA: 3.5 mg/m ³ 8 hours. Form: inhalable fraction
	Recommended monitoring procedures	:	Reference should be made to appropria national guidance documents for metho substances will also be required.	ate monitoring standards. Reference to ods for the determination of hazardous
В.	Appropriate engineering controls	:	Use only with adequate ventilation. Use ventilation or other engineering controls contaminants below any recommended	to keep worker exposure to airborne
	Environmental exposure controls	:		
C .	Personal protective equip	ome	ent	
	Respiratory protection	:	hazards of the product and the safe we workers are exposed to concentrations appropriate, certified respirators. Use	known or anticipated exposure levels, the orking limits of the selected respirator. If a above the exposure limit, they must use a properly fitted, air-purifying or air-fed standard if a risk assessment indicates this is
	Eye protection	:	Chemical splash goggles and face shi	eld.
	Hand protection	:	be worn at all times when handling che this is necessary. Considering the par check during use that the gloves are si should be noted that the time to breakt	ers. In the case of mixtures, consisting of
	Gloves	:	nitrile neoprene	
	Body protection	:		body should be selected based on the task and should be approved by a specialist

Date of issue 9/3/2024 (month/day/year)

Product name SIGMASHIELD 1200 LT HARDENER BLACK

Section 8. Exposure controls/personal protection

- Hygiene measures
- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

A. Appearance

	Physical state	:	Liquid.
	Color	:	Black.
В.	Odor	:	Amine-like.
C .	Odor threshold	:	Not available.
D.	рН	:	Not applicable.
Ε.	Melting/freezing point	:	Not available.

- : >37.78°C (>100°F) F. Boiling point/boiling range
- G. Flash point

H. Evaporation rate

: Closed cup: 105°C (221°F) : Not available.

: Not available.

- Flammability (solid, gas) : Not available. I. –
- J. Lower and upper explosive (flammable) limits
- **K.** V

K.	Vapor pressure	:	Va		or Pressure at 20°C		Va	Vapor pressure at 50°C	
			Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
			2,4,6-tris (dimethylaminomethyl) phenol	0.056	0.0075	EU A.4			
	Solubility(ies)		Media	Re	sult				
	conducting (100)		cold water	Nc	t soluble	9			
	Solubility in water	:	Not available.						
И.	Vapor density	:	Not available.						
1.	Relative density	1	0.97						
ч. Э.	Partition coefficient: n- octanol/water	:	Not applicable.						
> .	Auto-ignition temperature	:							
			Ingredient name		°C	°F		Method	
			2,2'-dimethyl-4,4'-methyl (cyclohexylamine)	enebis	275	527			

: Greatest known range: Lower: 1.3% Upper: 13% (benzyl alcohol)

Decomposition Q. temperature

Korea (GHS) Page: 6/13

Date of issue 9/3/2024 (month/day/year)

Product name SIGMASHIELD 1200 LT HARDENER BLACK

Section 9. Physical and chemical properties

Viscosity R.

- : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)
- Flow time (ISO 2431) : Not available. Molecular weight
- S.

: Not applicable.

Section 10. Stability and reactivity

Α.	Chemical stability	:	The product is stable.
	Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
в.	Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products.
C.	Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
D.	Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides Formaldehyde. metal oxide/oxides

Section 11. Toxicological information

A. Information on the likely : Not available. routes of exposure

Potential acute health effects

Inhalation Ingestion Skin contact Eye contact	 Toxic if inhaled. Harmful if swallowed. Causes severe burns. Toxic in contact with skin. May cause an allergic skin reaction. Causes serious eye damage.
Over-exposure signs	s/symptoms
Inhalation	: No specific data.
Ingestion	: Adverse symptoms may include the following: stomach pains
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Eye contact	: Adverse symptoms may include the following: pain watering redness

B. Health hazards

Acute toxicity

Version 3.01

Product name SIGMASHIELD 1200 LT HARDENER BLACK

Section 11. Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
2,2'-dimethyl-4,4'-methylenebis	LC50 Inhalation Dusts and	Rat	420 mg/m ³	4 hours
(cyclohexylamine)	mists		_	
	LD50 Dermal	Rabbit	>0.2 g/kg	-
	LD50 Oral	Rat	>0.32 g/kg	-
benzyl alcohol	LC50 Inhalation Dusts and	Rat	>4178 mg/m ³	4 hours
	mists		Ū Ū	
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-
N-(3-(trimethoxysilyl)propyl)	LD50 Dermal	Rabbit	>2000 mg/kg	-
ethylenediamine				
•	LD50 Oral	Rat	2413 mg/kg	-
2,4,6-tris(dimethylaminomethyl)phenol	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
carbon black	LD50 Oral	Rat	>10 g/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Consitingtion	
Sensitization Conclusion/Summary	
	There are no data available on the mixture itself
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Mutagonicity	
Mutagenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Carcinogenicity	
	: There are no data available on the mixture itself.
Conclusion/Summary	
Reproductive toxicity	
	. There are no data available on the misture itself
Conclusion/Summary	: There are no data available on the mixture itself.
Teratogenicity	
	. There are no date available on the winter its off
Conclusion/Summary	: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name	Classification	Route of exposure	Target organs
N-(3-(trimethoxysilyl)propyl)ethylenediamine	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product name SIGMASHIELD 1200 LT HARDENER BLACK

Section 11. Toxicological information

Name		Route of exposure	Target organs
2,2'-dimethyl-4,4'-methylenebis(cyclohexylamine)	Category 2	-	-

Aspiration hazard

Name	Result
benzyl alcohol	ASPIRATION HAZARD - Category 2

Potential chronic health effects

General	: May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Additional information

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C (140F). Exposure to amine vapor has been reported to cause transient corneal edema described as blue haze, halo effect, foggy or blurred vision for several hours. This condition is typically temporary and does not cause permanent visual effects. When the proper eye protection specified in Section 8 is worn, exposure is significantly reduced and the condition has not been observed.

Chemical name	Identifiers	GHS Classification
2,2'-dimethyl-4,4'-methylenebis (cyclohexylamine)	CAS: 6864-37-5	ACUTE TOXICITY (oral) - Category 4
(cyclonex)lanc)		ACUTE TOXICITY (dermal) - Category 3
		ACUTE TOXICITY (inhalation) - Category 3
		SKIN CORROSION - Category 1A
		SERIOUS EYE DAMAGE - Category 1
		SPECIFIC TARGET ORGAN TOXICITY
		(REPEATED EXPOSURE) - Category 2
hanmi alashal	CAR: 100 E1 C	AQUATIC HAZARD (LONG-TERM) - Category 2
benzyl alcohol	CAS: 100-51-6	ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4
		ACUTE TOXICITY (inhalation) - Category 4
		EYE IRRITATION - Category 2A
		ASPIRATION HAZARD - Category 2
Formaldehyde polymer with N,N- dimethyl-1,3-propanediamine and phenol	CAS: 445498-00-0	ACUTE TOXICITY (oral) - Category 4
		AQUATIC HAZARD (ACUTE) - Category 1
		AQUATIC HAZARD (LONG-TERM) - Category 1
N-(3-(trimethoxysilyl)propyl) ethylenediamine	CAS: 1760-24-3	SERIOUS EYE DAMAGE - Category 1
		SKIN SENSITIZATION - Category 1B
		SPECIFIC TARGET ORGAN TOXICITY (SINGLE
	<u>.</u>	Korea (GHS) Page: 9/13

Product name SIGMASHIELD 1200 LT HARDENER BLACK

Section 11. Toxicological information

		EXPOSURE) (Respiratory tract irritation) -
		Category 3
2,4,6-tris(dimethylaminomethyl)phenol	CAS: 90-72-2	CORROSIVE TO METALS - Category 1
		ACUTE TOXICITY (oral) - Category 4
		ACUTE TOXICITY (dermal) - Category 4
		SKIN CORROSION - Category 1C
		SERIOUS EYE DAMAGE - Category 1
carbon black	CAS: 1333-86-4	CARCINOGENICITY - Category 2

Section 12. Ecological information

A. <u>Ecotoxicity</u>

Product/ingredient name	Result	Species	Exposure
N-(3-(trimethoxysilyl)propyl) ethylenediamine	EC50 597 mg/l	Fish	96 hours
2,4,6-tris (dimethylaminomethyl) phenol	Acute LC50 >100 mg/l	Daphnia	48 hours
1	Acute LC50 >100 mg/l	Fish	96 hours

B. Persistence and degradability

Product/ingredient name	Test	Result		Dose		Inoculum
2,4,6-tris (dimethylaminomethyl) phenol	OECD 301D Ready Biodegradability - Closed Bottle Test	4 % - Not r	eadily - 28 days	-		-
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
benzyl alcohol 2,4,6-tris (dimethylaminomethyl) phenol	-		-		Readily Not readily	

C. Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine) benzyl alcohol 2,4,6-tris (dimethylaminomethyl) phenol	1.8 0.87 0.219		Low Low Low

D. Mobility in soil

Soil/water partition coefficient (Koc)

- : Not available.
- E. <u>Other adverse effects</u> : N
 - : No known significant effects or critical hazards.

Product name SIGMASHIELD 1200 LT HARDENER BLACK

Section 13. Disposal considerations

with the requirements of environmental protection and waste disposal legisla any regional local authority requirements. Dispose of surplus and non-recyc products via a licensed waste disposal contractor. Waste should not be disp untreated to the sewer unless fully compliant with the requirements of all aut with jurisdiction. Waste packaging should be recycled. Incineration or landf should only be considered when recycling is not feasible.	able osed of norities
---	-----------------------------

B. Disposal precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
A. UN number	UN2922	UN2922	UN2922
B. UN proper shipping name	CORROSIVE LIQUID, TOXIC, N.O.S.	CORROSIVE LIQUID, TOXIC, N.O.S.	CORROSIVE LIQUID, TOXIC, N.O.S.
	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine), 2,4,6-tris (dimethylaminomethyl)phenol)	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine), 2,4,6-tris (dimethylaminomethyl)phenol)	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine), 2,4,6-tris (dimethylaminomethyl)phenol)
C. Transport hazard class(es)	8 (6.1)	8 (6.1)	8 (6.1)
D. Packing group	II	II	II
Environmental hazardsYes. The environmentally hazardous substance mark is not required.		Yes.	Yes. The environmentally hazardous substance mark is not required.
E. Marine pollutant substances	Not applicable.	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine))	Not applicable.

Additional information

UN

IMDG

- : None identified.
 - - : The marine pollutant mark is not required when transported in sizes of ≤ 5 L or ≤ 5 kg.
- ΙΑΤΑ : The environmentally hazardous substance mark may appear if required by other transportation regulations.

F. Special precaution which a user to be aware of or needs to comply with in connection with transport or tranportation

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Date of issue 9/3/2024 (month/day/year)

Version 3.01

Product name SIGMASHIELD 1200 LT HARDENER BLACK

Section 15. Regulatory information

	•		-	
Α.	. <u>Regulation according to ISHA</u>			
	ISHA article 117 : None of the components are listed. (Harmful substances prohibited from manufacture)		None of the components are listed.	
	ISHA article 118 (Harmful substances requiring permission)	:	None of the components are listed.	
	Article 2 of Youth Protection Act on Substances Hazardous to Youth	:	It is not allowed to sell to persons under the age of 19.	
	Exposure Limits of Chemical Substances and Physical Factors			
The following components have an OEL: carbon black				
	Annex 19 (Exposure standards established	:	None of the components are listed.	
	for harmful factors) ISHA Enforcement Regs Annex 21 (Harmful factors subject to Work Environment Measurement)	:	None of the components are listed.	
	ISHA Enforcement Regs Annex 22 (Harmful Factors Subject to Special Health Check- up)	:	None of the components are listed.	
	Standard of Industrial Safety and Health Annex 12 (Hazardous substances subject to control)	:	None of the components are listed.	
В.	3. <u>Regulation according to Chemicals Control Act</u>			
	Article 11 (TRI)	:	None of the components are listed.	
	Article 18 Prohibited (K- Reach Article 27)	:	None of the components are listed.	
	Article 19 Subject to authorization (K-Reach Article 25)	1	None of the components are listed.	
	Article 20 Restricted (K- Reach Article 27)	1	None of the components are listed.	
	Article 20 Toxic Chemicals (K-Reach Article 20)	:	Not applicable	
	Korea inventory	1	All components are listed or exempted.	
	Article 39 (Accident Precaution Chemicals)	:	None of the components are listed.	
			Korea (GHS)	

Korea (GHS) Page: 12/13

Product name SIGMASHIELD 1200 LT HARDENER BLACK

Section 15. Regulatory information

C.	Dangerous Materials Safety Management Act	:	Class: Class 4 - Flammable Liquid Item: 5. Class 3 petroleums - Water-insoluble liquid Threshold: 2000 L Danger category: III Signal word: Contact with sources of ignition prohibited
D.	Wastes regulation	1	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Ε.	Regulation according to other foreign laws		
	Safety, health and environmental regulations specific for the product	:	No known specific national and/or regional regulations applicable to this product (including its ingredients).

Section 16. Other information

A.	References	 Korean Ministry of Environment; Chemical Control Act Korean Ministry of Labor; Industrial Safety and Health Act NIER Notice Registry of Toxic Effects of Chemical Substances (RTECS) U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information Retrieval) ECOTOX Database System.
В.	First issue date	: 1/18/2021
C.	Date of issue/Date of revision	: 9/3/2024
D.	Version	: 3.01
	Prepared by	: EHS
-	Other	

E. Other

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.