Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SAFETY DATA SHEET

Date of issue/Date of revision

: 6 September 2024



: 1.03

Version

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

| 1.1 Product identifier | |
|----------------------------------|---|
| Product name | : PSX 700 BASE RAL 7040 |
| Product code | : 00384173 |
| Product type | : Liquid. |
| Other means of identification | : Not available. |
| 1.2 Relevant identified uses | of the substance or mixture and uses advised against |
| Product use | : Professional applications, Used by spraying. |
| Use of the substance/ mixture | : Coating. |
| Uses advised against | : Product is not intended, labelled or packaged for consumer use. |

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL Tweemontstraat 104 B-2100 Deurne Belgium Telephone +32-33606311 Fax +32-33606435

e-mail address of person responsible for this SDS

: Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture Classification according to UK CLP/GHS Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412 The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements Hazard pictograms



Signal word Hazard statements : Warning

: May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

Precautionary statements

English (GB)

| Code : 003841 PSX 700 BASE RAL 70 | | : 6 September 2024 |
|--------------------------------------|--|---------------------|
| SECTION 2: Hazards identification | | |
| Prevention | : Wear protective gloves. Wear eye or face protection. A | void release to the |

| | 1 | environment. Avoid breathing vapour. |
|---|-----|---|
| Response | : | Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. |
| Storage | 1 | Not applicable. |
| Disposal | : | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| | | P280, P273, P261, P362 + P364, P302 + P352, P501 |
| Supplemental label elements | : | Not applicable. |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : | Not applicable. |
| Special packaging requirem | nen | <u>its</u> |
| Containers to be fitted with child-resistant fastenings | : | Not applicable. |
| Tactile warning of danger | : | Not applicable. |
| 2.3 Other hazards | | |
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | : | This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do not result in classification | : | None known. |

SECTION 3: Composition/information on ingredients

| 3.2 Mixtures : N | lixture | | | |
|---|--|--------------|---|---------|
| Product/ingredient name | Identifiers | % | Classification | Туре |
| 4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane | REACH #: 01-2119959495-22 EC: 500-070-7 CAS: 30583-72-3 | ≥25 - ≤50 | Skin Sens. 1, H317 Aquatic Chronic 3, H412 | [1] |
| Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5 | ≥0.30 - <2.5 | Skin Sens. 1A, H317 Repr. 2, H361f Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1) | [1] |
| Poly(oxy-1,2-ethanediyl), α- (nonylphenyl)-ω-hydroxy-, branched, phosphates | CAS: 68412-53-3 | ≥1.0 - <3.0 | Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412 | [1] |
| methanol | REACH #: 01-2119433307-44 EC: 200-659-6 CAS: 67-56-1 Index: 603-001-00-X | ≤0.30 | Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT SE 1, H370 | [1] [2] |
| | | | See Section 16 for the full text of the H statements declared above. | |

Code : 00384173 PSX 700 BASE RAL 7040 Date of issue/Date of revision

: 6 September 2024

SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

This mixture contains \geq 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

| Eye contact | Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. |
|----------------------------|---|
| Inhalation | Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. |
| Skin contact | Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. |
| Ingestion | : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting. |
| Protection of first-aiders | No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

4.2 Most important symptoms and effects, both acute and delayed

| | · · · · · · · · · · · · · · · · · · · |
|---------------------------------|--|
| Potential acute health effect | <u>S</u> |
| Eye contact | : Causes serious eye irritation. |
| Inhalation | : No known significant effects or critical hazards. |
| Skin contact | : May cause an allergic skin reaction. |
| Ingestion | : No known significant effects or critical hazards. |
| <u>Over-exposure signs/symp</u> | <u>toms</u> |
| Eye contact | : Adverse symptoms may include the following: pain or irritation watering redness |
| Inhalation | : No specific data. |
| Skin contact | : Adverse symptoms may include the following: irritation redness |
| Ingestion | : No specific data. |
| 4.3 Indication of any immed | ate medical attention and special treatment needed |
| Notes to physician | : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Specific treatments | : No specific treatment. |

| Code : 00384173 PSX 700 BASE RAL 7040 | Date of issue/Date of revision : 6 September 2024 |
|--|--|
| SECTION 5: Firefigh | iting measures |
| 5.1 Extinguishing media | |
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. |
| Unsuitable extinguishing media | : None known. |
| 5.2 Special hazards arising | from the substance or mixture |
| Hazards from the substance or mixture | : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. |
| Hazardous combustion products | Decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/oxides |

| 5.3 Advice for firefighters | |
|--|---|
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for fire-fighters | Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |

SECTION 6: Accidental release measures

| 6.1 Personal precautions, pro | ective equipment and emergency procedures |
|--------------------------------|---|
| For non-emergency personnel | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
| For emergency responders | : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| 6.2 Environmental precautions | : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. |
| 6.3 Methods and material for | containment and cleaning up |
| Small spill | : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
| Large spill | : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. |

| Code | : 00384173 | Date of issue/Date of revision | : 6 September 2024 |
|-------------|-------------|--------------------------------|--------------------|
| PSX 700 BAS | SE RAL 7040 | | |
| | | | |

SECTION 6: Accidental release measures

| 6.4 Reference to other | 1 | See Section 1 for emergency contact information. |
|------------------------|---|---|
| sections | | See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information. |

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

| Protective measures | : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
|--|--|
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional |

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

information on hygiene measures.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|---|---|
| methanol | EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 333 mg/m ³ 15 minutes. STEL: 250 ppm 15 minutes. TWA: 266 mg/m ³ 8 hours. TWA: 200 ppm 8 hours. |
| Product/ingredient name | Exposure indices |
| Recommended monitoring : Reference s procedures national gui | should be made to appropriate monitoring standards. Reference to dance documents for methods for the determination of hazardous will also be required. |

DNELs/DMELs

Code : 00384173 PSX 700 BASE RAL 7040 Date of issue/Date of revision

: 6 September 2024

SECTION 8: Exposure controls/personal protection

| Product/ingredient name | Туре | Exposure | Value | Population | Effects |
|-------------------------------|------|-----------------------|-------------------------------|--------------------|----------|
| 4 ,4'- | DNEL | Long term Dermal | 0.021 mg/cm ² skin | Workers | Local |
| Isopropylidenedicyclohexanol, | | - | - | | |
| oligomeric reaction products | | | | | |
| with 1-chloro- | | | | | |
| 2,3-epoxypropane | | | | | |
| | DNEL | Short term Dermal | 0.23 mg/cm ² skin | Workers | Local |
| | DNEL | Short term Dermal | 21 µg/cm² | General population | Local |
| | DNEL | Long term Dermal | 21 µg/cm² | General population | Local |
| | DNEL | Long term Dermal | 21 µg/cm² | Workers | Local |
| | DNEL | Short term Dermal | 0.23 mg/cm ² | Workers | Local |
| | DNEL | Long term Oral | 0.5 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Dermal | 0.5 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 0.5 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Dermal | 1 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Dermal | 1 mg/kg bw/day | Workers | Systemic |
| | DNEL | Short term Inhalation | 1.76 mg/m³ | General population | Systemic |
| | DNEL | Long term Inhalation | 1.76 mg/m³ | General population | Systemic |
| | DNEL | Long term Inhalation | 3.25 mg/m ³ | Workers | Systemic |
| | DNEL | Short term Inhalation | 3.52 mg/m³ | Workers | Systemic |
| methanol | DNEL | Short term Oral | 4 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Oral | 4 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Dermal | 4 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 4 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Dermal | 20 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Dermal | 20 mg/kg bw/day | Workers | Systemic |
| | DNEL | Short term Inhalation | 26 mg/m ³ | General population | Local |
| | DNEL | Long term Inhalation | 26 mg/m³ | General population | Local |
| | DNEL | Short term Inhalation | 26 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 26 mg/m ³ | General population | Systemic |
| | DNEL | Short term Inhalation | 130 mg/m³ | Workers | Local |
| | DNEL | Long term Inhalation | 130 mg/m³ | Workers | Local |
| | DNEL | Short term Inhalation | 130 mg/m³ | Workers | Systemic |
| | DNEL | Long term Inhalation | 130 mg/m³ | Workers | Systemic |

PNECs

| Product/ingredient name | Compartment Detail | Value | Method Detail |
|--|------------------------|-----------------|--------------------------|
| 4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- | Fresh water | 11.5 µg/l | Assessment Factors |
| 2,3-epoxypropane | | | |
| | Marine water | 11.5 µg/l | Assessment Factors |
| | Sewage Treatment Plant | 100 mg/l | Assessment Factors |
| | Fresh water sediment | 0.229 mg/kg dwt | - |
| | Marine water sediment | 0.023 mg/kg dwt | Equilibrium Partitioning |
| | Soil | 0.099 mg/kg dwt | Equilibrium Partitioning |
| methanol | Fresh water | 20.8 mg/l | Assessment Factors |
| | Marine water | 2.08 mg/l | Assessment Factors |
| | Sewage Treatment Plant | 100 mg/l | Assessment Factors |
| | Fresh water sediment | 77 mg/kg | Equilibrium Partitioning |
| | Marine water sediment | 7.7 mg/kg | Equilibrium Partitioning |
| | Soil | 100 mg/kg | Assessment Factors |

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

| <mark>Code</mark> PSX 700 | : 00384173 BASE RAL 7040 | Date of issue/Date of revision | : 6 September 2024 | | |
|--|-----------------------------|--------------------------------|--------------------|--|--|
| SECTION 8: Exposure controls/personal protection | | | | | |

| | e controis/personal protection |
|---|--|
| Hygiene measures | : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |
| Eye/face protection <u>Skin protection</u> | : Chemical splash goggles. |
| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. butyl rubber |
| Body protection | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Other skin protection | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3 |
| Environmental exposure controls | : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. |

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

| English (GB) | United Kingdom (UK) 7/13 |
|--|---|
| Upper/lower flammability or explosive limits | : Not available. |
| Flammability (solid, gas) | : liquid |
| Initial boiling point and boiling range | : >37.78°C (>100°F) |
| Melting point/freezing point | May start to solidify at the following temperature: -12.9°C (8.8°F) This is based on data for the following ingredient: 4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane. |
| Odour threshold | : Not available. |
| Odour | : Characteristic. |
| Colour | : Grey. |
| Physical state | : Liquid. |
| <u>Appearance</u> | |

| Code : 00384173 | Date of issue/Date of revision | : 6 September 2024 |
|-----------------------|--------------------------------|--------------------|
| PSX 700 BASE RAL 7040 | | |

SECTION 9: Physical and chemical properties

| J | | |
|--|-----|---|
| Flash point | : (| Closed cup: Not applicable. |
| Auto-ignition temperature | : 1 | Not available. |
| рН | : 1 | Not applicable. |
| | 1 | Not applicable. insoluble in water. |
| Viscosity | : 1 | Kinematic (40°C): >21 mm²/s |
| Solubility(ies) | : | |
| Media | | Result |
| cold water | | Not soluble |
| Miscible with water | : 1 | No. |
| Partition coefficient: n-octanol/ water | : 1 | Not applicable. |
| Vapour pressure | : 1 | Not available. |
| Relative density | : 1 | 1.34 |
| Explosive properties | | The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible. |
| Oxidising properties | : F | Product does not present an oxidizing hazard. |
| Particle characteristics | | |
| Median particle size | : 1 | Not applicable. |
| | | |

SECTION 10: Stability and reactivity

| 10.1 Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
|--|--|
| 10.2 Chemical stability | : The product is stable. |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| 10.4 Conditions to avoid | : When exposed to high temperatures may produce hazardous decomposition produce Refer to protective measures listed in sections 7 and 8. |
| 10.5 Incompatible materials | : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids. |
| 10.6 Hazardous decomposition products | : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/ oxides |

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|--|-----------------------|--|-------------------|
| Reaction mass of bis (1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate | LD50 Dermal | Rat | >3170 mg/kg | - |
| · [-] | LD50 Oral | Rat - Male, Female | 3230 mg/kg | - |
| methanol | LC50 Inhalation Vapour LD50 Dermal LD50 Oral | Rat Rabbit Rat | 64000 ppm 15800 mg/kg 5600 mg/kg | 4 hours - - |
| English (GB) | United | Kingdom (UK) | | 8/ |

Code : 00384173 PSX 700 BASE RAL 7040

Date of issue/Date of revision

: 6 September 2024

SECTION 11: Toxicological information

: There are no data available on the mixture itself.

Conclusion/Summary Acute toxicity estimates

| Product/ingredient name | Oral (mg/ kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|---|------------------|-------------------|--------------------------------|-----------------------------------|--|
| SX 700 BASE RAL 7040 Reaction mass of bis(1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | 93396.8 3230 | 280190.5 N/A | N/A N/A | 2801.9 N/A | N/A N/A |
| methanol | 100 | 300 | 64000 | 3 | N/A |

Irritation/Corrosion

| Conclusion/Summary Skin | Not available.There are no data available on the mixture itself. |
|----------------------------|---|
| Eyes | : There are no data available on the mixture itself. |
| Respiratory | : There are no data available on the mixture itself. |
| Sensitisation | |
| Conclusion/Summary | |
| Skin | : There are no data available on the mixture itself. |
| Respiratory | : There are no data available on the mixture itself. |
| Mutagenicity | |
| Conclusion/Summary | : There are no data available on the mixture itself. |
| Carcinogenicity | |
| Conclusion/Summary | : There are no data available on the mixture itself. |
| Reproductive toxicity | |
| Conclusion/Summary | : There are no data available on the mixture itself. |
| Teratogenicity | |
| Conclusion/Summary | : There are no data available on the mixture itself. |
| | |

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|---------------|
| methanol | Category 1 | - | - |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes : Not available. of exposure

| Potential acute health effects | | |
|--------------------------------|---|---|
| Eye contact | : | Causes serious eye irritation. |
| Inhalation | : | No known significant effects or critical hazards. |
| Skin contact | : | May cause an allergic skin reaction. |
| Ingestion | : | No known significant effects or critical hazards. |

Symptoms related to the physical, chemical and toxicological characteristics

| Code PSX 700 | : 00384173 9 BASE RAL 7040 | Date of issue/Date of revision | : 6 September 2024 | |
|---------------------------------------|-------------------------------|--------------------------------|--------------------|--|
| SECTION 11: Toxicological information | | | | |

| Eye contact | : Adverse symptoms may include the following: pain or irritation watering redness |
|--------------|--|
| Inhalation | : No specific data. |
| Skin contact | : Adverse symptoms may include the following: irritation redness |
| Ingestion | : No specific data. |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| Short term exposure | |
|--------------------------------|---|
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Long term exposure | |
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Potential chronic health effe | ects |
| Not available. | |
| Conclusion/Summary | : Not available. |
| General | : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. |
| Carcinogenicity | : No known significant effects or critical hazards. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Reproductive toxicity | : No known significant effects or critical hazards. |
| | |

Other information

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|--|---|----------------------|----------------------|
| 4,4'- Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- | LC50 11.5 mg/l | Fish - Trout | 96 hours |
| 2,3-epoxypropane Reaction mass of bis (1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate | EC50 1.68 mg/l | Algae | 72 hours |
| methanol | LC50 0.9 mg/l Acute LC50 13 mg/l Fresh water | Fish Fish - Trout | 96 hours 96 hours |
| Conclusion/Summary | : Not available. | I | |

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

| Code : 00384173 | Date of issue/Date of revision | : 6 September 2024 |
|-----------------------|--------------------------------|--------------------|
| PSX 700 BASE RAL 7040 | | |

SECTION 12: Ecological information

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| methanol | -0.77 | - | Low |

12.4 Mobility in soil

| Soil/water partition coefficient (Koc) | : Not available. |
|--|------------------|
| Mobility | : Not available. |

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Methods of disposal

I The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | Waste catalogue | | |
|---------------------|--|--|--|
| Container | 15 01 06 mixed packaging | | |
| Special precautions | : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of | | |

| Empty containere | | | | |
|--------------------|-------------------|---------------------|-----------------|-----------|
| spilt material and | runoff and contac | t with soil, waterv | vays, drains an | d sewers. |

| | ADR/RID | ADN | IMDG | IATA |
|------------------------------------|----------------|--|----------------|----------------|
| 14.1 UN number | Not regulated. | 9006 | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. | - | - |
| 14.3 Transport hazard class(es) | - | 9 | - | - |

English (GB)

| | | - | | | |
|-----------|--------------|---|--------------------------------|--------------------|--|
| PSX 700 B | ASE RAL 7040 | | | | |
| Code | : 00384173 | | Date of issue/Date of revision | : 6 September 2024 | |

SECTION 14: Transport information 14.4 Packing group 14.5 Yes. No. No. No. **Environmental** hazards Marine pollutant Not applicable. Not applicable. Not applicable. Not applicable. substances

Additional information

| ADR/RID | : None identified. |
|---------|--|
| ADN | : The product is only regulated as a dangerous good when transported in tank vessels. |
| IMDG | : None identified. |
| ΙΑΤΑ | : None identified. |
| | |
| 44.0.0 | The second state of the se |

| 14.6 Special precautions for | : Transport within user's premises: always transport in closed containers that are |
|------------------------------|---|
| user | upright and secure. Ensure that persons transporting the product know what to do in |
| | the event of an accident or spillage. |
| | |

| 14.7 Transport in bulk | : Not available. |
|------------------------|------------------|
| according to IMO | |
| instruments | |

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

<u>Seveso Directive</u> This product is not controlled under the Seveso Directive.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

| Abbreviations and acronyms | : ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 |
|-------------------------------|--|
| | No. 720 and amendments |
| | DMEL = Derived Minimal Effect Level |
| | DNEL = Derived No Effect Level |
| | EUH statement = GB CLP-specific Hazard statement |
| | N/A = Not available |
| | PBT = Persistent, Bioaccumulative and Toxic |
| | PNEC = Predicted No Effect Concentration |
| | RRN = REACH Registration Number |

| Code | : 00384173 |
|-----------|--------------|
| PSX 700 B | ASE RAL 7040 |

Date of issue/Date of revision

: 6 September 2024

SECTION 16: Other information

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

| Classification | Justification | |
|-------------------------|--------------------|--|
| Eye Irrit. 2, H319 | Calculation method | |
| Skin Sens. 1, H317 | Calculation method | |
| Aquatic Chronic 3, H412 | Calculation method | |

Full text of abbreviated H statements

| <mark>⊮</mark> 225 | Highly flammable liquid and vapour. |
|--------------------|---|
| H301 | Toxic if swallowed. |
| H311 | Toxic in contact with skin. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H361f | Suspected of damaging fertility. |
| H370 | Causes damage to organs. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |

Full text of classifications

| Acute Tox. 3 | ACUTE TOXICITY - Category 3 |
|---------------------------------|---|
| Aquatic Acute 1 | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 |
| Aquatic Chronic 1 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 |
| Eye Dam. 1 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 |
| Eye Irrit. 2 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 |
| Flam. Liq. 2 | FLAMMABLE LIQUIDS - Category 2 |
| Repr. 2 | REPRODUCTIVE TOXICITY - Category 2 |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 |
| Skin Sens. 1 | SKIN SENSITISATION - Category 1 |
| Skin Sens. 1A | SKIN SENSITISATION - Category 1A |
| STOT SE 1 | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1 |
| History | |
| Date of issue/ Date of revision | : 6 September 2024 |
| | |

| Date of previous issue | : | 1 February 2024 |
|------------------------|---|-----------------|
| Prepared by | ÷ | EHS |
| Version | : | 1.03 |

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.