# **SAFETY DATA SHEET**

pPG

Version4

Date of issue/Date of revision 10 September 2024

## Section 1. Identification

Product code	: 000001194862
Product name	: SIGMAGLIDE 2390 BASE REDBROWN
CAS number	: Not applicable.
EC number	: Mixture.
Other means of identification 00467224	
Product type	: Liquid.
Relevant identified uses of th	e substance or mixture and uses advised against
Product use	<ul> <li>Coating.</li> <li>Professional applications, Used by spraying.</li> </ul>
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
Supplier's details	: PPG Yung Chi Coatings Co. Ltd Lot 219, Amata Street, Long Binh IZ Bien Hoa City, Dong Nai Province Vietnam Tel : +84 61 3936121/22
Emergency telephone number (with hours of operation)	: CHEMTREC +(84)-444581938 (CCN 17704)

## Section 2. Hazards identification

Classification of the substance or mixture	<ul> <li>FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (dermal) - Category 5 SKIN IRRITATION - Category 3 SERIOUS EYE DAMAGE - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 91.9%</li> <li>Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 31.2%</li> </ul>
GHS label elements Hazard pictograms	
Signal word	: Danger

#### Section 2. Hazards identification

Hazard statements	: Flammable liquid and vapor. May be harmful in contact with skin. Causes mild skin irritation. Causes serious eye damage.
	Causes damage to organs through prolonged or repeated exposure.
Precautionary statements	
Prevention	: Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.
Response	: Get medical advice or attention if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Routes of entry	: Not available.
Other hazards which do not result in classification	: Prolonged or repeated contact may dry skin and cause irritation.

## Section 3. Composition/information on ingredients

Sub	stance	/mixt	ture
<b>U</b> un	otaniou		

: Mixture

#### **CAS number/other identifiers**

CAS number EC number	: Not applicable. : Mixture.		
Ingredient name		CAS number	Chemical formula
cristobalite (<10 microns)		14464-46-1	O2-Si
2-methylpropan-1-ol		78-83-1	C4-H10-O
Cyclosiloxanes, di-Me	Cyclosiloxanes, di-Me		-

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SUB codes represent substances without registered CAS Numbers.

Occupational exposure limits, if available, are listed in Section 8.

#### Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	<ul> <li>Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.</li> </ul>
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

%

<1

≥10 - ≤25 ≤5

# Date of issue 10 September 2024

Version 4

Product name SIGMAGLIDE 2390 BASE REDBROWN

## Section 4. First aid measures

Skin contact		Remove contaminated clothing and shoes. Wash skin thoroughly with soap and vater or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion		swallowed, seek medical advice immediately and show this container or label. Seep person warm and at rest. Do NOT induce vomiting.
Most important symptoms/e	ffects.	acute and delayed
Potential acute health effe	<u>ts</u>	
Eye contact	: C	causes serious eye damage.
Inhalation	: N	lo known significant effects or critical hazards.
Skin contact		lay be harmful in contact with skin. Causes mild skin irritation. Defatting to the kin.
Ingestion	: N	lo known significant effects or critical hazards.
<u>Over-exposure signs/symp</u>	<u>toms</u>	
Eye contact	pa wa	dverse symptoms may include the following: ain /atering edness
Inhalation	: N	lo specific data.
Skin contact	pa re dr cr	dverse symptoms may include the following: ain or irritation edness ryness racking listering may occur
Ingestion		dverse symptoms may include the following: tomach pains
Indication of immediate med	lical at	ttention and special treatment needed, if necessary
Notes to physician		reat symptomatically. Contact poison treatment specialist immediately if large uantities have been ingested or inhaled.
Specific treatments	: N	lo specific treatment.
Protection of first-aiders	is m pr	lo action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate hask or self-contained breathing apparatus. It may be dangerous to the person roviding aid to give mouth-to-mouth resuscitation. Wash contaminated clothing horoughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

	Viet Nam Page: 3/11
Specific hazards arising from the chemical	: Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Unsuitable extinguishing media	: Do not use water jet.
Suitable extinguishing media	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Extinguishing media	

## Section 5. Fire-fighting measures

Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides Formaldehyde.
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

Personal precautions, protec	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	onta	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth

and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for

emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

Precautions	for safe	handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### Control parameters

**Occupational exposure limits** 

Ingredient name	Exposure limits
cristobalite (<10 microns) 2-methylpropan-1-ol	ACGIH TLV (United States, 7/2023). [Silica, crystalline] TWA: 0.025 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction Ministry of Health (Viet Nam, 6/2019). [butanols] STEL: 250 mg/m <sup>3</sup> 15 minutes. TWA: 150 mg/m <sup>3</sup> 8 hours.
Recommended monitoring procedures	: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls

limits. Use explosion-proof ventilation equipment.

also need to keep gas, vapor or dust concentrations below any lower explosive

## Section 8. Exposure controls/personal protection

Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measu	<u>lres</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Chemical splash goggles and face shield.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: For prolonged or repeated handling, use the following type of gloves:
	Recommended: butyl rubber, nitrile rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# Section 9. Physical and chemical properties

	Viet Nam Page: 6/11
Flash point	: ℤlosed cup: 37°C (98.6°F) [Product does not sustain combustion.]
Boiling point	: >37.78°C (>100°F)
Melting point	: Not available.
рН	: Not applicable.
Odor threshold	: Not available.
Odor	: Characteristic.
Color	: Brownish-red.
Physical state	: Liquid.
Appearance	

## Section 9. Physical and chemical properties

Evaporation rate	1	Not available.	
Flammability (solid, gas)	1	Not available.	
Lower and upper explosive (flammable) limits	:	<b>№</b> ot applicable.	
Vapor pressure	:	Not available.	
Vapor density	:	Not available.	
Relative density	1	1.14	
		Media	Result
Solubility(ies)	1	cold water	Not soluble
Partition coefficient: n- octanol/water	:	Not applicable.	
Auto-ignition temperature	1	Not available.	
Decomposition temperature	:	Not available.	
Viscosity	:	Kinematic (40°C): >21 mr	n²/s
Viscosity	1	30 - <40 s (ISO 6mm)	

## Section 10. Stability and reactivity

Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides Formaldehyde. metal oxide/oxides
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Chemical stability	: The product is stable.
Reactivity	: No specific test data related to reactivity available for this product or its ingredients

## Section 11. Toxicological information

#### Information on toxicological effects

Product/ingredient name	Result	<b>Species</b>	Dose	Exposure
2-methylpropan-1-ol	LC50 Inhalation Vapor LD50 Dermal LD50 Oral	Rat Rabbit Rat	24.6 mg/l 2460 mg/kg 2830 mg/kg	4 hours - -
Conclusion/Summary Irritation/Corrosion Conclusion/Summary	: There are no data availab	le on the mixture i	tself.	
Skin	: There are no data availab	le on the mixture i	tself.	

Product code 000001194862

Product name SIGMAGLIDE 2390 BASE REDBROWN

## Section 11. Toxicological information

Eyes	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Sensitization	
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
<u>Mutagenicity</u>	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
<b>Carcinogenicity</b>	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
<b>Teratogenicity</b>	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Specific target organ toxic	<u>city (single exposure)</u>

# NameCategoryRoute of<br/>exposureTarget organs2-methylpropan-1-olCategory 3-Respiratory tract<br/>irritation<br/>Narcotic effects

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
cristobalite (<10 microns)	Category 1	inhalation	-

#### Aspiration hazard

Name	Result
2-methylpropan-1-ol	ASPIRATION HAZARD - Category 2

Information on the likely routes of exposure	: Not available.
Potential acute health effect	<u>s</u>
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	<ul> <li>May be harmful in contact with skin. Causes mild skin irritation. Defatting to the skin.</li> </ul>
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the ph	vsical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.

## Section 11. Toxicological information

	_
Skin contact	: Adverse symptoms may include the following: pain or irritation redness dryness cracking blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains

#### Delayed and immediate effects and also chronic effects from short and long term exposure

<u>Short term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
<u>Long term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health eff	<u>ects</u>
General	: Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

#### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	52192.37 mg/kg
Dermal	4999.74 mg/kg

#### Other information

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C (140F). Avoid contact with skin and clothing.

## Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
2-methylpropan-1-ol	Acute EC50 1100 mg/l	Daphnia	48 hours

#### Persistence and degradability

Not available.

Product code 000001194862

# Date of issue 10 September 2024

Version 4

Product name SIGMAGLIDE 2390 BASE REDBROWN

## Section 12. Ecological information

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
2-methylpropan-1-ol	1	-	Low

#### Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

#### Section 13. Disposal considerations

**Disposal methods** The generation of waste should be avoided or minimized wherever possible. 2 Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

 $\mathcal{D}$  ass 3 is not applicable. Product does not sustain combustion.

- UN : None identified.
- IMDG : None identified.
- IATA : None identified.

Product code 000001194862

# Date of issue 10 September 2024

Version 4

Product name SIGMAGLIDE 2390 BASE REDBROWN

## Section 14. Transport information

Special precautions for user	:	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Transport in bulk according		Not applicable.

to IMO instruments

## Section 15. Regulatory information

Safety, health and : No known specific national and/or regional regulations applicable to this product (including its ingredients).

Toxic classification (TCVN : 4 3164-79)

#### International regulations

#### Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

## Section 16. Other information

#### **History**

Date of issue/Date of revision	: 10 September 2024
Date of previous issue	: 8/23/2024
Version	: 4
Prepared by	: EHS
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations</li> </ul>
References	: Not available.

✓ Indicates information that has changed from previously issued version.

#### Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.