

# SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision 12 September 2024

Version 19.02

## Section 1. Identification

**Product name** : AMERLOCK 400C / 400GFA CURE

**Product code** : 00291580

**Other means of identification** : Not available.

**Product type** : Liquid.

### Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

**Use of the substance/mixture** :  Coating.; Hardener.

**Uses advised against** : Not applicable.

**Supplier** : PPG Architectural Coatings Canada, Inc.  
1550, rue Ampère, bureau 500  
Boucherville (Québec) J4B 7L4  
Canada  
+1 450-655-3121

PPG Industries, Inc.  
One PPG Place  
Pittsburgh, PA 15272

**Emergency telephone number** : (412) 434-4515 (U.S.)  
(514) 645-1320 (Canada)  
SETIQ Interior de la República: 800-00-214-00 (México)  
SETIQ Ciudad de México: (55) 5559-1588 (México)

**Technical Phone Number** : 888-977-4762

## Section 2. Hazard identification

**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 3  
ACUTE TOXICITY (inhalation) - Category 4  
SKIN CORROSION - Category 1  
SERIOUS EYE DAMAGE - Category 1  
SKIN SENSITIZATION - Category 1A  
CARCINOGENICITY - Category 2  
TOXIC TO REPRODUCTION - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
Health Hazards Not Otherwise Classified - Category 1

### GHS label elements

## Section 2. Hazard identification

**Hazard pictograms****Signal word**

: Danger

**Hazard statements**

: Flammable liquid and vapor.  
Causes severe skin burns and eye damage.  
May cause an allergic skin reaction.  
Harmful if inhaled.  
May cause respiratory irritation.  
Suspected of causing cancer.  
Suspected of damaging fertility or the unborn child.  
Causes digestive tract burns.  
Prolonged or repeated contact may dry skin and cause irritation.

**Precautionary statements****Prevention**

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

**Response**

: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

**Storage**

: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

**Disposal**

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Supplemental label elements**

: Sanding and grinding dusts may be harmful if inhaled. Do not taste or swallow. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes when heated.  
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity:  
14.1% (oral), 59.8% (dermal), 70.6% (inhalation)

## Section 3. Composition/information on ingredients

**Substance/mixture**

: Mixture

**Product name**

: AMERLOCK 400C / 400GFA CURE

**Other means of identification**

: Not available.

**CAS number/other identifiers**

## Section 3. Composition/information on ingredients

Ingredient name	Synonyms	% (w/w)	CAS number
Talc , not containing asbestiform fibres	Talc; magnesium silicate monohydrate (talc) not containing asbestiform fibres	30 - 60*	14807-96-6
4-methylpentan-2-one	isobutyl methyl ketone; 2-Pentanone, 4-methyl-; METHYL ISOBUTYL KETONE; 4-Methyl-2-pentanone; Isopropyl acetone; Hexone (Methyl isobutyl ketone); Hexone; 4-Methyl 2-pentanone; MIBK; methyl isobutyl ketone; MIBK; isopropylacetone; MIK; methyl iso-butyl ketone; hexone; methyl 2-methylpropyl ketone; 4-methyl-2-oxopentane	7 - 13*	108-10-1
Polyaminoamide	Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine; C36 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polyamide; C36 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer; Dimer acid, triethylenetetramine, tall oil fatty acids polymer; Dimer fatty acids, tall oil fatty acids, triethylenetetramine polymer; Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine; Tall oil acids and fatty acids, C18-unsaturated, dimer, condensate with triethylene tetramine; Triethylenetetramine, dimer fatty acids, tall oil fatty acids polymer; Fatty acids, C18-unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine	5 - 10*	68082-29-1
benzyl alcohol	Benzenemethanol; .alpha.-Hydroxytoluene; Phenylcarbinol; Phenylmethanol; E 1519; α-hydroxytoluene; Phenylmethyl alcohol; toluenol, alpha-; (hydroxymethyl)benzene; BENZENECARBINOL; alpha-Hydroxytoluene	1 - 5*	100-51-6
cyclohexanone	Pimelic ketone; Cyclohexyl ketone; Anone; sextone; ketohexamethylene; nadone; hexanon; Cyclohexanone (I); PIMELIN KETONE; Hytrol O; Anon	1 - 5*	108-94-1
3-aminomethyl-3,5,5-trimethylcyclohexylamine	Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-; Isophorone diamine; 3-(Aminomethyl)-3,5,5-trimethylcyclohexan-1-amine; 5-Amino-1,3,3-trimethylcyclohexanemethanamine; 1-amino-3-aminomethyl-3,5,5-trimethylcyclohexane; 1,3,3-trimethyl-1-aminomethyl-5-aminocyclohexane; 1-amino-3-aminomethyl-3,3,5-trimethylcyclohexane; 5-amino-	1 - 5*	2855-13-2

## Section 3. Composition/information on ingredients

	1,3,3-trimethylcyclohexanemethylamine; Aminomethyl-5 trimethyl-3,5,5 cyclohexylamine; 3-Aminomethyl-3,5,5-trimethyl cyclohexylamine (Isophoronediamine) and preparations containing it; 3-(aminomethyl)-3,5,5-trimethylcyclohexylamine		
4-nonylphenol, branched	Phenol, 4-nonyl-, branched; Branched 4-nonylphenol (mixed isomers); Nonylphenol, 4-branched; N-NONYLPHENOL; Nonylphenol; C9-Branched alkyl phenol; Branched p-nonylphenol; 4-Nonylphenol; branched; Monoalkyl(C3-9)phenol; C9 branched alkyl phenol	1 - 5*	84852-15-3
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 5-amino-1,3,3-trimethylcyclohexanemethanamine and (chloromethyl)oxirane; Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 5-amino-1,3,3-trimethylcyclohexanemethanamine and 2-(chloromethyl)oxirane; 4,4'-(1-Methylethylidene)bisphenol polymer with 5-amino-1,3,3-trimethylcyclohexanemethanamine and (chloromethyl)oxirane; Reaction product of 3-aminomethyl-3,5,5-trimethylcyclohexanamine with oligomerisation products of 4,4'-propane-2,2-diyldiphenol with 2-(chloromethyl)oxirane	1 - 5*	38294-64-3
2-methylpropan-1-ol	iso-butanol; 1-Propanol, 2-methyl-; Isobutyl alcohol; Isobutanol; 2-Methyl-1-propanol; Isopropylcarbinol; IBA; i-Butyl alcohol; isobutanol; iso-butanol; Isobutyl alcohol (I,T); 1-Propanol, 2-methyl- (I,T)	1 - 5*	78-83-1
2,4,6-tris(dimethylaminomethyl)phenol	Phenol, 2,4,6-tris[(dimethylamino)methyl]-; Phenol, 2,4,6-tris(dimethylaminomethyl)-; 2,4,6-tris((dimethylamino)methyl)phenol; Phenol, 2,4,6-tris{(dimethylamino)methyl}-; 2,4,6-Tris[(dimethylamino)methyl]phenol; 2,4,6-Tri(dimethylaminomethyl)phenol; 2,4,6-Tris(N,N-dimethylaminomethyl)phenol; 2,4,6-Tridimethylaminomethylphenol; TRIS (2,4,6-DIMETHYLAMINOMONOMETHYL)PHENOL; TRIS (2,4,6-DIMETHYLAMINOMETHYL)PHENOL; TRIS[(DIMETHYLAMINO)METHYL]PHENOL, 2,4,6-	1 - 5*	90-72-2

### Section 3. Composition/information on ingredients

salicylic acid	Benzoic acid, 2-hydroxy-; 2-hydroxybenzoic acid; 2-Carboxyphenol; 2-Hydroxybenzenecarboxylic acid; HYDROXYBENZOIC ACID, O-; Salicylic acid (8CA); o-Hydroxybenzoic acid; Hydroxybenzoic acid; ORTHOHYDROXY BENZOIC ACID; SALICYCLIC ACID	0.1 - 1*	69-72-7
----------------	--	----------	---------

\*Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

**Occupational exposure limits, if available, are listed in Section 8.**

### Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

#### Description of necessary first aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

##### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Harmful if inhaled. May cause respiratory irritation.
- Skin contact** : Causes severe burns. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : Corrosive to the digestive tract. Causes burns.

##### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

## Section 4. First-aid measures

- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
dryness  
cracking  
blistering may occur  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
stomach pains  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon oxides  
nitrogen oxides  
halogenated compounds  
metal oxide/oxides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.



## Section 7. Handling and storage

- Special precautions** : Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
- Advice on general occupational hygiene** : Wash hands thoroughly after handling.
- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
alc , not containing asbestiform fibres	<p><b>CA British Columbia Provincial (Canada, 8/2023).</b> TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable</p> <p><b>CA Quebec Provincial (Canada, 7/2023).</b> TWAEV: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable dust.</p> <p><b>CA Alberta Provincial (Canada, 3/2023).</b> OEL: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable particulate</p> <p><b>CA Ontario Provincial (Canada, 6/2019).</b> TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable particulate matter.</p> <p><b>CA Saskatchewan Provincial (Canada, 7/2013).</b> TWA: 2 mg/m<sup>3</sup> 8 hours. Form: respirable fraction</p>
4-methylpentan-2-one	<p><b>CA Alberta Provincial (Canada, 3/2023).</b> OEL: 307 mg/m<sup>3</sup> 15 minutes. OEL: 75 ppm 15 minutes. OEL: 205 mg/m<sup>3</sup> 8 hours. OEL: 50 ppm 8 hours.</p> <p><b>CA British Columbia Provincial (Canada, 8/2023).</b> STEL: 75 ppm 15 minutes. TWA: 20 ppm 8 hours.</p> <p><b>CA Ontario Provincial (Canada, 6/2019).</b></p>



## Section 8. Exposure controls/personal protection

Polyaminoamide  
benzyl alcohol

cyclohexanone

3-aminomethyl-3,5,5-trimethylcyclohexylamine  
4-nonylphenol, branched  
4,4'-Isopropylidenediphenol, oligomeric reaction products with  
1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-  
3,5,5-trimethylcyclohexylamine  
2-methylpropan-1-ol

STEL: 75 ppm 15 minutes.

TWA: 20 ppm 8 hours.

**CA Quebec Provincial (Canada, 7/2023).**

STEV: 75 ppm 15 minutes.

TWAEV: 20 ppm 8 hours.

**CA Saskatchewan Provincial (Canada, 7/2013).**

STEL: 75 ppm 15 minutes.

TWA: 50 ppm 8 hours.

None.

**IPEL (-).**

TWA: 5 ppm

STEL: 10 ppm

**CA Alberta Provincial (Canada, 3/2023).**

**Absorbed through skin.**

OEL: 80 mg/m<sup>3</sup> 8 hours.

OEL: 20 ppm 8 hours.

OEL: 200 mg/m<sup>3</sup> 15 minutes.

OEL: 50 ppm 15 minutes.

**CA British Columbia Provincial (Canada, 8/2023). Absorbed through skin.**

STEL: 50 ppm 15 minutes.

TWA: 20 ppm 8 hours.

**CA Ontario Provincial (Canada, 6/2019).**

**Absorbed through skin.**

STEL: 50 ppm 15 minutes.

TWA: 20 ppm 8 hours.

**CA Quebec Provincial (Canada, 7/2023).**

**Absorbed through skin.**

TWAEV: 100 mg/m<sup>3</sup> 8 hours.

TWAEV: 25 ppm 8 hours.

**CA Saskatchewan Provincial (Canada, 7/2013). Absorbed through skin.**

STEL: 50 ppm 15 minutes.

TWA: 20 ppm 8 hours.

None.

None.

None.

**CA Alberta Provincial (Canada, 3/2023).**

**Skin sensitizer.**

OEL: 152 mg/m<sup>3</sup> 8 hours.

OEL: 50 ppm 8 hours.

**CA British Columbia Provincial (Canada, 8/2023).**

TWA: 50 ppm 8 hours.

**CA Ontario Provincial (Canada, 6/2019).**

TWA: 50 ppm 8 hours.

**CA Quebec Provincial (Canada, 7/2023).**

TWAEV: 152 mg/m<sup>3</sup> 8 hours.

TWAEV: 50 ppm 8 hours.

**CA Saskatchewan Provincial (Canada, 7/2013).**

STEL: 60 ppm 15 minutes.

## Section 8. Exposure controls/personal protection

2,4,6-tris(dimethylaminomethyl)phenol  
salicylic acid

TWA: 50 ppm 8 hours.  
None.  
None.

### Consult local authorities for acceptable exposure limits.

**Recommended monitoring procedures** : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Chemical splash goggles and face shield.

#### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** : butyl rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

## Section 9. Physical and chemical properties

### Appearance

Physical state	: Liquid.
Color	: Colorless.
Odor	: Amine-like. [Strong]
Odor threshold	: Not available.
pH	: Not applicable.
Melting point	: Not available.
Boiling point	: >37.78°C (>100°F)
Flash point	: Closed cup: 37°C (98.6°F)
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Flammability	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Evaporation rate	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 1.36
Density ( lbs / gal )	: 11.35

	Media	Result
Solubility(ies)	cold water	Not soluble

Partition coefficient: n-octanol/water	: Not applicable.
Viscosity	: Kinematic (40°C (104°F)): >21 mm <sup>2</sup> /s (>21 cSt)
Volatility	: 28% (v/v), 17.188% (w/w)
% Solid. (w/w)	: 82.812

## Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/oxides

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
4-methylpentan-2-one	LC50 Inhalation Vapor	Rat	11 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	2.08 g/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>4178 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-
cyclohexanone	LC50 Inhalation Gas.	Rat	8000 ppm	4 hours
	LD50 Dermal	Rabbit	1100 mg/kg	-
	LD50 Oral	Rat	1800 mg/kg	-
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	LC50 Inhalation Dusts and mists	Rat	>5.01 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1030 mg/kg	-
4-nonylphenol, branched	LD50 Dermal	Rabbit	2.14 g/kg	-
	LD50 Oral	Rat	1300 mg/kg	-
	LC50 Inhalation Vapor	Rat	24.6 mg/l	4 hours
2-methylpropan-1-ol	LD50 Dermal	Rabbit	2460 mg/kg	-
	LD50 Oral	Rat	2830 mg/kg	-
	LD50 Dermal	Rat	1280 mg/kg	-
2,4,6-tris (dimethylaminomethyl) phenol	LD50 Oral	Rat	1200 mg/kg	-
	LD50 Oral	Rat	0.891 g/kg	-
	LD50 Oral	Rat	0.891 g/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
4-nonylphenol, branched	Skin - Erythema/Eschar	Rabbit	4	-	-

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

#### Sensitization

Product/ingredient name	Route of exposure	Species	Result
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	skin	Guinea pig	Sensitizing

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

#### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Classification

**Section 11. Toxicological information**

Product/ingredient name	OSHA	IARC	NTP
4-methylpentan-2-one	-	2B	-
cyclohexanone	-	3	-

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

**Reproductive toxicity****Conclusion/Summary** : There are no data available on the mixture itself.**Teratogenicity****Conclusion/Summary** : There are no data available on the mixture itself.**Specific target organ toxicity (single exposure)**

Name	Category	Route of exposure	Target organs
Talc , not containing asbestiform fibres	Category 3	-	Respiratory tract irritation
4-methylpentan-2-one	Category 3	-	Narcotic effects
cyclohexanone	Category 3	-	Respiratory tract irritation
2-methylpropan-1-ol	Category 3	-	Respiratory tract irritation
	Category 3		Narcotic effects

**Specific target organ toxicity (repeated exposure)**

Not available.

**Target organs**

: Contains material which causes damage to the following organs: blood, liver, heart, brain, skin, central nervous system (CNS).  
 Contains material which may cause damage to the following organs: kidneys, lungs, the reproductive system, cardiovascular system, upper respiratory tract, bones, eye, lens or cornea.

**Aspiration hazard**

Not available.

**Information on the likely routes of exposure****Potential acute health effects****Eye contact** : Causes serious eye damage.**Inhalation** : Harmful if inhaled. May cause respiratory irritation.**Skin contact** : Causes severe burns. Defatting to the skin. May cause an allergic skin reaction.**Ingestion** : Corrosive to the digestive tract. Causes burns.**Over-exposure signs/symptoms****Eye contact** : Adverse symptoms may include the following:  
 pain  
 watering  
 redness

## Section 11. Toxicological information

- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
dryness  
cracking  
blistering may occur  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
stomach pains  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

- Conclusion/Summary** : There are no data available on the mixture itself. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Short term exposure

- Potential immediate effects** : There are no data available on the mixture itself.
- Potential delayed effects** : There are no data available on the mixture itself.

### Long term exposure

- Potential immediate effects** : There are no data available on the mixture itself.
- Potential delayed effects** : There are no data available on the mixture itself.

### Potential chronic health effects

- General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.

## Section 11. Toxicological information

**Reproductive toxicity** : Suspected of damaging fertility or the unborn child.

### Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
AMERLOCK 400C / 400GFA CURE	4277.6	3406.1	54805.2	31.5	2.9
4-methylpentan-2-one	2080	N/A	N/A	11	1.5
benzyl alcohol	1230	2000	N/A	N/A	1.5
cyclohexanone	1800	1100	8000	N/A	N/A
3-aminomethyl-3,5,5-trimethylcyclohexylamine	1030	2500	N/A	N/A	N/A
4-nonylphenol, branched	1300	2140	N/A	N/A	N/A
2-methylpropan-1-ol	2830	2460	N/A	24.6	N/A
2,4,6-tris(dimethylaminomethyl)phenol	1200	1280	N/A	N/A	N/A
salicylic acid	891	N/A	N/A	N/A	N/A

## Section 12. Ecological information

### Toxicity

Product/ingredient name	Result	Species	Exposure
4-methylpentan-2-one	Acute LC50 >179 mg/l	Fish	96 hours
4-nonylphenol, branched	Acute EC50 0.044 mg/l	Crustaceans - <i>Moina macrocopa</i>	48 hours
	Acute LC50 0.221 mg/l	Fish	96 hours
2-methylpropan-1-ol	Acute EC50 1100 mg/l	Daphnia	48 hours
2,4,6-tris (dimethylaminomethyl)phenol	Acute LC50 >100 mg/l	Daphnia	48 hours
salicylic acid	Acute LC50 >100 mg/l	Fish	96 hours
	Acute EC50 1147.57 mg/l Fresh water	Daphnia - <i>Daphnia longispina</i> - Neonate	48 hours
	Chronic NOEC 5.6 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	21 days

### Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
4-methylpentan-2-one	OECD 301F	83 % - Readily - 28 days	-	-
2,4,6-tris (dimethylaminomethyl)phenol	OECD 301D	4 % - Not readily - 28 days	-	-
	Ready Biodegradability - Closed Bottle Test			

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
4-methylpentan-2-one	-	-	Readily
benzyl alcohol	-	-	Readily
2,4,6-tris (dimethylaminomethyl)phenol	-	-	Not readily

### Bioaccumulative potential



## Section 12. Ecological information

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
4-methylpentan-2-one	1.9	-	Low
benzyl alcohol	0.87	-	Low
cyclohexanone	0.86	-	Low
3-aminomethyl-3,5,5-trimethylcyclohexylamine	0.99	-	Low
4-nonylphenol, branched	5.4	251.19	Low
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine	-	5.13	Low
2-methylpropan-1-ol	1	-	Low
2,4,6-tris(dimethylaminomethyl)phenol	0.219	-	Low
salicylic acid	2.21 to 2.26	-	Low

### Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

## Section 14. Transport information

**Section 14. Transport information**

	<b>TDG</b>	<b>IMDG</b>	<b>IATA</b>
<b>UN number</b>	UN3469	UN3469	UN3469
<b>UN proper shipping name</b>	PAINT, FLAMMABLE, CORROSIVE	PAINT, FLAMMABLE, CORROSIVE	PAINT, FLAMMABLE, CORROSIVE
<b>Transport hazard class (es)</b>	3 (8)	3 (8)	3 (8)
<b>Packing group</b>	III	III	III
<b>Environmental hazards</b>	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
<b>Marine pollutant substances</b>	(4-nonylphenol, branched)	(4-nonylphenol, branched)	Not applicable.

**Additional information**

- TDG** : The marine pollutant mark is not required when transported by road or rail.
- IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not applicable.

**Proof of classification statement** : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3), 2.40-2.42 (Class 8), 2.7 (Marine pollutant mark).

**Section 15. Regulatory information****National Inventory List**

**Canada inventory (DSL)** : All components are listed or exempted.

**Section 16. Other information****Hazardous Material Information System (U.S.A.)**

**Health** : 3 \* **Flammability** : 3 **Physical hazards** : 0

(\* ) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

**National Fire Protection Association (U.S.A.)**

**Health** : 3 **Flammability** : 3 **Instability** : 0

## Section 16. Other information

Date of issue/Date of revision 12 September 2024

Organization that prepared the SDS : EHS

Key to abbreviations : ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
N/A = Not available  
SGG = Segregation Group  
UN = United Nations

▣ Indicates information that has changed from previously issued version.

### Disclaimer

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*