# **SAFETY DATA SHEET**

Date of issue/Date of revision 20 September 2024

Version3

## Section 1. Identification

Product code	: 000001190404	
Product name	: STEELGUARD 951 BASE LIGHT GREY	
CAS number	: Not applicable.	
EC number	: Mixture.	
Other means of identification 00453044; 00472632; 004769	3	
Product type	: Liquid.	
Relevant identified uses of t	e substance or mixture and uses advised against	
Product use	Coating. Professional applications, Used by spraying.	
Uses advised against	: Product is not intended, labelled or packaged for consumer use.	
Supplier's details	: PPG Yung Chi Coatings Co. Ltd Lot 219, Amata Street, Long Binh IZ Bien Hoa City, Dong Nai Province Vietnam Tel : +84 61 3936121/22	
Emergency telephone number (with hours of operation)	: CHEMTREC +(84)-444581938 (CCN 17704)	

## Section 2. Hazards identification

Classification of the substance or mixture	<ul> <li>KIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 AQUATIC TOXICITY (ACUTE) - Category 2 AQUATIC TOXICITY (CHRONIC) - Category 2</li> <li>Fercentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 12.2%</li> </ul>
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	<ul> <li>Causes skin irritation.</li> <li>May cause an allergic skin reaction.</li> <li>Causes serious eye irritation.</li> <li>Toxic to aquatic life with long lasting effects.</li> </ul>
Precautionary statements	

## Section 2. Hazards identification

Prevention	:	Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
Response	:	Collect spillage. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Routes of entry	:	Not available.
Other hazards which do not result in classification	:	Contains a substance that may emit formaldehyde if stored beyond its shelf life and/ or during cure at curing temperatures greater than 60C (140F).

## Section 3. Composition/information on ingredients

Substance/mixture	1	Mixture

### **CAS number/other identifiers**

CAS number: Not applicable.EC number: Mixture.			
Ingredient name	CAS number	Chemical formula	%
✓olyphosphoric acids, ammonium salts Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	68333-79-9 9003-36-5	- (C6-H6-O. C3-H5-CI-O.C- H2-O)x	≥25 - ≤50 ≥10 - ≤25
hexamethylene diacrylate tris(2-chloro-1-methylethyl) phosphate Phenol, styrenated Phenol, polymer with formaldehyde, glycidyl ether (MW<=700)	13048-33-4 13674-84-5 61788-44-1 28064-14-4	C12-H18-O4 C9-H18-CI3-O4-P - (C6H6O.CH2O)x	≤10 ≤8 ≤6.5 ≤3
[MW <-700] Dodecanedioic acid, polymer with 2,2'- [1,4-butanediylbis(oxymethylene)]bis[oxirane], (chloromethyl)oxirane, 4,4'-(1-methylethylidene)bis [phenol], nonanedioic acid and 2,2'-oxybis[ethanol]	139651-91-5	-	≤3
carbon	7440-44-0	С	≤3

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SUB codes represent substances without registered CAS Numbers.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

### Description of necessary first aid measures

Eye contact	:	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
		In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact.
Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	1	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	1	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

most important symptoms/e		
Potential acute health effect		
Eye contact	uses serious eye irritation.	
Inhalation	known significant effects or critical hazards.	
Skin contact	uses skin irritation. May cause an allergic skin reaction.	
Ingestion	known significant effects or critical hazards.	
<u>Over-exposure signs/symp</u>		
Eye contact	verse symptoms may include the following: n or irritation ering ness	
Inhalation	specific data.	
Skin contact	rerse symptoms may include the following: ation ness	
Ingestion	specific data.	
Indication of immediate med	ention and special treatment needed, if necessary	
Notes to physician	at symptomatically. Contact poison treatment specialist intities have been ingested or inhaled.	immediately if large
Specific treatments	specific treatment.	
Protection of first-aiders	action shall be taken involving any personal risk or witho y be dangerous to the person providing aid to give mout sh contaminated clothing thoroughly with water before r ves.	h-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides phosphorus oxides halogenated compounds metal oxide/oxides Formaldehyde.
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and materials for co	ont	ainment and cleaning up
Small spill	÷	Stop leak if without risk. Move containers from spill area. Dilute with water and mop

licensed waste disposal contractor.

up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a

### Section 6. Accidental release measures

#### Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
		Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

Ingredient name	Exposure limits
carbon	Ministry of Health (Viet Nam, 6/2019). [bụi graphit] TWA: 1 mg/m³ 8 hours. Form: respirable dust TWA: 2 mg/m³ 8 hours. Form: total dust concentration

Viet Nam Page: 5/12

## Section 8. Exposure controls/personal protection

Recommended monitoring procedures	-	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measured	res	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Chemical splash goggles.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	:	polyethylene butyl rubber
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

## Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Gray.
Odor	: Not available.
Odor threshold	: Not available.
рН	: Not applicable.
Melting point	: Not available.

## Section 9. Physical and chemical properties

-				
Boiling point	:	>37.78°C (>100°F)		
Flash point	1	Closed cup: 130°C (266°F)		
Evaporation rate	1	Not available.		
Flammability (solid, gas)	1	Not available.		
Lower and upper explosive (flammable) limits	:	Not available.		
Vapor pressure	1	Not available.		
Vapor density	1	Not available.		
Relative density	1	1.54		
Solubility(ies)		Media Result		
Solubility(les)	1	cold water Not soluble		
Partition coefficient: n- octanol/water	:	Not applicable.		
Auto-ignition temperature	1	Not available.		
Decomposition temperature	:	Not available.		
Viscosity	1	Kinematic (40°C): >21 mm²/s		
Viscosity	:	> 100 s (ISO 6mm)		

## Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	<ul> <li>Depending on conditions, decomposition products may include the following materials: carbon oxides phosphorus oxides halogenated compounds Formaldehyde. metal oxide/oxides</li> </ul>

## Section 11. Toxicological information

Information on toxicological effects Acute toxicity

## Section 11. Toxicological information

Product/ingredient name	Result		Species	Dose	Exposure
Polyphosphoric acids, ammonium salts	LD50 Oral		Rat	4.74 g/kg	-
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	LD50 Oral		Rat	>10000 mg/kg	-
hexamethylene diacrylate	LD50 Dermal		Rabbit	3.65 g/kg	-
	LD50 Oral		Rat	>5000 mg/kg	-
tris(2-chloro-1-methylethyl) phosphate	LC50 Inhalation	Dusts and mists	Rat	>7 mg/l	4 hours
	LD50 Dermal		Rabbit	>5 g/kg	-
	LD50 Oral		Rat	1500 mg/kg	-
Phenol, styrenated	LD50 Dermal		Rabbit	>5010 mg/kg	-
	LD50 Oral		Rat	3550 mg/kg	-
Conclusion/Summary	: There are no	data available on	the mixture its	elf.	
rritation/Corrosion					
Conclusion/Summary					
Skin	: There are no	data available on	the mixture its	elf.	
Eyes	: There are no	data available on	the mixture its	elf.	
Respiratory	: There are no	data available on	the mixture its	elf.	
<u>Sensitization</u>					
Product/ingredient name	Route of	Species		Result	
	exposure				
hexamethylene diacrylate	skin	Guinea pig		Sensitizing	
Phenol, styrenated	skin	Mouse		Sensitizing	
Skin	: There are no	data available on	the mixture its	elf.	
Respiratory	: There are no	data available on	the mixture its	elf.	
<u>Mutagenicity</u>					
Conclusion/Summary	: There are no	data available on	the mixture its	elf.	
Carcinogenicity					
Conclusion/Summary	: There are no	data available on	the mixture its	elf.	
Reproductive toxicity					
Conclusion/Summary	: There are no	data available on	the mixture its	elf.	
Feratogenicity					
Conclusion/Summary	: There are no	data available on	the mixture its	elf.	
Specific target organ toxicit	<u>ty (single exposı</u>	<u>ıre)</u>			
Name			egory	Route of	Target organs

Name	• •	Route of exposure	Target organs
carbon	Category 3	-	Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

Product code 000001190404

Product name STEELGUARD 951 BASE LIGHT GREY

## Section 11. Toxicological information

Information on the likely routes of exposure	:	Not available.			
Potential acute health effects	2				
Eye contact	:	Causes serious eye irritation.			
Inhalation	:	No known significant effects or critical hazards.			
Skin contact	:	$ ot\!$			
Ingestion	:	No known significant effects or critical hazards.			
Eye contact	:	cal, chemical and toxicological characteristics Adverse symptoms may include the following: pain or irritation watering redness			
Inhalation		No specific data.			
Skin contact	-	Adverse symptoms may include the following: irritation redness			
Ingestion	:	No specific data.			
Delayed and immediate effects and also chronic effects from short and long term exposure					

Short term exposure	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
<u>Long term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health eff	f <u>ects</u>
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

### Numerical measures of toxicity

### Acute toxicity estimates

Route	ATE value
	6383.15 mg/kg 12054.86 mg/kg

### Other information

10

## Section 11. Toxicological information

Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure. The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion may cause nausea, weakness and central nervous system effects. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C (140F). In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact.

## Section 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
♥olyphosphoric acids, ammonium salts	Acute EC50 730.5 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Acute LC50 2.54 mg/l	Fish	96 hours
Phenol, styrenated	Acute EC50 3.8 mg/l	Daphnia	48 hours

### Persistence and degradability

Product/ingredient name	Test	Result		Dose		Inoculum
Phenol, styrenated	OECD 301F	7 % - Not re	eadily - 28 days	-		-
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
Phenol, styrenated	-		-		Not rea	adily

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol hexamethylene diacrylate tris(2-chloro-1-methylethyl) phosphate	2.7 2.81 2.68	- - 7.94	Low Low Low

### Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

## Date of issue 20 September 2024

Product name STEELGUARD 951 BASE LIGHT GREY

### Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	✔Epoxy Resin, hexamethylene diacrylate)	t €poxy Resin, hexamethylene diacrylate)	Epoxy Resin, hexamethylene diacrylate)
Transport hazard class(es)	9	9	9
Packing group		III	III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(Epoxy Resin)	Not applicable.

### Additional information

UN	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
Special preca	autions for user : <b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

## Section 15. Regulatory information

Safety, health and environmental regulations specific for the product	: No known specific national and/or regional regulations applicable to this product (including its ingredients).
Toxic classification (TCVN 3164-79)	: 3
International regulations	

### **Montreal Protocol**

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 20 September 2024
Date of previous issue	: 5/20/2024
Version	: 3
Prepared by	: EHS
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations</li> </ul>
References	: Not available.

Indicates information that has changed from previously issued version.

### Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.