# **SAFETY DATA SHEET**

Date of issue/Date of revision 26 September 2024

Version1.03

# Section 1. Identification

Product code	: 00445474
Product name	: SIGMASHIELD 1090 BASE GREY 3.75G 1225
CAS number	: Not applicable.
EC number	: Mixture.
Product type	: Liquid.
Relevant identified uses	of the substance or mixture and uses advised against
Product use	Coating. Professional applications, Used by spraying.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
Supplier's details	: PPG Yung Chi Coatings Co. Ltd Lot 219, Amata Street, Long Binh IZ Bien Hoa City, Dong Nai Province Vietnam Tel : +84 61 3936121/22
Emergency telephone number (with hours of operation)	: CHEMTREC +(84)-444581938 (CCN 17704)

# Section 2. Hazards identification

Classification of the	: ACUTE TOXICITY (oral) - Category 5
substance or mixture	ACUTE TOXICITY (dermal) - Category 5
	ACUTE TOXICITY (inhalation) - Category 4
	SKIN IRRITATION - Category 2
	EYE IRRITATION - Category 2A
	SKIN SENSITIZATION - Category 1
	GERM CELL MUTAGENICITY - Category 2
	AQUATIC TOXICITY (ACUTE) - Category 3
	AQUATIC TOXICITY (CHRONIC) - Category 3
	Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity. 76.9%
	Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 76.9%
	Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 95.8%
	Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 78.7%



Product code 00445474

Product name SIGMASHIELD 1090 BASE GREY 3.75G 1225

# Section 2. Hazards identification

Signal word	1	Warning
Hazard statements	:	May be harmful if swallowed or in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. Suspected of causing genetic defects. Harmful to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
Response	:	IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	:	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Routes of entry	:	Not available.
Other hazards which do not result in classification	;	None known.

# Section 3. Composition/information on ingredients

#### Substance/mixture

#### : Mixture

#### **CAS number/other identifiers**

CAS number	: Not applicable.
EC number	: Mixture.

Ingredient name	CAS number	Chemical formula	%
Peaction product: bisphenol-A-(epichlorohydrin); epoxy resin		(C15-H16-O2. C3-H5-Cl-O)x	≥10 - ≤21
2,3-epoxypropyl neodecanoate benzyl alcohol	26761-45-5 100-51-6	C13-H24-O3 C7-H8-O	≤3 ≤2.6

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SUB codes represent substances without registered CAS Numbers.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

Description of necess	ary first aid measures
Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/e	ffects, acute and delayed
Potential acute health effe	t <u>s</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: Harmful if inhaled.
Skin contact	: May be harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: May be harmful if swallowed.
Over-exposure signs/sym	<u>toms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Indication of immediate me	lical attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media		
Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.

## Section 5. Fire-fighting measures

-	
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	<ul> <li>Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.</li> </ul>

# Section 6. Accidental release measures

Personal precautions, protect	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
Methods and materials for co	nt	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

<b>Precautions</b>	for	safe	handling	

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

Control parameters	
Occupational exposure li	<u>mits</u>

None.		
Recommended monitoring procedures	:	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	<u>'es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Chemical splash goggles.

Product code 00445474

Product name SIGMASHIELD 1090 BASE GREY 3.75G 1225

# Section 8. Exposure controls/personal protection

#### Skin protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: butyl rubber
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# Section 9. Physical and chemical properties

#### **Appearance**

		Viet Nam Page:	6/12
Viscosity	1	Kinematic (40°C): >21 mm²/s	
Decomposition temperature		Not available.	
Auto-ignition temperature	-	Not available.	
Partition coefficient: n- octanol/water		Not applicable.	
		cold water Not soluble	
Solubility(ies)	:	Media Result	
Relative density	1	1.72	
Vapor density	:	Not available.	
Vapor pressure	1	Not available.	
Lower and upper explosive (flammable) limits	1	Greatest known range: Lower: 1.3% Upper: 13% (benzyl alcohol)	
Flammability (solid, gas)		Not available.	
Evaporation rate	÷	Not available.	
Flash point		Closed cup: Not applicable.	
Boiling point		>37.78°C (>100°F)	
Melting point		Not available.	
рН	1	Not applicable.	
Odor threshold	1	Not available.	
Odor		Characteristic.	
Color	4	Gray.	
Physical state	1	Liquid.	
Appearance			

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides

## Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
A-(epichlorohydrin); epoxy resin	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	>2 g/kg	-
2,3-epoxypropyl neodecanoate	LD50 Dermal	Rat	3800 mg/kg	-
	LD50 Oral	Rat	9.6 g/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>4178 mg/m <sup>3</sup>	4 hours
-	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
A-(epichlorohydrin); epoxy resin	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Eyes - Moderate irritant	Rabbit	_	_	-
	Skin - Moderate irritant	Rabbit	-	-	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 Ul	-
	Skin - Severe irritant	Rabbit	-	24 hours 2 mg	-

#### **Conclusion/Summary**

Skin	: There are no data available on the mixture itself.

Eyes Respiratory There are no data available on the mixture itself.There are no data available on the mixture itself.

Sensitization

Viet Nam Page: 7/12

# Section 11. Toxicological information

Product/ingredient name	Route of exposure	Species	Result
A-(epichlorohydrin); epoxy resin	skin	Mouse	Sensitizing
Skin	: There are no d	ata available on the mixture itse	lf.
Respiratory	: There are no da	ata available on the mixture itse	lf.
Mutagenicity			
Conclusion/Summary	: There are no d	ata available on the mixture itse	lf.
Carcinogenicity			
<b>Conclusion/Summary</b>	: There are no d	ata available on the mixture itse	lf.
Reproductive toxicity			
Conclusion/Summary	: There are no d	ata available on the mixture itse	lf.
Teratogenicity			
Conclusion/Summary	: There are no d	ata available on the mixture itse	lf.
Specific target organ toxicit	<u>y (single exposur</u>	<u>e)</u>	
Not available.			
Specific target organ toxicit	y (repeated expos	sure)	
Not available.			

#### Aspiration hazard

I	Name	Result
k	penzyl alcohol	ASPIRATION HAZARD - Category 2

Information on the likely routes of exposure	:	Not available.
Potential acute health effect	<u>s</u>	
Eye contact	1	Causes serious eye irritation.
Inhalation	1	Harmful if inhaled.
Skin contact	:	May be harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.
Ingestion	1	May be harmful if swallowed.
<u>Symptoms related to the phy</u> Eye contact		cal, chemical and toxicological characteristics Adverse symptoms may include the following:
		pain or irritation watering redness
Inhalation	1	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.

### Section 11. Toxicological information

Delayed and immediate effect	ts and also chronic effects from short and long term exposure			
<u>Short term exposure</u>				
Potential immediate effects	: There are no data available on the mixture itself.			
Potential delayed effects	: There are no data available on the mixture itself.			
<u>Long term exposure</u>				
Potential immediate effects	: There are no data available on the mixture itself.			
Potential delayed effects	: There are no data available on the mixture itself.			
Potential chronic health effects				
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.			
Carcinogenicity	: No known significant effects or critical hazards.			
Mutagenicity	: Suspected of causing genetic defects.			
Reproductive toxicity	: No known significant effects or critical hazards.			

#### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Dermal	2928.03 mg/kg 2861.16 mg/kg 3.45 mg/l

#### Other information

Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

# Section 12. Ecological information

2

Toxicity				
Product/ingredient name	Result	Species	Exposure	
A-(epichlorohydrin); epoxy resin	Chronic NOEC 0.3 mg/l	Daphnia	21 days	
2,3-epoxypropyl neodecanoate	Acute EC50 3.5 mg/l	Algae	96 hours	
	Acute EC50 4.8 mg/l Acute LC50 9.6 mg/l	Daphnia - <i>Daphnia magna</i> Fish - <i>Oncorhynchus mykiss</i>	48 hours 96 hours	

#### Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Feaction product: bisphenol- A-(epichlorohydrin); epoxy resin	OECD 301F	5 % - 28 days	-	-

Viet Nam	Page: 9/12
----------	------------

# Section 12. Ecological information

	<u> </u>		
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
A-(epichlorohydrin); epoxy resin	-	-	Not readily
2,3-epoxypropyl neodecanoate	-	-	Not readily
benzyl alcohol	-	-	Readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
A-(epichlorohydrin); epoxy resin	2.64 to 3.78	31	Low
2,3-epoxypropyl neodecanoate	4.4	-	High
benzyl alcohol	0.87	-	Low

#### Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
<u> </u>			Viet Nam Page: 10/12

Product code 00445474			Date of issue	26 September 2024	Version 1.03	
Product name SI	GMASHIELD	109	00 BASE GREY 3.7	75G 1225		
Section 14.	Transp	or	t informatio	on		
Marine pollutant substances	1	lot a	pplicable.	Not applicable.	Not	applicable.
Additional inform	nation					
UN	: None identified.					
IMDG	: None identified.					
ΙΑΤΑ	: None identified.					
Special precaution	ons for user			<b>user's premises:</b> always to Ensure that persons trans ident or spillage.		
Transport in bulk to IMO instrumer		:	Not applicable.			
Section 15.	Regula	to	ry informati	ion		
Safety, health and environmental reg specific for the pr	gulations		No known specific n including its ingredi	national and/or regional reg ients).	ulations applicable	e to this product

Toxic classification (TCVN : 4 3164-79)

International regulations

### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

# Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 26 September 2024
Date of previous issue	: 9/30/2021
Version	: 1.03
Prepared by	: EHS
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations</li> </ul>
References	: Not available.

✓ Indicates information that has changed from previously issued version.

### Section 16. Other information

#### Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.