SAFETY DATA SHEET



use.

Date of issue 9/30/2024 (month/day/year)

Version 1.01

Section 1. Chemical product and company identification

A. Product name : SIGMAGUARD CSF 585 BASE WHITE Product code : 000001188631

Other means of identification 00445008; 00461204

	Product use	: Professional applications, Used by spraying.
	Use of the substance/ mixture	: Coating.
	Uses advised against	: Product is not intended, labelled or packaged for consumer
C.	Supplier's or Importer's information	: PPG SSC (680-090) 19, Yeocheon-ro 217beon-gil, Nam-gu, Ulsan, Korea Tel: +82-52-210-8222
	Email Address	Korea.MSDS@PPG.COM
	Emergency telephone number:	: <mark>⊬</mark> 82-52-210-8331

Section 2. Hazards identification

A. Hazard classification	 FLAMMABLE LIQUIDS - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A AQUATIC HAZARD (LONG-TERM) - Category 2 This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

B. GHS label elements, including precautionary statements

Symbol



Signal word

: Danger

Date of issue 9/30/2024 (month/day/year)

Product name SIGMAGUARD CSF 585 BASE WHITE

Section 2. Hazards identification

Hazard statements	 H227 - Combustible liquid. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H350 - May cause cancer. H411 - Toxic to aquatic life with long lasting effects.
Precautionary stateme	nts
Prevention	 P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves, protective clothing and eye or face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P273 - Avoid release to the environment. P261 - Avoid breathing vapor. P264 - Wash thoroughly after handling.
Response	 P391 - Collect spillage. P370 + P378 - In case of fire: Never use water to extinguish. P308 + P313 - IF exposed or concerned: Get medical advice or attention. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P362 + P364 - Take off contaminated clothing and wash it before reuse. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention. P321 - Specific treatment (see the label).
Storage	: 🗗403 - Store in a well-ventilated place.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

C. Other hazards which do : None known. not result in classification

Section 3. Composition/information on ingredients

CAS number/other identifiers

CAS number

: Not applicable.

Chemical name	Common name	Identifiers	%
øis-[4-(2,3-epoxipropoxi)phenyl]propane	Bisphenol A diglycidyl ether	CAS: 1675-54-3	40 - <50
1,6-bis(2,3-epoxypropoxy)hexane	1,6-HEXANDIOLGLYCIDETHER	EC: 216-823-5 CAS: 16096-31-4 EC: 240-260-4	10 -<20
Talc , not containing asbestiform fibres	Talc, non-asbestos form	CAS: 14807-96-6 EC: 238-877-9	1 - <5
titanium dioxide	TITANIUM DIOXIDE	CAS: 13463-67-7 EC: 236-675-5	1 - <5
crystalline silica, respirable powder (>10 microns)	QUARTZ (>10 microns)	CAS: 14808-60-7	0.1 - <1
xylene	o-Xylene	EC: 238-878-4 CAS: 95-47-6 EC: 202-422-2	0.1 - <1

Korea (GHS) Page: 2/13

Product name SIGMAGUARD CSF 585 BASE WHITE

Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Α.	Eye contact	:	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.		
В.	Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.		
C.	Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.		
D.	Ingestion	:	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.		
Е.	Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.		
	Specific treatments	:	No specific treatment.		
	Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.		

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Α.	Extinguishing media		
	Suitable extinguishing media	1	Use dry chemical, CO ₂ , water spray (fog) or foam.
	Unsuitable extinguishing media	-	Do not use water jet.
В.	Specific hazards arising from the chemical	:	Combustible liquid. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
	Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon oxides metal oxide/oxides

Product name SIGMAGUARD CSF 585 BASE WHITE

Section 5. Fire-fighting measures

C.	Special equipment for fire-fighting	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
	Fire-fighting procedures	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Section 6. Accidental release measures

A. Personal precautions, protective equipment and emergency procedures	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.					
B. Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.					
C. Methods and materials for	C. Methods and materials for containment and cleaning up						
Small spill	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.					
Large spill	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.					

Section 7. Handling and storage

A. Precautions for safe handling
 Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.

Korea (GHS) Page: 4/13

Product name SIGMAGUARD CSF 585 BASE WHITE

Section 7. Handling and storage

B. Conditions for safe storage, including any incompatibilities
 Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

A. Occupational exposure limits

Ingredient name	Exposure limits
∄alc , not containing asbestiform fibres	ISHA Article 42 (Republic of Korea,
	1/2020)
	TWA 8 hours: 2 mg/m ³ (as asbestos).
	Form: fibers.
titanium dioxide	ISHA Article 42 (Republic of Korea,
	1/2020)
	TWA 8 hours: 10 mg/m ³ .
crystalline silica, respirable powder (>10 microns)	ISHA Article 42 (Republic of Korea,
	1/2020)
	TWA 8 hours: 0.05 mg/m ³ . Form:
	Respirable fraction.
xylene	ISHA Article 42 (Republic of Korea,
	1/2020) [Xylene]
	STEL 15 minutes: 150 ppm.
	TWA 8 hours: 100 ppm.
	appropriate monitoring standards. Reference to for methods for the determination of hazardous ed.

- B. Appropriate engineering controls
 Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
 Environmental
 Emissions from ventilation or work process equipment should be checked to ensure
 - exposure controls they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

C. Personal protective equipment

Respiratory protection
 Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
 Eye protection

Korea (GHS) Page: 5/13

Product name SIGMAGUARD CSF 585 BASE WHITE

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: butyl rubber
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Α.	Appearance					
	Physical state	:	Liquid.			
	Color	:	White.			
В.	Odor	:	Characteristic.			
С.	Odor threshold	:	Not available.			
D.	рН	:	Not applicable.			
Ε.	Melting/freezing point	1	Not available.			
F.	Boiling point/boiling range	:	>37.78°C (>100°F)			
G.	Flash point	:	Closed cup: 93°C (1	99.4°F)		
н.	Evaporation rate	1	Not available.			
Т.	Flammability (solid, gas)	:	Not available.			
J.	Lower and upper explosive (flammable) limits	:	Not available.			
Κ.	Vapor pressure	:		Vapo	r Pressu	re at 20°C
			Ingredient name	mm Hg	kPa	Method
			1,6-bis (2,3-epoxypropoxy) hexane	0.067505535	0.009	
	Solubility(ies)		Media	Re	sult	
L.	Solubility(ies)		cold water	No	t soluble	
	Solubility in water	:	Not available.			
	Vapor density	:	Not available.			

Korea (GHS) Page: 6/13

Vapor pressure at 50°C

Method

kPa

mm

Hg

Product name SIGMAGUARD CSF 585 BASE WHITE

Section 9. Physical and chemical properties

М. N.	Relative density	:	1.42
ю. О.	Partition coefficient: n- octanol/water	1	Not applicable.
Ρ.	Auto-ignition temperature	1	Not available.
Q.	Decomposition temperature	1	Not available.
R.	Viscosity	:	Øynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)
	Flow time (ISO 2431)	1	Not available.
S.	Molecular weight	;	Not applicable.

Section 10. Stability and reactivity

Α.	-		The product is stable. Under normal conditions of storage and use, hazardous reactions will not occur.
	reactions		
в.	Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products.
C.	Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
D.	Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

Section 11. Toxicological information

Α.	Information on the likely	: Not available.
	routes of exposure	

Potential acute health effects

Inhalation	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Eye contact	: Causes serious eye irritation.

Over-exposure signs/symptoms

Inhalation	: No specific data.
Ingestion	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness

Product name SIGMAGUARD CSF 585 BASE WHITE

Section 11. Toxicological information

B. Health hazards

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
s-[4-(2,3-epoxipropoxi)phenyl]propane		Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
titanium dioxide	LC50 Inhalation Dusts and	Rat	>6.82 mg/l	4 hours
	mists			
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
xylene	LC50 Inhalation Vapor	Rat	27124 mg/m ³	4 hours
-	LD50 Dermal	Rabbit	12126 mg/kg	-
	LD50 Oral	Rat	3523 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation	
bis-[4-(2,3-epoxipropoxi)phenyl] propane	Eyes - Mild irritant	Rabbit	-	24 hours	-	
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-	
	Skin - Edema	Rabbit	0.5	4 hours	-	
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-	
	Skin - Mild irritant	Rabbit	-	4 hours	-	

Conclusion/Summary

Skin	: There are	no data a	available	on the	mixture	itself.
Eyes	: There are		available			

Respiratory : There are no data available on the mixture itself.

Sensitization

Product/ingredient name	Route of exposure	Species	Result	
bis-[4-(2,3-epoxipropoxi) phenyl]propane	skin	Mouse	Sensitizing	
	• • • • • • • • • • • • • • • • • • • •	ta available on the mixtu ta available on the mixtu		
<u>Mutagenicity</u> Conclusion/Summary	: There are no da	ata available on the mixto	ure itself.	
<u>Carcinogenicity</u> Conclusion/Summary	: There are no da	ata available on the mixt	ure itself.	
Reproductive toxicity Conclusion/Summary	: There are no d	ata available on the mixi	ure itself.	
<u>Teratogenicity</u>				

Product name SIGMAGUARD CSF 585 BASE WHITE

Section 11. Toxicological information

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name	Classification	Route of exposure	Target organs
√alc , not containing asbestiform fibres	Category 3		Respiratory tract irritation
xylene	Category 3		Respiratory tract irritation
	Category 3		Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Classification	Route of exposure	Target organs
x ylene	Category 2	-	-

Aspiration hazard

Name	Result
x ylene	ASPIRATION HAZARD - Category 1

Potential chronic health effects

General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity Mutagenicity	 May cause cancer. Risk of cancer depends on duration and level of exposure. No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Additional information

Sanding and grinding dusts may be harmful if inhaled.

Chemical name	Identifiers	GHS Classification
s-[4-(2,3-epoxipropoxi)phenyl]propane	CAS: 1675-54-3	SKIN IRRITATION - Category 2
	EC: 216-823-5	EYE IRRITATION - Category 2A
		SKIN SENSITIZATION - Category 1B
		AQUATIC HAZARD (LONG-TERM) - Category 2
1,6-bis(2,3-epoxypropoxy)hexane	CAS: 16096-31-4	SKIN IRRITATION - Category 2
	EC: 240-260-4	EYE IRRITATION - Category 2A
		SKIN SENSITIZATION - Category 1B
		AQUATIC HAZARD (LONG-TERM) - Category 3
Talc , not containing asbestiform fibres	CAS: 14807-96-6	SPECIFIC TARGET ORGAN TOXICITY (SINGLE
		EXPOSURE) (Respiratory tract irritation) -
		Category 3
	EC: 238-877-9	
titanium dioxide	CAS: 13463-67-7	CARCINOGENICITY - Category 2
	EC: 236-675-5	
crystalline silica, respirable powder (>10	CAS: 14808-60-7	CARCINOGENICITY - Category 1A
microns)		
	EC: 238-878-4	
xylene	CAS: 95-47-6	FLAMMABLE LIQUIDS - Category 3
		Korea (GHS) Page: 9/13

Date of issue 9/30/2024 (month/day/year)

Product name SIGMAGUARD CSF 585 BASE WHITE

Section 11. Toxicological information

EC: 202-422-2	ACUTE TOXICITY (inhalation) - Category 4
	SKIN IRRITATION - Category 2
	EYE IRRITATION - Category 2A
	TOXIC TO REPRODUCTION - Category 2
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE
	EXPOSURE) (Respiratory tract irritation) -
	Category 3
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE
	EXPOSURE) (Narcotic effects) - Category 3
	SPECIFIC TARGET ORGAN TOXICITY
	(REPEATED EXPOSURE) - Category 2
	ASPIRATION HAZARD - Category 1
L	

Section 12. Ecological information

A. Ecotoxicity

Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia magna</i>	48 hours
titanium dioxide	Chronic NOEC 0.3 mg/l Acute LC50 >100 mg/l Fresh water	Daphnia Daphnia - <i>Daphnia magna</i>	21 days 48 hours

B. Persistence and degradability

Product/ingredient name	Test	Result		Dose		Inoculum
x ylene	OECD 301F 94 % - Rea		adily - 28 days	days -		-
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
s-[4-(2,3-epoxipropoxi)	-		-		Not rea	dily
xylene	-		-		Readily	

C. Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
,6-bis(2,3-epoxypropoxy)	0.822	-	Low
xylene	3.12	14.13	Low

D. Mobility in soil

Soil/water partition coefficient (Koc)

- : Not available.
- E. Other adverse effects : No known significant effects or critical hazards.

Product name SIGMAGUARD CSF 585 BASE WHITE

Section 13. Disposal considerations

Α.	Disposal methods	:	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
			should only be considered when recycling is not reasible.

B. Disposal precautions
 This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
A. UN number	UN3082	UN3082	UN3082
B. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)
C. Transport hazard class(es)	9	9	9
D. Packing groupIIIEnvironmental hazardsYes.		III	III
		Yes.	Yes.
E. Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Not applicable.

Additional information

UN	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

F. Special precaution which a user to be aware of or needs to comply with in connection with transport or transportation

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

19.

Version 1.01

Product name SIGMAGUARD CSF 585 BASE WHITE

Section 14. Transport information

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

A. Regulation according to ISHA

ISHA article 117 (Harmful substances prohibited from manufacture)	: None of the components are listed.
ISHA article 118 (Harmful substances requiring permission)	: None of the components are listed.
Article 2 of Youth Protection Act on Substances Hazardous to Youth	: It is not allowed to sell to persons under the age of

Exposure Limits of Chemical Substances and Physical Factors

The following components have an OEL:

	The following components			
	Annex 19 (Exposure standards established for harmful factors)	:	None of the components are listed.	
	ISHA Enforcement Regs Annex 11-5 (Harmful factors subject to Work Environment Measurement)	:	The following components are listed: talc / soapstone, titanium dioxide	
	ISHA Enforcement Regs Annex 22 (Harmful Factors Subject to Special Health Check- up)	:	None of the components are listed.	
	Standard of Industrial Safety and Health Annex 12 (Hazardous substances subject to control)	:	The following components are listed: titanium dioxide	
В.	Regulation according to (Ch	emicals Control Act	
	Article 11 (TRI)	:	None of the components are listed.	
	Article 18 Prohibited (K- Reach Article 27)	-	None of the components are listed.	
	Article 19 Subject to authorization (K-Reach Article 25)	:	None of the components are listed.	
	Article 20 Restricted (K- Reach Article 27)	-	None of the components are listed.	
	Article 20 Toxic Chemicals (K-Reach Article 20)	:	Not applicable	

Product name SIGMAGUARD CSF 585 BASE WHITE

Section 15. Regulatory information

•	Korea inventory	1	All components are listed or exempted.
	Article 39 (Accident	:	None of the components are listed.
	Precaution Chemicals)		
С.	Dangerous Materials	1	Class: Class 4 - Flammable Liquid
	Safety Management Act		Item: 5. Class 3 petroleums - Water-insoluble liquid
			Threshold: 2000 L
			Danger category: III
			Signal word: Contact with sources of ignition prohibited
D.	Wastes regulation	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Ε.	Regulation according to o	oth	ier foreign laws
	Safety, health and environmental regulations specific for the product	:	No known specific national and/or regional regulations applicable to this product (including its ingredients).

Section 16. Other information

Α.	References	 Korean Ministry of Environment; Chemical Control Act Korean Ministry of Labor; Industrial Safety and Health Act NIER Notice Registry of Toxic Effects of Chemical Substances (RTECS) U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information Retrieval) ECOTOX Database System.
В.	First issue date	: 10/16/2023
C.	Date of issue/Date of revision	: 9/30/2024
D.	Version	: 1.01
	Prepared by	: EHS
Ε.	Other	

Indicates information that has changed from previously issued version.

<u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.